



**Program Directory for
IBM DB2 Table Editor for z/OS**

V04.05.00

Program Number 5697-G65

FMID H25K150

for Use with
z/OS

Document Date: May 2016

GI10-8401-04

Note

Before using this information and the product it supports, be sure to read the general information under 7.0, "Notices" on page 23.

Contents

1.0 Introduction	1
1.1 DB2 Table Editor Description	1
1.2 DB2 Table Editor FMID	2
2.0 Program Materials	3
2.1 Basic Machine-Readable Material	3
2.2 Optional Machine-Readable Material	4
2.3 Program Publications	4
2.3.1 Optional Program Publications	4
2.4 Program Source Materials	4
2.5 Publications Useful During Installation	5
3.0 Program Support	6
3.1 Program Services	6
3.2 Preventive Service Planning	6
3.3 Statement of Support Procedures	7
4.0 Program and Service Level Information	8
4.1 Program Level Information	8
4.2 Service Level Information	8
5.0 Installation Requirements and Considerations	9
5.1 Driving System Requirements	9
5.1.1 Machine Requirements	9
5.1.2 Programming Requirements	9
5.2 Target System Requirements	10
5.2.1 Machine Requirements	10
5.2.2 Programming Requirements	10
5.2.2.1 Installation Requisites	10
5.2.2.2 Operational Requisites	11
5.2.2.3 Toleration/Coexistence Requisites	11
5.2.2.4 Incompatibility (Negative) Requisites	11
5.2.3 DASD Storage Requirements	12
5.3 FMIDs Deleted	14
5.4 Special Considerations	14
6.0 Installation Instructions	16
6.1 Installing DB2 Table Editor	16
6.1.1 SMP/E Considerations for Installing DB2 Table Editor	16
6.1.2 SMP/E Options Subentry Values	16
6.1.3 SMP/E CALLLIBS Processing	16
6.1.4 Sample Jobs	17

6.1.5 Allocate SMP/E CSI (Optional)	18
6.1.6 Initialize CSI zones (Optional)	19
6.1.7 Perform SMP/E RECEIVE	19
6.1.8 Allocate SMP/E Target and Distribution Libraries	19
6.1.9 Create DDDEF Entries	19
6.1.10 Perform SMP/E APPLY	19
6.1.11 Perform SMP/E ACCEPT	21
6.1.12 Run REPORT CROSSZONE	22
6.1.13 Cleaning Up Obsolete Data Sets and DDDEFs	22
6.2 Activating DB2 Table Editor	22
6.2.1 Product Customization	22
7.0 Notices	23
7.1 Trademarks	23
Reader's Comments	24

Figures

1. Program File Content	3
2. Basic Material: Unlicensed	4
3. Publications Useful During Installation	5
4. PSP Upgrade and Subset ID	6
5. Component IDs	7
6. Driving System Software Requirements	10
7. Target System Mandatory Operational Requisites	11
8. Total DASD Space Required by DB2 Table Editor	12
9. Storage Requirements for DB2 Table Editor Target Libraries	13
10. Storage Requirements for DB2 Table Editor Distribution Libraries	14
11. SMP/E Options Subentry Values	16
12. Sample Installation Jobs	17

1.0 Introduction

This program directory is intended for system programmers who are responsible for program installation and maintenance. It contains information about the material and procedures associated with the installation of IBM DB2 Table Editor for z/OS. This publication refers to IBM DB2 Table Editor for z/OS as DB2 Table Editor.

The Program Directory contains the following sections:

- 2.0, “Program Materials” on page 3 identifies the basic program materials and documentation for DB2 Table Editor.
- 3.0, “Program Support” on page 6 describes the IBM support available for DB2 Table Editor.
- 4.0, “Program and Service Level Information” on page 8 lists the APARs (program level) and PTFs (service level) that have been incorporated into DB2 Table Editor.
- 5.0, “Installation Requirements and Considerations” on page 9 identifies the resources and considerations that are required for installing and using DB2 Table Editor.
- 6.0, “Installation Instructions” on page 16 provides detailed installation instructions for DB2 Table Editor. It also describes the procedures for activating the functions of DB2 Table Editor, or refers to appropriate publications.

Before installing DB2 Table Editor, read the *CBPDO Memo To Users* and the *CBPDO Memo To Users Extension* that are supplied with this program in softcopy format and this program directory; then keep them for future reference. Section 3.2, “Preventive Service Planning” on page 6 tells you how to find any updates to the information and procedures in this program directory.

DB2 Table Editor is supplied in a Custom-Built Product Delivery Offering (CBPDO, 5751-CS3). The program directory that is provided in softcopy format on the CBPDO tape is identical to the hardcopy format if one was included with your order. All service and HOLDDATA for DB2 Table Editor are included on the CBPDO tape.

Do not use this program directory if you install DB2 Table Editor with a SystemPac or ServerPac. When you use one of those offerings, use the jobs and documentation supplied with the offering. The offering will point you to specific sections of this program directory as needed.

1.1 DB2 Table Editor Description

DB2 Table Editor for z/OS, V4.5 offers database administrators (DBA), developers, and the entire enterprise direct update and data creation operations on DB2 for z/OS database

- Quick and easy manipulation of data
 - DB2 Table Editor helps you make the best use of your time. It can reduce staff training time, enhance DBA productivity, increase the ability to respond to your workforce's need for high-

performance business applications, and enable the IT team to institute proactive database maintenance.

- DB2 Table Editor is designed to make quick and easy work of navigating DB2 databases, tables, and views, finding related data, and updating, deleting, or creating data with full support for your existing DB2 security and logon IDs.
- Control of data integrity
 - In today's competitive environment, data integrity is more important than ever. Whether your concern is as basic as accurate customer records or as complex as running applications that depend on hundreds of interdependent tables, DB2 Table Editor is designed to make preserving data integrity easy to accomplish, no matter the level of experience of your employees. With DB2 Table Editor, your knowledge workers, both novice and expert, can use this single, powerful tool to manipulate your data while maintaining tight control over data editing privileges.
- Performance improvement
 - Storage allocation and memory utilization is more efficient.
- Usability improvement
 - Usability has been improved by enabling more flexible viewing and editing options of DB2 table data.
 - DB2 Table Editor now retrieves all data rows that match the SELECT or WHERE clause without pausing to ask users if they want to continue retrieving the next set of rows. The pop-up window that is displayed for users to confirm that they want to continue retrieving the next set of rows has been removed.
 - DB2 Table Editor removed the 1MB size limitation for editing XML data. The XML data can be edited as long as the user region size is big enough to load the data into the memory.
 - The graphical user interface and LOB support has been deprecated. ISPF will be used exclusively.

1.2 DB2 Table Editor FMID

DB2 Table Editor consists of the following FMID:

H25K150

2.0 Program Materials

An IBM program is identified by a program number. The program number for DB2 Table Editor is 5697-G65.

Basic Machine-Readable Materials are materials that are supplied under the base license and are required for the use of the product.

The program announcement material describes the features supported by DB2 Table Editor. Ask your IBM representative for this information if you have not already received a copy.

2.1 Basic Machine-Readable Material

The distribution medium for this program is physical media or downloadable files. This program is in SMP/E RELFILE format and is installed by using SMP/E. See 6.0, "Installation Instructions" on page 16 for more information about how to install the program.

You can find information about the physical media for the basic machine-readable materials for DB2 Table Editor in the *CBPDO Memo To Users Extension*.

Figure 1 describes the program file content for DB2 Table Editor. You can refer to the *CBPDO Memo To Users Extension* to see where the files reside on the tape.

Notes:

1. The data set attributes in this table must be used in the JCL of jobs that read the data sets. However, because the data sets are in IEBCOPY unloaded format, their actual attributes might be different.
2. If any RELFILEs are identified as PDSEs, ensure that SMPTLIB data sets are allocated as PDSEs.

Figure 1 (Page 1 of 2). Program File Content

Name	ORG	RECFM	LEN	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.H25K150.F1	PDS	FB	80	8800
IBM.H25K150.F2	PDS	FB	80	8800
IBM.H25K150.F3	PDS	FB	80	8800
IBM.H25K150.F4	PDSE	U	0	6144
IBM.H25K150.F5	PDS	FB	80	8800

Figure 1 (Page 2 of 2). Program File Content

Name	OR G	RE C M	LR E C L	BLK SIZE
IBM.H25K150.F6	PDS	FB	80	8800
IBM.H25K150.F7	PDS	FB	80	8800
IBM.H25K150.F8	PDS	FB	80	8800
IBM.H25K150.F9	PDS	FB	80	8800

2.2 Optional Machine-Readable Material

No optional machine-readable materials are provided for DB2 Table Editor.

2.3 Program Publications

The following sections identify the basic publications for DB2 Table Editor.

Figure 2 identifies the basic unlicensed publications for DB2 Table Editor. Those that are in softcopy format publications can be obtained from the IBM Publications Center website at:
<http://www.ibm.com/shop/publications/order/>

Figure 2. Basic Material: Unlicensed

Publication Title	Form Number	Media Format
IBM DB2 Table Editor for z/OS License Information	GC27-1200	http://www.ibm.com/software/sla/sladb.nsf
DB2 Table Editor User's Guide	SC27-8804	http://www.ibm.com/support/docview.wss?uid=swg27020942

2.3.1 Optional Program Publications

No optional publications are provided for DB2 Table Editor.

2.4 Program Source Materials

No program source materials or viewable program listings are provided for DB2 Table Editor.

2.5 Publications Useful During Installation

You might want to use the publications listed in Figure 3 on page 5 during the installation of DB2 Table Editor.

<i>Figure 3. Publications Useful During Installation</i>		
Publication Title	Form Number	Media Format
<i>IBM SMP/E for z/OS User's Guide</i>	SA23-2277	http://www.ibm.com/shop/publications/order/
<i>IBM SMP/E for z/OS Commands</i>	SA23-2275	http://www.ibm.com/shop/publications/order/
<i>IBM SMP/E for z/OS Reference</i>	SA23-2276	http://www.ibm.com/shop/publications/order/
<i>IBM SMP/E for z/OS Messages, Codes, and Diagnosis</i>	GA32-0883	http://www.ibm.com/shop/publications/order/

3.0 Program Support

This section describes the IBM support available for DB2 Table Editor.

3.1 Program Services

Contact your IBM representative for specific information about available program services.

3.2 Preventive Service Planning

Before you install DB2 Table Editor, make sure that you have reviewed the current Preventive Service Planning (PSP) information. Review the PSP Bucket for General Information, Installation Documentation, and the Cross Product Dependencies sections. For the Recommended Service section, instead of reviewing the PSP Bucket, it is recommended you use the IBM.ProductInstall-RequiredService fix category in SMP/E to ensure you have all the recommended service installed. Use the **FIXCAT(IBM.ProductInstall-RequiredService)** operand on the **APPLY CHECK** command. See 6.1.10, "Perform SMP/E APPLY" on page 19 for a sample APPLY command.

If you obtained DB2 Table Editor as part of a CBPDO, HOLDDATA is included.

If the CBPDO for DB2 Table Editor is older than two weeks by the time you install the product materials, you can obtain the latest PSP Bucket information by going to the following website:

<http://www14.software.ibm.com/webapp/set2/psearch/search?domain=psp>

You can also use S/390 SoftwareXcel or contact the IBM Support Center to obtain the latest PSP Bucket information.

For program support, access the Software Support Website at <http://www-01.ibm.com/software/support/>.

PSP Buckets are identified by UPGRADEs, which specify product levels; and SUBSETs, which specify the FMIDs for a product level. The UPGRADE and SUBSET values for DB2 Table Editor are included in Figure 4.

UPGRADE	SUBSET	Description
5697G65	H25K150	IBM DB2 Table Editor for z/OS

3.3 Statement of Support Procedures

Report any problems which you feel might be an error in the product materials to your IBM Support Center. You may be asked to gather and submit additional diagnostics to assist the IBM Support Center in their analysis.

Figure 5 on page 7 identifies the component IDs (COMPID) for DB2 Table Editor.

<i>Figure 5. Component IDs</i>			
FMID	COMPID	Component Name	RETAIN Release
H25K150	5697G6500	IBM DB2 Table Editor for z/OS	450

4.0 Program and Service Level Information

This section identifies the program and relevant service levels of DB2 Table Editor. The program level refers to the APAR fixes that have been incorporated into the program. The service level refers to the PTFs that have been incorporated into the program.

4.1 Program Level Information

The following APAR fixes against previous releases of DB2 Table Editor have been incorporated into this release. They are listed by FMID.

- FMID H25K140

UI33407	UI22830	UI14352
UI32357	UI22452	UI13480
UI30238	UI22452	UI13486
UI29443	UI21197	UI12288
UI29443	UI21024	UK98352
UI29443	UI20166	UK98017
UI29443	UI18916	UK98017
UI27705	UI18037	UK98032
UI26811	UI17332	UK95750
UI26689	UI16666	UK92436
UI25028	UI15266	UK91191
UI23628	UI15026	UK83538

4.2 Service Level Information

No PTFs against this release of DB2 Table Editor have been incorporated into the product package.

Frequently check the DB2 Table Editor PSP Bucket for HIPER and SPECIAL attention PTFs against all FMIDs that you must install. You can also receive the latest HOLDDATA, then add the **FIXCAT(IBM.PRODUCTINSTALL-REQUIRESERVICE)** operand on your APPLY CHECK command. This will allow you to review the recommended and critical service that should be installed with your FMIDs.

5.0 Installation Requirements and Considerations

The following sections identify the system requirements for installing and activating DB2 Table Editor. The following terminology is used:

- *Driving system*: the system on which SMP/E is executed to install the program.

The program might have specific operating system or product level requirements for using processes, such as binder or assembly utilities during the installation.

- *Target system*: the system on which the program is configured and run.

The program might have specific product level requirements, such as needing access to the library of another product for link-edits. These requirements, either mandatory or optional, might directly affect the element during the installation or in its basic or enhanced operation.

In many cases, you can use a system as both a driving system and a target system. However, you can make a separate IPL-able clone of the running system to use as a target system. The clone must include copies of all system libraries that SMP/E updates, copies of the SMP/E CSI data sets that describe the system libraries, and your PARMLIB and PROCLIB.

Use separate driving and target systems in the following situations:

- When you install a new level of a product that is already installed, the new level of the product will replace the old one. By installing the new level onto a separate target system, you can test the new level and keep the old one in production at the same time.
- When you install a product that shares libraries or load modules with other products, the installation can disrupt the other products. By installing the product onto a separate target system, you can assess these impacts without disrupting your production system.

5.1 Driving System Requirements

This section describes the environment of the driving system required to install DB2 Table Editor.

5.1.1 Machine Requirements

The driving system can run in any hardware environment that supports the required software.

5.1.2 Programming Requirements

Figure 6. Driving System Software Requirements

Program Number	Product Name	Minimum VRM	Minimum Service Level will satisfy these APARs	Included in the shipped product?
Any one of the following:				
5694-A01	z/OS	V01.13.00	OA49661	No
5650-ZOS	z/OS	V02.01.00 or higher	N/A	No

Note: SMP/E is a requirement for Installation and is an element of z/OS but can also be ordered as a separate product, 5655-G44, minimally V03.06.00.

Note: Installation might require migration to new z/OS releases to be service supported. See http://www-03.ibm.com/systems/z/os/zos/support/zos_eos_dates.html.

5.2 Target System Requirements

This section describes the environment of the target system required to install and use DB2 Table Editor.

DB2 Table Editor installs in the DBS (P115) SREL.

5.2.1 Machine Requirements

The target system can run in any hardware environment that supports the required software.

5.2.2 Programming Requirements

5.2.2.1 Installation Requisites: Installation requisites identify products that are required and *must* be present on the system or products that are not required but *should* be present on the system for the successful installation of this product.

Mandatory installation requisites identify products that are required on the system for the successful installation of this product.

DB2 Table Editor has no mandatory installation requisites.

Conditional installation requisites identify products that are *not* required for successful installation of this product but can resolve such things as certain warning messages at installation time.

DB2 Table Editor has no conditional installation requisites.

5.2.2.2 Operational Requisites: Operational requisites are products that are required and *must* be present on the system or products that are not required but *should* be present on the system for this product to operate all or part of its functions.

Mandatory operational requisites identify products that are required for this product to operate its basic functions.

<i>Figure 7. Target System Mandatory Operational Requisites</i>	
Program Number	Product Name and Minimum VRM/Service Level
5655-V93	IBM Tools Base for z/OS V01.05.00 or higher - HTCZ110 (IBM Tools Customizer for z/OS)
Any one of the following:	
5605-DB2	DB2 for z/OS V10.01.00
5697-P31	DB2 Value Unit Edition for z/OS V10.01.00
5615-DB2	DB2 for z/OS V11.01.00
5697-P43	DB2 Value Unit Edition for z/OS V11.01.00

Note: IBM Tools Base for z/OS, (5655-V93) is a mandatory operational pre-requisite for DB2 Table Editor. IBM Tools Base for z/OS is a no-charge product that must be separately ordered. Tools Base contains IBM Tools Customizer for z/OS, FMID HTCZ110, which must be installed and at the current maintenance level in order to customize DB2 Table Editor. Refer to the IBM Tools Base for z/OS Program Directory (GI10-8819) for installation instructions.

Conditional operational requisites identify products that are *not* required for this product to operate its basic functions but are required at run time for this product to operate specific functions.

DB2 Table Editor has no conditional operational requisites.

5.2.2.3 Toleration/Coexistence Requisites: Toleration/coexistence requisites identify products that must be present on sharing systems. These systems can be other systems in a multisystem environment (not necessarily sysplex), a shared DASD environment (such as test and production), or systems that reuse the same DASD environment at different time intervals.

DB2 Table Editor has no toleration/coexistence requisites.

5.2.2.4 Incompatibility (Negative) Requisites: Negative requisites identify products that must *not* be installed on the same system as this product.

DB2 Table Editor has no negative requisites.

5.2.3 DASD Storage Requirements

DB2 Table Editor libraries can reside on all supported DASD types.

Figure 8 on page 12 lists the total space that is required for each type of library.

Library Type	Total Space Required in 3390 Trks
Target	1842
Distribution	1842

Notes:

1. For non-RECFM U data sets, IBM recommends using system-determined block sizes for efficient DASD utilization. For RECFM U data sets, IBM recommends using a block size of 32760, which is most efficient from the performance and DASD utilization perspective.
2. Abbreviations used for data set types are shown as follows.

- U** Unique data set, allocated by this product and used by only this product. This table provides all the required information to determine the correct storage for this data set. You do not need to refer to other tables or program directories for the data set size.
- S** Shared data set, allocated by this product and used by this product and other products. To determine the correct storage needed for this data set, add the storage size given in this table to those given in other tables (perhaps in other program directories). If the data set already exists, it must have enough free space to accommodate the storage size given in this table.
- E** Existing shared data set, used by this product and other products. This data set is *not* allocated by this product. To determine the correct storage for this data set, add the storage size given in this table to those given in other tables (perhaps in other program directories). If the data set already exists, it must have enough free space to accommodate the storage size given in this table.

If you currently have a previous release of this product installed in these libraries, the installation of this release will delete the old release and reclaim the space that was used by the old release and any service that had been installed. You can determine whether these libraries have enough space by deleting the old release with a dummy function, compressing the libraries, and comparing the space requirements with the free space in the libraries.

For more information about the names and sizes of the required data sets, see 6.1.8, "Allocate SMP/E Target and Distribution Libraries" on page 19.

3. All target and distribution libraries listed have the following attributes:
 - The default name of the data set can be changed.
 - The default block size of the data set can be changed.
 - The data set can be merged with another data set that has equivalent characteristics.

- The data set can be either a PDS or a PDSE, except for SETILOAD and AETILOAD, which must be PDSEs.
4. All target libraries listed have the following attributes:
- These data sets can be SMS-managed, but they are not required to be SMS-managed.
 - These data sets are not required to reside on the IPL volume.
 - The values in the "Member Type" column are not necessarily the actual SMP/E element types that are identified in the SMPMCS.
5. All target libraries that are listed and contain load modules have the following attributes:
- These data sets can be in the LPA, but they are not required to be in the LPA.
 - These data sets can be in the LNKLIST.
 - These data sets are not required to be APF-authorized.
 - DB2 Table Editor requires that the SMPLTS data set must be a PDSE. If your existing SMPLTS is a PDS, you will need to allocate a new PDSE and copy your existing SMPLTS into it and then change the SMPLTS DDDEF entry to indicate the new PDSE data set.

The following figures describe the target and distribution libraries required to install DB2 Table Editor. The storage requirements of DB2 Table Editor must be added to the storage required by other programs that have data in the same library.

Note: Use the data in these tables to determine which libraries can be merged into common data sets. In addition, since some ALIAS names may not be unique, ensure that no naming conflicts will be introduced before merging libraries.

Figure 9. Storage Requirements for DB2 Table Editor Target Libraries

Library DDNAME	Member Type	Target Volume	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
SETIDBRM	Macro	Any	U	PDS	FB	80	5	5
SETIDENU	Data	Any	U	PDS	FB	80	12	5
SETILOAD	LMOD	Any	U	PDSE	U	0	1750	n/a
SETIMENU	Message	Any	U	PDS	FB	80	5	5
SETIPENU	Panel	Any	U	PDS	FB	80	40	20
SETISAMP	Sample	Any	U	PDS	FB	80	10	5
SETISLIB	SKL	Any	U	PDS	FB	80	10	5
SETITENU	Table	Any	U	PDS	FB	80	10	5

Figure 10. Storage Requirements for DB2 Table Editor Distribution Libraries

Library DDNAME	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
AETIDBRM	U	PDS	FB	80	5	5
AETIDENU	U	PDS	FB	80	12	5
AETILOAD	U	PDSE	U	0	1750	n/a
AETIMENU	U	PDS	FB	80	5	5
AETIPENU	U	PDS	FB	80	40	20
AETISAMP	U	PDS	FB	80	10	5
AETISLIB	U	PDS	FB	80	10	5
AETITENU	U	PDS	FB	80	10	5

5.3 FMIDs Deleted

Installing DB2 Table Editor might result in the deletion of other FMIDs. To see which FMIDs will be deleted, examine the ++VER statement in the SMPMCS of the product.

If you do not want to delete these FMIDs at this time, install DB2 Table Editor into separate SMP/E target and distribution zones.

Note: These FMIDs are not automatically deleted from the Global Zone. If you want to delete these FMIDs from the Global Zone, use the SMP/E REJECT NOFMID DELETEFMID command. See the SMP/E Commands book for details.

5.4 Special Considerations

APAR OA49661 is required when performing SMP/E installation on z/OS V01.13.00.

PDSE Considerations:

DB2 Table Editor uses the "partitioned data set extended" or PDSE format for the SETILOAD target library. There are some operational differences between PDS and PDSE data sets. The PDS format may be shared by more than one z/OS system and no special precautions are necessary. However the PDSE format may only be shared by z/OS systems which are part of a sysplex or which are connected using Global Resource Serialization (are in a GRS complex). If z/OS systems share use of a PDSE data set outside of a sysplex or GRS environment, you may experience severe problems when the data set is updated. This is due to the fact that PDSE directory information is cached in storage, and when the data

set is updated from one system the other system(s) have no knowledge of the update, and their cached directory information will be incorrect.

You must take care not to share the SETILOAD data set between z/OS systems unless they are in a sysplex or are connected in a GRS complex. If you need to share the content of the SETILOAD data set, a separate copy must be created for each z/OS system.

6.0 Installation Instructions

This chapter describes the installation method and the step-by-step procedures to install and to activate the functions of DB2 Table Editor.

Please note the following points:

- If you want to install DB2 Table Editor into its own SMP/E environment, consult the SMP/E manuals for instructions on creating and initializing the SMPCSI and the SMP/E control data sets.
- You can use the sample jobs that are provided to perform part or all of the installation tasks. The SMP/E jobs assume that all DDDEF entries that are required for SMP/E execution have been defined in appropriate zones.
- You can use the SMP/E dialogs instead of the sample jobs to accomplish the SMP/E installation steps.

6.1 Installing DB2 Table Editor

6.1.1 SMP/E Considerations for Installing DB2 Table Editor

Use the SMP/E RECEIVE, APPLY, and ACCEPT commands to install this release of DB2 Table Editor.

6.1.2 SMP/E Options Subentry Values

The recommended values for certain SMP/E CSI subentries are shown in Figure 11. Using values lower than the recommended values can result in failures in the installation. DSSPACE is a subentry in the GLOBAL options entry. PEMAX is a subentry of the GENERAL entry in the GLOBAL options entry. See the SMP/E manuals for instructions on updating the global zone.

Figure 11. SMP/E Options Subentry Values

Subentry	Value	Comment
DSSPACE	(200,200,500)	3390 DASD tracks
PEMAX	SMP/E Default	IBM recommends using the SMP/E default for PEMAX.

6.1.3 SMP/E CALLLIBS Processing

DB2 Table Editor uses the CALLLIBS function provided in SMP/E to resolve external references during installation. When DB2 Table Editor is installed, ensure that DDDEFs exist for the following libraries:

- CSSLIB
- SISpload
- SCEEBND2

- SCEELIB
- SCCNOBJ

Note: CALLLIBS uses the previous DDDEFs only to resolve the link-edit for DB2 Table Editor. These data sets are not updated during the installation of DB2 Table Editor.

6.1.4 Sample Jobs

The following sample installation jobs are provided as part of the product to help you install DB2 Table Editor:

<i>Figure 12. Sample Installation Jobs</i>			
Job Name	Job Type	Description	RELFILE
ETIALA	SMP/E	Sample job to allocate and initialize a new SMP/E CSI data set (Optional)	IBM.H25K150.F7
ETIALB	SMP/E	Sample job to allocate SMP/E data sets (Optional)	IBM.H25K150.F7
ETIRECEV	RECEIVE	Sample RECEIVE job	IBM.H25K150.F7
ETIALLOC	ALLOCATE	Sample job to allocate target and distribution libraries	IBM.H25K150.F7
ETIDDEF	DDDEF	Sample job to define SMP/E DDDEFs	IBM.H25K150.F7
ETIAPPLY	APPLY	Sample APPLY job	IBM.H25K150.F7
ETIACCEP	ACCEPT	Sample ACCEPT job	IBM.H25K150.F7

You can access the sample installation jobs by performing an SMP/E RECEIVE (refer to 6.1.7, “Perform SMP/E RECEIVE” on page 19) then copy the jobs from the RELFILES to a work data set for editing and submission. See Figure 12 to find the appropriate refile data set.

You can also copy the sample installation jobs from the tape or product files by submitting the following job. Depending on your distribution medium, use either the //TAPEIN or the //FILEIN DD statement and comment out or delete the other statement. Before you submit the job, add a job card and change the lowercase parameters to uppercase values to meet the requirements of your site.

```
//STEP1 EXEC PGM=IEBCOPY
//SYSPRINT DD SYSOUT=*
//*****
/* Make the //TAPEIN DD statement below active if you install*
/* from a CBPDO tape by uncommenting the DD statement below. *
//*****
//*TAPEIN DD DSN=IBM.H25K150.F7,UNIT=tunit,
//* VOL=SER=25K150,LABEL=(x,SL),
//* DISP=(OLD,KEEP)
//*****
/* Make the //TAPEIN DD statement below active if you install*
/* from a product tape received outside the CBPDO process *
```

```

/* (using the optional SMP/E RECEIVE job) by uncommenting      *
/* the DD statement below.                                     *
/******
/*TAPEIN  DD DSN=IBM.H25K150.F7,UNIT=tunit,
/*          VOL=SER=volser,LABEL=(4,SL),
/*          DISP=(OLD,KEEP)
/******
/* Make the //FILEIN DD statement below active for            *
/* downloaded DASD files.                                     *
/******
/*FILEIN  DD DSN=IBM.H25K150.F7,UNIT=SYSALLDA,DISP=SHR,
/*          VOL=SER=filevol
//OUT     DD DSNAME=jcl-library-name,
//          DISP=(NEW,CATLG,DELETE),
//          VOL=SER=dasdvol,UNIT=SYSALLDA,
//          SPACE=(TRK,(20,10,5))
//SYSUT3  DD UNIT=SYSALLDA,SPACE=(CYL,(1,1))
//SYSIN   DD *
          COPY INDD=xxxxIN,OUTDD=OUT
          SELECT MEMBER=(ETIACCEP,ATIALA,ETIALB,ATIALLOC,ETIAPPLY)
          SELECT MEMBER=(ETIDDEF,ETIRECEV)
/*

```

See the following information to update the statements in the previous sample:

TAPEIN:

- tunit** is the unit value that matches the product package.
- volser** is the volume serial that matches the product package.
- x** is the tape file number that indicates the location of the data set name on the tape.
- See the documentation that is provided by CBPDO for the location of IBM.H25K150.F7 on the tape.

FILEIN:

- filevol** is the volume serial of the DASD device where the downloaded files reside.

OUT:

- jcl-library-name** is the name of the output data set where the sample jobs are stored.
- dasdvol** is the volume serial of the DASD device where the output data set resides.

SYSIN:

- xxxxIN** is either TAPEIN or FILEIN depending on your input DD statement.

6.1.5 Allocate SMP/E CSI (Optional)

If you are using an existing CSI, do not execute this job.

If you are allocating a new SMP/E data set for this install, edit and submit sample job ETIALA to allocate the SMP/E data set for DB2 Table Editor. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

6.1.6 Initialize CSI zones (Optional)

If you are using an existing CSI, do not execute this job.

Edit and submit sample job ETIALB to initialize SMP/E zones for DB2 Table Editor. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

6.1.7 Perform SMP/E RECEIVE

If you have obtained DB2 Table Editor as part of a CBPDO, use the RCVPDO job in the CBPDO RIMLIB data set to receive the DB2 Table Editor FMIDs, service, and HOLDDATA that are included on the CBPDO package. For more information, see the documentation that is included in the CBPDO.

You can also choose to edit and submit sample job ETIRECEV to perform the SMP/E RECEIVE for DB2 Table Editor. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

6.1.8 Allocate SMP/E Target and Distribution Libraries

Edit and submit sample job ETIALLOC to allocate the SMP/E target and distribution libraries for DB2 Table Editor. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

6.1.9 Create DDDEF Entries

Edit and submit sample job ETIDDDEF to create DDDEF entries for the SMP/E target and distribution libraries for DB2 Table Editor. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

6.1.10 Perform SMP/E APPLY

1. Ensure that you have the latest HOLDDATA; then edit and submit sample job ETIAPPLY to perform an SMP/E APPLY CHECK for DB2 Table Editor. Consult the instructions in the sample job for more information.

The latest HOLDDATA is available through several different portals, including <http://service.software.ibm.com/holdata/390holddata.html>. The latest HOLDDATA may identify HIPER and FIXCAT APARs for the FMIDs you will be installing. An APPLY CHECK will help you determine if any HIPER or FIXCAT APARs are applicable to the FMIDs you are installing. If there are any applicable HIPER or FIXCAT APARs, the APPLY CHECK will also identify fixing PTFs that will resolve the APARs, if a fixing PTF is available.

You should install the FMIDs regardless of the status of unresolved HIPER or FIXCAT APARs. However, do not deploy the software until the unresolved HIPER and FIXCAT APARs have been analyzed to determine their applicability. That is, before deploying the software either ensure fixing PTFs are applied to resolve all HIPER or FIXCAT APARs, or ensure the problems reported by all HIPER or FIXCAT APARs are not applicable to your environment.

To receive the full benefit of the SMP/E Causer SYSMOD Summary Report, do *not* bypass the PRE, ID, REQ, and IFREQ on the APPLY CHECK. The SMP/E root cause analysis identifies the cause only of *errors* and not of *warnings* (SMP/E treats bypassed PRE, ID, REQ, and IFREQ conditions as warnings, instead of errors).

Here are sample APPLY commands:

- a. To ensure that all recommended and critical service is installed with the FMIDs, receive the latest HOLDDATA and use the APPLY CHECK command as follows

```
APPLY S(fmid,fmid,...) CHECK
FORFMID(fmid,fmid,...)
SOURCEID(RSU*)
FIXCAT(IBM.ProductInstall-RequiredService)
GROUPEXTEND .
```

Some HIPER APARs might not have fixing PTFs available yet. You should analyze the symptom flags for the unresolved HIPER APARs to determine if the reported problem is applicable to your environment and if you should bypass the specific ERROR HOLDS in order to continue the installation of the FMIDs.

This method requires more initial research, but can provide resolution for all HIPERs that have fixing PTFs available and are not in a PE chain. Unresolved PEs or HIPERs might still exist and require the use of BYPASS.

- b. To install the FMIDs without regard for unresolved HIPER APARs, you can add the BYPASS(HOLDCLASS(HIPER)) operand to the APPLY CHECK command. This will allow you to install FMIDs even though one or more unresolved HIPER APARs exist. After the FMIDs are installed, use the SMP/E REPORT ERRSYSMODS command to identify unresolved HIPER APARs and any fixing PTFs.

```
APPLY S(fmid,fmid,...) CHECK
FORFMID(fmid,fmid,...)
SOURCEID(RSU*)
FIXCAT(IBM.ProductInstall-RequiredService)
GROUPEXTEND
BYPASS(HOLDCLASS(HIPER),HOLDFIXCAT) .
..any other parameters documented in the program directory
```

This method is quicker, but requires subsequent review of the Exception SYSMOD report produced by the REPORT ERRSYSMODS command to investigate any unresolved HIPERs. If you have received the latest HOLDDATA, you can also choose to use the REPORT MISSINGFIX command and specify Fix Category IBM.ProductInstall-RequiredService to investigate missing recommended service.

If you bypass HOLDs during the installation of the FMIDs because fixing PTFs are not yet available, you can be notified when the fixing PTFs are available by using the APAR Status Tracking (AST) function of ServiceLink or the APAR Tracking function of ResourceLink.

2. After you take actions that are indicated by the APPLY CHECK, remove the CHECK operand and run the job again to perform the APPLY.

Note: The GROUPEXTEND operand indicates that SMP/E applies all requisite SYSMODs. The requisite SYSMODS might be applicable to other functions.

Expected Return Codes and Messages from APPLY CHECK: You will receive a return code of 0 if this job runs correctly.

Expected Return Codes and Messages from APPLY: You will receive a return code of 0 if this job runs correctly.

6.1.11 Perform SMP/E ACCEPT

Edit and submit sample job ETIACCEP to perform an SMP/E ACCEPT CHECK for DB2 Table Editor. Consult the instructions in the sample job for more information.

To receive the full benefit of the SMP/E Causer SYSMOD Summary Report, do *not* bypass the PRE, ID, REQ, and IFREQ on the ACCEPT CHECK. The SMP/E root cause analysis identifies the cause of *errors* but not *warnings* (SMP/E treats bypassed PRE, ID, REQ, and IFREQ conditions as warnings rather than errors).

Before you use SMP/E to load new distribution libraries, it is recommended that you set the ACCJCLIN indicator in the distribution zone. In this way, you can save the entries that are produced from JCLIN in the distribution zone whenever a SYSMOD that contains inline JCLIN is accepted. For more information about the ACCJCLIN indicator, see the description of inline JCLIN in the SMP/E Commands book for details.

After you take actions that are indicated by the ACCEPT CHECK, remove the CHECK operand and run the job again to perform the ACCEPT.

Note: The GROUPEXTEND operand indicates that SMP/E accepts all requisite SYSMODs. The requisite SYSMODS might be applicable to other functions.

Expected Return Codes and Messages from ACCEPT CHECK: You will receive a return code of 0 if this job runs correctly.

If PTFs that contain replacement modules are accepted, SMP/E ACCEPT processing will link-edit or bind the modules into the distribution libraries. During this processing, the Linkage Editor or Binder might issue messages that indicate unresolved external references, which will result in a return code of 4 during the ACCEPT phase. You can ignore these messages, because the distribution libraries are not executable and the unresolved external references do not affect the executable system libraries.

Expected Return Codes and Messages from ACCEPT: You will receive a return code of 0 if this job runs correctly.

6.1.12 Run REPORT CROSSZONE

The SMP/E REPORT CROSSZONE command identifies requisites for products that are installed in separate zones. This command also creates APPLY and ACCEPT commands in the SMPPUNCH data set. You can use the APPLY and ACCEPT commands to install those cross-zone requisites that the SMP/E REPORT CROSSZONE command identifies.

After you install DB2 Table Editor, it is recommended that you run REPORT CROSSZONE against the new or updated target and distribution zones. REPORT CROSSZONE requires a global zone with ZONEINDEX entries that describe all the target and distribution libraries to be reported on.

For more information about REPORT CROSSZONE, see the SMP/E manuals.

6.1.13 Cleaning Up Obsolete Data Sets and DDDEFs

The following data sets, which were allocated and used by previous releases of this product, are no longer used in this release. You can delete these obsolete data sets after you delete the previous release from your system.

- AETICLNT
- SETICLNT

The following DDDEF entries, which were created and used by previous releases of this product, are no longer used in this release. You can delete these obsolete DDDEF entries after you delete the previous release from your system.

- AETICLNT
- SETICLNT

6.2 Activating DB2 Table Editor

6.2.1 Product Customization

The publication *DB2 Table Editor User's Guide* (SC27-8804) contains the necessary information to customize and use DB2 Table Editor.

7.0 Notices

This information was developed for products and services offered in the U.S.A. IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

APAR numbers are provided in this document to assist in locating PTFs that may be required. Ongoing problem reporting may result in additional APARs being created. Therefore, the APAR lists in this document may not be complete. To obtain current service recommendations and to identify current product service requirements, always contact the IBM Customer Support Center or use S/390 SoftwareXcel to obtain the current "PSP Bucket".

IBM may have patents or pending patent applications covering subject matter in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to the

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, New York 10504-1785
USA

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan, Ltd.
19-21, Nihonbashi-Hakozakicho, Chuo-ku
Tokyo 103-8510, Japan

7.1 Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

Reader's Comments

Program Directory for IBM DB2 Table Editor for z/OS, May 2016

We appreciate your input on this publication. Feel free to comment on the clarity, accuracy, and completeness of the information or give us any other feedback that you might have.

Use one of the following methods to send us your comments:

1. Send an email to comments@us.ibm.com
2. Use the form on the Web at:

www.ibm.com/software/data/rcf

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

IBM or any other organizations will only use the personal information that you supply to contact you about the issues that you submit.

Thank you for your participation.



Printed in USA

G110-8401-04

