



**Program Directory for  
IBM Application Performance Analyzer for z/OS**

V14.00.00

Program Number 5655-Q49

FMIDs HAD0E00, JAD0E0J, JAD0E0K

for Use with  
z/OS

Document Date: September 2016

GI13-4303-00

**Note**

Before using this information and the product it supports, be sure to read the general information under 7.0, "Notices" on page 35.

---

# Contents

<b>1.0 Introduction</b>	1
1.1 Application Performance Analyzer Description	1
1.2 Application Performance Analyzer FMIDs	4
<b>2.0 Program Materials</b>	5
2.1 Basic Machine-Readable Material	5
2.2 Optional Machine-Readable Material	7
2.3 Program Publications	7
2.4 Program Source Materials	7
2.5 Publications Useful During Installation	7
<b>3.0 Program Support</b>	9
3.1 Program Services	9
3.2 Preventive Service Planning	9
3.3 Statement of Support Procedures	10
<b>4.0 Program and Service Level Information</b>	11
4.1 Program Level Information	11
4.2 Service Level Information	11
<b>5.0 Installation Requirements and Considerations</b>	12
5.1 Driving System Requirements	12
5.1.1 Machine Requirements	12
5.1.2 Programming Requirements	12
5.2 Target System Requirements	13
5.2.1 Machine Requirements	13
5.2.2 Programming Requirements	13
5.2.2.1 Installation Requisites	14
5.2.2.2 Operational Requisites	15
5.2.2.3 Toleration/Coexistence Requisites	17
5.2.2.4 Incompatibility (Negative) Requisites	17
5.2.3 DASD Storage Requirements	17
5.3 FMIDs Deleted	22
5.4 Special Considerations	22
<b>6.0 Installation Instructions</b>	23
6.1 Installing Application Performance Analyzer	23
6.1.1 SMP/E Considerations for Installing Application Performance Analyzer	23
6.1.2 SMP/E Options Subentry Values	23
6.1.3 Sample Jobs	23
6.1.4 Allocate and Initialize the SMP/E Data Sets (Optional)	27
6.1.5 Perform SMP/E RECEIVE	27

6.1.6	Allocate SMP/E Target and Distribution Libraries	28
6.1.7	Allocate, create and mount ZFS Files (Optional)	28
6.1.8	Allocate File System Paths	29
6.1.9	Create DDDEF Entries	30
6.1.10	Perform SMP/E APPLY	31
6.1.11	Perform SMP/E ACCEPT	32
6.1.12	Run REPORT CROSSZONE	33
6.1.13	Cleaning Up Obsolete Data Sets, Paths, and DDDEFs	34
6.2	Activating Application Performance Analyzer	34
6.2.1	File System Execution	34
6.2.2	Product Customization	34
<b>7.0</b>	<b>Notices</b>	<b>35</b>
7.1	Other Notices	35
7.2	Trademarks	36
<b>Reader's Comments</b>		<b>37</b>

---

## Figures

1.	Program File Content Application Performance Analyzer - Base	5
2.	Program File Content Application Performance Analyzer - Japanese	6
3.	Program File Content Application Performance Analyzer - Korean	6
4.	Basic Material: Unlicensed	7
5.	Publications Useful During Installation	8
6.	PSP Upgrade and Subset ID	9
7.	Component IDs	10
8.	Driving System Software Requirements	13
9.	Target System Mandatory Installation Requisites	14
10.	Target System Conditional Operational Requisites	15
11.	Total DASD Space Required by Application Performance Analyzer - Base	17
12.	Total DASD Space Required by Application Performance Analyzer - Japanese	17
13.	Total DASD Space Required by Application Performance Analyzer - Korean	17
14.	Storage Requirements for Application Performance Analyzer Target Libraries - Base	19
15.	Storage Requirements for Application Performance Analyzer Target Libraries - Japanese	19
16.	Storage Requirements for Application Performance Analyzer Target Libraries - Korean	20
17.	Application Performance Analyzer File System Paths	20
18.	Storage Requirements for Application Performance Analyzer Distribution Libraries - Base	20
19.	Storage Requirements for Application Performance Analyzer Distribution Libraries - Japanese	21
20.	Storage Requirements for Application Performance Analyzer Distribution Libraries - Korean	21
21.	Storage Requirements for Application Performance Analyzer Non-SMP/E Data Sets	21
22.	SMP/E Options Subentry Values	23

23.	Sample Installation Jobs - Base	24
24.	Sample Installation Jobs - Japanese	24
25.	Sample Installation Jobs - Korean	24



---

## 1.0 Introduction

This program directory is intended for system programmers who are responsible for program installation and maintenance. It contains information about the material and procedures associated with the installation of IBM Application Performance Analyzer for z/OS. This publication refers to IBM Application Performance Analyzer for z/OS as Application Performance Analyzer.

The Program Directory contains the following sections:

- 2.0, “Program Materials” on page 5 identifies the basic program materials and documentation for Application Performance Analyzer.
- 3.0, “Program Support” on page 9 describes the IBM support available for Application Performance Analyzer.
- 4.0, “Program and Service Level Information” on page 11 lists the APARs (program level) and PTFs (service level) that have been incorporated into Application Performance Analyzer.
- 5.0, “Installation Requirements and Considerations” on page 12 identifies the resources and considerations that are required for installing and using Application Performance Analyzer.
- 6.0, “Installation Instructions” on page 23 provides detailed installation instructions for Application Performance Analyzer. It also describes the procedures for activating the functions of Application Performance Analyzer, or refers to appropriate publications.

Before installing Application Performance Analyzer, read the *CBPDO Memo To Users* and the *CBPDO Memo To Users Extension* that are supplied with this program in softcopy format and this program directory; then keep them for future reference. Section 3.2, “Preventive Service Planning” on page 9 tells you how to find any updates to the information and procedures in this program directory.

Application Performance Analyzer is supplied in a Custom-Built Product Delivery Offering (CBPDO, 5751-CS3). The program directory that is provided in softcopy format on the CBPDO tape is identical to the hardcopy format if one was included with your order. All service and HOLDDATA for Application Performance Analyzer are included on the CBPDO tape.

Do not use this program directory if you install Application Performance Analyzer with a SystemPac or ServerPac. When you use one of those offerings, use the jobs and documentation supplied with the offering. The offering will point you to specific sections of this program directory as needed.

---

### 1.1 Application Performance Analyzer Description

**IBM Application Performance Analyzer for z/OS V14.0** helps developers and systems personnel tune applications and resolve performance constraints. Application Performance Analyzer helps optimize the performance of existing z/OS application resources.

- Easy-to-use functions helps isolate application performance problems.

- Helps pinpoint performance bottlenecks affecting online transaction-response times.
- Assists in reducing batch application turnaround time.
- Supports C/C++, Assembler, COBOL, PL/I, Java, CICS, DB2, IMS, WebSphere MQ, and WebSphere Application Server.
- Increases application understanding during stress and regression testing.

**IBM Application Performance Analyzer for z/OS V14.0** includes the following enhancements:

Enhancements to started tasks, sampling, exits and intercepts include:

- Support up to 30,000 observations in the observation list. Request numbers are increased from four digits to five digits. This release requires checkpoint file conversion when upgrading from a previous version of Application Performance Analyzer.
- Control the timing of observation maintenance, including the regular deletion of expired observations and completed observations that are missing their associated sample files.
- Indicate under what conditions the ErrMsg status is to be displayed in the observation list.
- Support user level security when creating, updating, reading and deleting sample file data sets, and those data sets containing exported sample files.
- Support up to six alternate CICS execution module names.
- Control the behavior of Application Performance Analyzer sampling after the DB2 intercept traps an abend.
- Control the SYSOUT class for all Application Performance Analyzer SYSOUTs.
- Support specific sample file data set name in the batch interface and Application Performance Analyzer API.
- Support for Parallel Access Volumes.
- Cancel Multi-step threshold measurements when the target job runs without a step exceeding the threshold criteria.
- Trigger another measurement when a threshold request exceeds the criteria.
- Generate a single measurement request for repeat measurements requesting only one occurrence.
- Limit ExpiryDays value to 3660 days (10 years).
- Allow description to be updated after observation starts.
- Support PRF in IMS intercept.
- Support DB2 group name for DB2 Stored Procedure requests.
- Introduce sub capacity reporting in support of solution packs.
- Support Java in IMS JMP and JBP regions using preloaded Application Performance Analyzer JVMTI agent.



Enhancements to Reporting include:

- Sample and report CPU time consumed by Service Request Block (SRB) units of work.
- New MQ Intercept captures and reports timeline and service time data.
- Combined timeline report for DB2, IMS and MQ.
- Summarize all transactions executing in a single IMS MPP region.
- Capture and report WAS asynchronous data.
- Capture and report WOLA inbound and outbound requests.
- Display up to three possible interpretations of the instruction before the PSW.
- Report the Natural statement number when Natural calls Adabas.
- Report the Adabas DBID in the detail window ADABAS Call Information.
- Report the NATURAL INCLUDE member name.
- Display Application Performance Analyzer APAR number with Application Performance Analyzer version.
- Report the number of extents for each sampled volume of multi-volume datasets.
- Select an observation for reporting directly from the observation list.
- Report more than 999 PCBs per PSB.
- Source map PL/I programs using sequential SYSDEBUG source mapping files.
- Source map Java programs using jar files that reside on z/OS.
- Source map MVS C/C++ programs using DWARF files.
- Source map COBOL v6 programs using DWARF and Listing files.
- Additional lines available on the generated JOB statement for printed reports in ISPF.

Enhancements specific to the plugin include:

- Edit capability for the Source Program Mapping Repository.
- Add YEAR to Date/Time column.
- STC view supports multiple connections.
- Observation view supports selection of multiple observations.
- Reports list supports selection of multiple reports.

---

## 1.2 Application Performance Analyzer FMIDs

Application Performance Analyzer consists of the following FMIDs:

HAD0E00

JAD0E0J

JAD0E0K

---

## 2.0 Program Materials

An IBM program is identified by a program number. The program number for Application Performance Analyzer is 5655-Q49.

Basic Machine-Readable Materials are materials that are supplied under the base license and are required for the use of the product.

The program announcement material describes the features supported by Application Performance Analyzer. Ask your IBM representative for this information if you have not already received a copy.

---

### 2.1 Basic Machine-Readable Material

The distribution medium for this program is physical media or downloadable files. This program is in SMP/E RELFILE format and is installed by using SMP/E. See 6.0, "Installation Instructions" on page 23 for more information about how to install the program.

You can find information about the physical media for the basic machine-readable materials for Application Performance Analyzer in the *CBPDO Memo To Users Extension*.

Figure 1 describes the program file content for Application Performance Analyzer. You can refer to the *CBPDO Memo To Users Extension* to see where the files reside on the tape.

#### Notes:

1. The data set attributes in this table must be used in the JCL of jobs that read the data sets. However, because the data sets are in IEBCOPY unloaded format, their actual attributes might be different.
2. If any RELFILEs are identified as PDSEs, ensure that SMPTLIB data sets are allocated as PDSEs.

*Figure 1 (Page 1 of 2). Program File Content Application Performance Analyzer - Base*

<b>Name</b>	<b>O R G</b>	<b>R E C F M</b>	<b>L R E C L</b>	<b>BLK SIZE</b>
SMPMCS	SEQ	FB	80	3120
IBM.HAD0E00.F1	PDSE	U	0	6144
IBM.HAD0E00.F2	PDS	FB	80	8800
IBM.HAD0E00.F3	PDS	FB	80	8800
IBM.HAD0E00.F4	PDS	FB	80	8800
IBM.HAD0E00.F5	PDS	FB	80	8800

Figure 1 (Page 2 of 2). Program File Content Application Performance Analyzer - Base

<b>Name</b>	<b>O R G</b>	<b>R E C F M</b>	<b>L R E C L</b>	<b>BLK SIZE</b>
IBM.HAD0E00.F6	PDS	FB	80	8800
IBM.HAD0E00.F7	PDS	FB	80	8800
IBM.HAD0E00.F8	PDS	VB	1028	27998

Figure 2. Program File Content Application Performance Analyzer - Japanese

<b>Name</b>	<b>O R G</b>	<b>R E C F M</b>	<b>L R E C L</b>	<b>BLK SIZE</b>
SMPMCS	SEQ	FB	80	3120
IBM.JAD0E0J.F1	PDSE	U	0	6144
IBM.JAD0E0J.F2	PDS	FB	80	8800
IBM.JAD0E0J.F3	PDS	FB	80	8800
IBM.JAD0E0J.F4	PDS	FB	80	8800
IBM.JAD0E0J.F5	PDS	FB	80	8800
IBM.JAD0E0J.F6	PDS	FB	80	8800

Figure 3. Program File Content Application Performance Analyzer - Korean

<b>Name</b>	<b>O R G</b>	<b>R E C F M</b>	<b>L R E C L</b>	<b>BLK SIZE</b>
SMPMCS	SEQ	FB	80	3120
IBM.JAD0E0K.F1	PDSE	U	0	6144
IBM.JAD0E0K.F2	PDS	FB	80	8800
IBM.JAD0E0K.F3	PDS	FB	80	8800
IBM.JAD0E0K.F4	PDS	FB	80	8800
IBM.JAD0E0K.F5	PDS	FB	80	8800
IBM.JAD0E0K.F6	PDS	FB	80	8800

---

## 2.2 Optional Machine-Readable Material

No optional machine-readable materials are provided for Application Performance Analyzer.

---

## 2.3 Program Publications

The following sections identify the basic publications for Application Performance Analyzer.

Figure 4 identifies the basic unlicensed publications for Application Performance Analyzer. Those that are in softcopy format publications can be obtained from the IBM Publications Center website at: <http://www.ibm.com/shop/publications/order/>

<i>Figure 4. Basic Material: Unlicensed</i>		
<b>Publication Title</b>	<b>Form Number</b>	<b>Media Format</b>
IBM Application Performance Analyzer for z/OS License Information	LC27-8510	<a href="http://www.ibm.com/software/sla/sladb.nsf">http://www.ibm.com/software/sla/sladb.nsf</a>
IBM Application Performance Analyzer for z/OS User's Guide	SC27-8403	<a href="http://www.ibm.com/support/docview.wss?uid=swg27020942">http://www.ibm.com/support/docview.wss?uid=swg27020942</a>
IBM Application Performance Analyzer for z/OS Messages Guide	SC27-8402	<a href="http://www.ibm.com/software/awdtools/apa/library/">http://www.ibm.com/software/awdtools/apa/library/</a>
Application Performance Analyzer Customization Guide	SC27-8401	<a href="http://www.ibm.com/software/awdtools/apa/library/">http://www.ibm.com/software/awdtools/apa/library/</a>

---

## 2.4 Program Source Materials

No program source materials or viewable program listings are provided for Application Performance Analyzer.

---

## 2.5 Publications Useful During Installation

You might want to use the publications listed in Figure 5 during the installation of Application Performance Analyzer.

Figure 5. Publications Useful During Installation

<b>Publication Title</b>	<b>Form Number</b>	<b>Media Format</b>
<i>IBM SMP/E for z/OS User's Guide</i>	SA23-2277	<a href="http://www.ibm.com/shop/publications/order/">http://www.ibm.com/shop/publications/order/</a>
<i>IBM SMP/E for z/OS Commands</i>	SA23-2275	<a href="http://www.ibm.com/shop/publications/order/">http://www.ibm.com/shop/publications/order/</a>
<i>IBM SMP/E for z/OS Reference</i>	SA23-2276	<a href="http://www.ibm.com/shop/publications/order/">http://www.ibm.com/shop/publications/order/</a>
<i>IBM SMP/E for z/OS Messages, Codes, and Diagnosis</i>	GA32-0883	<a href="http://www.ibm.com/shop/publications/order/">http://www.ibm.com/shop/publications/order/</a>
<i>z/OS UNIX System Services Planning</i>	GA32-0884	<a href="http://www.ibm.com/shop/publications/order/">http://www.ibm.com/shop/publications/order/</a>
<i>z/OS UNIX System Services User's Guide</i>	SA23-2279	<a href="http://www.ibm.com/shop/publications/order/">http://www.ibm.com/shop/publications/order/</a>
<i>z/OS UNIX System Services Messages and Codes</i>	SA23-2284	<a href="http://www.ibm.com/shop/publications/order/">http://www.ibm.com/shop/publications/order/</a>

---

## 3.0 Program Support

This section describes the IBM support available for Application Performance Analyzer.

---

### 3.1 Program Services

Contact your IBM representative for specific information about available program services.

---

### 3.2 Preventive Service Planning

Before you install Application Performance Analyzer, make sure that you have reviewed the current Preventive Service Planning (PSP) information. Review the PSP Bucket for General Information, Installation Documentation, and the Cross Product Dependencies sections. For the Recommended Service section, instead of reviewing the PSP Bucket, it is recommended you use the IBM.ProductInstall-RequiredService fix category in SMP/E to ensure you have all the recommended service installed. Use the **FIXCAT(IBM.ProductInstall-RequiredService)** operand on the **APPLY CHECK command**. See 6.1.10, "Perform SMP/E APPLY" on page 31 for a sample APPLY command.

If you obtained Application Performance Analyzer as part of a CBPDO, HOLDDATA is included.

If the CBPDO for Application Performance Analyzer is older than two weeks by the time you install the product materials, you can obtain the latest PSP Bucket information by going to the following website:

<http://www14.software.ibm.com/webapp/set2/psearch/search?domain=psp>

You can also use S/390 SoftwareXcel or contact the IBM Support Center to obtain the latest PSP Bucket information.

For program support, access the Software Support Website at <http://www-01.ibm.com/software/support/>.

PSP Buckets are identified by UPGRADEs, which specify product levels; and SUBSETs, which specify the FMIDs for a product level. The UPGRADE and SUBSET values for Application Performance Analyzer are included in Figure 6.

*Figure 6. PSP Upgrade and Subset ID*

UPGRADE	SUBSET	Description
APAE00	HAD0E00	Application Performance Analyzer Base
	JAD0E0J	Application Performance Analyzer JPN
	JAD0E0K	Application Performance Analyzer KOR

---

### 3.3 Statement of Support Procedures

Report any problems which you feel might be an error in the product materials to your IBM Support Center. You may be asked to gather and submit additional diagnostics to assist the IBM Support Center in their analysis.

Figure 7 on page 10 identifies the component IDs (COMPID) for Application Performance Analyzer.

<i>Figure 7. Component IDs</i>			
<b>FMID</b>	<b>COMPID</b>	<b>Component Name</b>	<b>RETAIN Release</b>
HAD0E00	5655Q4900	Application Performance Analyzer	E00
JAD0E0J	5655Q4900	Application Performance Analyzer JPN	E0J
JAD0E0K	5655Q4900	Application Performance Analyzer KOR	E0K



---

## 4.0 Program and Service Level Information

This section identifies the program and relevant service levels of Application Performance Analyzer. The program level refers to the APAR fixes that have been incorporated into the program. The service level refers to the PTFs that have been incorporated into the program.

---

### 4.1 Program Level Information

The following APAR fixes against previous releases of Application Performance Analyzer have been incorporated into this release. They are listed by FMID.

- FMID HAD0D10

PI07819	PI28227	PI51519
PI09076	PI28845	PI54147
PI11017	PI32318	PI54391
PI14436	PI35391	PI54533
PI15584	PI38849	PI54688
PI21804	PI40482	PI58371
PI24275	PI42905	PI65083
PI25085	PI46867	

---

### 4.2 Service Level Information

No PTFs against this release of Application Performance Analyzer have been incorporated into the product package.

Frequently check the Application Performance Analyzer PSP Bucket for HIPER and SPECIAL attention PTFs against all FMIDs that you must install. You can also receive the latest HOLDDATA, then add the **FIXCAT(IBM.PRODUCTINSTALL-REQUIRESERVICE)** operand on your APPLY CHECK command. This will allow you to review the recommended and critical service that should be installed with your FMIDs.

---

## 5.0 Installation Requirements and Considerations

The following sections identify the system requirements for installing and activating Application Performance Analyzer. The following terminology is used:

- *Driving system*: the system on which SMP/E is executed to install the program.  
The program might have specific operating system or product level requirements for using processes, such as binder or assembly utilities during the installation.
- *Target system*: the system on which the program is configured and run.  
The program might have specific product level requirements, such as needing access to the library of another product for link-edits. These requirements, either mandatory or optional, might directly affect the element during the installation or in its basic or enhanced operation.

In many cases, you can use a system as both a driving system and a target system. However, you can make a separate IPL-able clone of the running system to use as a target system. The clone must include copies of all system libraries that SMP/E updates, copies of the SMP/E CSI data sets that describe the system libraries, and your PARMLIB and PROCLIB.

Use separate driving and target systems in the following situations:

- When you install a new level of a product that is already installed, the new level of the product will replace the old one. By installing the new level onto a separate target system, you can test the new level and keep the old one in production at the same time.
- When you install a product that shares libraries or load modules with other products, the installation can disrupt the other products. By installing the product onto a separate target system, you can assess these impacts without disrupting your production system.

---

### 5.1 Driving System Requirements

This section describes the environment of the driving system required to install Application Performance Analyzer.

#### 5.1.1 Machine Requirements

The driving system can run in any hardware environment that supports the required software.

#### 5.1.2 Programming Requirements

Figure 8. Driving System Software Requirements

Program Number	Product Name	Minimum VRM	Minimum Service Level will satisfy these APARs	Included in the shipped product?
Any <b>one</b> of the following:				
5694-A01	z/OS	V01.13.00	N/A	No
5650-ZOS	z/OS	V02.01.00	N/A	No

**Note:** SMP/E is a requirement for Installation and is an element of z/OS but can also be ordered as a separate product, 5655-G44, minimally V03.06.00.

**Note:** Installation might require migration to new z/OS releases to be service supported. See [http://www-03.ibm.com/systems/z/os/zos/support/zos\\_eos\\_dates.html](http://www-03.ibm.com/systems/z/os/zos/support/zos_eos_dates.html).

Application Performance Analyzer is installed into a file system, either HFS or zFS. Before installing Application Performance Analyzer, you must ensure that the target system file system data sets are available for processing on the driving system. OMVS must be active on the driving system and the target system file data sets must be mounted on the driving system.

If you plan to install Application Performance Analyzer in a zFS file system, this requires that zFS be active on the driving system. Information on activating and using zFS can be found in z/OS Distributed File Service zSeries File System Administration, SC24-5989.

---

## 5.2 Target System Requirements

This section describes the environment of the target system required to install and use Application Performance Analyzer.

Application Performance Analyzer installs in the z/OS (Z038) SREL.

### 5.2.1 Machine Requirements

Application Performance Analyzer requires one of the following IBM z System servers:

- z13 or z13s
- zEnterprise EC12 or BC12
- zEnterprise 196 or 114
- z10 Enterprise or Business Class

### 5.2.2 Programming Requirements

**5.2.2.1 Installation Requisites:** Installation requisites identify products that are required and *must* be present on the system or products that are not required but *should* be present on the system for the successful installation of this product.

Mandatory installation requisites identify products that are required on the system for the successful installation of this product.

Figure 9. Target System Mandatory Installation Requisites

Program Number	Product Name	Minimum VRM	Minimum Service Level will satisfy these APARs	Included in the shipped product?
Any <b>one</b> of the following:				
5694-A01	z/OS	V1.13.00	N/A	No
5650-ZOS	z/OS	V2.01.00	N/A	No

**Note**

Application Performance Analyzer V14.0 is tested and supported only for use with the currently supported levels of IBM software and hardware. If your operating system is an unsupported z/OS release (z/OS V1.12 or lower), IBM will undertake to fix any problems that you might encounter when running Application Performance Analyzer V14.0 on that level of unsupported product. However, IBM must be able to reproduce the problem using a supported level of the same product. If the problem can be reproduced and fixed, the fix will be developed and tested using the supported levels of IBM software. If a fix is made available, it is likely to work on the unsupported product level; however, IBM cannot guarantee that the fix will work in this case.

**Note:** Installation might require migration to new z/OS releases to be service supported. See [http://www-03.ibm.com/systems/z/os/zos/support/zos\\_eos\\_dates.html](http://www-03.ibm.com/systems/z/os/zos/support/zos_eos_dates.html).

Conditional installation requisites identify products that are *not* required for successful installation of this product but can resolve such things as certain warning messages at installation time.

Application Performance Analyzer has no conditional installation requisites.

**5.2.2.2 Operational Requisites:** Operational requisites are products that are required and *must* be present on the system or products that are not required but *should* be present on the system for this product to operate all or part of its functions.

Mandatory operational requisites identify products that are required for this product to operate its basic functions.

Application Performance Analyzer has no mandatory operational requisites.

Conditional operational requisites identify products that are *not* required for this product to operate its basic functions but are required at run time for this product to operate specific functions.

<i>Figure 10 (Page 1 of 2). Target System Conditional Operational Requisites</i>		
<b>Program Number</b>	<b>Product Name and Minimum VRM/Service Level</b>	<b>Function</b>
5696-234	High Level Assembler for MVS & VM & VSE V1.6	Debug of Assembler programs
5724-T07	Rational Developer for System z V8.5.x or V9.0.x	Remote debug on workstation
Any <b>one</b> of the following:		
5655-N02	WebSphere Application Server for z/OS V7.0 or later	MQ support
5655-W65	WebSphere Application Server for z/OS V8.0 or later	MQ support
Any <b>one</b> of the following:		
5655-R36	WebSphere MQ for z/OS V7.1 or later	MQ support
5724-H72	IBM MQ V8.0 or later	MQ support
Any <b>one</b> of the following:		
5655-R31	IBM 31-bit SDK for z/OS Java Technology Edition V6.0 or later	Java support
5655-R32	IBM 64-bit SDK for z/OS Java Technology Edition V6.0 or later	Java support
5655-W43	IBM 31-bit SDK for z/OS Java Technology Edition V7.0 or later	Java support
5655-W44	IBM 64-bit SDK for z/OS Java Technology Edition V7.0 or later	Java support
5655-DGG	IBM 31-bit SDK for z/OS Java Technology Edition V8.0 or later	Java support
5655-DGH	IBM 64-bit SDK for z/OS Java Technology Edition V8.0 or later	Java support
Any <b>one</b> of the following:		
5655-S97	CICS TS for z/OS V4.1 or later	CICS support

Figure 10 (Page 2 of 2). Target System Conditional Operational Requisites

<b>Program Number</b>	<b>Product Name and Minimum VRM/Service Level</b>	<b>Function</b>
5655-Y04	CICS TS for z/OS V5.1 or later	CICS support
5722-DFJ	CICS TS for z/OS Value Unit Edition V5.1 or later	CICS support
Any <b>one</b> of the following:		
5605-DB2	DB2 for z/OS V10	DB2 support
5697-P31	DB2 for z/OS Value Unit Edition, V10	DB2 support
5615-DB2	DB2 for z/OS V11	DB2 support
5697-P43	DB2 for z/OS Value Unit Edition, V11	DB2 support
Any <b>one</b> of the following:		
5635-A03	IMS V12	IMS support
5655-DSQ	IMS Database Value Unit Edition, V12	IMS support
5655-TM1	IMS Transaction Manager Value Unit Edition, V12	IMS support
5635-A04	IMS V13	IMS support
5655-DSM	IMS Database Value Unit Edition, V13	IMS support
5655-TM2	IMS Transaction Manager Value Unit Edition, V13	IMS support
5635-A05	IMS V14	IMS support
5655-DSE	IMS Database Value Unit Edition, V14	IMS support
5655-TM3	IMS Transaction Manager Value Unit Edition, V14	IMS support
Any <b>one</b> of the following:		
5694-A01	z/OS V1.13 (or later) C/C++ Element	Debug of C/C++ programs
5650-ZOS	z/OS V2.1 (or later) C/C++ Element	Debug of C/C++ programs
Any <b>one</b> of the following:		
5655-W67	IBM Enterprise PL/I for z/OS V4.2 or later	Debug of PL/I programs
5655-PL5	IBM Enterprise PL/I for z/OS V5.1 or later	Debug of PL/I programs
Any <b>one</b> of the following:		
5655-S71	IBM Enterprise COBOL for z/OS V4.2 or later	Debug of COBOL programs
5655-W32	IBM Enterprise COBOL for z/OS V5.1 or later	Debug of COBOL programs
5697-ECV	IBM Enterprise COBOL Value Unit Edition for z/OS V5.2 or later	Debug of COBOL programs
5655-EC6	IBM Enterprise COBOL for z/OS V6.1 or later	Debug of COBOL programs
5697-V61	IBM Enterprise COBOL Value Unit Edition for z/OS V6.1 or later	Debug of COBOL programs

**5.2.2.3 Toleration/Coexistence Requisites:** Toleration/coexistence requisites identify products that must be present on sharing systems. These systems can be other systems in a multisystem environment (not necessarily sysplex), a shared DASD environment (such as test and production), or systems that reuse the same DASD environment at different time intervals.

Application Performance Analyzer has no toleration/coexistence requisites.

**5.2.2.4 Incompatibility (Negative) Requisites:** Negative requisites identify products that must *not* be installed on the same system as this product.

Application Performance Analyzer has no negative requisites.

## 5.2.3 DASD Storage Requirements

Application Performance Analyzer libraries can reside on all supported DASD types.

Figure 11 lists the total space that is required for each type of library.

<i>Figure 11. Total DASD Space Required by Application Performance Analyzer - Base</i>		
<b>Library Type</b>	<b>Total Space Required in 3390 Trks</b>	<b>File System Description</b>
Target	945 Tracks	Target Datasets
Distribution	960 Tracks	Distribution Datasets
File System(s)	75 Tracks	/usr/lpp/IBM/apa/v14r0

<i>Figure 12. Total DASD Space Required by Application Performance Analyzer - Japanese</i>	
<b>Library Type</b>	<b>Total Space Required</b>
Target	255 Tracks
Distribution	255 Tracks

<i>Figure 13. Total DASD Space Required by Application Performance Analyzer - Korean</i>	
<b>Library Type</b>	<b>Total Space Required</b>
Target	255 Tracks
Distribution	255 Tracks

### Notes:

1. For non-RECFM U data sets, IBM recommends using system-determined block sizes for efficient DASD utilization. For RECFM U data sets, IBM recommends using a block size of 32760, which is most efficient from the performance and DASD utilization perspective.

2. Abbreviations used for data set types are shown as follows.

- U** Unique data set, allocated by this product and used by only this product. This table provides all the required information to determine the correct storage for this data set. You do not need to refer to other tables or program directories for the data set size.
- S** Shared data set, allocated by this product and used by this product and other products. To determine the correct storage needed for this data set, add the storage size given in this table to those given in other tables (perhaps in other program directories). If the data set already exists, it must have enough free space to accommodate the storage size given in this table.
- E** Existing shared data set, used by this product and other products. This data set is *not* allocated by this product. To determine the correct storage for this data set, add the storage size given in this table to those given in other tables (perhaps in other program directories). If the data set already exists, it must have enough free space to accommodate the storage size given in this table.

If you currently have a previous release of this product installed in these libraries, the installation of this release will delete the old release and reclaim the space that was used by the old release and any service that had been installed. You can determine whether these libraries have enough space by deleting the old release with a dummy function, compressing the libraries, and comparing the space requirements with the free space in the libraries.

For more information about the names and sizes of the required data sets, see 6.1.6, "Allocate SMP/E Target and Distribution Libraries" on page 28.

3. Abbreviations used for the file system path type are as follows.

- N** New path, created by this product.
- X** Path created by this product, but might already exist from a previous release.
- P** Previously existing path, created by another product.

4. All target and distribution libraries listed have the following attributes:

- The default name of the data set can be changed.
- The default block size of the data set can be changed.
- The data set can be merged with another data set that has equivalent characteristics.
- The data set can be either a PDS or a PDSE, except for SCAZAUTH and ACAZAUTH which must be PDSEs.

5. All target libraries listed have the following attributes:

- These data sets can be SMS-managed, but they are not required to be SMS-managed.
- These data sets are not required to reside on the IPL volume.
- The values in the "Member Type" column are not necessarily the actual SMP/E element types that are identified in the SMPMCS.

6. All target libraries that are listed and contain load modules have the following attributes:

- These data sets can be in the LPA, but they are not required to be in the LPA.
- SCAZLINK must be in the LNKLIST.
- SCAZLINK and SCAZAUTH must be APF-authorized.



7. Application Performance Analyzer requires that the SMPLTS data set must be a PDSE. If your existing SMPLTS is a PDS, you will need to allocate a new PDSE and copy your existing SMPLTS into it and then change the SMPLTS DDDEF entry to indicate the new PDSE data set.

The following figures describe the target, distribution libraries and file system paths required to install Application Performance Analyzer. The storage requirements of Application Performance Analyzer must be added to the storage required by other programs that have data in the same library or path.

**Note:** Use the data in these tables to determine which libraries can be merged into common data sets. In addition, since some ALIAS names may not be unique, ensure that no naming conflicts will be introduced before merging libraries.

*Figure 14. Storage Requirements for Application Performance Analyzer Target Libraries - Base*

Library DDNAME	Member Type	Target Volume	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
SCAZAUTH	LMOD	ANY	U	PDSE	U	0	600	N/A
SCAZDBRM	Data	ANY	U	PDS	FB	80	15	3
SCAZEXEC	EXEC	ANY	U	PDS	FB	80	30	6
SCAZLINK	LMOD	ANY	U	PDS	U	0	15	5
SCAZMENU	Message	ANY	U	PDS	FB	80	15	13
SCAZPENU	Panel	ANY	U	PDS	FB	80	225	120
SCAZSAMP	Sample	ANY	U	PDS	FB	80	30	16
SCAZTENU	Table	ANY	U	PDS	FB	80	15	2

*Figure 15. Storage Requirements for Application Performance Analyzer Target Libraries - Japanese*

Library DDNAME	Member Type	Target Volume	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
SCAZMJPN	Message	ANY	U	PDS	FB	80	15	13
SCAZPJPN	Panel	ANY	U	PDS	FB	80	225	120
SCAZTJPN	Table	ANY	U	PDS	FB	80	15	2

Figure 16. Storage Requirements for Application Performance Analyzer Target Libraries - Korean

Library DDNAME	Member Type	Target Volume	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
SCAZMKOR	Message	ANY	U	PDS	FB	80	15	13
SCAZPKOR	Panel	ANY	U	PDS	FB	80	225	120
SCAZTKOR	Table	ANY	U	PDS	FB	80	15	2

Figure 17. Application Performance Analyzer File System Paths

DDNAME	T Y P E	Path Name
SCAZPAX	N	/usr/lpp/IBM/apa/v14r0/IBM/

Figure 18. Storage Requirements for Application Performance Analyzer Distribution Libraries - Base

Library DDNAME	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
ACAZDBRM	U	PDS	FB	80	15	3
ACAZEXEC	U	PDS	FB	80	30	6
ACAZMENU	U	PDS	FB	80	15	13
ACAZMOD	U	PDSE	U	0	600	N/A
ACAZPAX	U	PDS	VB	1028	30	2
ACAZPENU	U	PDS	FB	80	225	120
ACAZSAMP	U	PDS	FB	80	30	16
ACAZTENU	U	PDS	FB	80	15	2

Figure 19. Storage Requirements for Application Performance Analyzer Distribution Libraries - Japanese

Library DDNAME	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
ACAZMJPN	U	PDS	FB	80	15	13

Figure 19. Storage Requirements for Application Performance Analyzer Distribution Libraries - Japanese

Library DDNAME	T Y P E	O R G G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
ACAZPJPN	U	PDS	FB	80	225	120
ACAZTJPN	U	PDS	FB	80	15	2

Figure 20. Storage Requirements for Application Performance Analyzer Distribution Libraries - Korean

Library DDNAME	T Y P E	O R G G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
ACAZMKOR	U	PDS	FB	80	15	13
ACAZPKOR	U	PDS	FB	80	225	120
ACAZTKOR	U	PDS	FB	80	15	2

The following figures list data sets that are not used by SMP/E, but are required for Application Performance Analyzer to run.

Figure 21. Storage Requirements for Application Performance Analyzer Non-SMP/E Data Sets

Data Set Name	T Y P E	O R G G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
CHECKPT	U	PS	F	2048	477	0
CAZLANGX <sup>1</sup>	U	PDS	VB	1562	10	10

**Note:**

1. This data set is required only if you want Application Performance Analyzer to process a side file. CAZLANGX is now being shipped as an alias in the IPV.SIPVMODA library of the Problem Determination Common Components product (5655-Q12). A copy of PDTCC is being provided free of charge. Please see the *IBM Application Performance Analyzer for z/OS User's Guide* for more information on installation and use.

---

## 5.3 FMIDs Deleted

Installing Application Performance Analyzer might result in the deletion of other FMIDs. To see which FMIDs will be deleted, examine the ++VER statement in the SMPMCS of the product.

If you do not want to delete these FMIDs at this time, install Application Performance Analyzer into separate SMP/E target and distribution zones.

**Note:** These FMIDs are not automatically deleted from the Global Zone. If you want to delete these FMIDs from the Global Zone, use the SMP/E REJECT NOFMID DELETEFMID command. See the SMP/E Commands book for details.

---

## 5.4 Special Considerations

A UID of 0 and READ access to the BPX.FILEATTR.APF facility class profile in order to successfully install the PAX file.

### **PDSE Considerations:**

Application Performance Analyzer uses the "partitioned data set extended" or PDSE format for the SCAZAUTH target library. There are some operational differences between PDS and PDSE data sets. The PDS format may be shared by more than one z/OS system and no special precautions are necessary. However the PDSE format may only be shared by z/OS systems which are part of a sysplex or which are connected using Global Resource Serialization (are in a GRS complex). If z/OS systems share use of a PDSE data set outside of a sysplex or GRS environment, you may experience severe problems when the data set is updated. This is due to the fact that PDSE directory information is cached in storage, and when the data set is updated from one system the other system(s) have no knowledge of the update, and their cached directory information will be incorrect.

You must take care not to share the SCAZAUTH data set between z/OS systems unless they are in a sysplex or are connected in a GRS complex. If you need to share the content of the SCAZAUTH data set, a separate copy must be created for each z/OS system.

---

## 6.0 Installation Instructions

This chapter describes the installation method and the step-by-step procedures to install and to activate the functions of Application Performance Analyzer.

Please note the following points:

- If you want to install Application Performance Analyzer into its own SMP/E environment, consult the SMP/E manuals for instructions on creating and initializing the SMPCSI and the SMP/E control data sets.
- You can use the sample jobs that are provided to perform part or all of the installation tasks. The SMP/E jobs assume that all DDDEF entries that are required for SMP/E execution have been defined in appropriate zones.
- You can use the SMP/E dialogs instead of the sample jobs to accomplish the SMP/E installation steps.

---

### 6.1 Installing Application Performance Analyzer

#### 6.1.1 SMP/E Considerations for Installing Application Performance Analyzer

Use the SMP/E RECEIVE, APPLY, and ACCEPT commands to install this release of Application Performance Analyzer.

#### 6.1.2 SMP/E Options Subentry Values

The recommended values for certain SMP/E CSI subentries are shown in Figure 22. Using values lower than the recommended values can result in failures in the installation. DSSPACE is a subentry in the GLOBAL options entry. PEMAX is a subentry of the GENERAL entry in the GLOBAL options entry. See the SMP/E manuals for instructions on updating the global zone.

<i>Figure 22. SMP/E Options Subentry Values</i>		
<b>Subentry</b>	<b>Value</b>	<b>Comment</b>
DSSPACE	(300,150,250)	Space allocation for SMPTLIB data
PEMAX	SMP/E Default	IBM recommends using the SMP/E default for PEMAX.

#### 6.1.3 Sample Jobs

The following sample installation jobs are provided as part of the product to help you install Application Performance Analyzer:

Figure 23. Sample Installation Jobs - Base

Job Name	Job Type	Description	RELFILE
CAZWSMPE (Optional)	SMP/E	Sample job to define and prime a new SMP/E CSI	IBM.HAD0E00.F4
CAZWRECV	RECEIVE	Sample RECEIVE job	IBM.HAD0E00.F4
CAZWALOC	ALLOCATE	Sample job to allocate target and distribution libraries	IBM.HAD0E00.F4
CAZWZFS	ALLOCATE	Sample job to allocate new ZFS data set (Optional)	IBM.HAD0E00.F4
CAZWISMK	MKDIR	Sample job to invoke the supplied CAZWMKDR EXEC to allocate paths	IBM.HAD0E00.F4
CAZWDDEF	DDDEF	Sample job to define SMP/E DDDEFs	IBM.HAD0E00.F4
CAZWAPLY	APPLY	Sample APPLY job	IBM.HAD0E00.F4
CAZWACPT	ACCEPT	Sample ACCEPT job	IBM.HAD0E00.F4

Figure 24. Sample Installation Jobs - Japanese

Job Name	Job Type	Description	RELFILE
CAZWRECV	RECEIVE	Sample RECEIVE job	IBM.JAD0E0J.F3
CAZWALOC	ALLOCATE	Sample job to allocate target and distribution libraries	IBM.JAD0E0J.F3
CAZWDEFJ	DDDEF	Sample job to define SMP/E DDDEFs	IBM.JAD0E0J.F3
CAZWAPLJ	APPLY	Sample APPLY job	IBM.JAD0E0J.F3
CAZWACPJ	ACCEPT	Sample ACCEPT job	IBM.JAD0E0J.F3

Figure 25. Sample Installation Jobs - Korean

Job Name	Job Type	Description	RELFILE
CAZWRECK	RECEIVE	Sample RECEIVE job	IBM.JAD0E0K.F3
CAZWALOK	ALLOCATE	Sample job to allocate target and distribution libraries	IBM.JAD0E0K.F3
CAZWDEFK	DDDEF	Sample job to define SMP/E DDDEFs	IBM.JAD0E0K.F3
CAZWAPLK	APPLY	Sample APPLY job	IBM.JAD0E0K.F3
CAZWACPK	ACCEPT	Sample ACCEPT job	IBM.JAD0E0K.F3

You can access the sample installation jobs by performing an SMP/E RECEIVE (refer to 6.1.5, “Perform SMP/E RECEIVE” on page 27) then copy the jobs from the RELFILES to a work data set for editing and submission. See Figure 23 on page 23 to find the appropriate relfile data set.

You can also copy the sample installation jobs from the tape or product files by submitting the following job. Depending on your distribution medium, use either the //TAPEIN or the //FILEIN DD statement and comment out or delete the other statement. Before you submit the job, add a job card and change the lowercase parameters to uppercase values to meet the requirements of your site.

To copy the sample jobs for the Application Performance Analyzer English components, use this JCL.

```
//STEP1 EXEC PGM=IEBCOPY
//SYSPRINT DD SYSOUT=*
//*****
//* Make the //TAPEIN DD statement below active if you install*
//* from a CBPDO tape by uncommenting the DD statement below. *
//*****
//*TAPEIN DD DSN=IBM.HAD0E00.F4,UNIT=tunit,
//* VOL=SER=volser,LABEL=(x,SL),
//* DISP=(OLD,KEEP)
//*****
//* Make the //TAPEIN DD statement below active if you install*
//* from a product tape received outside the CBPDO process *
//* (using the optional SMP/E RECEIVE job) by uncommenting *
//* the DD statement below. *
//*****
//*TAPEIN DD DSN=IBM.HAD0E00.F4,UNIT=tunit,
//* VOL=SER=AD0E00,LABEL=(4,SL),
//* DISP=(OLD,KEEP)
//*****
//* Make the //FILEIN DD statement below active for *
//* downloaded DASD files. *
//*****
//*FILEIN DD DSN=IBM.HAD0E00.F4,UNIT=SYSALLDA,DISP=SHR,
//* VOL=SER=filevol
//OUT DD DSN=jc1-library-name,
// DISP=(NEW,CATLG,DELETE),
// VOL=SER=dasdvol,UNIT=SYSALLDA,
// SPACE=(TRK,(20,10,5))
//SYSUT3 DD UNIT=SYSALLDA,SPACE=(CYL,(1,1))
//SYSIN DD *
COPY INDD=xxxxIN,OUTDD=OUT
/*
```

To copy the sample jobs for the Application Performance Analyzer Japanese components, use this JCL.

```
//STEP1 EXEC PGM=IEBCOPY
//SYSPRINT DD SYSOUT=*
//*****
//* Make the //TAPEIN DD statement below active if you install*
//* from a CBPDO tape by uncommenting the DD statement below. *
//*****
//*TAPEIN DD DSN=IBM.JAD0E0J.F4,UNIT=tunit,
//* VOL=SER=volser,LABEL=(x,SL),
```

```

//*          DISP=(OLD,KEEP)
/*****
/* Make the //TAPEIN DD statement below active if you install*
/* from a product tape received outside the CBPDO process   *
/* (using the optional SMP/E RECEIVE job) by uncommenting   *
/* the DD statement below.                                   *
/*****
/*TAPEIN   DD DSN=IBM.JAD0E0J.F4,UNIT=tunit,
/*          VOL=SER=AD0E0J,LABEL=(3,SL),
/*          DISP=(OLD,KEEP)
/*****
/* Make the //FILEIN DD statement below active for           *
/* downloaded DASD files.                                    *
/*****
/*FILEIN   DD DSN=IBM.JAD0E0J.F4,UNIT=SYSALLDA,DISP=SHR,
/*          VOL=SER=filevol
//OUT      DD DSNAME=jcl-library-name,
//          DISP=(NEW,CATLG,DELETE),
//          VOL=SER=dasdvol,UNIT=SYSALLDA,
//          SPACE=(TRK,(20,10,5))
//SYSUT3   DD UNIT=SYSALLDA,SPACE=(CYL,(1,1))
//SYSIN    DD *
          COPY INDD=xxxxIN,OUTDD=OUT
/*

```

To copy the sample jobs for the Application Performance Analyzer Korean components, use this JCL.

```

//STEP1    EXEC PGM=IEBCOPY
//SYSPRINT DD SYSOUT=*
/*****
/* Make the //TAPEIN DD statement below active if you install*
/* from a CBPDO tape by uncommenting the DD statement below. *
/*****
/*TAPEIN   DD DSN=IBM.JAD0E0K.F4,UNIT=tunit,
/*          VOL=SER=volser,LABEL=(x,SL),
/*          DISP=(OLD,KEEP)
/*****
/* Make the //TAPEIN DD statement below active if you install*
/* from a product tape received outside the CBPDO process   *
/* (using the optional SMP/E RECEIVE job) by uncommenting   *
/* the DD statement below.                                   *
/*****
/*TAPEIN   DD DSN=IBM.JAD0E0K.F4,UNIT=tunit,
/*          VOL=SER=AD0E0J,LABEL=(3,SL),
/*          DISP=(OLD,KEEP)
/*****
/* Make the //FILEIN DD statement below active for           *
/* downloaded DASD files.                                    *
/*****

```



```

//*FILEIN DD DSN=IBM.JAD0E0K.F4,UNIT=SYSALLDA,DISP=SHR,
//*      VOL=SER=filevol
//OUT DD DSNAME=jcl-library-name,
//      DISP=(NEW,CATLG,DELETE),
//      VOL=SER=dasdvol,UNIT=SYSALLDA,
//      SPACE=(TRK,(20,10,5))
//SYSUT3 DD UNIT=SYSALLDA,SPACE=(CYL,(1,1))
//SYSIN DD *
        COPY INDD=xxxxIN,OUTDD=OUT
/*

```

See the following information to update the statements in the previous sample:

**TAPEIN:**

**tunit** is the unit value that matches the product package.  
**volser** is the volume serial that matches the product package.  
**x** is the tape file number that indicates the location of the data set name on the tape.  
 See the documentation that is provided by CBPDO for the location of IBM.HAD0E00.F4, IBM.JAD0E0J.F4, and IBM.JAD0E0K.F4 on the tape.

**FILEIN:**

**filevol** is the volume serial of the DASD device where the downloaded files reside.

**OUT:**

**jcl-library-name** is the name of the output data set where the sample jobs are stored.  
**dasdvol** is the volume serial of the DASD device where the output data set resides.

**SYSIN:**

**xxxxIN** is either TAPEIN or FILEIN depending on your input DD statement.

## 6.1.4 Allocate and Initialize the SMP/E Data Sets (Optional)

You can install Application Performance Analyzer in the same SMP/E zone as z/OS V1.13.0 (or later), or in a different zone.

- If you install into existing SMP/E data sets, ensure that you have enough space.
- If you plan to install into an existing zone, the cluster should have already been allocated and primed. You can go on to the next step to perform an SMP/E RECEIVE.
- To install into a new zone, edit and submit sample job CAZWSMPE to define and prime a new SMP/E CSI cluster. Consult the instructions in the sample job for more information.

**Expected Return Codes and Messages:** You will receive a return code of 0 if the job runs correctly.

## 6.1.5 Perform SMP/E RECEIVE

If you have obtained Application Performance Analyzer as part of a CBPDO, use the RCVPDO job in the CBPDO RIMLIB data set to receive the Application Performance Analyzer FMIDs, service, and HOLDDATA that are included on the CBPDO package. For more information, see the documentation that is included in the CBPDO.

You can also choose to edit and submit sample job CAZWRECV to perform the SMP/E RECEIVE for Application Performance Analyzer. Consult the instructions in the sample job for more information.

If your order contains the Japanese feature, edit and submit sample job CAZWRECJ to perform the SMP/E RECEIVE for that feature. Consult the instructions in the sample job for more information.

If your order contains the Korean feature, edit and submit sample job CAZWRECK to perform the SMP/E RECEIVE for that feature. Consult the instructions in the sample job for more information.

**Expected Return Codes and Messages:** For all RECEIVE jobs above, you will receive a return code of 0 if the job(s) runs correctly.

## 6.1.6 Allocate SMP/E Target and Distribution Libraries

Edit and submit sample job CAZWALOC to allocate the SMP/E target and distribution libraries for Application Performance Analyzer. Consult the instructions in the sample job for more information.

If your order contains the Japanese feature, edit and submit sample job CAZWALOJ to allocate the SMP/E target and distribution libraries for that feature. Consult the instructions in the sample job for more information.

If your order contains the Korean feature, edit and submit sample job CAZWALOK to allocate the SMP/E target and distribution libraries for that feature. Consult the instructions in the sample job for more information.

**Expected Return Codes and Messages:** For all the ALLOCATE jobs, you will receive a return code of 0 if the job(s) runs correctly.

## 6.1.7 Allocate, create and mount ZFS Files (Optional)

This job allocates, creates a mountpoint, and mounts zFS data sets.

If you plan to install Application Performance Analyzer into a new z/OS UNIX file system, you can edit and submit the optional CAZWZFS job to perform the following tasks:

- Create the z/OS UNIX file system
- Create a mount point
- Mount the z/OS UNIX file system on the mountpoint

Consult the instructions in the sample job for more information.

The recommended z/OS UNIX file system type is *zFS*. The recommended mount point is */usr/lpp/IBM/apa/v14r0*.

Before running the sample job to create the z/OS UNIX file system, you must ensure that OMVS is active on the driving system. zFS must be active on the driving system if you are installing Application Performance Analyzer into a file system that is zFS.

If you create a new file system for this product, consider updating the BPXPRMxx PARMLIB member to mount the new file system at IPL time. This action can be helpful if an IPL occurs before the installation is completed.

```
MOUNT FILESYSTEM('#dsn')
MOUNTPOINT('/usr/lpp/IBM/apa/v14r0')
MODE(RDRW) /* can be MODE(READ) */
TYPE(ZFS) PARM('AGGRGROW') /* zFS, with extents */
```

See the following information to update the statements in the previous sample:

**#dsn** is the name of the data set holding the z/OS UNIX file system.  
**/usr/lpp/IBM/apa/v14r0** is the name of the mount point where the z/OS UNIX file system will be mounted.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

## 6.1.8 Allocate File System Paths

The target system HFS or zFS data set must be mounted on the driving system when running the sample CAZWISMK job since the job will create paths in the HFS or zFS.

Before running the sample job to create the paths in the file system, you must ensure that OMVS is active on the driving system and that the target system's HFS or zFS file system is mounted to the driving system. zFS must be active on the driving system if you are installing Application Performance Analyzer into a file system that is zFS.

If you plan to install Application Performance Analyzer into a new HFS or zFS file system, you must create the mountpoint and mount the new file system to the driving system for Application Performance Analyzer.

The recommended mountpoint is */usr/lpp/IBM/apa/v14r0*.

Edit and submit sample job CAZWISMK to allocate the HFS or zFS paths for Application Performance Analyzer. Consult the instructions in the sample job for more information.

If you create a new file system for this product, consider updating the BPXPRMxx PARMLIB member to mount the new file system at IPL time. This action can be helpful if an IPL occurs before the installation is completed.

**Expected Return Codes and Messages:** You will receive a return code of 0 if the job runs correctly.

## 6.1.9 Create DDDEF Entries

If you choose to install Application Performance Analyzer V14.0 in the **SAME** Target Zone as prior releases (V13.1 or lower), you must run a Dummy Delete job to delete the prior release before you run the new CAZWDDEF job. Failure to delete the prior release will cause an abend on the APPLY if installed in the same Zone. Otherwise, install Application Performance Analyzer in a new Target Zone and continue to the CAZWDDEF job.

Provided is a partial example of code to accomplish the delete. It is not intended to be run as-is. The prior release in this instance is HAD0D10 (V13.1). If you have other releases you will need to run the dummy delete for all. Once you have successfully deleted the prior version, you can continue to the CAZWDDEF job.

```
++FUNCTION(DUMMY01).
++VER (Z038)
  DELETE(HAD0D10).
//SMPCTL DD *
  SET BDY(GLOBAL).
  RECEIVE S(DUMMY01).
  SET BDY(TZONE).
  APPLY S(DUMMY01) REDO.
  SET BDY(DZONE).
  ACCEPT S(DUMMY01) BYPASS(APPLYCHECK) REDO .
  SET BDY(TZONE).
  UCLIN.
  DEL SYSMOD(HAD0D10).
  DEL SYSMOD(DUMMY01).
  ENDUCL.
  SET BDY(DZONE).
  UCLIN.
  DEL SYSMOD(HAD0D10).
  DEL SYSMOD(DUMMY01).
  ENDUCL.
/*
```

Edit and submit sample job CAZWDDEF to create DDDEF entries for the SMP/E target and distribution libraries for Application Performance Analyzer. Consult the instructions in the sample job for more information.

If your order contains the Japanese feature, edit and submit sample job CAZWDEFJ to create DDDEF entries for that feature. Consult the instructions in the sample job for more information.

If your order contains the Korean feature, edit and submit sample job CAZWDEFK to create DDDEF entries for that feature. Consult the instructions in the sample job for more information.

**Expected Return Codes and Messages:** For all the DDDEF jobs, you will receive a return code of 0 if the job(s) runs correctly.

## 6.1.10 Perform SMP/E APPLY

1. Ensure that you have the latest HOLDDATA; then edit and submit sample job CAZWAPLY to perform an SMP/E APPLY CHECK for Application Performance Analyzer. Consult the instructions in the sample job for more information.

If your order contains the Japanese feature, edit and submit sample job CAZWAPLJ to perform an SMP/E APPLY CHECK for that feature. Consult the instructions in the sample job for more information.

If your order contains the Korean feature, edit and submit sample job CAZWAPLK to perform an SMP/E APPLY CHECK for that feature. Consult the instructions in the sample job for more information.

The latest HOLDDATA is available through several different portals, including <http://service.software.ibm.com/holddata/390holddata.html>. The latest HOLDDATA may identify HIPER and FIXCAT APARs for the FMIDs you will be installing. An APPLY CHECK will help you determine if any HIPER or FIXCAT APARs are applicable to the FMIDs you are installing. If there are any applicable HIPER or FIXCAT APARs, the APPLY CHECK will also identify fixing PTFs that will resolve the APARs, if a fixing PTF is available.

You should install the FMIDs regardless of the status of unresolved HIPER or FIXCAT APARs. However, do not deploy the software until the unresolved HIPER and FIXCAT APARs have been analyzed to determine their applicability. That is, before deploying the software either ensure fixing PTFs are applied to resolve all HIPER or FIXCAT APARs, or ensure the problems reported by all HIPER or FIXCAT APARs are not applicable to your environment.

To receive the full benefit of the SMP/E Causer SYSMOD Summary Report, do *not* bypass the PRE, ID, REQ, and IFREQ on the APPLY CHECK. The SMP/E root cause analysis identifies the cause only of *errors* and not of *warnings* (SMP/E treats bypassed PRE, ID, REQ, and IFREQ conditions as warnings, instead of errors).

Here are sample APPLY commands:

- a. To ensure that all recommended and critical service is installed with the FMIDs, receive the latest HOLDDATA and use the APPLY CHECK command as follows

```
APPLY S(fmid,fmid,...) CHECK
FORFMID(fmid,fmid,...)
SOURCEID(RSU*)
FIXCAT(IBM.ProductInstall-RequiredService)
GROUPEXTEND .
```

Some HIPER APARs might not have fixing PTFs available yet. You should analyze the symptom flags for the unresolved HIPER APARs to determine if the reported problem is applicable to your environment and if you should bypass the specific ERROR HOLDS in order to continue the installation of the FMIDs.

This method requires more initial research, but can provide resolution for all HIPERs that have fixing PTFs available and are not in a PE chain. Unresolved PEs or HIPERs might still exist and require the use of BYPASS.

- b. To install the FMIDs without regard for unresolved HIPER APARs, you can add the BYPASS(HOLDCLASS(HIPER)) operand to the APPLY CHECK command. This will allow you to install FMIDs even though one or more unresolved HIPER APARs exist. After the FMIDs are installed, use the SMP/E REPORT ERRSYSMODS command to identify unresolved HIPER APARs and any fixing PTFs.

```
APPLY S(fmid,fmid,...) CHECK
FORFMID(fmid,fmid,...)
SOURCEID(RSU*)
FIXCAT(IBM.ProductInstall-RequiredService)
GROUPEXTEND
BYPASS(HOLDCLASS(HIPER),HOLDFIXCAT) .
..any other parameters documented in the program directory
```

This method is quicker, but requires subsequent review of the Exception SYSMOD report produced by the REPORT ERRSYSMODS command to investigate any unresolved HIPERs. If you have received the latest HOLDDATA, you can also choose to use the REPORT MISSINGFIX command and specify Fix Category IBM.ProductInstall-RequiredService to investigate missing recommended service.

If you bypass HOLDs during the installation of the FMIDs because fixing PTFs are not yet available, you can be notified when the fixing PTFs are available by using the APAR Status Tracking (AST) function of ServiceLink or the APAR Tracking function of ResourceLink.

2. After you take actions that are indicated by the APPLY CHECK, remove the CHECK operand and run the job again to perform the APPLY.

**Note:** The GROUPEXTEND operand indicates that SMP/E applies all requisite SYSMODs. The requisite SYSMODS might be applicable to other functions.

**Expected Return Codes and Messages from APPLY CHECK:** For all the APPLY CHECK jobs, you will receive a return code of 0 if the job(s) run correctly.

**Expected Return Codes and Messages from APPLY:** For all the APPLY jobs, you will receive a return code of 0 if the job(s) run correctly.

### 6.1.11 Perform SMP/E ACCEPT

Edit and submit sample job CAZWACPT to perform an SMP/E ACCEPT CHECK for Application Performance Analyzer. Consult the instructions in the sample job for more information.

If your order contains the Japanese feature, edit and submit sample job CAZWACPJ to perform an SMP/E ACCEPT CHECK for that feature. Consult the instructions in the sample job for more information.

If your order contains the Korean feature, edit and submit sample job CAZWACPK to perform an SMP/E ACCEPT CHECK for that feature. Consult the instructions in the sample job for more information.

To receive the full benefit of the SMP/E Causer SYSMOD Summary Report, do *not* bypass the PRE, ID, REQ, and IFREQ on the ACCEPT CHECK. The SMP/E root cause analysis identifies the cause of *errors*

but not *warnings* (SMP/E treats bypassed PRE, ID, REQ, and IFREQ conditions as warnings rather than errors).

Before you use SMP/E to load new distribution libraries, it is recommended that you set the ACCJCLIN indicator in the distribution zone. In this way, you can save the entries that are produced from JCLIN in the distribution zone whenever a SYSMOD that contains inline JCLIN is accepted. For more information about the ACCJCLIN indicator, see the description of inline JCLIN in the SMP/E Commands book for details.

After you take actions that are indicated by the ACCEPT CHECK, remove the CHECK operand and run the job again to perform the ACCEPT.

**Note:** The GROUPEXTEND operand indicates that SMP/E accepts all requisite SYSMODs. The requisite SYSMODS might be applicable to other functions.

**Expected Return Codes and Messages from ACCEPT CHECK:** For all ACCEPT CHECK jobs, you will receive a return code of 0 if the job(s) run correctly.

If PTFs that contain replacement modules are accepted, SMP/E ACCEPT processing will link-edit or bind the modules into the distribution libraries. During this processing, the Linkage Editor or Binder might issue messages that indicate unresolved external references, which will result in a return code of 4 during the ACCEPT phase. You can ignore these messages, because the distribution libraries are not executable and the unresolved external references do not affect the executable system libraries.

**Expected Return Codes and Messages from ACCEPT:** For all the ACCEPT jobs, you will receive a return code of 0 if the job(s) run correctly

## 6.1.12 Run REPORT CROSSZONE

The SMP/E REPORT CROSSZONE command identifies requisites for products that are installed in separate zones. This command also creates APPLY and ACCEPT commands in the SMPPUNCH data set. You can use the APPLY and ACCEPT commands to install those cross-zone requisites that the SMP/E REPORT CROSSZONE command identifies.

After you install Application Performance Analyzer, it is recommended that you run REPORT CROSSZONE against the new or updated target and distribution zones. REPORT CROSSZONE requires a global zone with ZONEINDEX entries that describe all the target and distribution libraries to be reported on.

For more information about REPORT CROSSZONE, see the SMP/E manuals.

### 6.1.13 Cleaning Up Obsolete Data Sets, Paths, and DDDEFs

The following file system paths, which were created and used by previous releases of this product, are no longer used in this release. You can delete these obsolete file system paths after you delete the previous release from your system.

- /usr/lpp/apa/v13r1

---

## 6.2 Activating Application Performance Analyzer

### 6.2.1 File System Execution

If you mount the file system in which you have installed Application Performance Analyzer in read-only mode during execution, then you do not have to take further actions to activate Application Performance Analyzer.

### 6.2.2 Product Customization

The publication *Application Performance Analyzer Customization Guide* (SC27-8401) contains the necessary information to customize and use Application Performance Analyzer.



---

## 7.0 Notices

This information was developed for products and services offered in the U.S.A. IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

APAR numbers are provided in this document to assist in locating PTFs that may be required. Ongoing problem reporting may result in additional APARs being created. Therefore, the APAR lists in this document may not be complete. To obtain current service recommendations and to identify current product service requirements, always contact the IBM Customer Support Center or use S/390 SoftwareXcel to obtain the current "PSP Bucket".

IBM may have patents or pending patent applications covering subject matter in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to the

IBM Director of Licensing  
IBM Corporation  
North Castle Drive  
Armonk, New York 10504-1785  
USA

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing  
Legal and Intellectual Property Law  
IBM Japan, Ltd.  
19-21, Nihonbashi-Hakozakicho, Chuo-ku  
Tokyo 103-8510, Japan

---

## 7.1 Other Notices

NOTICES.TXT can be found in CAZNOTIC in the SCAZSAMP PDS.

---

## 7.2 Trademarks

IBM, the IBM logo, and [ibm.com](http://ibm.com) are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at [www.ibm.com/legal/copytrade.shtml](http://www.ibm.com/legal/copytrade.shtml).

---

## Reader's Comments

### Program Directory for IBM Application Performance Analyzer for z/OS, September 2016

We appreciate your input on this publication. Feel free to comment on the clarity, accuracy, and completeness of the information or give us any other feedback that you might have.

Use one of the following methods to send us your comments:

1. Send an email to [comments@us.ibm.com](mailto:comments@us.ibm.com)
2. Use the form on the Web at:

[www.ibm.com/software/data/rcf](http://www.ibm.com/software/data/rcf)

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

IBM or any other organizations will only use the personal information that you supply to contact you about the issues that you submit.

Thank you for your participation.



Printed in USA

G113-4303-00

