

Content Manager OnDemand
Version 10 Release 1

Messages and Codes



Note

Before using this information and the product it supports, read the information in [“Notices” on page 547.](#)

This edition applies to the following products and to all subsequent releases and modifications until otherwise indicated in new editions:

- IBM® Content Manager OnDemand for z/OS®, Version 10 Release 1
- IBM Content Manager OnDemand for Multiplatforms, Version 10 Release 1
- IBM Content Manager OnDemand for i, Version 7 Release 3

© **Copyright 2017 - 2018 All Rights Reserved. UNICOM Systems, Inc. – a division of UNICOM Global.**

© **Copyright International Business Machines Corporation 2001, 2018.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

- ibm.com® and related resources..... xli**
 - Contacting IBM..... xli
- How this guide is organized..... xlii**
- Conventions..... xliii**
- Accessibility information for Content Manager OnDemand..... xliv**

- Chapter 1. Server messages..... 1**
 - Other message sources..... 1
 - Message identifiers..... 1
 - Common server messages..... 2
 - ARS000E..... 2
 - ARS0013E..... 2
 - ARS0014I..... 3
 - ARS0015E..... 3
 - ARS0016E..... 3
 - ARS0020E..... 3
 - ARS0021E..... 5
 - ARS0022E..... 6
 - ARS0023E..... 6
 - ARS0024E..... 6
 - ARS0025E..... 6
 - ARS0026E..... 7
 - ARS0027E..... 7
 - ARS0030I..... 7
 - ARS0031W..... 7
 - ARS0032I..... 8
 - ARS0033I..... 8
 - ARS0034I..... 8
 - ARS0035I..... 8
 - ARS0036I..... 9
 - ARS0037I..... 9
 - ARS0038W..... 9
 - ARS0039I..... 9
 - ARS0040I..... 10
 - ARS0041I..... 10
 - ARS0042I..... 10
 - ARS0043I..... 10
 - ARS0044I..... 11
 - ARS0045I..... 11
 - ARS0046I..... 11
 - ARS0047I..... 12
 - ARS0048I..... 12
 - ARS0049I..... 12
 - ARS0050I..... 12
 - ARS0051I..... 13
 - ARS0052I..... 13
 - ARS0053I..... 13
 - ARS0054I..... 13
 - ARS0055I..... 14
 - ARS0056I..... 14
 - ARS0057I..... 14

ARS0058I.....	14
ARS0059I.....	15
ARS0060I.....	15
ARS0061I.....	15
ARS0062I.....	16
ARS0063I.....	16
ARS0064I.....	16
ARS0065I.....	16
ARS0066I.....	17
ARS0067I.....	17
ARS0068I.....	17
ARS0069I.....	18
ARS0070I.....	18
ARS0071I.....	18
ARS0072I.....	18
ARS0073I.....	19
ARS0074I.....	19
ARS0075I.....	19
ARS0076I.....	19
ARS0077I.....	19
ARS0078I.....	19
ARS0079I.....	20
ARS0080I.....	20
ARS0081I.....	20
ARS0082I.....	20
ARS0083I.....	21
ARS0084I.....	21
ARS0085I.....	21
ARS0086I.....	22
ARS0087I.....	22
ARS0088E.....	22
ARS0089I.....	23
ARS0090I.....	23
ARS0091I.....	23
ARS0092I.....	23
ARS0093I.....	24
ARS0094I.....	24
ARS0095I.....	24
ARS0096I.....	24
ARS0097I.....	24
ARS0100I.....	24
ARS0101I.....	25
ARS0102I.....	25
ARS0103I.....	25
ARS0106E.....	26
ARS0107E.....	26
ARS0108E.....	26
ARS0109I.....	27
ARS0110I.....	27
ARS0111E.....	27
ARS0112E.....	27
ARS0113E.....	28
ARS0114E.....	28
ARS0115E.....	28
ARS0116E.....	28
ARS0117E.....	29
ARS0118E.....	29
ARS0119E.....	29

ARS0122E.....	29
ARS0123E.....	30
ARS0124I.....	30
ARS0125E.....	30
ARS0126I.....	31
ARS0127I.....	31
ARS0128I.....	31
ARS0129E.....	31
ARS0130E.....	32
ARS0131E.....	32
ARS0132I.....	32
ARS0133I.....	32
ARS0134I.....	32
ARS0135I.....	33
ARS0136I.....	33
ARS0137I.....	33
ARS0138E.....	33
ARS0139E.....	33
ARS0140E.....	34
ARS0141E.....	34
ARS0142E.....	34
ARS0145E.....	34
ARS0146E.....	35
ARS0147E.....	35
ARS0149E.....	35
ARS0150E.....	35
ARS0151E.....	35
ARS0152E.....	36
ARS0153E.....	36
ARS0154E.....	36
ARS0155E.....	36
ARS0157E.....	37
ARS0158E.....	37
ARS0159E.....	37
ARS0160E.....	37
ARS0161E.....	38
ARS0162E.....	39
ARS0163E.....	39
ARS0164I.....	39
ARS0165I.....	39
ARS0166I.....	40
ARS0167I.....	40
ARS0168E.....	40
ARS0169E.....	41
ARS0171E.....	41
ARS0172E.....	41
ARS0173I.....	41
ARS0174I.....	41
ARS0175E.....	42
ARS0176E.....	42
ARS0178E.....	42
ARS0179E.....	42
ARS0186I.....	42
ARS0187E.....	43
ARS0188E.....	43
ARS0189E.....	43
ARS0190E.....	43
ARS0191I.....	44

ARS0192E.....	44
ARS0193E.....	44
ARS0194E.....	44
ARS0195E.....	44
ARS0196I.....	45
ARS0197I.....	45
ARS0198E.....	45
ARS0199E.....	46
ARS0200E.....	46
ARS0201I.....	46
ARS0204I.....	46
ARS0205I.....	47
ARS0206I.....	47
ARS0207I.....	47
ARS0208I.....	47
ARS0209I.....	47
ARS0210I.....	48
ARS0211I.....	48
ARS0212I.....	48
ARS0213I.....	48
ARS0214I.....	49
ARS0215I.....	49
ARS0216E.....	49
ARS0217E.....	49
ARS0218E.....	49
ARS0219E.....	50
ARS0220I.....	50
ARS0221I.....	50
ARS0222W.....	50
ARS0226I.....	51
ARS0227W.....	51
ARS0228E.....	51
ARS0229I.....	51
ARS0230I.....	51
ARS0231I.....	51
ARS0232I.....	52
ARS0233I.....	52
ARS0234I.....	52
ARS0235I.....	52
ARS0236I.....	52
ARS0237E.....	53
ARS0238E.....	53
ARS0239E.....	53
ARS0240E.....	53
ARS0241E.....	53
ARS0242E.....	54
ARS0243E.....	54
ARS0244E.....	54
ARS0246W.....	54
ARS0247I.....	54
ARS0248I.....	55
ARS0249I.....	55
ARS0250I.....	55
ARS0251I.....	55
ARS0252I.....	55
ARS0253I.....	56
ARS0254I.....	56
ARS0255I.....	56

ARS0256I.....	56
ARS0257E.....	56
ARS0258I.....	57
ARS0259E.....	57
ARS0260I.....	57
ARS0261E.....	57
ARS0262I.....	57
ARS0263E.....	58
ARS0264I.....	58
ARS0265E.....	58
ARS0266I.....	58
ARS0267E.....	58
ARS0268I.....	59
ARS0269E.....	59
ARS0270I.....	59
ARS0271E.....	59
ARS0272I.....	59
ARS0273E.....	60
ARS0275I.....	60
ARS0276E.....	60
ARS0277I.....	60
ARS0278E.....	60
ARS0279I.....	61
ARS0280E.....	61
ARS0281I.....	61
ARS0282E.....	61
ARS0283I.....	61
ARS0284E.....	62
ARS0285I.....	63
ARS0286I.....	63
ARS0287I.....	63
ARS0288I.....	63
ARS0289E.....	63
ARS0290E.....	63
ARS0291I.....	63
ARS0292E.....	63
ARS0293I.....	63
ARS0294I.....	63
ARS0295I.....	63
ARS0296E.....	63
ARS0297I.....	63
ARS0298I.....	63
ARS0299I.....	63
ARS0300I.....	63
ARS0301I.....	63
ARS0302I.....	64
ARS0303I.....	64
ARS0304I.....	64
ARS0305I.....	64
ARS0306I.....	64
ARS0307I.....	64
ARS0329I.....	64
ARS0330I.....	64
ARS0331E.....	64
ARS0333W.....	65
ARS0334E.....	65
ARS0335E.....	65
ARS0344E.....	65

ARS0346E.....	65
ARS0347E.....	66
ARS0348E.....	66
ARS0349E.....	66
ARS0350E.....	66
ARS0351I.....	66
ARS0352I.....	67
ARS0353I.....	67
ARS0354I.....	67
ARS0355I.....	67
ARS0356I.....	67
ARS0357I.....	67
ARS0358I.....	68
ARS0359I.....	68
ARS0360I.....	68
ARS0364I.....	68
ARS0365I.....	68
ARS0366I.....	69
ARS0367I.....	69
ARS0368I.....	69
ARS0369I.....	69
ARS0370I.....	69
ARS0371I.....	70
ARS0372I.....	70
ARS0373I.....	70
ARS0374I.....	70
ARS0375I.....	70
ARS0376I.....	70
ARS0377I.....	71
ARS0378I.....	71
ARS0379I.....	71
ARS0380I.....	71
ARS0381I.....	71
ARS0382I.....	72
ARS0383I.....	72
ARS0384E.....	72
ARS0385W.....	72
ARS0389I.....	72
ARS0390I.....	73
ARS0391I.....	73
ARS0392I.....	73
ARS0393D.....	73
ARS0394I.....	73
ARS0395I.....	74
ARS0396I.....	74
ARS0397I.....	74
ARS0398E.....	74
ARS0399I.....	74
ARS0400E.....	75
ARS0401I.....	75
ARS0402E.....	75
ARS0403I.....	75
ARS0404E.....	75
ARS0405I.....	76
ARS0406E.....	76
ARS0407I.....	76
ARS0408E.....	76
ARS0409E.....	76

ARS0410W.....	77
ARS0429E.....	77
ARS0430E.....	77
ARS0431E.....	77
ARS0432E.....	77
ARS0433E.....	78
ARS0434E.....	78
ARS0436E.....	78
ARS0437E.....	78
ARS0438I.....	78
ARS0439E.....	79
ARS0443I.....	79
ARS0444I.....	79
ARS0445I.....	79
ARS0446E.....	79
ARS0447W.....	80
ARS0448E.....	80
ARS0449E.....	80
ARS0450E.....	80
ARS0452E.....	80
ARS0453E.....	81
ARS0454E.....	81
ARS0455E.....	81
ARS0456I.....	81
ARS0457E.....	81
ARS0458E.....	82
ARS0459E.....	82
ARS0777I.....	82
ARS0980I.....	82
ARS0981E.....	83
ARS1000I.....	83
ARS1001I.....	83
ARS1002I.....	84
ARS1003I.....	84
ARS1004I.....	85
ARS1005I.....	85
ARS1006I.....	86
ARS1007I.....	86
ARS1008I.....	87
ARS1009I.....	87
ARS1010I.....	88
ARS1011I.....	88
ARS1012I.....	89
ARS1013I.....	89
ARS1014I.....	90
ARS1015I.....	90
ARS1016I.....	90
ARS1017E.....	91
ARS1018E.....	91
ARS1019E.....	91
ARS1020E.....	92
ARS1023E.....	92
ARS1024I.....	92
ARS1025I.....	92
ARS1026E.....	93
ARS1027E.....	93
ARS1028I.....	93
ARS1029E.....	93

ARS1102E.....	94
ARS1103E.....	94
ARS1104E.....	94
ARS1105E.....	94
ARS1106E.....	94
ARS1107E.....	95
ARS1108E.....	95
ARS1109E.....	95
ARS1110E.....	95
ARS1111E.....	95
ARS1112E.....	96
ARS1113E.....	96
ARS1114E.....	96
ARS1115E.....	96
ARS1116E.....	97
ARS1117E.....	97
ARS1118E.....	97
ARS1119E.....	97
ARS1120E.....	97
ARS1121E.....	98
ARS1122E.....	98
ARS1123E.....	98
ARS1124E.....	98
ARS1125E.....	98
ARS1126E.....	99
ARS1127E.....	99
ARS1128E.....	99
ARS1129E.....	99
ARS1130E.....	99
ARS1131E.....	100
ARS1132I.....	100
ARS1133I.....	100
ARS1134E.....	100
ARS1135E.....	100
ARS1136E.....	101
ARS1137E.....	101
ARS1138W.....	101
ARS1139E.....	101
ARS1140I.....	101
ARS1141I.....	102
ARS1142I.....	102
ARS1143I.....	102
ARS1144I.....	102
ARS1145E.....	102
ARS1146I.....	103
ARS1147I.....	103
ARS1148E.....	103
ARS1149E.....	103
ARS1150E.....	103
ARS1154W.....	104
ARS1155E.....	104
ARS1156E.....	104
ARS1157E.....	104
ARS1158E.....	104
ARS1159E.....	105
ARS1160E.....	105
ARS1161E.....	105
ARS1162E.....	105

ARS1163E.....	105
ARS1164E.....	106
ARS1165E.....	106
ARS1166E.....	106
ARS1167E.....	106
ARS1168E.....	106
ARS1169W.....	107
ARS1170W.....	107
ARS1171E.....	107
ARS1172E.....	107
ARS1173E.....	107
ARS1174E.....	108
ARS1175I.....	108
ARS1176E.....	108
ARS1179E.....	108
ARS1181E.....	108
ARS1182E.....	109
ARS1183E.....	109
ARS1184I.....	109
ARS1185W.....	109
ARS1186I.....	109
ARS1187W.....	110
ARS1188E.....	110
ARS1189W.....	110
ARS1190E.....	110
ARS1191E.....	110
ARS1192I.....	110
ARS1193I.....	111
ARS1194I.....	111
ARS1195I.....	111
ARS1196E.....	111
ARS1197E.....	111
ARS1198E.....	112
ARS1199W.....	112
ARS1201I.....	112
ARS1202E.....	113
ARS1301I.....	113
ARS1302E.....	113
ARS1303I.....	114
ARS1304I.....	114
ARS1305I.....	114
ARS1306E.....	114
ARS1307I.....	114
ARS1308E.....	115
ARS1309I.....	115
ARS1310E.....	115
ARS1311E.....	115
ARS1312E.....	115
ARS1313I.....	116
ARS1314E.....	116
ARS1315W.....	116
ARS1400E.....	116
ARS1401I.....	116
ARS1403I.....	117
ARS1404I.....	117
ARS1405I.....	117
ARS1406E.....	117
ARS1407W.....	117

ARS1408W.....	118
ARS1409I.....	118
ARS1410W.....	118
ARS1411W.....	118
ARS1412E.....	118
ARS1413I.....	119
ARS1414E.....	119
ARS1415E.....	119
ARS1416E.....	119
ARS1417E.....	119
ARS1418E.....	120
ARS1419E.....	120
ARS1420E.....	120
ARS1421E.....	120
ARS1500I.....	120
ARS1507E.....	121
ARS1600I.....	121
ARS1601E.....	122
ARS1602E.....	122
ARS1603I.....	122
ARS1604E.....	122
ARS1605I.....	122
ARS1606E.....	122
ARS1607E.....	123
ARS1608E.....	123
ARS1609W.....	123
ARS1610E.....	123
ARS2061W.....	124
ARS2076E.....	124
ARS2077E.....	124
ARS2078E.....	124
ARS2083E.....	124
ARS2084E.....	125
ARS2085E.....	125
ARS2086E.....	125
ARS2087E.....	125
ARS2088E.....	125
ARS2089E.....	126
ARS2090E.....	126
ARS2091E.....	126
ARS2092E.....	126
ARS2093E.....	126
ARS2094E.....	127
ARS2095E.....	127
ARS2096E.....	127
ARS2097E.....	127
ARS2098E.....	127
ARS2099E.....	128
ARS2100E.....	128
ARS2101E.....	128
ARS2102E.....	128
ARS2103E.....	128
ARS2104E.....	129
ARS2105E.....	129
ARS2106E.....	129
ARS2107E.....	129
ARS2108E.....	129
ARS2109E.....	130

ARS2110E.....	130
ARS2111E.....	130
ARS2112E.....	130
ARS2113I.....	130
ARS2114E.....	131
ARS2115E.....	131
ARS2116E.....	131
ARS2117E.....	131
ARS2118E.....	131
ARS2119E.....	132
ARS2120E.....	132
ARS2121E.....	132
ARS2122E.....	132
ARS2123E.....	132
ARS2124I.....	133
ARS2125I.....	133
ARS2126I.....	133
ARS2127E.....	133
ARS2128E.....	133
ARS2129E.....	134
ARS2130E.....	134
ARS2131I.....	134
ARS2132E.....	134
ARS2133E.....	134
ARS2134E.....	134
ARS2135E.....	135
ARS2136E.....	135
ARS2137E.....	135
ARS2138E.....	135
ARS2139E.....	135
ARS2140E.....	136
ARS2141E.....	136
ARS2142E.....	136
ARS2143E.....	136
ARS2144E.....	136
ARS2145E.....	137
ARS2146E.....	137
ARS2147E.....	137
ARS2148E.....	137
ARS2149E.....	137
ARS2150E.....	138
ARS2151E.....	138
ARS2152E.....	138
ARS2153E.....	138
ARS2154E.....	138
ARS2155E.....	139
ARS2156E.....	139
ARS2157E.....	139
ARS2158E.....	139
ARS2159E.....	139
ARS2160E.....	140
ARS2161E.....	140
ARS2162E.....	140
ARS2163E.....	140
ARS2164I.....	140
ARS2166E.....	141
ARS2167I.....	141
ARS2168E.....	141

ARS2169E.....	141
ARS2170I.....	141
ARS2171E.....	141
ARS2172E.....	142
ARS2173E.....	142
ARS2174E.....	142
ARS2175E.....	142
ARS2176I.....	142
ARS2177E.....	143
ARS2184I.....	143
ARS2185I.....	143
ARS2187I.....	143
ARS2192I.....	143
ARS2193I.....	143
ARS2194I.....	144
ARS2195I.....	144
ARS2196I.....	144
ARS2197I.....	144
ARS2198I.....	144
ARS2201W.....	144
ARS2202I.....	145
ARS2203I.....	145
ARS2207I.....	145
ARS2209E.....	145
ARS2210I.....	145
ARS2211I.....	146
ARS2215E.....	146
ARS2216E.....	146
ARS2217E.....	146
ARS2218E.....	146
ARS2220E.....	147
ARS3001E.....	147
ARS3002E.....	147
ARS3003E.....	147
ARS3004E.....	147
ARS3005E.....	147
ARS3006E.....	148
ARS3007E.....	148
ARS3008E.....	148
ARS3009E.....	148
ARS3010E.....	148
ARS3014E.....	149
ARS3015E.....	149
ARS3016E.....	149
ARS3017E.....	149
ARS3018E.....	149
ARS3019E.....	150
ARS3020E.....	150
ARS3021E.....	150
ARS3022E.....	150
ARS3023E.....	150
ARS3024E.....	150
ARS3025E.....	151
ARS3026E.....	151
ARS3027E.....	151
ARS3050I.....	151
ARS3051I.....	151
ARS3052I.....	151

ARS3053I.....	152
ARS3054I.....	152
ARS3055I.....	152
ARS3056I.....	152
ARS3057E.....	152
ARS3058I.....	152
ARS3059I.....	153
ARS3060I.....	153
ARS3061I.....	153
ARS3062E.....	153
ARS3063E.....	153
ARS3064E.....	153
ARS3065E.....	154
ARS3066E.....	154
ARS3067E.....	154
ARS3068E.....	154
ARS3069E.....	154
ARS3070I.....	155
ARS3072I.....	155
ARS3074I.....	155
ARS3076I.....	155
ARS3078I.....	155
ARS3080I.....	155
ARS3082I.....	156
ARS3084I.....	156
ARS3086I.....	156
ARS3088I.....	156
ARS3090E.....	156
ARS3100I.....	156
ARS3101E.....	157
ARS3102I.....	157
ARS3103E.....	157
ARS3104I.....	157
ARS3105E.....	157
ARS3106I.....	158
ARS3107E.....	158
ARS3108I.....	158
ARS3109E.....	158
ARS3110I.....	158
ARS3111E.....	159
ARS3112I.....	159
ARS3113E.....	159
ARS3114I.....	159
ARS3115E.....	159
ARS3116I.....	160
ARS3117E.....	160
ARS3118I.....	160
ARS3119I.....	160
ARS3120W.....	160
ARS3121W.....	161
ARS3122I.....	161
ARS3123E.....	161
ARS3124I.....	161
ARS3125E.....	161
ARS3126I.....	161
ARS3127I.....	162
ARS3128E.....	162
ARS3129I.....	162

ARS3130E.....	162
ARS3131I.....	162
ARS3132E.....	162
ARS3133I.....	163
ARS3134E.....	163
ARS3135E.....	163
ARS3136I.....	163
ARS3137E.....	163
ARS3138I.....	164
ARS3139E.....	164
ARS3140I.....	164
ARS3141E.....	164
ARS3142I.....	164
ARS3143E.....	164
ARS3144E.....	165
ARS3145I.....	165
ARS3146E.....	165
ARS3147I.....	165
ARS3148E.....	165
ARS3149I.....	165
ARS3153I.....	166
ARS3158I.....	166
ARS3159E.....	166
ARS3160E.....	166
ARS3161I.....	166
ARS3162E.....	166
ARS3163I.....	167
ARS3164W.....	167
ARS3165E.....	167
ARS3166E.....	167
ARS3167I.....	167
ARS3169I.....	168
ARS3171I.....	168
ARS3173E.....	168
ARS3174E.....	168
ARS3175E.....	168
ARS3176E.....	168
ARS3178I.....	169
ARS3179I.....	169
ARS3180E.....	169
ARS3182E.....	169
ARS3183I.....	169
ARS3184I.....	170
ARS3185E.....	170
ARS3186E.....	170
ARS3300E.....	170
ARS3301E.....	170
ARS3302I.....	170
ARS3303I.....	171
ARS3304I.....	171
ARS3305I.....	172
ARS3306I.....	172
ARS3307I.....	172
ARS3309E.....	172
ARS3310E.....	173
ARS3313E.....	173
ARS3314E.....	173
ARS3315E.....	173

ARS3317E.....	173
ARS4010I.....	173
ARS4011E.....	174
ARS4012E.....	174
ARS4013E.....	175
ARS4014E.....	175
ARS4015I.....	175
ARS4016E.....	175
ARS4017I.....	176
ARS4018I.....	176
ARS4019E.....	176
ARS4020E.....	176
ARS4021I.....	176
ARS4022I.....	177
ARS4023E.....	177
ARS4024I.....	177
ARS4025E.....	177
ARS4026I.....	177
ARS4027E.....	178
ARS4028I.....	178
ARS4029E.....	178
ARS4030I.....	178
ARS4031E.....	178
ARS4032I.....	179
ARS4033E.....	179
ARS4034I.....	179
ARS4035E.....	179
ARS4036I.....	179
ARS4037E.....	180
ARS4038I.....	180
ARS4039E.....	180
ARS4040I.....	180
ARS4041E.....	180
ARS4042I.....	181
ARS4043E.....	181
ARS4044I.....	181
ARS4045E.....	181
ARS4046E.....	181
ARS4048I.....	182
ARS4049E.....	182
ARS4051I.....	182
ARS4052E.....	182
ARS4053I.....	182
ARS4054E.....	183
ARS4055E.....	183
ARS4056E.....	183
ARS4057I.....	183
ARS4058E.....	183
ARS4059E.....	184
ARS4060E.....	184
ARS4062I.....	184
ARS4063E.....	184
ARS4064E.....	184
ARS4065E.....	185
ARS4067E.....	185
ARS4068I.....	185
ARS4069E.....	185
ARS4070E.....	185

ARS4071I.....	186
ARS4072E.....	186
ARS4073I.....	186
ARS4074E.....	186
ARS4075W.....	186
ARS4076E.....	186
ARS4077E.....	187
ARS4078I.....	187
ARS4079E.....	187
ARS4080E.....	187
ARS4081E.....	187
ARS4082E.....	188
ARS4083E.....	188
ARS4084E.....	188
ARS4086E.....	188
ARS4088E.....	188
ARS4089E.....	189
ARS4090E.....	189
ARS4092E.....	189
ARS4094E.....	189
ARS4095E.....	189
ARS4096E.....	190
ARS4097E.....	190
ARS4098E.....	190
ARS4112E.....	190
ARS4113W.....	190
ARS4114E.....	191
ARS4115I.....	191
ARS4116I.....	191
ARS4118E.....	191
ARS4119I.....	191
ARS4120E.....	192
ARS4121I.....	192
ARS4122E.....	192
ARS4123I.....	192
ARS4124I.....	192
ARS4125I.....	192
ARS4126W.....	193
ARS4127I.....	193
ARS4128I.....	193
ARS4129W.....	193
ARS4130I.....	193
ARS4131I.....	193
ARS4132I.....	194
ARS4200E.....	194
ARS4201I.....	194
ARS4203I.....	194
ARS4204I.....	195
ARS4206I.....	195
ARS4207I.....	195
ARS4208I.....	195
ARS4209I.....	195
ARS4211E.....	195
ARS4212I.....	196
ARS4213I.....	196
ARS4300I.....	196
ARS4302I.....	198
ARS4303I.....	198

ARS4304W.....	198
ARS4305E.....	198
ARS4306E.....	198
ARS4307E.....	199
ARS4308I.....	199
ARS4309E.....	199
ARS4310I.....	199
ARS4311E.....	199
ARS4312I.....	199
ARS4313E.....	200
ARS4314E.....	200
ARS4315I.....	200
ARS4316E.....	200
ARS4317I.....	200
ARS4318E.....	201
ARS4319W.....	201
ARS4320I.....	201
ARS4321I.....	201
ARS4322E.....	201
ARS4323E.....	202
ARS4324E.....	202
ARS4325E.....	202
ARS4326E.....	202
ARS4327E.....	202
ARS4328E.....	203
ARS4329E.....	203
ARS4330E.....	203
ARS4331E.....	203
ARS4332E.....	203
ARS4333I.....	203
ARS4335I.....	204
ARS4336I.....	204
ARS4337I.....	204
ARS4338E.....	204
ARS4339I.....	204
ARS4340I.....	204
ARS4341I.....	205
ARS4342I.....	205
ARS4343I.....	205
ARS4344I.....	205
ARS4345E.....	205
ARS4346I.....	206
ARS4347I.....	206
ARS4348I.....	206
ARS4349I.....	206
ARS4400I.....	206
ARS4401E.....	207
ARS4402I.....	207
ARS4403I.....	207
ARS4500I.....	208
ARS4501I.....	209
ARS4502E.....	209
ARS4601I.....	209
ARS4602E.....	209
ARS4700I.....	209
ARS4703E.....	210
ARS4800I.....	210
ARS4801I.....	210

ARS4802I.....	210
ARS4803E	210
ARS4804I	211
ARS4805I.....	211
ARS4806I.....	211
ARS4807E.....	211
ARS4808E.....	211
ARS4809I	211
ARS4900I	212
ARS4901I.....	212
ARS4902I.....	212
ARS4903E.....	212
ARS4904E.....	213
ARS4905E.....	213
ARS4906E.....	213
ARS4907E.....	213
ARS4908E.....	213
ARS4909E.....	214
ARS4910E.....	214
ARS4911E.....	214
ARS4912E.....	214
ARS4913E.....	214
ARS4914E.....	215
ARS4915E.....	215
ARS4916E.....	215
ARS4917E.....	215
ARS4918E.....	216
ARS4919E.....	216
ARS4920E.....	216
ARS4921E.....	216
ARS4922I	217
ARS4923E.....	217
ARS4924E.....	217
ARS4925I.....	217
ARS4926I.....	218
ARS4927I.....	218
ARS4928I.....	218
ARS4929I.....	218
ARS4930I.....	218
ARS4931I.....	218
ARS4936E.....	219
ARS4937E.....	219
ARS4938E.....	219
ARS4939E.....	219
ARS4940E.....	219
ARS4941I.....	220
ARS4942E.....	220
ARS4943E.....	220
ARS4944E.....	220
ARS4945E.....	220
ARS4946E.....	220
ARS4947E.....	221
ARS4948E.....	221
ARS4949E.....	221
ARS4950E.....	221
ARS4951E.....	221
ARS5001I.....	222
ARS5002I.....	222

ARS5004I.....	222
ARS5005I.....	222
ARS5006I.....	222
ARS5007I.....	223
ARS5008I.....	223
ARS5009I.....	223
ARS5010I.....	223
ARS5011I.....	223
ARS5012I.....	223
ARS5013I.....	224
ARS5014I.....	224
ARS5015I.....	224
ARS5016I.....	224
ARS5017I.....	224
ARS5018I.....	225
ARS5019I.....	225
ARS5020I.....	225
ARS5021I.....	225
ARS5022I.....	226
ARS5023I.....	226
ARS5024I.....	226
ARS5025I.....	226
ARS5026I.....	226
ARS5027I.....	226
ARS5028I.....	227
ARS5029I.....	227
ARS5030I.....	227
ARS5031I.....	227
ARS5100I.....	227
ARS5101E.....	228
ARS5102E.....	228
ARS5103E.....	228
ARS5400E.....	228
ARS5401E.....	228
ARS5403E.....	229
ARS5404E.....	229
ARS5405E.....	229
ARS5406E.....	229
ARS5407E.....	229
ARS5408E.....	230
ARS5409E.....	230
ARS5410E.....	230
ARS5411E.....	230
ARS5412E.....	230
ARS5413E.....	231
ARS5414E.....	231
ARS5415E.....	231
ARS5417E.....	231
ARS5418I.....	231
ARS5419E.....	232
ARS5430E.....	232
ARS5431E.....	232
ARS5432I.....	232
ARS5433E.....	232
ARS5435E.....	233
ARS5436E.....	233
ARS5438I.....	233
ARS5439I.....	233

ARS5440E.....	233
ARS5441E.....	234
ARS5442E.....	234
ARS5443E.....	234
ARS5444E.....	234
ARS5445E.....	234
ARS5446I.....	234
ARS5447E.....	235
ARS5448E.....	235
ARS5449I.....	235
ARS5450E.....	235
ARS5454E.....	235
ARS5455E.....	236
ARS5456E.....	236
ARS5457E.....	236
ARS5458E.....	236
ARS5459E.....	236
ARS5460E.....	236
ARS5461E.....	237
ARS5462E.....	237
ARS5463E.....	237
ARS5464E.....	237
ARS5465E.....	237
ARS5466E.....	238
ARS5467E.....	238
ARS5468E.....	238
ARS5469E.....	238
ARS5470E.....	238
ARS5471E.....	239
ARS5472E.....	239
ARS5473E.....	239
ARS5474E.....	239
ARS5475E.....	239
ARS5476E.....	240
ARS5477E.....	240
ARS5478E.....	240
ARS5479E.....	240
ARS5480E.....	240
ARS5481I.....	241
ARS5482E.....	241
ARS5483E.....	241
ARS5484E.....	241
ARS5485E.....	242
ARS5486E.....	242
ARS5487E.....	242
ARS5488E.....	242
ARS5489E.....	242
ARS6000I.....	242
ARS6001I.....	243
ARS6002I.....	244
ARS6003I.....	244
ARS6004I.....	245
ARS6005I.....	246
ARS6006E.....	246
ARS6007E.....	246
ARS6009E.....	247
ARS6010E.....	247
ARS6011E.....	247

ARS6012E.....	247
ARS6013E.....	247
ARS6014E.....	248
ARS6015E.....	248
ARS6016E.....	248
ARS6017E.....	248
ARS6018E.....	248
ARS6019E.....	249
ARS6020E.....	249
ARS6021E.....	249
ARS6022E.....	249
ARS6023E.....	249
ARS6024E.....	250
ARS6025E.....	250
ARS6026I.....	250
ARS6027E.....	250
ARS6028E.....	250
ARS6029E.....	251
ARS6030E.....	251
ARS6031E.....	251
ARS6032E.....	251
ARS6033E.....	251
ARS6034W.....	252
ARS6035E.....	252
ARS6036E.....	252
ARS6037E.....	252
ARS6038E.....	252
ARS6039E.....	253
ARS6040E.....	253
ARS6041E.....	253
ARS6043E.....	253
ARS6044E.....	253
ARS6045E.....	254
ARS6046E.....	254
ARS6047E.....	254
ARS6048E.....	254
ARS6049E.....	254
ARS6050E.....	255
ARS6052E.....	255
ARS6053E.....	255
ARS6054E.....	255
ARS6055E.....	255
ARS6056E.....	256
ARS6057E.....	256
ARS6058E.....	256
ARS6059W.....	256
ARS6061I.....	256
ARS6062I.....	257
ARS6063I.....	257
ARS6064I.....	257
ARS6065I.....	257
ARS6066I.....	257
ARS6067I.....	257
ARS6068I.....	258
ARS6069I.....	258
ARS6070I.....	258
ARS6071I.....	258
ARS6072I.....	258

ARS6073I.....	258
ARS6080I.....	259
ARS6081E.....	259
ARS6082I.....	259
ARS6083E.....	259
ARS6084I.....	259
ARS6085E.....	260
ARS6086I.....	260
ARS6087E.....	260
ARS6088I.....	260
ARS6089E.....	260
ARS6090I.....	261
ARS6091E.....	261
ARS6092I.....	261
ARS6093E.....	261
ARS6094I.....	261
ARS6095I.....	262
ARS6096E.....	262
ARS6097I.....	262
ARS6098E.....	262
ARS6099E.....	262
ARS6100E.....	263
ARS6101E.....	263
ARS6102E.....	263
ARS6106E.....	263
ARS6107I.....	263
ARS6108I.....	264
ARS6109E.....	264
ARS6110I.....	264
ARS6111I.....	264
ARS6112I.....	264
ARS6113E.....	264
ARS6114E.....	265
ARS6116E.....	265
ARS6117I.....	265
ARS6118I.....	265
ARS6119I.....	265
ARS6120E.....	266
ARS6121W.....	266
ARS6122E.....	266
ARS6123E.....	267
ARS6124I.....	267
ARS6125I.....	268
ARS6126I.....	268
ARS6128E.....	269
ARS6129I.....	269
ARS6130E.....	269
ARS6131I.....	269
ARS6132E.....	270
ARS6133E.....	270
ARS6134I.....	270
ARS6135I.....	270
ARS6136E.....	270
ARS6137I.....	271
ARS6138E.....	271
ARS6139I.....	271
ARS6140E.....	271
ARS6141E.....	271

ARS6142E.....	271
ARS6143E.....	272
ARS6144E.....	272
ARS6145E.....	272
ARS6146E.....	272
ARS6147E.....	272
ARS6148I.....	273
ARS6149I.....	273
ARS6150I.....	274
ARS6151E.....	274
ARS6152I.....	274
ARS6153I.....	274
ARS6154I.....	274
ARS6155E.....	275
ARS6167W.....	275
ARS6500I.....	275
ARS6501I.....	276
ARS6502I.....	277
ARS6503E.....	277
ARS6504E.....	277
ARS6505E.....	278
ARS6524E.....	278
ARS6525E.....	278
ARS6538I.....	278
ARS6539I.....	278
ARS6700I.....	279
ARS6703E.....	279
ARS6707I.....	279
ARS6708I.....	280
ARS6712E.....	280
ARS6720E.....	280
ARS6815E.....	280
ARS6816E.....	280
ARS6817E.....	280
ARS6819E.....	281
ARS6822I.....	281
ARS6825I.....	281
ARS6826I.....	281
ARS6827E.....	281
ARS6828I.....	282
ARS6829I.....	282
ARS6830E.....	282
ARS6831E.....	282
ARS6832E.....	282
ARS6833E.....	283
ARS6834E.....	283
ARS6835E.....	283
ARS6836I.....	283
ARS6837E.....	283
ARS6838E.....	284
ARS6839I.....	284
ARS6840E.....	284
ARS6841E.....	284
ARS6842E.....	284
ARS6843E.....	285
ARS6844E.....	285
ARS7000I.....	285
ARS7001I.....	286

ARS7002E.....	286
ARS7003E.....	286
ARS7004E.....	286
ARS7005E.....	286
ARS7006E.....	286
ARS7008E.....	287
ARS7009E.....	287
ARS7010I.....	287
ARS7011I.....	287
ARS7012I.....	287
ARS7013I.....	288
ARS7014I.....	288
ARS7015E.....	288
ARS7016E.....	288
ARS7100I.....	288
ARS7101W.....	289
ARS7102W.....	289
ARS7103E.....	289
ARS7104I.....	289
ARS7105W.....	289
ARS7106W.....	290
ARS7107I.....	290
ARS7108I.....	290
ARS7109I.....	290
ARS7110I.....	290
ARS7111I.....	291
ARS7112W.....	291
ARS7113I.....	291
ARS7114I.....	291
ARS7115I.....	291
ARS7116W.....	291
ARS7117W.....	292
ARS7118W.....	292
ARS7514E.....	292
ARS7525E.....	292
ARS7526E.....	292
ARS7527E.....	293
ARS7528E.....	293
ARS7529E.....	293
ARS7530E.....	293
ARS7531I.....	293
ARS7532I.....	293
ARS7533I.....	294
ARS7571E.....	294
ARS7572E.....	294

Chapter 2. OAM support services ABEND codes..... 295

OAM support services reason codes.....	295
0250.....	295
0251.....	295
0252.....	296
0253.....	296
0254.....	296
0255.....	296
0256.....	297
0257.....	297
0258.....	297

0259.....	297
025A.....	297
025B.....	297
0270.....	297
0271.....	298
0272.....	298
0273.....	298
0274.....	299
0275.....	299
0276.....	299
027A.....	299
027B.....	300
027D.....	300
027E.....	300
027F.....	300
0292.....	301
0293.....	301
0296.....	301
029A.....	302
029B.....	302
037A.....	302

Chapter 3. ABEND codes for the JES spool data capture facility..... 303

JES spool data capture facility reason codes.....	303
025C.....	304
025D.....	304
025E.....	304
025F.....	304
0260.....	304
0261.....	304
0401.....	305
0402.....	305
0403.....	305
0404.....	305
0405.....	306
0470.....	306
0471.....	306
0472.....	306
0473.....	307
0474.....	307
0476.....	307
047A.....	308
047B.....	308
047D.....	308
047E.....	309
047F.....	309
0480.....	309
0490.....	309
0491.....	309
0492.....	309
0493.....	310
0494.....	310
0496.....	310
049A.....	311
049B.....	311
049C.....	311
049D.....	311

04A9.....	312
04AA.....	312
04AB.....	312
04AC.....	312
04AD.....	313
04AE.....	313
04AF.....	313
04B0.....	313
04B3.....	314
04B5.....	314
04D0.....	314
JES spool data capture facility messages.....	314
ARSY0100E.....	315
ARSY0101E.....	315
ARSY0102E.....	315
ARSY0103I.....	315
ARSY0104E.....	315
ARSY0105E.....	316
ARSY0106E.....	316
ARSY0107E.....	316
ARSY0108E.....	316
ARSY0109E.....	317
ARSY0110E.....	317
ARSY0111E.....	317
ARSY0112E.....	317
ARSY0113I.....	317
ARSY0114E.....	318
ARSY0115E.....	318

Chapter 4. ACIF messages..... 319

Message identifiers.....	319
Multiple message scenarios.....	320
ACIF messages.....	320
APK104S.....	320
APK105I.....	321
APK106I.....	321
APK108I.....	322
APK109I.....	322
APK110S.....	322
APK112S.....	323
APK113S.....	324
APK114S.....	324
APK116S.....	325
APK117S.....	325
APK118W.....	326
APK120S.....	326
APK130S.....	327
APK135I.....	327
APK138S.....	328
APK139S.....	328
APK140S.....	329
APK141S.....	329
APK143S.....	330
APK145S.....	330
APK146S.....	331
APK147S.....	331
APK152S.....	332

APK154S.....	332
APK155S.....	333
APK156S.....	333
APK157S.....	334
APK158I.....	334
APK159S.....	335
APK162S.....	335
APK163S.....	336
APK166S.....	336
APK167S.....	337
APK169S.....	337
APK170S.....	338
APK171S.....	338
APK172S.....	339
APK178S.....	339
APK179S.....	340
APK181S.....	340
APK188S (removed).....	341
APK190S.....	341
APK191S.....	341
APK210S.....	342
APK212S.....	342
APK217S.....	342
APK221S.....	343
APK223I.....	343
APK244I.....	344
APK245I.....	344
APK250S.....	345
APK251S.....	345
APK253S.....	346
APK254S.....	346
APK258S.....	347
APK259I.....	347
APK260S.....	348
APK261S.....	348
APK262S.....	349
APK263S.....	349
APK264S.....	350
APK267S.....	350
APK268S.....	351
APK269S.....	351
APK270S.....	352
APK271S.....	352
APK272S.....	352
APK273S.....	353
APK274S.....	353
APK275S.....	354
APK278S.....	354
APK289I.....	355
APK299I.....	355
APK300I.....	356
APK301S.....	356
APK307S.....	357
APK309S.....	357
APK310S.....	358
APK312S.....	358
APK314S.....	359
APK315S.....	359

APK316S.....	360
APK317S.....	360
APK319I.....	361
APK320S.....	361
APK321S.....	362
APK322S.....	362
APK323S.....	363
APK324S.....	363
APK326S.....	364
APK327S.....	364
APK329S.....	365
APK330I.....	365
APK334S.....	366
APK335S.....	366
APK337I.....	367
APK339I.....	367
APK340I.....	368
APK342I.....	368
APK343I.....	369
APK344S.....	369
APK346W.....	370
APK350S.....	370
APK352I.....	371
APK353S.....	371
APK355S.....	372
APK356S.....	372
APK359I.....	373
APK364I.....	373
APK366I.....	374
APK367I.....	374
APK368S.....	375
APK369S.....	375
APK380S.....	376
APK381S.....	376
APK384S.....	377
APK385S.....	377
APK386S.....	378
APK387S.....	379
APK388S.....	379
APK389S.....	380
APK390S.....	380
APK392I.....	381
APK393I.....	381
APK395I.....	382
APK396I.....	382
APK397I.....	383
APK398I.....	383
APK400S.....	383
APK401S.....	384
APK402S.....	384
APK403S.....	384
APK404S.....	385
APK405S.....	385
APK406S.....	386
APK407S.....	386
APK408S.....	386
APK409S.....	387
APK410S.....	387

APK411S.....	388
APK412W.....	389
APK413S.....	389
APK414I.....	390
APK415I.....	390
APK416I.....	391
APK417I.....	391
APK418S.....	391
APK419S.....	391
APK420S.....	392
APK421S.....	393
APK422S.....	394
APK423S.....	395
APK424I.....	396
APK425S.....	396
APK426S.....	396
APK427I.....	397
APK428S.....	397
APK431S.....	397
APK432S.....	398
APK435W.....	398
APK436S.....	398
APK437S.....	399
APK438S.....	399
APK440I.....	399
APK441I.....	399
APK442S.....	400
APK443S.....	400
APK444S.....	401
APK445S.....	401
APK446S.....	401
APK447S.....	402
APK448S.....	402
APK449S.....	402
APK450S.....	403
APK451S.....	403
APK452S.....	403
APK453S.....	404
APK454S.....	404
APK455S.....	404
APK456S.....	404
APK457S.....	405
APK458S.....	405
APK459S.....	405
APK460S.....	406
APK461S.....	406
APK462S.....	406
APK463S.....	407
APK464S.....	407
APK465S.....	407
APK466S.....	407
APK467S.....	408
APK468S.....	408
APK469S.....	408
APK470S.....	409
APK471S.....	409
APK472S.....	409
APK473S.....	410

APK474S.....	410
APK475S.....	410
APK476S.....	410
APK478I.....	411
APK479I.....	411
APK484S.....	413
APK485S.....	414
APK486S.....	414
APK487S.....	414
APK488S.....	415
APK489S.....	415
APK490S.....	415
APK491S.....	416
APK499I.....	416
APK532S.....	416
APK610I.....	417
APK900S.....	418
APK901S.....	418
APK902S.....	419
APK903S.....	419
APK904S.....	419
APK905S.....	420
APK906S.....	420
APK907S.....	420
APK908S.....	420
APK909S.....	421
APK910S.....	421
APK911S.....	421
APK912S.....	422
APK913S.....	422
APK914S.....	422
APK915S.....	422
APK916S.....	423
APK917S.....	423
APK918S.....	423
APK919S.....	424
APK920S.....	424
APK921S.....	424
APK2000S.....	425
APK2003S.....	425
APK2004S.....	426
APK2005S.....	426
APK2006S.....	427
APK2007S.....	427
APK2008I.....	428
APK2009S.....	428
APK2010S.....	429
APK2011I.....	429
APK2012S.....	430
APK2013S.....	430
APK2014I.....	431
APK2015S.....	431
APK2016S.....	432
APK2017S.....	432
APK2018S.....	433
APK2019S.....	433
APK2020I.....	434
APK2021I.....	434

APK2022I.....	435
APK2023I.....	435
APK2024I.....	436
APK2025I.....	436
APK2026I.....	437
APK2027I.....	438
APK2029I.....	438
APK2030I.....	439
APK2033I.....	439
APK2039I.....	440
APK2040I.....	440
APK2041I.....	440
APK2042I.....	441
APK2044I.....	441
APK2045I.....	442
APK2046I.....	442
APK2047I.....	443
APK2048I.....	443
APK2049I.....	444
APK2050I.....	444
APK2051I.....	444
APK2052I.....	445
APK2053I.....	445
APK2054I.....	446
APK2055I.....	446
APK2056I.....	447
APK2057I.....	447
APK2072I.....	448
APK2073I.....	448
APK2074I.....	449
APK2075S.....	449
APK2076I.....	450
APK2077I.....	450
APK2078I.....	451
APK2079I.....	451
APK2080I.....	452
APK2082I.....	452
APK2083I.....	453
APK2084I.....	453
APK2088I.....	454
APK2089I.....	454
APK2090I.....	454
APK2093I.....	455
APK2096I.....	455
APK2102I.....	456
APK2103I.....	456
APK2104I.....	457
APK2105W.....	457
APK2108I.....	458
APK2116S.....	458
APK2120I.....	459
APK3506I.....	459
APK3507I.....	460

Chapter 5. Structured APIs messages.....	461
Structured APIs messages.....	461
9101.....	461

9102.....	461
9103.....	462
9104.....	462
9105.....	462
9106.....	462
9107.....	462
9108.....	463
9109.....	463
9110.....	463
9111.....	463
9112.....	463
9113.....	464
9114.....	464
9115.....	464
9116.....	464
9117.....	464
9118.....	465
9119.....	465
9120.....	465
9121.....	465
9122.....	465
9123.....	466
9124.....	466
9125.....	466
9126.....	466
9127.....	466
9128.....	467
9129.....	467
9130.....	467
9131.....	467
9132.....	467
9133.....	468
9134.....	468
9135.....	468
9136.....	468
9137.....	468
9138.....	469
9139.....	469
9140.....	469
9141.....	469
9142.....	469
9143.....	470
9144.....	470
9145.....	470
9146.....	470
9147.....	470
9148.....	471
9149.....	471
9150.....	471
9151.....	471
9152.....	471
9153.....	472
9154.....	472
9155.....	472
9156.....	472
9157.....	472
9158.....	473
9159.....	473

9160.....	473
9161.....	473
9162.....	473
9163.....	474
9164.....	474
9165.....	474

Chapter 6. XML messages..... 475

XML messages.....	475
ARS7700I.....	475
ARS7701I.....	475
ARS7702I.....	476
ARS7703I.....	476
ARS7704I.....	477
ARS7705I.....	477
ARS7706I.....	477
ARS7707I.....	477
ARS7708I.....	478
ARS7709I.....	478
ARS7710I.....	478
ARS7711I.....	478
ARS7712I.....	478
ARS7713I.....	478
ARS7714I.....	479
ARS7715I.....	479
ARS7716I.....	479
ARS7720E.....	479
ARS7721E.....	479
ARS7722E.....	479
ARS7723E.....	480
ARS7724E.....	480
ARS7725E.....	480
ARS7726E.....	480
ARS7728E.....	480
ARS7729E.....	480
ARS7730E.....	481
ARS7732E.....	481
ARS7733E.....	481
ARS7734E.....	481
ARS7735E.....	481
ARS7736E.....	482
ARS7737W.....	482
ARS7738E.....	482
ARS7739E.....	482
ARS7740E.....	482
ARS7741E.....	483
ARS7742E.....	483
ARS7743E.....	483
ARS7744E.....	483
ARS7745E.....	483
ARS7747E.....	483
ARS7748E.....	484
ARS7749E.....	484
ARS7750E.....	484
ARS7751E.....	484
ARS7754E.....	484
ARS7755E.....	485

ARS7756E.....	485
ARS7757E.....	485
ARS7758E.....	485
ARS7759E.....	485
ARS7760E.....	485
ARS7761I.....	486
ARS7762I.....	486
ARS7763I.....	486
ARS7764I.....	486
ARS7765E.....	486
ARS7766E.....	486
ARS7767E.....	487
ARS7770E.....	487
ARS7776E.....	487
ARS7779E.....	487
ARS7781E.....	487
ARS7782E.....	488
ARS7783E.....	488
ARS7784E.....	488
ARS7785E.....	488
ARS7786E.....	488
ARS7787E.....	489
ARS7793E.....	489
ARS7794E.....	489
ARS7795E.....	489
ARS7796E.....	489
ARS7797I.....	489
ARS7798E.....	490
ARS7799E.....	490
ARS7800I.....	490
ARS7801I.....	490
ARS7802E.....	490
ARS7803E.....	491
ARS7804E.....	491
ARS7805E.....	491
ARS7806I.....	491
ARS7807E.....	491
ARS7808E.....	492
ARS7810E.....	492
ARS7811E.....	492
ARS7812E.....	492
ARS7813W.....	492
ARS7814E.....	492
ARS7815E.....	493
ARS7816E.....	493
ARS7817E.....	493
ARS7818E.....	493
ARS7819E.....	493
ARS7820E.....	494
ARS7821E.....	494
ARS7822E.....	494
ARS7823W.....	494
ARS7824E.....	494
ARS7825E.....	495
ARS7826E.....	495
ARS7827E.....	495
ARS7828E.....	495
ARS7829E.....	495

ARS7830E.....	495
ARS7831E.....	496
ARS7832E.....	496
ARS7833E.....	496
ARS7834E.....	496
ARS7835E.....	496
ARS7836E.....	497
ARS7837E.....	497
ARS7838E.....	497
ARS7839W.....	497
ARS7840E.....	497
ARS7841W.....	497
ARS7842E.....	498
ARS7843E.....	498
ARS7844E.....	498
ARS7845E.....	498
ARS7846E.....	498
ARS7847E.....	499
ARS7848E.....	499
ARS7849E.....	499
ARS7850E.....	499
ARS7851E.....	499
ARS7852E.....	500
ARS7853E.....	500
ARS7854E.....	500
ARS7855W.....	500
ARS7856E.....	500
ARS7857E.....	501
ARS7858E.....	501
ARS7859E.....	501
ARS7860E.....	501
ARS7861E.....	501
ARS7862E.....	502
ARS7863E.....	502
ARS7864E.....	502

Chapter 7. ODF Server messages.....503

ARS7900I.....	503
ARS7901E.....	503
ARS7902E.....	503
ARS7903E.....	503
ARS7904E.....	504
ARS7905E.....	504
ARS7906E.....	504
ARS7907E.....	504
ARS7908E.....	504
ARS7909I.....	505
ARS7910I.....	505
ARS7911I.....	505
ARS7912I.....	505
ARS7913E.....	506
ARS7914I.....	506
ARS7915E.....	506
ARS7916E.....	506
ARS7917E.....	507
ARS7918E.....	507
ARS7919E.....	507

ARS7920E.....	507
ARS7922E.....	508
ARS7923E.....	508
ARS7924E.....	508
ARS7925E.....	508
ARS7926E.....	509
ARS7927E.....	509
ARS7928E.....	509
ARS7929E.....	509
ARS7930E.....	509
ARS7931E.....	510
ARS7932E.....	510
ARS7933E.....	510
ARS7934W.....	510
ARS7935E.....	511
ARS7936E.....	511
ARS7937E.....	511
ARS7938E.....	511
ARS7939I.....	511
ARS7940E.....	512
ARS7941E.....	512
ARS7942I.....	512
ARS7943I.....	512
ARS7944I.....	512
ARS7945E.....	513
ARS7946I.....	513
ARS7947I.....	513
ARS7948E.....	514
ARS7949E.....	514
ARS7950E.....	514
ARS7951E.....	514
ARS7952E.....	515
ARS7953I.....	515
ARS7955E.....	515
ARS7956E.....	515
ARS7957E.....	516
ARS7958E.....	516
ARS7959E.....	516
ARS7960E.....	516
ARS7961E.....	516
ARS7962E.....	517
ARS7964E.....	517
ARS7965E.....	517
ARS7966E.....	517
ARS7967E.....	518
ARS7968E.....	518
ARS7969E.....	518
ARS7970E.....	518
ARS7971I.....	518
ARS7972I.....	519
ARS7973E.....	519
ARS7974I.....	519
ARS7975I.....	519
ARS7976E.....	520
ARS7977I.....	520
ARS7978I.....	520
ARS7979E.....	520
ARS7980I.....	521

ARS7981I	521
ARS7982E	521
ARS7983E	521
ARS7984I.....	522
ARS7985I.....	522
ARS7986E.....	522

Chapter 8. ABEND Codes.....523

0A01	523
0A02	523
0A03	524
0A04.....	524
0B0F.....	524
0B01	524
0B02	525
0B03.....	525
0B04.....	525
0C01	525
0C02	526
0C03.....	526
0C04.....	526
0C06.....	527
0C07.....	527
0D01	527
0D02.....	527
0D03.....	528
0D04.....	528
0D05.....	528
0D06.....	528
0D07.....	529
0D0F.....	529
0D10.....	529
0D11.....	529
0D12.....	530
0D13.....	530
0D14.....	530
0E01.....	530
0F01	531
0F02	531
0F03.....	531
0F04.....	531
0F05.....	532
0F06.....	532
0F07.....	532
0F08.....	532
0F09.....	533
0F0A.....	533
0F0B.....	533
0901.....	533
0902.....	534

Chapter 9. Hints and tips..... 535

Troubleshooting scenarios.....	535
Incorrect code page conversion of AFP to line data.....	535
Cannot read AFP documents in Internet Explorer 6.0.....	535
Unable to initialize PDF document from Content Manager OnDemand Windows client.....	535
ARSLOAD fails to start.....	536

ARSLOAD: Unable to establish connection.....	536
ARSLOAD error when loading report from spool.....	537
ARSLOAD not loading from HFS directory.....	537
ARSLOAD unable to store data to cache.....	538
LOADEXIT error for DB2 subsystem occurs during otherwise successful ARSLOAD.....	538
ARSADMIN fails when attempting to run from USS.....	539
ARSADMIN fails with unload [options] syntax.....	539
Informational messages appear in z/OS SYSLOG instead of OnDemand system log.....	540
The DB2 log is full.....	540
SMP/E apply job results in GIM23911E message.....	541
Attempting to stop DB2 results in SQL1035 message.....	542
IBM Content Manager OnDemand PDF Indexer trace facility.....	542
Table space file systems.....	544
Tivoli Storage Manager issues.....	544
Deleting application groups.....	544
Detecting network communication errors involving Content Manager OnDemand.....	544
Notices.....	547
Trademarks.....	548
Terms and conditions for product documentation.....	549
IBM Online Privacy Statement.....	549
Trademarks.....	550
Privacy policy considerations	550

ibm.com® and related resources

Product support and documentation are available from ibm.com®.

Support and assistance

From ibm.com, click **Support & downloads** and select the type of support that you need. From the Support Portal, you can search for product information, download fixes, open service requests, and access other tools and resources.

IBM Knowledge Center

See your online product information in IBM Knowledge Center at one of the following locations:

- For IBM Content Manager OnDemand for Multiplatforms, see https://www.ibm.com/support/knowledgecenter/SSEPCD_10.1.0/com.ibm.ondemandtoc.doc/ondemandmp_10.1.0.htm
- For IBM Content Manager OnDemand for z/OS, see https://www.ibm.com/support/knowledgecenter/SSQHWE_10.1.0/com.ibm.ondemandtoc.doc/ondemandzos_10.1.0.htm
- For IBM Content Manager OnDemand for i, see <https://www.ibm.com/support/knowledgecenter/SSB2EG>

PDF publications

See the following web sites for PDF publications for your product:

- For IBM Content Manager OnDemand for Multiplatforms, see <http://www.ibm.com/support/docview.wss?uid=swg27050851>.
- For IBM Content Manager OnDemand for z/OS, see <http://www.ibm.com/support/docview.wss?uid=swg27050852>.
- For IBM Content Manager OnDemand for i, see <http://www.ibm.com/support/docview.wss?uid=swg27041971>.

Contacting IBM

For general inquiries, call 800-IBM-4YOU (800-426-4968). To contact IBM customer service in the United States or Canada, call 1-800-IBM-SERV (1-800-426-7378).

For more information about how to contact IBM, including TTY service, see the Contact IBM website at <http://www.ibm.com/contact/us/>.

How this guide is organized

This reference guide lists the messages that are returned by the Content Manager OnDemand server programs.

- Chapter 1, “[Server messages](#),” on [page 1](#) lists the messages that are returned by the Content Manager OnDemand server programs.
- Chapter 2, “[OAM support services ABEND codes](#),” on [page 295](#) lists the ABEND codes and reason codes that are returned by the OAM component of Content Manager OnDemand for z/OS.
- Chapter 3, “[ABEND codes for the JES spool data capture facility](#),” on [page 303](#) contains ABEND codes, reason codes and messages for the ARSYSPIN program.
- Chapter 4, “[ACIF messages](#),” on [page 319](#) lists the messages that are returned by ACIF.
- Chapter 5, “[Structured APIs messages](#),” on [page 461](#) lists the messages that are returned by the structured APIs.
- Chapter 6, “[XML messages](#),” on [page 475](#) lists the messages that are returned by the `arsxml` command line routine.
- Chapter 7, “[ODF Server messages](#),” on [page 503](#) lists the messages that are returned by the ODF server.
- Chapter 8, “[ABEND Codes](#),” on [page 523](#) lists the ABEND codes that are issued.
- Chapter 9, “[Hints and tips](#),” on [page 535](#) contains troubleshooting scenarios in addition to information about the IBM Content Manager OnDemand PDF Indexer trace facility, table space file systems, Tivoli® Storage Manager issues, and the ARSSOCK debug option.

Conventions

The format for date and time, and the characters used as separators for date and time, are intended for a system configured to use the United States national language format (code page 850). These might be different on your display, depending on the code page used by your system.

Accessibility information for Content Manager OnDemand

For complete information about accessibility features that are supported by this product, see your *Administration Guide*.

Chapter 1. Server messages

You can use the information in this publication to identify Content Manager OnDemand server errors or problems and resolve them by using the appropriate recovery action.

Other message sources

Some server components return messages that are not described in this publication. Some of the message might include:

- Operating system
- Database manager
- Archive storage manager
- Server print manager

In most cases, these messages provide sufficient information to determine the cause of the warning or error. For more information about the product that generated the messages, see the appropriate manual where the product is documented. It is assumed that you are familiar with the functions of the operating system, database management product, archive storage manager, and server print manager that you are using with Content Manager OnDemand. You should use the documentation provided for each of these products to identify errors or problems and resolve them by using the appropriate recovery actions.

On IBM i, detailed descriptions and recovery information for messages with message identifiers beginning with OND and RDR can be displayed on the IBM i command line by using the Display Message Description (DSPMSGD) command. Use the following command, where msgnum is the ONDxxxx or RDRxxxx message identifier and QRLCMSGF is the Content Manager OnDemand message file in library QRDARS:

```
DSPMSGD RANGE(msgnum) MSGF(QRDARS/QRLCMSGF)
```

Message identifiers

The Content Manager OnDemand programs issue the same messages for AIX®, IBM i, Linux, Solaris Operating Environment (hereinafter referred to as Solaris), Windows, and z/OS.

The format of the message identifier is **ARSnnnt**, where:

ARS

The message prefix for Content Manager OnDemand messages.

nnnn

The message number

t

The type and severity of the message. One of the following values:

A

Alert message. A warning for an administrator to take action to avoid performance and reliability problems.

D

Debug message. Contains information that an administrator can use to help service and development resolve problems.

E

Error message. Occurs when a Content Manager OnDemand server program fails.

I

Informational message. Issued by the Content Manager OnDemand server when a program completes successfully. These messages can assist in providing an audit trail.

W

Warning message. Issued by the Content Manager OnDemand server when the results of a program might be in question.

The messages that are written to the Content Manager OnDemand System Log do not contain the ARS prefix and the type suffix. For example, the message that is associated with the failure of a load process would be written as 88 to the system log, while it is listed as ARS0088E in this publication. However, 88 and ARS0088E are one and the same message.

In this publication, the messages and explanations are listed according to the four-digit message numbers (for example, 0088).

Common server messages

The following messages are issued by the Content Manager OnDemand server programs.

Unless otherwise stated, all error codes described here are internal error codes used by IBM service and IBM development. A return code of 0 (zero) means that the Content Manager OnDemand program completed processing without any errors. Unless otherwise stated in a specific message explanation or response, any other return code means that the Content Manager OnDemand program failed.

ARS000E

Initialization of ICU for directory *locale_dir* failed - please ensure proper installation.

Explanation

An error occurred during startup when initializing ICU for the OnDemand server or an OnDemand command line program. The likely cause is that the Content Manager OnDemand was not installed properly. The OnDemand server or the command program tried to load ICU from the directory indicated by *locale_dir* but failed. *locale_dir* is the locale directory where the ICU converters are located.

User response

Make sure Content Manager OnDemand is installed correctly without errors.

ARS0013E

DB Error: *db_text* -- SQLSTATE=*sqlstate*, SQLCODE=*sqlcode*, File=*file*, Line=*line*

Explanation

The database failed and provided the given information. The messages and codes publication for the database manager product that you are using might provide additional information, including information about database errors and SQL return codes.

Example:

```
DB Error: Column PATIENT# not in specified tables. --
SQLSTATE=42703, SQLCODE=-206, File=arsdoc.c,
Line=624
DB Error: Row not found for UPDATE. --
SQLSTATE=02000, SQLCODE=100, File=arsdoc.c,
Line=1682
DB Error: Warning: Unexpected SQL_NO_DATA --
SQLSTATE=Not Defined, SQLCODE=100, File=arsdoc.c,
Line=1718
```

User response

See the messages and codes publication of the database manager product that you are using with OnDemand for information about database errors and SQL return codes.

ARS0014I

DB Info: *text*

Explanation

The *text* information is provided by the database manager. The messages and codes publication for the database manager product that you are using might provide additional information, including information about database errors and SQL return codes.

User response

See the messages and codes publication of the database manager product that you are using with OnDemand.

ARS0015E

Unable to find SMS tablespace filesystems. Either the defined SMS filesystems are full or there are no SMS filesystems defined.

Explanation

No storage management subsystem (SMS) filesystems have been defined in `ars.dbfs`, or the SMS filesystems are full or have the wrong permissions. SMS filesystems need to have read-write-execute permissions for the database owner.

User response

Verify the configuration of the SMS filesystem. Either define SMS filesystems or extend the existing SMS filesystems. Verify that the permissions are correct. Then restart the server and resubmit the command.

ARS0016E

Unable to allocate enough DMS filesystem space for table. Need(*needed_extents*), Available(*available_extents*), Extent(*extent_size*)

Explanation

There is not enough document management system (DMS) filesystem space available to complete the command.

User response

Define more DMS filesystems. Then restart the server and resubmit the command.

ARS0020E

SM Error: *text*, RC=*return_code*, Reason=*reason*, File=*file*, Line=*line*

Explanation

The storage manager failed. The SM Error portion of this message contains the error message provided to Content Manager OnDemand by the storage manager in use. The messages and codes publication of the storage manager might provide additional information.

Example 1:

```
SM Error: ASM FAILED TO RETRIEVE OBJECT, RC=2,  
Reason=0, File=arssmsms.C, Line=789  
SVR->www.example.com 192.0.2.0<-
```

Example 2:

```
ARS0020E SM Error: RC=9, REASON=0,  
FILE=ARSSMSMS.C, LINE=431
```

Example 3:

```
SM Error: ARSMVSDW: 0000000B(0000000C-7404FCDB)
PROD.ONDEMAND.DATA(BAA.R11), RC=11, REASON=0,
FILE=ARSSMSMS.C, LINE=304
SRVR->WWW.EXAMPLE.COM 192.0.2.0<-
```

When the reason code is 11 in an ARS0020E message, the value in the first parenthetical expression (0000000C-7412FCDB) corresponds to the OAM return code and reason code (*return_code-reason_code*). In this example, the following list explains the value:

- The OAM return code is 12 (X'C).
- Byte 0 of the OAM reason code is X'74, which indicates a DB2® error.
- Bytes 2 and 3 of the OAM reason code are X'FCDB. Convert it to decimal, which is -805. Look up -805 in the list of DB2 messages and codes, which is message DBRM OR PACKAGE NAME *location-name.collection-id.dbrm-name.consistency-token* NOT FOUND IN PLAN *plan-name*. REASON *reason-code*.

An alternative way to identify the OAM return code and reason code is to issue the following TSO OSREQ command. Specify the collection and object names from the ARS0020E message:

```
OSREQ QUERY PROD.ONDEMAND.DATA BAA.R11
OSREQ QUERY unsuccessful. Return code = 0000000C, reason code = 7412FCDB.
OSREQ QUERY response time is 53 milliseconds.
```

When the reason code is 10 in an ARS0020E message, the value in parentheses is an internal diagnostic code used by IBM Support.

Example 4: In the following example, OAM passes the corresponding DB2 errors to Content Manager OnDemand through the OAM OSREQ MSGAREA:

```
SM Error: ARSMVSRE: 0000000B(0000000C-8802FC78) PROD.ONDEMAND.
DATA(BAA.R11) OAM OSREQ MSGAREA: DSNT408I SQLCODE =
-904, ERROR: UNSUCCESSFUL EXECUTION CAUSED BY AN
UNAVAILABLE RESOURCE. REASON 00C90081, TYPE OF RESOURCE
00000200, AND RESOURCE NAME GROUP00 .OSMOTS04
DSNT418I SQLSTATE = 57011 SQLSTATE RETURN CODE
DSNT415I SQLERRP = DSNXRINS SQL PROCEDURE DETECTING ERROR
DSNT416I SQLERRD = -110 13172746 0 13223106 -974970879
12714050 SQL DIAGNOSTIC INFORMATION
DSNT416I SQLERRD = X'FFFFFF92' X'00C9000A' X'00000000'
X'00C9C4C2' X'C5E32001' X'00C20042' SQL
DIAGNOSTIC INFORMATION
, RC=11, REASON=0, FILE=ARSSMSMS.C, LINE=304 SRVR->WWW.EXAMPLE.COM 127.0.0.1<-
```

As in example 3, the value in the first parenthetical expression corresponds to the OAM return code and reason code. However, the OAM OSREQ MSGAREA displays the corresponding DB2 errors so that you do not need to convert X'0000000C-8802FC78' to decimal and then look up the return codes and reason codes in the OAM or DB2 publications. If you did convert X'0000000C-8802FC78' and look up return codes and reason codes, the following list explains the results:

- The OAM return code is X'C'.
- Byte 0 of the OAM reason code is X'88', which indicates a DB2 error.
- Bytes 2 and 3 of the OAM reason code are X'FC78'. Convert X'FC78' to decimal, which is -904. Look up -904 in the list of DB2 messages and codes, which is UNSUCCESSFUL EXECUTION CAUSED BY AN UNAVAILABLE RESOURCE. REASON *reason-code*, TYPE OF RESOURCE *resource-type*, AND RESOURCE NAME *resource-name*.

The OAM OSREQ MSGAREA displays SQLCODE -904 with values for *reason-code*, *resource-type*, and *resource-name*: UNSUCCESSFUL EXECUTION CAUSED BY AN UNAVAILABLE RESOURCE. REASON 00C90081, TYPE OF RESOURCE 00000200, AND RESOURCE NAME GROUP00 .OSMOTS04.

Example 5:

```
SM Error: ANS0266I (RC2302) The dsmEndTxn is ABORT, so check the reason field.,
RC=2302, Reason=29, File=arssmsms.C, Line=744, Srvr->spnode05<-
An error occurred. Contact your System Administrator and/or consult the
System Log. File=arsadmin.c, Line=576
Unable to store the object >2339FAAA<. Object size 239831.
Loaded 0 rows into the database.
ars_load: Thu Oct 28 17:31:04 BST 2003 -- Loading failed
```

User response

See the messages and codes publication of the storage manager product that you are using with OnDemand for information about the SM Error, RC, and Reason.

Example 1: Check the Archive Storage Manager (ASM) joblog for more information.

Example 2: RC=9 indicates that OnDemand OAM support is not enabled. Check that the following ars.cfg parameters are set correctly (shown here with sample values):

```
ARS_NUM_OAMSRVR=4
ARS_OAM_DB2SSID=DSNA
ARS_OAM_PLAN=CBRIDBS
```

ARS_NUM_OAMSRVR specifies the number of OAM interface tasks to create within the ARSSOCKD address space. A value of zero disables all OAM support within OnDemand. 4 is a typical value.

ARS_OAM_DB2SSID specifies the name of the DB2 subsystem with which OAM interacts. The DB2 subsystem name must be the same as the name that is specified as the operand of the DB2SSID parameter within the IGDSMSxx member of SYS1.PARMLIB.

ARS_OAM_PLAN specifies the name of the DB2 application plan used by OAM.

Example 3: It is likely that a bind is needed for the CBRIDBS plan. If you recently applied OAM maintenance, ensure that binds that are indicated by hold data are performed.

Example 4: The OAM OSREQ MSGAREA text indicates that table space GROUPO0.OSMOTS04 is stopped. Start that table space.

Example 5: The error is a symptom of having no optical platters available for the storage set that is used by the Application Group. Verify the following settings:

- Scratch platters are available.
- The *max-scratch* value is set high enough.
- The platters in the storage pool have read and write permission.

Related information

[Object Access Method Planning, Installation and Storage Administration Guide for Object Support \(SC35-0391\)](#)

ARS0021E

Unable to store data to cache because there is no cache defined

Explanation

There are no cache storage filesystems defined on the system. See your *Installation and Configuration Guide* for information about defining cache storage filesystems.

User response

Define and configure one or more cache storage filesystems. Then restart the server and resubmit the command.

ARS0022E

Unable to delete the Application Group >appl_group_name<. You must manually delete the TSM filespace >file_space_name< with TSM utilities

Explanation

The storage manager failed because the application group data could not be deleted from Tivoli Storage Manager. If the owner of the Content Manager OnDemand instance is not root, when a user deletes an application group, Content Manager OnDemand will delete the application group tables from the Content Manager OnDemand database but will not delete the application group data from Tivoli Storage Manager.

User response

To delete the application group data from Tivoli Storage Manager, log on to Tivoli Storage Manager and use its utilities to delete the file space that is associated with the application group. The name of the file space is specified in the message. See your Tivoli Storage Manager documentation for details and instructions.

ARS0023E

Object >object_name< in Application Group >appl_grp_name< not found in cache, no other storage defined

Explanation

The object no longer exists in the Content Manager OnDemand cache and no other storage manager was defined to store the data. The data was expired. Depending on how the application group index expiration was configured, the index information will also expire in the future.

Example:

```
Object >1FAAA< in Application Group >LOANS<
not found in cache, no other storage defined
```

User response

Verify the storage management configuration on the system and verify the storage management settings for the specified application group.

ARS0024E

Object >object_name< in Application Group >appl_grp_name< not found in node >node_name<

Explanation

The object cannot be found in the specified storage node. The data expired from the storage node.

Example:

```
Object >2FAA< in Application Group >JIF<
not found in node >PriForever<
```

User response

Verify the storage management settings for the specified application group.

ARS0025E

Unable to store data because the cache is full

Explanation

The cache storage filesystems are full.

User response

Add or extend the cache storage filesystems. Then restart the server and resubmit the command.

To check for insufficient space on the filesystems, complete the following steps:

1. Look at the cache configuration file (for example, `ars.cache`) that is pointed to by the `SRVR_SM_CFG` parameter in `/usr/lpp/ars/V10R1M0/config/ars.ini`.
2. Check the directory or directories specified in `ars.ini` for available space.
3. Use the USS command `df -kP /ars1` (where `/ars1` is a directory specified in `ars.cache`) to see how much cache space remains.

ARS0026E

Unable to perform action because this server is cache only and does not support the Storage Management Subsystem

Explanation

The system is configured for cache only. However, the storage node definitions are pointing to a storage manager that is not configured.

User response

Either define and configure the storage manager or change the storage node to be cache only. Then restart the server and resubmit the command.

ARS0027E

Unable to load the TSM dynamic load library

Explanation

The command failed when attempting to load the Tivoli Storage Manager dynamic load library.

User response

Verify that Tivoli Storage Manager is correctly installed and configured. Then restart the server and resubmit the command.

ARS0030I

Login: *hostname*

Explanation

A client successfully logged on to the server. This message is for your information only.

Example:

```
Login: www.example.com 192.0.2.0
```

User response

No action is required.

ARS0031W

Failed login: *hostname*

Explanation

A client failed when attempting to log on to the server.

Example 1:

```
Failed login: www.example.com 192.0.2.0
```

If there is no hostname parameter in the message this indicates that the process is running using the NOTCPIP option.

Example 2:

```
ARS0031W ONDUSR1 FAILED LOGIN: [blank]
```

In this example, the userid appears before the *Failed login:* text. This indicates that the Content Manager OnDemand system log was unavailable to the process and this message was issued as a Write To Operator (WTO).

User response

Verify the user ID, password, and server selection. Passwords might be case sensitive. Then resubmit the command.

ARS0032I

Logoff

Explanation

A client logged off from the server. This message is for your information only.

User response

No action is required.

ARS0033I

Logoff Timeout

Explanation

The server forced a client to log off from the server because the client did not perform an action on the server within the interval of time that is specified by the Inactivity Time Out value.

User response

Log off from the server and log back on to the server. Then resubmit the command. A system administrator can increase the Inactivity Time Out value for this or any other server in the Content Manager OnDemand administrative client. See the online help in the Content Manager OnDemand administrative client for more information.

ARS0034I

User Add: Userid(*user_name*) Id(*uid*)

Explanation

The specified user was added to the system. This message is for your information only.

Example:

```
User Add: Userid(TBROWN) Id(3)
```

User response

No action is required.

ARS0035I

User Delete: Userid(*user_name*) Id(*uid*)

Explanation

The specified user was deleted from the system. This message is for your information only.

Example:

```
User Delete: Userid(SBOWMAN) Id(5)
```

User response

No action is required.

ARS0036I

```
User Update: Userid(user_name) Id(uid)
```

Explanation

The specified user was updated. This message is for your information only.

Example:

```
User Update: Userid(TBROWN) Id(3)
```

User response

No action is required.

ARS0037I

```
User Update with new Password: Userid(user_name) Id(uid)
```

Explanation

The specified user's password was successfully updated. This message is for your information only.

Example:

```
User Update with new Password: Userid(QONDADM)  
Id(1)
```

User response

No action is required.

ARS0038W

```
User Failed Update with new Password: Userid(user_name) Id(uid)
```

Explanation

An attempt to update the specified user's password failed.

Example:

```
User Failed Update with new Password:  
Userid(QONDADM) Id(1)
```

User response

Verify the user ID and the new password and then resubmit the command.

ARS0039I

```
Group Add: Group(group_name) Id(gid)
```

Explanation

The specified group was added to the system. This message is for your information only.

Example:

```
Group Add: Group(SUPPORT) Id(80102)
```

User response

No action is required.

ARS0040I

```
Group Delete: Group(group_name) Id(gid)
```

Explanation

The specified group was deleted from the system. This message is for your information only.

Example:

```
Group Delete: Group(Accounting) Id(1080021)
```

User response

No action is required.

ARS0041I

```
Group Update: Group(group_name) Id(gid)
```

Explanation

The specified group was updated. This message is for your information only.

Example:

```
Group Update: Group(ACCOUNTING) Id(1080001)
```

User response

No action is required.

ARS0042I

```
User to Group Add: User(user_name) Id(uid), Group(group_name) Id(gid)
```

Explanation

The specified user was added to the specified group. This message is for your information only.

Example:

```
User to Group Add: User(oduser) Id(10),  
Group(Accounting) Id(1080021)  
User to Group Add: User(CALLEN) Id(4),  
Group(Accounting) Id(1080021)
```

User response

No action is required.

ARS0043I

```
User to Group Delete: User(user_name) Id(uid), Group(group_name) Id(gid)
```

Explanation

The specified user was deleted from the specified group. This message is for your information only.

Example:

```
User to Group Delete: User(CALLEN) Id(4),  
Group(Accounting) Id(1080021)
```

User response

No action is required.

ARS0044I

Folder Add: Name(*folder_name*) Fid(*fid*)

Explanation

The specified folder was added to the system. This message is for your information only.

Example:

```
Folder Add: Name(CHKSTMTS1R) Fid(5015)
```

User response

No action is required.

ARS0045I

Folder Delete: Name (*name*) Fid(*fid*)

Explanation

The specified folder was deleted from the system. This message is for your information only.

Example:

```
Folder Delete: Name(Credit Card Statement)  
Fid(5486)  
Folder Delete: Name(Loan Statements) Fid(5487)
```

User response

No action is required.

ARS0046I

Folder Update: Name(*folder_name*) Fid(*fid*)

Explanation

The specified folder was updated. This message is for your information only.

Example:

```
Folder Update: Name(Check Statements Folder)  
Fid(5064)
```

User response

No action is required.

ARS0047I

Application Group to Folder Add: ApplGroup(*appl_grp_name*) Agid(*agid*) Appl(*appl_name*) Aid(*aid*)
Folder(*folder_name*) Fid(*fid*)

Explanation

The specified application group was added to the specified folder. This message is for your information only.

Example:

```
ApplGroup to Folder Add:  
ApplGroup(2014 Monthly Credit Card Statements)  
Agid(5028) Appl(Monthly Credit Card Statement)  
Aid(5029) Folder(Credit Card Statements) Fid(5030)
```

User response

No action is required.

ARS0048I

Application Group to Folder Delete: ApplGroup(*appl_grp_name*) Agid(*agid*) Appl(*appl_name*) Aid(*aid*)
Folder(*folder_name*) Fid(*fid*)

Explanation

The specified application group was deleted from the specified folder. This message is for your information only.

User response

No action is required.

ARS0049I

Application Group to Folder Update: ApplGroup(*appl_grp_name*) Agid(*agid*) Folder(*folder_name*) Fid(*fid*)

Explanation

The specified application group was updated in the specified folder. This message is for your information only.

User response

No action is required.

ARS0050I

Id to Folder Add: Name(*id_name*) Id(*id*) Folder(*folder_name*) Fid(*fid*)

Explanation

Permissions were added to the specified folder for the user or group with the specified ID. This message is for your information only.

Example:

```
Id to Folder Add: Name(oduser) Id(2)  
Folder(Credit Card Statements) Fid(5015)
```

User response

No action is required.

ARS0051I

Id to Folder Delete: Name(*id_name*) Id(*id*) Folder(*folder_name*) Fid(*fid*)

Explanation

Permissions were deleted from the specified folder for the user or group with the specified ID. This message is for your information only.

User response

No action is required.

ARS0052I

Id to Folder Update: Name(*id_name*) Id(*id*) Folder(*folder_name*) Fid(*fid*)

Explanation

Permissions were updated in the specified folder for the user or group with the specified ID. This message is for your information only.

Example:

```
Id to Folder Update: Name(oduser) Id(20)
Folder(Credit Card Statements) Fid(5065)
```

User response

No action is required.

ARS0053I

Application Group Add: Name(*appl_grp_name*) Agid(*agid*)

Explanation

The specified application group was added to the system. This message is for your information only.

Example:

```
Application Group Add:
Name(2014 Monthly Credit Card Statements)
Agid(5174)
```

User response

No action is required.

ARS0054I

Application Group Delete: Name(*appl_grp_name*) Agid(*agid*)

Explanation

The specified application group was deleted from the system. This message is for your information only.

Example:

```
Application Group Delete:
Name(2014 Monthly Credit Card Statements)
Agid(5061)
```

User response

No action is required.

ARS0055I

Application Group Update: Name(*appl_grp_name*) Agid(*agid*)

Explanation

The specified application group was updated. This message is for your information only.

Example:

```
Application Group Update:  
Name(2014 Monthly Credit Card Statements)  
Agid(5016)
```

User response

No action is required.

ARS0056I

Id to Application Group Add: Name(*id_name*) Id(*id*) ApplGroup(*appl_grp_name*) Agid(*agid*)

Explanation

Permissions were added to the specified application group for the user or group with the specified ID. This message is for your information only.

Example:

```
Id to ApplGroup Add: Name(oduser) Id(29)  
ApplGroup(2014 Monthly Credit Statements) Agid(15224)
```

User response

No action is required.

ARS0057I

Id to Application Group Delete: Name(*id_name*) Id(*id*) ApplGroup(*appl_grp_name*) Agid(*agid*)

Explanation

Permissions were deleted from the specified application group for the user or group with the specified ID. This message is for your information only.

User response

No action is required.

ARS0058I

Id to Application Group Update: Name(*id_name*) Id(*id*) ApplGroup(*appl_grp_name*) Agid(*agid*)

Explanation

Permissions were updated in the specified application group for the user or group with the specified ID. This message is for your information only.

User response

No action is required.

ARS0059I

Application to Application Group Add: Name(*appl_name*) Aid(*aid*) ApplGroup(*appl_grp_name*) Agid(*agid*)

Explanation

The specified application was added to the specified application group. This message is for your information only.

Example:

```
Appl to ApplGroup Add:  
Name(Monthly Credit Card Statement) Aid(5514)  
ApplGroup(2014 Monthly Credit Card Statements)  
Agid(5512)
```

User response

No action is required.

ARS0060I

Application to Application Group Delete: Appl(*appl_name*) Aid(*aid*) ApplGroup(*appl_grp_name*) Agid(*agid*)

Explanation

The specified application was deleted from the specified application group. This message is for your information only.

Example:

```
Appl to ApplGroup Delete:  
Appl(Monthly Credit Card Statement) Aid(5042)  
ApplGroup(2014 Monthly Credit Card Statements)  
Agid(5044)
```

User response

No action is required.

ARS0061I

Application to Application Group Update: Name(*appl_name*) Aid(*aid*) ApplGroup(*appl_grp_name*) Agid(*agid*)

Explanation

The specified application was updated in the specified application group. This message is for your information only.

Example:

```
Appl to ApplGroup Update:  
Name(Monthly Credit Card Statement) Aid(5063)  
ApplGroup(2014 Monthly Credit Card Statements)  
Agid(5062)
```

User response

No action is required.

ARS0062I

Id to Appl Add: Name(*id_name*) Id(*id*) Appl(*appl_name*) Aid(*aid*) ApplGroup(*appl_grp_name*) Agid(*agid*)

Explanation

Logical views were added to the specified application for the user with the specified ID. This message is for your information only.

Example:

```
Id to Appl Add: Name(oduser) Id(17)
Appl(Monthly Credit Card Statement) Aid(5057)
ApplGroup(2014 Monthly Credit Card Statements)
Agid(5056)
```

User response

No action is required.

ARS0063I

Id to Appl Delete: Name(*id_name*) Id(*id*) Appl(*appl_name*) Aid(*aid*) ApplGroup(*appl_grp_name*) Agid(*agid*)

Explanation

Logical views were deleted from the specified application for the user with the specified ID. This message is for your information only.

User response

No action is required.

ARS0064I

Id to Appl Update: Name(*id_name*) Id(*id*) Appl(*appl_name*) Aid(*aid*) ApplGroup(*appl_grp_name*) Agid(*agid*)

Explanation

Logical views were updated in the specified application for the user with the specified ID. This message is for your information only.

Example:

```
Id to Appl Update: Name(oduser) Id(10)
Appl(Monthly Credit Card Statement) Aid(5027)
ApplGroup(2014 Monthly Credit Card Statements)
Agid(5024)
```

User response

No action is required.

ARS0065I

Application Group Query: Name(*appl_grp_name*) Agid(*agid*) Count(*count*) SegStart(*seg_start_date*) SegStop(*seg_stop_date*) *additional_fields*

Explanation

A query was run against the specified application group. This message is for your information only.

Example:

```
ApplGroup Query:  
Name(2014 Monthly Credit Card Statements) Agid(5081)  
Count() SegStart(2014-08-25 23:07:41.000000)  
SegStop(2014-08-27 22:58:32.000000)  
Sql(WHERE jobdate BETWEEN 11470 AND 11654 )  
SqlR() TextSearch( ) AnnColor(-1) AnnText()
```

User response

No action is required.

ARS0066I

Application Group Document Get: Name(*appl_grp_name*) Agid(*agid*) ApplName(*appl_name*) Aid(*aid*)
NodeName(*node_name*) Nid(*nid*) Server(*server*) Time(*time*) *additional_fields*

Explanation

A document was retrieved from the specified application group. This message is for your information only.

Example:

```
Application Group Document Get:  
Name(2014 Monthly Credit Card Statements)  
Agid(5081)  
ApplName(Monthly Credit Card Statement)  
Aid(5082) NodeName(-CACHE-) Nid(1)  
Server(-LOCAL-) Time(0.322) Flds()
```

User response

No action is required.

ARS0067I

Application Group Resource Get: Name(*appl_grp_name*) Agid(*agid*) NodeName(*node_name*) Nid(*nid*)
Server(*server*) Time(*time*) Rid() Size()

Explanation

A resource was retrieved from the specified application group. This message is for your information only.

Example:

```
Application Group Resource Get:  
Name(2014 Monthly Credit Card Statements)  
Agid(6843) NodeName(-CACHE-) Nid(25)  
Server(-LOCAL-) Time(0.069) Rid() Size()
```

User response

No action is required.

ARS0068I

Annotation Add: Name(*appl_grp_name*) Agid(*agid*)

Explanation

An annotation to a document was added to the specified application group. This message is for your information only.

Example:

```
Annotation Add: Name(CHECKSTMTS) Agid(5081)
```

User response

No action is required.

ARS0069I

```
Annotation Id Add: Name(id_name) Id(id) ApplGroup(appl_grp_name) Agid(agid)
```

Explanation

An annotation to a document was added to the specified application group for the user or group with the specified ID. This message is for your information only.

Example:

```
Annotation Id Add: Name(oduser) Id(3)  
ApplGroup(2014 Monthly Credit Card Statements)  
Agid(5015)
```

User response

No action is required.

ARS0070I

```
Annotation Delete: Name(appl_grp_name) Agid(agid)
```

Explanation

An annotation to a document was deleted from the specified application group. This message is for your information only.

User response

No action is required.

ARS0071I

```
Annotation Id Delete: Name() Id(id) ApplGroup(appl_grp_name) Agid(agid)
```

Explanation

An annotation to a document was deleted from the specified application group for the user or group with the specified ID. This message is for your information only.

User response

No action is required.

ARS0072I

```
Named Query Add: Name(named_query) Folder(folder_name) Fid(fid)
```

Explanation

The specified named query was added to the system. This message is for your information only.

User response

No action is required.

ARS0073I

Id Named Query Add: Name(*named_query*) IdName(*id_name*) Id(*id*) Folder(*folder_name*) Fid(*fid*)

Explanation

The specified named query was added to the system for the user or group with the specified ID. This message is for your information only.

User response

No action is required.

ARS0074I

Named Query Delete: Name(*named_query*) Folder(*folder_name*) Fid(*fid*)

Explanation

The specified named query was deleted from the system. This message is for your information only.

User response

No action is required.

ARS0075I

Id Named Query Delete: Name(*named_query*) IdName(*id_name*) Id(*id*) Folder(*folder_name*) Fid(*fid*)

Explanation

The specified named query was deleted from the system for the user or group with the specified ID. This message is for your information only.

User response

No action is required.

ARS0076I

Named Query Update: Name(*named_query*) Folder(*folder_name*) Fid(*fid*)

Explanation

The specified named query was updated. This message is for your information only.

User response

No action is required.

ARS0077I

Id Named Query Update: Name(*named_query*) IdName(*id_name*) Id(*id*) Folder(*folder_name*) Fid(*fid*)

Explanation

The specified named query was updated for the user or group with the specified ID. This message is for your information only.

User response

No action is required.

ARS0078I

System Update

Explanation

This message is for your information only.

User response

No action is required.

ARS0079I

Application Group Document Delete: Name(*appl_grp_name*) Agid(*agid*) Flds(*fields*)

Explanation

A document was deleted from the specified application group. This message is for your information only.

User response

No action is required.

ARS0080I

Application Group Document Update: Name(*appl_grp_name*) Agid(*agid*) OrigFlds(*original_fields*)
UpdFlds(*updated_fields*)

Explanation

A document was updated in the specified application group. This message is for your information only.

Example:

```
Application Group Document Update:  
Name(2014 Monthly Credit Card Statements)  
Agid(5056) OrigFlds(951807600,'RED','')  
UpdFlds(951807600,'GREEN','')
```

User response

No action is required.

ARS0081I

Application Group Object Retrieve: Name(*appl_grp_name*) Agid(*agid*) ObjName(*object_name*)
NodeName(*node_name*) Nid(*nid*) Server(*server*) Off(*offset*) Len(*length*) Time(*time*)

Explanation

The specified storage object was retrieved from the specified application group. This message is for your information only.

Example:

```
Application Group Object Retrieve:  
Name(2014 Monthly Credit Card Statements)  
Agid(5016) ObjName(2FAAA) NodeName(-CACHE-)  
Nid(1) Server(-LOCAL-) Off(0) Len(33778)  
Time(0.013)
```

User response

No action is required.

ARS0082I

Application Group Object Store: Name(*appl_grp_name*) Agid(*agid*) NodeName(*node_name*) Nid(*nid*)
Server(*server*) ObjName(*object_name*) Time(*time*)

Explanation

The specified storage object was stored in the specified application group. This message is for your information only.

Example:

```
Application Group Object Store:  
Name(2014 Monthly Credit Card Statements)  
Agid(5028) NodeName(-CACHE-) Nid(1)  
Server(-LOCAL-) ObjName(2) Time(0.852)  
  
Application Group Object Store:  
Name(2014 Monthly Loan Statements) Agid(5017)  
NodeName(TESTMP) Nid(2) Server(-LOCAL-)  
ObjName(1494FAAA) Time(1.230)
```

User response

No action is required. For more information about this message, see [“Troubleshooting scenarios”](#) on page 535.

ARS0083I

```
Application Group Object Store Append: Name(appl_grp_name) Agid(agid) NodeName(node_name)  
Nid(nid) Server(server) ObjName(object_name) CompOff(compress_offset) CompLen(compress_length)
```

Explanation

The specified storage object was updated. This message is for your information only.

User response

No action is required.

ARS0084I

```
Application Group Unload Database: Name(appl_grp_name) Agid(agid) LoadId(load_id) Rows  
Deleted(rows_deleted) SM UnLoad Ready()
```

Explanation

A report was deleted from the database. The message identifies the load ID, which represents the report in the system, the application group, and the number of rows that were deleted from the database. This message is for your information only.

Example:

```
Application Group Unload Database:  
Name(2014 Monthly Credit Card Statements) Agid(5017)  
LoadId(41428-1-0-1FAA-20050801000000-20050801000000-41429)  
Rows Deleted(25) SM UnLoad Ready()
```

User response

No action is required.

ARS0085I

```
Application Group Unload Storage Manager: Name(appl_grp_name) Agid(agid) NodeName(node_name)  
Nid(nid) Server(server) LoadId(load_id) Objects Deleted(objects_deleted)
```

Explanation

A report was deleted by the storage manager. The message identifies the load ID, which represents the report in the system, the application group, storage node, and number of objects that were deleted. This message is for your information only.

Example:

```
Application Group Unload Storage Manager:  
Name(2014 Monthly Credit Card Statements)  
Agid(5017) NodeName(-CACHE-) Nid(0) Server(-LOCAL-)  
LoadId(41428-1-0-1FAA-20050801000000-20050801000000-41429)  
Objects Deleted(1)
```

User response

No action is required.

ARS0086I

Application Group Load Database: Name(*appl_grp_name*) Agid(*agid*) Rows(*rows*)

Explanation

A report was loaded into the database. The message identifies the application group and the number of rows that were loaded into the database. This message is for your information only.

Example:

```
Application Group Load Database:  
Name(2014 Monthly Credit Card Statements)  
Agid(5028) Rows(100)
```

User response

No action is required.

ARS0087I

Application Group Load: Name(*appl_grp_name*) LoadId(*load_id*) File(*file*) InputSize(*input_size*)
OutputSize(*output_size*) Rows(*rows*) Time(*time*) Appl(*appl_name*) InputFileSize(*input_file_size*)

Explanation

A report was loaded into the system. The message identifies the application group, the input file, and the load ID. This message is for your information only.

Example:

```
Application Group Load: Name(2014 Montly Credit Card Statements)  
LoadId(41428-1-0-1FAA-20050801000000-20050801000000-41429)  
File(/QIBM/USERDATA/ONDEMAND/QUSROND/TMP/  
SP_MOSUNPO_WTH7HTWCXA_064315_000009_RDR400M_1031023_210136)  
InputSize(225789) OutputSize(16380) Rows() Time()  
Appl(Monthly Credit Card Statement) InputFileSize()
```

User response

No action is required.

ARS0088E

Application Group Failed Load: Name(*appl_grp_name*) LoadId(*load_id*) File(*file*)

Explanation

The load process failed.

Example:

```
Application Group Failed Load: Name(2014 Monthly Credit Card Statements)  
LoadId(41428-1-0-1FAA-20050801000000-20050801000000-41429)
```

File(/QIBM/USERDATA/ONDEMAND/QUSROND/TMP/
SP_QPRLR133_QPRTJOB_001467_000022_RDR400M_1021226_132052)

User response

See the other messages that were generated by the ARSLOAD program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS0089I

CD-ROM Creation Manifest: Volume(*volume*)

Explanation

A CD-ROM manifest was created with the specified volume label. This message is for your information only.

User response

No action is required.

ARS0090I

BulkProcess: Time(*time*) NumDocs()

Explanation

This message is for your information only.

Example:

```
BulkProcess: Time(1.798) NumDocs()
```

User response

No action is required.

ARS0091I

BulkPrint: Time(*time*)

Explanation

This message is for your information only.

Example:

```
BulkPrint: Time(1.766) Svr->www.example.com 192.0.2.0<-  
BULK DOCUMENT RETRIEVAL  
Application Group                               Agid Flds->Handle  
-----  
2014 Monthly Credit Card Statements             5014 ->7FAAA,3852,968,0,3272,0x4E,0x4F,0,1,0
```

User response

No action is required.

ARS0092I

StorageNode Add: Name(*node_name*) Server(*server*) Nid(*nid*) Set(*set_name*) Sid(*sid*)

Explanation

The specified storage node was added to the system. This message is for your information only.

User response

No action is required.

ARS0093I

StorageNode Delete: Name(*node_name*) Server(*server*) Nid(*nid*) Set(*set_name*) Sid(*sid*)

Explanation

The specified storage node was deleted from the system. This message is for your information only.

User response

No action is required.

ARS0094I

StorageNode Update: Name(*node_name*) Server(*server*) Nid(*nid*) Set(*set_name*) Sid(*sid*)

Explanation

The specified storage node was updated. This message is for your information only.

User response

No action is required.

ARS0095I

StorageSet Add: Name(*set_name*) Sid(*sid*)

Explanation

The specified storage set was added to the system. This message is for your information only.

User response

No action is required.

ARS0096I

StorageSet Delete: Name(*set_name*) Sid(*sid*)

Explanation

The specified storage set was deleted from the system. This message is for your information only.

User response

No action is required.

ARS0097I

StorageSet Update: Name(*set_name*) Sid(*sid*)

Explanation

The specified storage set was updated. This message is for your information only.

User response

No action is required.

ARS0100I

Printer Add: Name(*printer_name*) Queue(*queue*) Pid(*pid*)

Explanation

The specified server printer was added to the system. This message is for your information only.

Example:

```
Printer Add: Name(QPRINT2) Queue(QGPL/QPRINT2)
Pid(5098)
```

User response

No action is required.

ARS0101I

```
Printer Delete: Name(printer_name) Queue(queue) Pid(pid)
```

Explanation

The specified server printer was deleted from the system. This message is for your information only.

Example:

```
Printer Delete: Name(QPRINT2) Queue(QGPL/QPRINT2)
Pid(5098)
```

User response

No action is required.

ARS0102I

```
Printer Update: Name(printer_name) Queue(queue) Pid(pid)
```

Explanation

The specified server printer was updated. This message is for your information only.

Example:

```
Printer Update: Name(QPRINT2) Queue(QGPL/QPRINT2)
Pid(5098)
```

User response

No action is required.

ARS0103I

```
Application Group Document Add: Name(appl_grp_name) Agid(agid) Flds(fields)
```

Explanation

A document was added to the specified application group. This message is for your information only.

Example:

```
Application Group Document Add:
Name(2014 Monthly Credit Card Statements)
Agid(15796) Flds()
```

User response

No action is required.

ARS0106E

Content Manager OnDemand failed to unlink the file *>file<*. The error number is *errno*

Explanation

An error occurred while this program was running.

The specified file does not exist, or the Content Manager OnDemand instance owner does not have permission to access it. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

Example:

```
Unlink failed for file >/QIBM/USERDATA/ONDEMAND/QUSROND/CACHE/retr/KCA/RES/1FAA1<.  
errno=3025  Svr->www.example.com 192.0.2.0<-
```

User response

Verify that the file exists and that the Content Manager OnDemand instance owner has permission to access it. Also verify that the link is valid. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0107E

An unknown file or directory was found in the Content Manager OnDemand cache *>path_name<*

Explanation

An error occurred while this program was running.

Example:

```
Unknown file/dir in cache >/arscache1/everest<  
Svr->www.example.com 192.0.2.0<-
```

User response

Remove the file from the Content Manager OnDemand cache. If the problem persists, contact your IBM Service Representative.

ARS0108E

Unable to validate library server

Explanation

The library and object servers failed to validate that they belong to the same Content Manager OnDemand instance.

Example:

```
Unable to validate library server  
Svr->www.example.com<-
```

User response

Verify that the Content Manager OnDemand instance is properly configured. Restart the servers. If the problem persists, contact your IBM Service Representative.

ARS0109I

Cache Expiration: Internal Date(*internal_date*) MinPct(*minimum_percentage*)
MaxPct(*maximum_percentage*) Server(*server*)

Explanation

The ARSMANT program has started to expire data from cache storage. This message is for your information only.

Example:

```
Cache Expiration: Internal Date(11850) MinPct(0)  
MaxPct(0) Server(www.example.com)
```

User response

No action is required.

ARS0110I

Cache Migration: Date(*date*) Internal Date(*internal_date*) Server(*server*)

Explanation

The ARSMANT program writes this message to the system log each time that it starts to migrate data to archive storage. This message is for your information only.

User response

No action is required.

ARS0111E

Content Manager OnDemand is unable to determine the link for the file *>file_name<*. *errno=errno*

Explanation

The Content Manager OnDemand server was unable to access the specified file. Either the link does not exist, or the link exists but does not point to a file. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

If the link does not exist in the Content Manager OnDemand retrieval directory for this file, either recreate the link or delete the file. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0112E

Content Manager OnDemand is unable to change permissions on the file *>file_name<*. *errno=errno*

Explanation

An error occurred while this program was running.

The Content Manager OnDemand server was unable to access the specified file. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Check to ensure that the Content Manager OnDemand instance owner has permissions for this file in the Content Manager OnDemand cache. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0113E

Cache Migration Failed: ApplGroup(*appl_grp_name*) Agid(*agid*) ObjName(*object_name*) Date(*date*)
InternalDate() Server(*server*)

Explanation

The ARSMAINT program failed when attempting to migrate data to archive storage.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the migration. If the problem persists, contact your IBM Service Representative.

ARS0114E

Unable to open file >*file_name*<. errno=*errno*

Explanation

The command failed when attempting to open the specified file. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Verify that the file exists and that the file permissions are correct, then resubmit the command. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0115E

OnDemand is unable to seek within file >*file_name*< from *offset* to *length*. errno=*errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Check to ensure that the byte offset and length values are correct for this file, and try the command again. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0116E

Unable to stat file >*file_name*<. errno=*errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Check to ensure that the file and directory path are correct, and that the file and directory exist. Then try the command again. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0117E

The byte count between offset *off* and length *len* is larger than the size of the file *>file_name<* of size bytes

Explanation

An error occurred while this program was running.

Example:

```
Offset **UNK** and length **UNK** is larger
than the size of the file >**UNK**< of
**UNK** bytes
Srvr->www.example.com 192.0.2.0<-
```

User response

Check to ensure that the byte offset and length values are correct for this file, and try the command again. If the problem persists, contact your IBM Service Representative.

ARS0118E

Unable to read from file *>file_name<*. *errno=errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Verify that the file exists and that the file permissions are correct, and try the command again. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0119E

Unable to write to file *>file_name<*. *errno=errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

Example:

```
Unable to write to file
>/arscache1/13585/SL/DOC/1502FAA<.
errno=28 Srvr->www.example.com<-
```

User response

Verify that the directory path exists and that the file permissions are correct. Then try the command again. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0122E

Unable to close the file *>file_name<*. *errno=errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Verify that the path for the file exists, and that the file permissions are correct. Then try the command again. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0123E

Unable to stat filesystem *>filesystem_name<*. `errno=errno`

Explanation

The ARSMaint program failed when attempting to run statistics on the specified filesystem. The `errno` value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Verify that the filesystem exists and verify the filesystem permissions, then resubmit the command. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0124I

Filesystem Stats Name(*filesystem_name*) Data(*percent_full%*) Inodes(*inode_percent_full%*)

Explanation

The ARSMaint program has started to run statistics on the specified filesystem. This message is for your information only.

Example:

```
Filesystem Stats Name(/arscache1)
Data(84%) Inodes(1%)
Srvr->www.example.com 192.0.2.0<-
```

User response

No action is required.

ARS0125E

Unable to create symbolic link from file *>symbolic_name<* to *>file_name<*. `errno=errno`

Explanation

An error occurred while this program was running. The `errno` value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

Example:

```
Unable to create symbolic link from file
>/QIBM/USERDATA/ONDEMAND/ONDPERFORM/CACHE/ONDPERFORM/retr/SL/APPEND<
to
>/QIBM/USERDATA/ONDEMAND/ONDPERFORM/CACHE/ONDPERFORM/21667/SL/DOC/9FAA<.
errno=3457 Srvr->www.example.com<-
```

User response

Verify that the target file and path exist, and that the directory permissions are correct. Then try the command again. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0126I

Application Group Document Expire: Name(*appl_grp_name*) Agid(*agid*) Cnt(*documents_expired*)

Explanation

The ARSMANT program is using the document expiration method to delete items from an application group. This message is for your information only.

Example:

```
Application Group Document Expire:  
Name(2014 Monthly Credit Card Statements)  
Agid(15197) Cnt(14)
```

User response

No action is required.

ARS0127I

Application Group Load Expire: Name(*appl_grp*) Agid(*agid*) LoadId(*load_id*) UnLoad Storage Manager(*sm_unload*)

Explanation

The ARSMANT program writes this message to the system log when using the Load expiration method to delete items from an application group. This message is for your information only.

Example:

```
Application Group Load Expire:  
Name(2014 Monthly Credit Card Statements) Agid(5015)  
LoadId(41428-1-0-1FAA-20050801000000-20050801000000-41429)  
UnLoad Storage Manager()
```

User response

No action is required.

ARS0128I

Application Group Segment Expire: Name(*appl_grp_name*) Agid(*agid*) Seg(*segment_name*)

Explanation

The ARSMANT program is using the segment expiration method to delete items from an application group. This message is for your information only.

Example:

```
Application Group Segment Expire:  
Name(2014 Monthly Credit Card Statements)  
Agid(15757) Seg(YJF1)
```

User response

No action is required.

ARS0129E

Filesystem Full Name(*filesystem_name*) Data(*percent_full%*) Inodes(*inode_percent_full%*)

Explanation

The cache storage filesystem is almost full.

User response

Either extend the existing cache storage filesystem or add new cache storage filesystems. Then restart the server.

ARS0130E

No logical place to store object *>object_name<*

Explanation

The command failed when attempting to store the object because there are no cache storage file systems that are defined to the system or the archive storage manager is not properly configured.

User response

To use cache storage, define and configure OnDemand cache storage filesystems. To use archive storage, install and configure the archive storage manager. Then restart the server and resubmit the command.

ARS0131E

No logical place to retrieve object *>object_name<*

Explanation

The command failed when attempting to retrieve the object because there are no cache storage filesystems defined to the system or the archive storage manager is not properly configured.

User response

To use cache storage, define and configure OnDemand cache storage filesystems. To use archive storage, install and configure the archive storage manager. Then restart the server and resubmit the command.

ARS0132I

Printer Options Add: Name(*printer_opts_name*)

Explanation

Printer options were added. This message is for your information only.

User response

No action is required.

ARS0133I

Id Printer Options Add: Id(*id*) Name(*printer_opts_name*)

Explanation

Printer options were added for the user with the specified ID. This message is for your information only.

Example:

```
Id Prt Options Add: Id(12) Name(rosa)
```

User response

No action is required.

ARS0134I

Printer Options Delete: Name(*printer_opts_name*)

Explanation

Printer options were deleted. This message is for your information only.

User response

No action is required.

ARS0135I

Id Printer Options Delete: Id(*id*) Name(*printer_opts_name*)

Explanation

This message is for your information only.

User response

No action is required.

ARS0136I

Printer Options Update: Name(*printer_opts_name*)

Explanation

This message is for your information only.

User response

No action is required.

ARS0137I

Id Printer Options Update: Id(*id*) Name(*printer_opts_name*)

Explanation

This message is for your information only.

User response

No action is required.

ARS0138E

BulkPrint Failed

Explanation

The server print function failed.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the server print function. If the problem persists, contact your IBM Service Representative.

ARS0139E

Unable to run program >*command*<. *errno=errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Check the installation directory to ensure that the file exists and is executable, then try the command again. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0140E

Unable to fork a child process. *errno=errno*, *File=file*, *Line=line*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Shut down any other running processes to free memory, or restart Content Manager OnDemand. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0141E

Ran out of load-id naming conventions. Increase the size of the Application Group Object Size.

Explanation

The system was unable to create new object names because it exceeded the number of available object names for this application group. The object size controls how much space is allotted for objects in an application group.

User response

Increase the object size on the application group's Advanced Storage Management page in the OnDemand administrative client. Then resubmit the command.

ARS0142E

Connection cannot be established for the `>hostname<` server

Explanation

The client was unable to connect to the specified server.

Example:

```
Connection cannot be established for
the >PRODUCTION< server.
SIVT->www.example.com<-
```

User response

Verify that the server is available, that it is properly configured, and that the required programs are running. Then resubmit the command.

ARS0145E

The communication layer was unable to send data. *errno=errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems and resides in `/usr/include/errno.h` on z/OS systems.

User response

Check to ensure that an instance of the Content Manager OnDemand server is not already running. Then restart the Content Manager OnDemand server. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0146E

The communication layer was unable to receive data. *errno=errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Stop and restart the Content Manager OnDemand server. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0147E

Unable to initialize server environment. *rc=returnCode*

Explanation

An error occurred while this program was running.

User response

Check the configuration files `ars.ini` and `ars.cfg` to verify that they exist, that file system paths and parameters are correct, and that the files have the correct permissions. Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS0149E

Unable to initialize server communications. *rc=returnCode*

Explanation

An error occurred while this program was running.

A communication error occurred. Either the Content Manager OnDemand server was already started, TCP/IP was not started, or there is a configuration problem.

User response

Ensure that the maximum amount of memory per process is unlimited. Check to see that the server is running and that TCP/IP is started. Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS0150E

Unable to allocate enough memory. *File=file, Line=line*

Explanation

An error occurred while this program was running.

User response

Ensure that there is enough memory to support all processes that are currently running, and try the command again. If the problem persists, contact your IBM Service Representative.

ARS0151E

Unable to initialize server database system parameters. Contact your system administrator.

Explanation

The command failed when attempting to initialize the database.

User response

Verify that the Content Manager OnDemand instance and the database are properly configured. Then resubmit the command.

ARS0152E

The command *>command<* can only be run by the owner of the command

Explanation

The command failed when attempting to run the specified command.

User response

Log on to the system as the owner of the command and then resubmit the command.

ARS0153E

Unable to change directory to *>directory_name<*. *errno=errno*

Explanation

The system failed when attempting to change to the specified directory. The *errno* value, which might provide additional information, resides in */usr/include/sys/errno.h* on UNIX systems, */usr/include/errno.h* on z/OS systems, and */QIBM/include/errno.h* on IBM i systems.

User response

Verify that the directory exists and verify the directory permissions. Then resubmit the command. See the *errno.h* file for more information.

ARS0154E

Unable to establish server communications with network. *rc=returnCode*

Explanation

An error occurred while this program was running.

A communication error occurred. Either the Content Manager OnDemand server was already started, TCP/IP was not started, or there is a configuration problem. The *ARSSOCK= debug* parameter in *ars.cfg* can help you troubleshoot TCP/IP errors.

User response

Ensure that TCP/IP is running, then try the command again. If the problem persists, contact your IBM Service Representative.

ARS0155E

Server is unable to communicate to receive client requests. *rc=returnCode*

Explanation

An error occurred while this program was running.

A TCP/IP failure occurred.

User response

Check to see if TCP/IP is running. Stop and restart the Content Manager OnDemand Server. If the problem persists, contact your IBM Service Representative.

ARS0157E

SubSrvr is unable to communicate request with Server

Explanation

An error occurred while this program was running.

A TCP/IP failure occurred.

User response

Check to see if TCP/IP is running. Stop and restart the Content Manager OnDemand Server. If the problem persists, contact your IBM Service Representative.

ARS0158E

Server is unable to initialize database connection. *rc=returnCode*

Explanation

The server failed when attempting to initialize the database.

User response

Verify that the database is running and that you can connect to it. See the Content Manager OnDemand System Log for other messages that are associated with database initialization. If the problem persists, contact your IBM Service Representative.

ARS0159E

Server is unable to terminate database connection properly. *rc=returnCode*

Explanation

The server failed when attempting to terminate the database connection.

User response

Verify that the database is running and that you can connect to it. See the Content Manager OnDemand System Log for other messages that are associated with database initialization. If the problem persists, contact your IBM Service Representative.

ARS0160E

Unable to load module *>function_name<*. *rc=returnCode*

Explanation

The system failed when attempting to load the specified dynamic load library. Permissions on the dynamic load library need to be at least read and execute. On a UNIX system, the load module must also exist in the server exits directory (`/opt/IBM/ondemand/V10.1/bin/exits`). On a Windows system, the load module must also exist in the server bin directory.

Example 1:

```
Unable to load module /opt/IBM/ondemand/V10.1/exits/arsusxct. rc=2
Srvr->www.example.com 192.0.0.0<-
```

Example 2:

```
ARS0160E ARSSOCKD UNABLE TO LOAD MODULE >/opt/IBM/ondemand/V10.1/BIN/EXITS/
ARSUSEC<.
RC=157 SRVR->ARSSRV02<-
```

User response

Verify that the dynamic load library exists and verify the file permissions. Then resubmit the command.

For example, if you receive this message with return code 157 as shown in Example 2 above, verify that `/opt/IBM/ondemand/V10.1/bin/exits/arsusec` has the APF bit set by issuing the following from omvs or telnet:

```
ls -lE /opt/IBM/ondemand/V10.1/bin/exits/arsusec
```

If the result does not include the 'a' flag, as shown below:

```
-rwxr-xr-x a-s- /opt/IBM/ondemand/V10.1/bin/exits/arsusec
```

use

```
extattr +a /opt/IBM/ondemand/V10.1/bin/exits/arsusec
```

to set the APF bit.

If the APF flag is already set, confirm how the HFS was mounted for `/opt/IBM/ondemand/V10.1/bin/exits`. If `nosetuid` was specified when the mount was issued, the APF bit is ignored. This might also cause return code 157 from ARS0160E even when the APF flag is set for the exit load modules.

ARS0161E

The userexit `>userexit_name<` failed. The return code is `rc returnCode`

Explanation

The specified user exit program failed. The return codes are:

Return Code	Description
3	Permissions on the user exit program need to be at least read and execute. On a UNIX system, the exit module must also exist in the server exits directory (<code>/opt/IBM/ondemand/V10.1/bin/exits</code>). On a Windows system, the exit module must also exist in the server bin directory.
12	this is a fixed recfm and the lrecl isn't between 1 and 32767
13	CC returned was not NONE, ANSI, or Machine
14	Recfm returned was not Fixed, Variable or Stream
15	the application name the exit returned does not exist
16	the application group information the exit returned doesn't exist
17	storage node not in storage set
18	the delimiter in a stream recfm is not valid

Example:

```
The userexit >QRDARS/ARSUSEC< failed.
rc=3  Srvr->WWW.EXAMPLE.COM<-
```

User response

Review the user exit documentation for possible return codes. Verify that the user exit program functions properly outside of the Content Manager OnDemand environment. Then resubmit the command.

ARS0162E

Unable to determine codepage. Check configuration file `ars.cfg` for `ARS_CODEPAGE` variable.

Explanation

The command failed when attempting to determine the codepage.

User response

Verify that the Content Manager OnDemand instance is configured correctly and then resubmit the command.

ARS0163E

Unable to initialize converter from (codepage, codeset) `input_codepage,input_codeset` to (codepage, codeset) `output_codepage,output_codeset`. `rc=returnCode`

Explanation

An error occurred while running this program.

User response

Check to make sure the converter codepage exists in the `cnvtrts.txt` file and that the ICU Data Library is in the locale directory and has the correct permissions. If the problem persists, contact your IBM Service Representative.

ARS0164I

Application Group Segment Maintenance: Name(`appl_grp_name`) Agid(`agid`) SegName(`segment_name`)
Action(`action`) Time(`time`)

Explanation

The ARSMAINT program collected statistics on the specified table. This message is for your information only.

Example:

```
Application Group Segment Maintenance:  
Name(2014 Monthly Credit Card Statements)  
Agid(15912) SegName(WLF1) Action(15) Time(0.195)
```

User response

No action is required.

ARS0165I

Application Group Segment Expire Maintenance: Name(`appl_grp_name`) Agid(`agid`)
SegName(`segment_name`)

Explanation

The ARSMAINT program expired the specified segment from the specified application group. This message is for your information only.

Example:

```
Application Group Segment Expire Maintenance:  
Name(2014 Monthly Credit Card Statements)  
Agid(15404) SegName(MFF1)
```

User response

No action is required.

ARS0166I

Application Group Segment Export: Name(*appl_grp_name*) Agid(*agid*) SegName(*segment_name*)
Time(*time*)

Explanation

The ARSMAINT program migrated the specified segment from the database to archive storage. This message is for your information only.

Example:

```
Application Group Segment Export:  
Name(2014 Monthly Credit Card Statements)  
Agid(15673) SegName(VIF1FAA) Time(2.364)
```

User response

No action is required.

ARS0167I

Application Group Segment Import: Name(*appl_grp_name*) Agid(*agid*) SegName(*segment_name*)
Time(*time*)

Explanation

The ARSADMIN program imported the specified segment from archive storage to the database. This message is for your information only.

Example:

```
Application Group Segment Import:  
Name(2014 Monthly Credit Card Statements) Agid(15673)  
SegName(VIF1FAA) Time(2.364)
```

User response

No action is required.

ARS0168E

Application Group Segment Not Available: Name(*appl_grp_name*) Agid(*agid*) SegName(*segment_name*)

Explanation

The specified segment was required to perform a query, however, the segment was not found in the database.

Example:

```
Application Group Segment Not Available:  
Name(2014 Monthly Credit Card Statements)  
Agid(15365) SegName(WEF2)
```

User response

Ask an administrator to import the specified segment from the archive storage to the database. Then resubmit the command.

ARS0169E

Application Group Segment Migration Failed: Name(*appl_grp_name*) Agid(*agid*)
SegName(*segment_name*). rc=*returnCode*

Explanation

The command failed when attempting to migrate a segment.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the migration. If the problem persists, contact your IBM Service Representative.

ARS0171E

Application Group Segment Exists: Name(*appl_grp_name*) Agid(*agid*) SegName(*segment_name*).
rc=*returnCode*

Explanation

The command did not import the segment because the segment already exists in the database.

User response

Verify the name of the segment, and the name and ID of the application group. Then resubmit the command.

ARS0172E

Filesystem >*filesystem_name*< is not unique. It is common with filesystem >*common_filesystem_name*<

Explanation

Duplicate filesystem names were used in the `ars.dbfs` configuration file. Filesystem names must be unique.

User response

Change the filesystem configuration so that it contains only unique filesystem names. Then restart the server and resubmit the command.

ARS0173I

Annotation Update: Name(*appl_grp_name*) Agid(*agid*)

Explanation

An annotation was updated. This message is for your information only.

Example:

```
Annotation Update: Name(CHECKSDB) Agid(5025)
```

User response

No action is required.

ARS0174I

Annotation Id Update: Id(*id*) Name(*appl_grp_name*) Agid(*agid*)

Explanation

This message is for your information only.

User response

No action is required.

ARS0175E

User *>user_name<* does not have permission to perform the specified action. File=*file*, Line=*line*

Explanation

The specified user does not have the permissions that are required to perform the action.

User response

Update the user to provide the user with permission to perform the action and then resubmit the command. Otherwise, resubmit the command with a different user ID.

ARS0176E

BulkTextSearch Failed

Explanation

The command failed when attempting a text search.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the text search. If the problem persists, contact your IBM Service Representative.

ARS0178E

System call failed for command *>command<*. *errno=errno*

Explanation

The Content Manager OnDemand server failed trying to execute the command. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Check the Content Manager OnDemand installation directory to ensure that the file exists and is executable, then try the command again. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0179E

License Server Failed. *rc=returnCode*

Explanation

An error occurred while this program was running.

A licensing problem occurred.

User response

If the problem persists, contact your IBM Service Representative.

ARS0186I

OnDemand started - Version *version_number* Operating system *operating_system*
operating_system_version_number Database *database_product_name* *database_version_number* Storage

Manager *storage_manager_product_name* *storage_manager_version_number* Install location
installation_path_name

Explanation

This message is for informational purposes only.

ARS0187E

Unable to establish thread server connection. *rc=returnCode*

Explanation

An error occurred while this program was running.

User response

Ensure that the maximum amount of memory per process is unlimited, then try the command again. If the problem persists, contact your IBM Service Representative.

ARS0188E

The thread cannot be created. The return code is *rc=returnCode*

Explanation

There might not be enough memory for each process.

User response

Ensure that the maximum amount of memory per process is unlimited. Then try the command again. If the problem persists, contact IBM Software Support.

ARS0189E

Unable to create pipe communications. The error number is *errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Ensure that there is enough available memory for Content Manager OnDemand to use, then try the command again. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0190E

System command failed `>command<`. *errno=errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Check the Content Manager OnDemand installation directory to ensure that the file exists and is executable, then try the command again. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0191I

Segment >*segment_name*< unknown in System Migration

Explanation

The command failed when attempting to find the specified segment in the Content Manager OnDemand System Migration application group.

User response

Verify the migration parameters, including the name of the segment and the name of the application group. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS0192E

Unable to create file >*file_name*<. *errno=errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Check, and if necessary, correct the permissions for the directory in which the file is stored. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0193E

Unable to query System Migration Application Group. *rc=returnCode*

Explanation

An error occurred while this program was running.

User response

Verify that the System Migration Application Group and Folder exist. If they do not, create them. Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS0194E

Unable to open directory >*directory_name*<. *errno=errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Verify that the directory exists, and that its permissions are set correctly. Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS0195E

Unable to close directory >*directory_name*<. *errno=errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

Example:

```
Unable to close directory >**UNK**<.  err=(**UNK**)  
Srvr->everest.ibm.com 192.0.2.0<-
```

User response

Verify that the directory exists, and that its permissions are set correctly. Then try the command again. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS0196I

Cache Expiration: Server(*server*)

Explanation

The ARSMANT program expired the specified storage object from the specified application group. This message is for your information only.

Example:

```
Cache Expiration: Server(WWW.EXAMPLE.COM)
```

User response

To view the Cache Expiration Report, use the Content Manager OnDemand client and search the System Log for message number 196.

ARS0197I

Cache Migration

Explanation

The ARSMANT program migrated the specified storage object from cache storage to archive storage. This message is for your information only.

User response

No action is required.

ARS0198E

Invalid ownership and/or permissions on cache file/directory >*path_name*<

Explanation

The ownership or permissions for the specified cache storage file or directory are not correct. Cache filesystems have specific permissions for directories, which are described in the *Installation and Configuration Guide*.

Example:

```
Invalid ownership and/or permissions on cache file/dir >/arscache1<  
Srvr ->www.example.com<-
```

User response

Verify the ownership and permissions for the cache storage filesystems and then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS0199E

Unexpected empty directory in cache >*directory_name*<

Explanation

The cache directory is empty.

User response

Verify the configuration of the cache storage filesystems and resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS0200E

CD-ROM Creation Failed: Volume(*volume*)

Explanation

The command failed when attempting to create the specified CD-ROM.

Example:

```
CD-ROM Creation Failed: Volume(1290)
```

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM creation process. If the problem persists, contact your IBM Service Representative.

ARS0201I

Activities: Current(*current_licenses*)

Explanation

The server generates this message approximately every 30 minutes to display the number of activities on the system (at the time that the message was generated).

Example:

```
Activities: Current(8)
```

User response

No action is required.

ARS0204I

Printer ID Add: Name(*printer_name*) Queue(*queue*) Pid(*pid*) IdName(*id_name*) Id(*id*)

Explanation

This message is for your information only.

Example:

```
Printer ID Add: Name(QPRINT2) Queue(QGPL/QPRINT2)  
Pid(5098) IdName(oduser) Id(3)
```

User response

No action is required.

ARS0205I

Printer Delete: Name(*printer_name*) Queue(*queue*) Pid(*pid*) IdName(*id_name*) Id(*id*)

Explanation

The specified printer was deleted from Content Manager OnDemand. This message is for your information only.

Example:

```
Printer Delete: Name(QPRINT) Queue(QGPL/QPRINT)
Pid(5193) IdName() Id(0)
```

User response

No action is required.

ARS0206I

User Id Add: User(*name*) Id(*id*), Owner User(*owner_name*) Id(*owner_id*), Perms(*permissions*)

Explanation

The specified user ID was added with the specified permissions. This message is for your information only.

User response

No action is required.

ARS0207I

User Id Delete: User(*name*) Id(*id*), Owner User(*owner_name*) Id(*owner_id*)

Explanation

The specified user ID was deleted. This message is for your information only.

Example:

```
User Id Delete: User(oduser1) Id(998),
Owner User(oduser2) Id(74)
```

User response

No action is required.

ARS0208I

User Id Update: User(*name*) Id(*id*), Owner User(*owner_name*) Id(*owner_id*), Perms(*permissions*)

Explanation

The specified user ID was updated as shown. This message is for your information only.

User response

No action is required.

ARS0209I

User Id Add: User(*name*) Id(*id*), Group(*owner_name*) Id(*owner_id*), Perms(*permissions*)

Explanation

This message is for your information only.

Example:

```
User Id Add: User(oduser) Id(20),
Group(odusergroup) Id(1080041), Perms(3)
```

User response

No action is required.

ARS0210I

User Id Delete: User(*name*) Id(*id*), Group(*owner_name*) Id(*owner_id*)

Explanation

This message is for your information only.

User response

No action is required.

ARS0211I

User Id Update: User(*name*) Id(*id*), Group(*owner_name*) Id(*owner_id*), Perms(*permissions*)

Explanation

This message is for your information only.

User response

No action is required.

ARS0212I

BulkTextSearch: Time(*time*)

Explanation

The search was completed in the length of time indicated. This message is for your information only.

Example:

```
BulkTextSearch: Time(2.752)  Srvr->www.example.com<-
BULK DOCUMENT RETRIEVAL
Application Group                Agid Flds->Handle
-----
2014 Monthly Credit Card Statements  5014 ->7FAAA,3852,968,0,3272,0x4E,0x4F,0,1,0
```

User response

No action is required.

ARS0213I

Unable to load the Content Manager OnDemand DB2 dynamic load library (arsdb2). Check to make sure DB2 is installed and that the db2ln command has been run

Explanation

The command failed when attempting to load the DB2 dynamic load library.

User response

Verify that DB2 is correctly installed and configured. Verify that the links were created for the DB2 files. (Verify that the db2ln command was run successfully.)

ARS0214I

Unable to load the Content Manager OnDemand Microsoft SQL Server dynamic load library (arsmssql.dll)

Explanation

The command failed when attempting to load the Microsoft SQL Server dynamic load library.

User response

Verify that Microsoft SQL Server is correctly installed and configured.

ARS0215I

Unable to load the Content Manager OnDemand Oracle dynamic load library (arsorcle). Check to make sure that Oracle is installed and that the Oracle shared library (libclntsh.a (AIX), libclntsh.so (SunOS), oci.dll (Windows)) is in the shared library path

Explanation

The command failed when attempting to load the Oracle dynamic load library.

User response

Verify that Oracle is correctly installed and configured.

ARS0216E

Unable to determine SMS/DMS tablespace type or filesystem is invalid >filesystem_name<. errno=errno

Explanation

The definition of the storage management subsystem (SMS) or document management system (DMS) tablespaces is not valid. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Verify and correct the tablespace filesystem definitions, then restart the server and resubmit the command. See the `errno.h` file for more information.

ARS0217E

Application Group(*appl_grp_name*) Application(*appl_name*) defines a document with a data type that can not be printed by this server

Explanation

The server print function failed to print a document.

User response

The server print function could not handle the data type of the document that was selected. Resubmit the document to the local print function, which will send the print job to a different printer.

ARS0218E

rtn, lmod, source, reason, cblock, addr, lineNum

rtn Routine producing the message

lmod Module producing the message

source Source file detecting the problem

reason Reason code describing the error

cblock Control block related to the error

addr Address related to the error

lineNum Line number of the source file detecting the error

Explanation

The software detected an inconsistency in a control block. An attempt was made to produce an SDUMP, but the attempt failed, possibly because DAE prevented it.

User response

The software will attempt to recover. Search the problem reporting database for a fix for the problem. If no fix exists, contact your IBM Service Representative.

ARS0219E

ARSMVSR2 Ssss Uuuuu RSN:xxxxxxx

sss System ABEND code

uuuu User ABEND code

xxxxxxx ABEND reason code

Explanation

The attempt to log on to Content Manager OnDemand with a PassTicket was rejected. An ABEND occurred attempting to verify a user PassTicket. An attempt was made to produce an SDUMP, but the attempt failed.

User response

There is probably an error with the information that was returned by the ARS.PTGN dynamic exit. Attempt to correct the exit.

ARS0220I

Server code page is *cpgid*

Explanation

The server is using the specified code page. This message is for your information only.

User response

No action is required.

ARS0221I

Folder Delete: Name(*name*) Fid(*fid*)

Explanation

The specified folder was deleted from the system. This message is for your information only.

User response

No action is required.

ARS0222W

SM Warning: *text*, The requested delete was ignored because data retention protection is turned on in the storage manager.

Explanation

The delete issued to the TSM storage manager did not succeed because data retention protection is turned on. The TSM storage manager issued return code 2302 and reason code 248.

User response

No action is required.

ARS0226I

Application Group Query: Name(*appl_grp_name*) Agid(*agid*) Time(*time*) Hits(*hits*) Count(*count*)
SegStart(*seg_start_date*) SegStop(*seg_stop_date*) Tables(*num_tables*) *additional_fields*

Explanation

A query was run against the specific application group. This message is for your information only.

User response

No action is required.

ARS0227W

Unable to determine application aid because no documents were found for ApplGroup (*appl_grp_name*)
LoadId(*agid-pri_nid-sec_nid-name-start_date-stop_date*)

Explanation

Semaphore initialization failed.

User response

No action is required.

ARS0228E

Unable to determine application aid for ApplGroup (*appl_grp_name*) LoadId (*agid-pri_nid-sec_nid-name-start_date-stop_date*)

Explanation

Semaphore initialization failed.

User response

No action is required.

ARS0229I

Cabinet Add: Name(*cabinet_name*) Cid(*cid*)

Explanation

The specified cabinet was added to the system. This message is for your information only.

User response

No action is required.

ARS0230I

Cabinet Delete: Name(*cabinet_name*) Cid(*cid*)

Explanation

The specified cabinet was deleted from the system. This message is for your information only.

User response

No action is required.

ARS0231I

Cabinet Update: Name(*cabinet_name*) Cid(*cid*)

Explanation

The specified cabinet was updated. This message is for your information only.

User response

No action is required.

ARS0232I

Folder to Cabinet Add: Folder(*folder_name*) Fid(*fid*) Cabinet(*cabinet_name*) Cid(*cid*)

Explanation

The specified folder was added to the specified cabinet. This message is for your information only.

User response

No action is required.

ARS0233I

Folder to Cabinet Delete: Folder(*folder_name*) Fid(*fid*) Cabinet(*cabinet_name*) Cid(*cid*)

Explanation

The specified folder was deleted from the specified cabinet. This message is for your information only.

User response

No action is required.

ARS0234I

Id to Cabinet Add: Name(*id_name*) Id(*id*) Cabinet(*cab_name*) Cid(*cid*)

Explanation

Permissions were added to the specified cabinet for the User or Group specified with the Id. This message is for your information only.

User response

No action is required.

ARS0235I

Id to Cabinet Delete: Name(*id_name*) Id(*id*) Cabinet(*cab_name*) Cid(*cid*)

Explanation

Permissions were deleted from the specified cabinet for the User or Group with the specified Id. This message is for your information only.

User response

No action is required.

ARS0236I

Id to Cabinet Update: Name(*id_name*) Id(*id*) Cabinet(*cab_name*) Cid(*cid*)

Explanation

Permissions were updated in the specified cabinet for the User or Group with the specified Id. This message is for your information only.

User response

No action is required.

ARS0237E

The system cannot parse the SQL tokenized query string that is provided starting at position marker position (position) with the string input value (str_val).

Explanation

The query string cannot be parsed because of one or more incorrect input parameters.

User response

Verify that the string input value is a string type and that it is enclosed in single quotation marks. Resubmit the command.

ARS0238E

The tokenized query string format has a nonnumeric value at marker position (position). Use a numeric value instead.

Explanation

An invalid numeric value was specified.

User response

Check that the value is numeric, and resubmit the command.

ARS0239E

In the tokenized query string format, the number of parameter markers (num_param) must be equal to the number of parameter names (array_size).

Explanation

The number of parameter markers must equal the number of parameter names.

User response

Provide valid values to the SQL string and resubmit the command.

ARS0240E

The SQL tokenized query string is missing parameter values and cannot be processed. The number of parameter markers specified is num_param.

Explanation

The number of parameters (num_param) is greater than the number of parameter values provided.

User response

Verify that the values in the parameter value string are equal to the number of parameters and resubmit the command.

ARS0241E

The tokenized query string format failed. The number of parameters (num_param) is not equal to the number of markers (num_marker) in the WHERE clause.

Explanation

The number of parameters is different than the number of markers in the WHERE clause.

User response

Verify that the number of parameters is equal to the number of markers in the WHERE clause and resubmit the command.

ARS0242E

The tokenized query string format failed. There is an invalid database field name (pname) at position (position) in the parameter name string.

Explanation

The parameter name string is not a database field name.

User response

Correct the spelling of the database field name in the parameter name string and resubmit the command.

ARS0243E

The system cannot parse the SQL tokenized document query binding parameter starting at position (col) with the variable value (sqldata) and return code (rc).

Explanation

The binding program variable does not match the parameter marker. This might be due to an incorrect mapping between the parameter name and its associated value.

User response

Verify the mapping between the parameter name and value. Resubmit the command.

ARS0244E

Tokenized query string format failed at database field names string. A valid format should be: dbfield1,dbfield2,dbfield3

Explanation

An invalid database field name string was specified.

User response

Check the database field name string format, and resubmit the command.

ARS0246W

String value ('str_val') is too long for: column(col_name), column size(col_size), at marker (marker_pos). A maximum of col_size character(s) may be entered

Explanation

A string value is too long.

User response

Make sure that the string length does not exceed the database column size, and resubmit the command.

ARS0247I

Hold Add: Name (*hold_name*) Hid (*hid*)

Explanation

The specified hold was added to the system. This message is for your information only.

User response

No action is required.

ARS0248I

Hold Delete: Name (*hold_name*) Hid (*hid*)

Explanation

The specified hold was deleted from the system. This message is for your information only.

User response

No action is required.

ARS0249I

Hold Update: Name (*hold_name*) Hid (*hid*)

Explanation

The specified hold was updated. This message is for your information only.

User response

No action is required.

ARS0250I

Id to Hold Add: Name(*id_name*) Id (*id*) Hold (*hold_name*) Hid (*hid*)

Explanation

Permissions were added to the specified hold for the User or Group with the specified Id. This message is for your information only.

User response

No action is required.

ARS0251I

Id to Hold Delete: Name(*id_name*) Id (*id*) Hold (*hold_name*) Hid (*hid*)

Explanation

Permissions were deleted from the specified hold for the User or Group with the specified Id. This message is for your information only.

User response

No action is required.

ARS0252I

Id to Hold Update: Name(*id_name*) Id(*id*) Hold(*hold_name*) Hid(*hid*)

Explanation

Permissions were updated in the specified hold for the User or Group with the specified Id. This message is for your information only.

User response

No action is required.

ARS0253I

Application to Hold Add: Hold(*hold_name*) Hid(*hid*) ApplGroupName(*appl_group_name*) Agid(*agid*)
ApplName(*appl_name*) Aid(*aid*)

Explanation

The application group/application was added to the specified hold. This message is for your information only.

User response

No action is required.

ARS0254I

Application group to Hold Add: Hold(*hold_name*) Hid(*hid*) ApplGroupName(*appl_group_name*) Agid(*agid*)

Explanation

The application group was added to the specified hold.

User response

No action is required.

ARS0255I

Application to Hold Delete: Hold(*hold_name*) Hid(*hid*) ApplGroup(*appl_grp_name*) Agid(*agid*)
Appl(*appl_name*) Aid(*aid*)

Explanation

The application group/application was deleted from the specified hold. This message is for your information only.

User response

No action is required.

ARS0256I

Application Group to Hold Delete: Hold(*hold_name*) Hid(*hid*) ApplGroupName(*appl_group_name*)
Agid(*agid*)

Explanation

The application group was deleted from the specified hold. This message is for your information only.

User response

No action is required.

ARS0257E

PDF document/resource conversion error. See stored document for more information.

Explanation

OnDemand failed while combining the PDF document and resource.

User response

See the document stored with the message for more information.

ARS0258I

Document Hold Add: Hold(*hold_name*) Hid(*hid*) ApplGroup(*appl_group_name*) Agid(*agid*) Count(*count*) Time(*time*)

Explanation

The application group document(s) were added to the specified hold. This message is for your information only.

User response

No action is required.

ARS0259E

Document Hold Add Failed: Hold(*hold_name*) Hid(*hid*) ApplGroup(*appl_group_name*) Agid(*agid*) Count(*count*) Time(*time*)

Explanation

The application group document(s) failed to be added to the specified hold. This message is for your information only.

User response

No action is required.

ARS0260I

Document Hold Delete: Hold(*hold_name*) Hid(*hid*) ApplGroup(*appl_group_name*) Agid(*agid*) Count(*count*) Time(*time*)

Explanation

The application group document(s) were deleted from the specified hold. This message is for your information only.

User response

No action is required.

ARS0261E

Document Hold Delete Failed: Hold(*hold_name*) Hid(*hid*) ApplGroup(*appl_group_name*) Agid(*agid*) Count(*count*) Time(*time*)

Explanation

The application group document(s) failed to be deleted from the specified hold. This message is for you information only.

User response

No action is required.

ARS0262I

Document Implied Hold Add: ApplGroup(*appl_group_name*) Agid(*agid*) Count(*count*) Time(*time*)

Explanation

The application group document(s) were added to the implied hold.

User response

No action is required.

ARS0263E

Document Implied Hold Add Failed: ApplGroup(*appl_group_name*) Agid(*agid*) Count(*count*) Time(*time*)

Explanation

The application group document(s) failed to be added to the implied hold.

User response

No action is required.

ARS0264I

Document Implied Hold Delete: ApplGroup(*appl_group_name*) Agid(*agid*) Count(*count*) Time(*time*)

Explanation

The application group document(s) were deleted from the implied hold. This message is for your information only.

User response

No action is required.

ARS0265E

Document Implied Hold Delete Failed: ApplGroup(*appl_group_name*) Agid(*agid*) Count(*count*) Time(*time*)

Explanation

The application group document(s) failed to be deleted from the implied hold. This message is for your information only.

User response

No action is required.

ARS0266I

Document CFS-OD Add: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*)
Count(*count*) Time(*time*)

Explanation

The application group document(s) were federated to CFS-OD.

User response

No action is required.

ARS0267E

Document CFS-OD Add Failed: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*)
Count(*count*) Time(*time*)

Explanation

The application group document(s) failed to be federated to CFS-OD.

User response

No action is required.

ARS0268I

Document CFS-OD Delete: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Count(*count*) Time(*time*)

Explanation

The application group document(s) were deleted from federated CFS-OD.

User response

No action is required.

ARS0269E

Document CFS-OD Delete Failed: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Count(*count*) Time(*time*)

Explanation

The application group document(s) failed to be deleted from federated CFS-OD.

User response

No action is required.

ARS0270I

Document CFS-OD Records Manager Add: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Count(*count*) Time(*time*)

Explanation

The application group document(s) were added to the CFS-OD Records Manager.

User response

No action is required.

ARS0271E

Document CFS-OD Records Manager Add Failed: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Count(*count*) Time(*time*)

Explanation

The application group document(s) failed to be added to the CFS-OD Records Manager.

User response

No action is required.

ARS0272I

Document CFS-OD Records Manager Delete: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Count(*count*) Time(*time*)

Explanation

The application group document(s) were deleted from CFS-OD Records Manager.

User response

No action is required.

ARS0273E

Document CFS-OD Records Manager Delete Failed: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Count(*count*) Time(*time*)

Explanation

The application group document(s) failed to be deleted from CFS-OD Records Manager.

User response

No action is required.

ARS0275I

Application Group CFS-OD Delete: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Time(*time*)

Explanation

The application group was deleted from CFS-OD.

User response

No action is required.

ARS0276E

Application Group CFS-OD Delete Failed: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Time(*time*)

Explanation

The application group failed to be deleted from CFS-OD.

User response

No action is required.

ARS0277I

Application Group Application CFS-OD Delete: ApplGroup(*appl_group_name*) Agid(*agid*) Aid(*aid*) CFS-OD Notified(*cfs_notified*) Time(*time*)

Explanation

The application was deleted from CFS-OD.

User response

No action is required.

ARS0278E

Application Group Application CFS-OD Delete Failed: ApplGroup(*appl_group_name*) Agid(*agid*) Aid(*aid*) CFS-OD Notified(*cfs_notified*) Time(*time*)

Explanation

The application failed to be deleted from CFS-OD.

User response

No action is required.

ARS0279I

Document CFS-OD Update: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Count(*count*) Time(*time*)

Explanation

The application group document(s) were federated to CFS-OD.

User response

No action is required.

ARS0280E

Document CFS-OD Update Failed: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Count(*count*) Time(*time*)

Explanation

The application group document(s) failed to be federated to CFS-OD.

User response

No action is required.

ARS0281I

Application Group CFS-OD Update: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Time(*time*)

Explanation

The application group was updated to no longer use CFS-OD.

User response

No action is required.

ARS0282E

Application Group CFS-OD Update Failed: ApplGroup(*appl_group_name*) Agid(*agid*) CFS-OD Notified(*cfs_notified*) Time(*time*)

Explanation

The application group failed to update CFS-OD that it no longer uses CFS-OD.

User response

No action is required.

ARS0283I

Application Group Check Unload: ApplGroup(*appl_grp_name*) Agid(*agid*) Aid(*aid*) LoadId(*load_id*) Total Load Rows(*total_rows*) Total Queried Rows(*total_query_rows*)totals

Explanation

The application group is checked to determine if an unload can occur. This message is for your information only.

User response

No action is required.

ARS0284E

Ran out of load id naming conventions. Please retry the operation.

Explanation

While creating the object names, the system exceeded the maximum possible values for this system generated load id. The system will attempt to re-adjust the available load ids. Please retry the operation.

User response

Retry the operation.

ARS0285I

Setting server locale: *locale*

ARS0286I

Messaging initialization complete

ARS0287I

Library server starting

ARS0288I

Object server starting

ARS0289E

Unknown server type

ARS0290E

Configuring server failed: *rc*

ARS0291I

Server instance: *instance*

ARS0292E

Obtaining connection information failed: *rc*

ARS0293I

See server trace file for more information

ARS0294I

Activate server trace for more information

ARS0295I

----- Start of server configuration information -----*od_conf*----- End of server configuration information -----

ARS0296E

Environment initialization failed for instance: *instance*

ARS0297I

Server environment: Use security exit

ARS0298I

Server environment: Force security exit

ARS0299I

Server environment: Use folder-application group permissions exit

ARS0300I

Server environment: Use document permissions exit

ARS0301I

Server environment: Use SQL query permissions exit

ARS0302I

Server environment: Use preview exit

ARS0303I

Server environment: Use cabinet permissions exit

ARS0304I

Server environment: Do not write system log messages

ARS0305I

Server environment: Debug server communications

ARS0306I

Server environment: Ignore maximum password length

ARS0307I

Server environment: Allow unified CICS access

ARS0329I

The following entry was added to the Load Monitor Table: Agid(*agid*) LoadId(*load_id*).

Explanation

An entry was added to the database. The message identifies the LoadId, which represents the report in the system. The message also identifies the application group. This message is for informational purposes only.

User response

No action is required.

ARS0330I

The following entry was deleted from Load Monitor Table: Agid(*agid*) LoadId(*load_id*).

Explanation

An entry was deleted from the database because data was unloaded from the system. The message identifies the LoadId, which represents the report in the system. The message also identifies the application group. This message is for informational purposes only.

User response

No action is required.

ARS0331E

Unable to create working directory <*directory*>.

Explanation

Unable to create the working directory. This is preventing the report distribution program from running properly.

User response

Check the permissions for the stated directory and resubmit the command.

ARS0333W

The following user does not have an e-mail address to send notifications: User ID(*userid*) Name(*name*).

Explanation

Sending an e-mail notification from report distribution has failed because the notification user has no e-mail address defined.

User response

Create an e-mail address for this user.

ARS0334E

Data conversion of the following report is not possible: Bundle Name(*bund_name*).

Explanation

The input data types from the associated reports cannot be converted to the requested output data type of the bundle.

User response

Redefine the bundle to contain only reports whose data type can be converted to the requested output type or install the necessary transform program to provide the requested conversion.

ARS0335E

Data conversion of the following report is not possible: Bundle Name(*bund_name*) Report Name(*rept_name*).

Explanation

The input data types from the associated report cannot be converted to the requested output data type of the bundle.

User response

Redefine the bundle to contain only reports whose data type can be converted to the requested output type or install the necessary transform program to provide the requested conversion.

ARS0344E

The SQL statement that was submitted is not allowed by the system.
Application Group Query String=*appl_grp_ws*, File=*name*, Line=*number*

Explanation

The command failed because the SQL statement that was submitted is not allowed by the application. The SQL command keywords select and from are not allowed.

User response

Correct the SQL statement and resubmit the command.

ARS0346E

The system cannot find the correct application group indexes based on the application group information provided. Order=*order*, Num=*num*, File=, Line=

Explanation

Unable to determine the application group definitions due to a logic error or database corruption

User response

See the Content Manager OnDemand system log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS0347E

The system cannot find the correct application group information based on the ID provided. ID=*order*, File=*num*, Line=

Explanation

The information required to run an application is specified in the application group. The application information submitted did not meet the requirements specified for this application in the application group.

User response

See the OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS0348E

The system cannot locate the information required to render a document. Application Group Name=*order*, Load Name=*num*, File=*%3*, Line=*%*

Explanation

The information available to retrieve and display the document was incorrect.

User response

Verify that the document information is correct. Then, resubmit the command.

ARS0349E

When the tracing feature is enabled, you must also extend the shared memory by setting the extended shared memory option to ON: EXTSHM=ON.

Explanation

When you run DB2 on AIX and tracing is enabled, the system is unable to allocate shared memory.

User response

Set the extended shared memory option to ON: EXTSHM=ON. Then, resubmit the command.

ARS0350E

The query cannot be sorted. The number of tables that are required (*order*) to perform the query exceeds the maximum number of tables that are allowed (*num*) for the sort.

Explanation

The server cannot perform the requested sort operation because the query is divided into multiple queries for performance reasons.

User response

Correct and resubmit the query.

ARS0351I

The program instance *instance* is ready.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0352I

The program instance *instance* is ending.

Explanation

The server processing is ending. This message is for informational purposes only.

User response

No action is required.

ARS0353I

The recipient (*recipient*) was added to ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0354I

The recipient (*recipient*) was deleted from ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0355I

The recipient(*recipient*) was updated in ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0356I

The recipient list (*recipient_list*) was added to ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0357I

The recipient list (*recipient_list*) was deleted from ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0358I

The recipient list (recipient_list) was updated in ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0359I

The recipient (recipient) was added to the recipient list (recipient_list) in ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0360I

The recipient (recipient) was deleted from the recipient list (recipient_list) in ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0364I

The report identifier (report_id) based on Application Group Name(applgrp_name) Application Name(appl_name) was added to ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0365I

The report identifier (report_id) based on Application Group Name(applgrp_name) Application Name(appl_name) was deleted from ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0366I

The report identifier (report_id) based on Application Group Name(applgrp_name) Application Name(appl_name) was updated from ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0367I

The bundle (Distribution Name(dist_name) Recipient(recipient) Sequence(sequence) Report Id(report_id)) was added to ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0368I

The bundle (Distribution Name(dist_name) Recipient(recipient) Sequence(sequence) Report Id(report_id)) was deleted from ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0369I

The report bundle (Distribution Name(dist_name) Recipient(recipient) Sequence(sequence) Report Id(report_id)) was updated in ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0370I

The distribution (Distribution Name(dist_name) Recipient(recipient)) was added to ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0371I

The distribution (Distribution Name(dist_name) Recipient(recipient)) was deleted from ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0372I

The distribution (Distribution Name(dist_name) Recipient(recipient)) was updated in ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0373I

The specified distribution (dist_name) and recipient(recipient) was copied based on an existing distribution (copy_dist_name) and recipient(copy_dist_recipient) in ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0374I

The report bundle sequences (Distribution Name(dist_name) Recipient(recipient)) were updated in ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0375I

time DISPLAY OAM

Explanation

This message is issued in response to a MODIFY ARSSOCKD ,D OAM command

User response

No action is required.

ARS0376I

Command rejected. Server busy.

Explanation

This message is issued in response to a MODIFY ARSSOCKD command. Processing the command will exceed the ARS_NUM_CMD_THREADS limit.

User response

Retry the command. If you regularly receive this message, consider increasing the ARS_NUM_CMD_THREADS.

ARS0377I

Command rejected. Verb *verb* invalid.

Explanation

This message is issued in response to a MODIFY ARSSOCKD command. The specified verb is invalid

User response

Retry the command with a valid verb.

ARS0378I

Command rejected. Parameter *parameter* invalid.

Explanation

This message is issued in response to a MODIFY ARSSOCKD command. The specified parameter is invalid

User response

Retry the command with a valid parameter.

ARS0379I

MODIFY ignored, no verb specified.

Explanation

This message is issued in response to a MODIFY ARSSOCKD command. No verb was specified.

User response

Reissue the command with a verb.

ARS0380I

Command failed creating task. Return code is *rc*

Explanation

This message is issued in response to a MODIFY ARSSOCKD command. An error occurred creating a task to process the command.

User response

Reissue the command. If the problem persists, contact your IBM Service Representative.

ARS0381I

Command rejected. Invalid comment.

Explanation

This message is issued in response to a MODIFY ARSSOCKD command. A closing '*' did not occur prior to the end of the command

User response

Reissue the command with a closing '*'

ARS0382I

verb authority invalid, failed by security product.

Explanation

This message is issued in response to a MODIFY ARSSOCKD command. The operator entered a command from a console that did not have the correct command authority.

User response

Enter the command from a console with the proper command authority.

ARS0383I

Command rejected. Excessive number of parameters.

Explanation

This message is issued in response to a MODIFY ARSSOCKD command. Too many parameters were specified.

User response

Enter the command with a correct number of parameters.

ARS0384E

LDAP Error: ldap_text -- ldap_rc=ldap_rc, extended_text -- extended_rc=extended_rc, errno_text -- ldap_errno=errno_rc, extra_rc=extra_rc, File=file, Line=line

Explanation

The database failed.

User response

See the messages and codes publication of the LDAP manager product that you are using with Content Manager OnDemand for information about ldap errors and return codes.

ARS0385W

ARSRD has been waiting *minutes* minutes for the *thread* subsystem to *status*: Distributions - Complete(*distributions_complete*) Incomplete(*distributions_incomplete*) Failed(*distributions_failed*) Retrying(*distributions_retrying*)

Explanation

The ARSRD command is waiting for a child thread to comply with a status change request from the parent process.

User response

Wait for the child threads to respond to the status change request or terminate the ARSRD process and restart it.

ARS0389I

Results of distribution processing: Total(*total*) - New(*new*) Backlog(*backlog*).

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0390I

The following report load is processing: Distribution Name(*report*) Report Name(*loadids*) Loads(%3).

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS0391I

time DISPLAY CONFIG

Explanation

This message is issued in response to a MODIFY ARSSOCKD ,D CONFIG command

User response

No action is required.

ARS0392I

time DISPLAY ENVAR

Explanation

This message is issued in response to a MODIFY ARSSOCKD ,D ENVAR command

User response

No action is required.

ARS0393D

Reply with TERM to terminate Content Manager OnDemand, CONT to continue, or start the DB2 subsystem.

Explanation

The DB2 subsystem ssid was not available when the server was initialized. The server is waiting for the DB2 subsystem to become available. When the DB2 subsystem becomes available, this message will be deleted.

For example: ARS0393D Waiting for DB1M DB2 subsystem. Reply 'TERM' to terminate CMOD, 'CONT' to continue, or start DB2

User response

Start the required DB2 subsystem. If the server terminates, reply with TERM. If the server attempts to initialize without the specified DB2 subsystem, reply with CONT.

ARS0394I

Invalid reply 'text'

Explanation

An invalid reply, text, was provided in response to a WTOR. The WTOR will be reissued.

For example: ARS0394I Invalid reply 'FOO'

User response

Provide a valid response to the reissued WTOR

ARS0395I

DB2 is terminating; therefore, Content Manager OnDemand will terminate.

Explanation

A -STOP DB2 command was issued. In order to allow the DB2 subsystem to terminate, the Content Manager OnDemand server is terminating.

User response

Issue a -START DB2 command and then restart the Content Manager OnDemand server.

ARS0396I

time DISPLAY STATUS

Explanation

This message is issued in response to a MODIFY ARSSOCKD,D STATUS command

User response

No action is required.

ARS0397I

Document Full Text Index Add: ApplGroup(*appl_group_name*) Agid(*agid*) Full Text Index Notified(*fti_notified*) Count(*count*) Time(*time*)

Explanation

The application group document(s) were sent to the full text index.

User response

No action is required.

ARS0398E

Document Full Text Index Add Failed: ApplGroup(*appl_group_name*) Agid(*agid*) Full Text Index Notified(*fti_notified*) Count(*count*) Time(*time*)

Explanation

The application group document(s) failed to be sent to the full text index.

User response

No action is required.

ARS0399I

Document Full Text Index Delete: ApplGroup(*appl_group_name*) Agid(*agid*) Full Text Index Notified(*fti_notified*) Count(*count*) Time(*time*)

Explanation

The application group document(s) were deleted from the full text index.

User response

No action is required.

ARS0400E

Document Full Text Index Delete Failed: ApplGroup(*appl_group_name*) Agid(*agid*) Full Text Index Notified(*fti_notified*) Count(*count*) Time(*time*).

Explanation

The application group document(s) failed to be deleted from the full text index.

User response

No action is required.

ARS0401I

Document Full Text Index Update: ApplGroup(*appl_group_name*) Agid(*agid*) Full Text Index Notified(*fti_notified*) Count(*count*) Time(*time*).

Explanation

The application group document(s) were sent to be updated in the full text index.

User response

No action is required.

ARS0402E

Document Full Text Index Update Failed: ApplGroup(*appl_group_name*) Agid(*agid*) Full Text Index Notified(*fti_notified*) Count(*count*) Time(*time*).

Explanation

The application group document(s) failed to be sent to be updated in the full text index.

User response

No action is required.

ARS0403I

Application Group Full Text Index Delete: ApplGroup(*appl_group_name*) Agid(*agid*) Full Text Index Notified(*fti_notified*) Time(*time*)

Explanation

The application group was deleted from the full text index.

User response

No action is required.

ARS0404E

Application Group Full Text Index Delete Failed: ApplGroup(*appl_group_name*) Agid(*agid*) Full Text Index Notified(*fti_notified*) Time(*time*).

Explanation

The application group failed to be deleted from the full text index.

User response

No action is required.

ARS0405I

Application Group Full Text Index Update: ApplGroup(*appl_group_name*) Agid(*agid*) Full Text Index Notified(*fti_notified*) Time(*time*).

Explanation

The application group was updated to no longer use full text indexing.

User response

No action is required.

ARS0406E

Application Group Full Text Index Update Failed: ApplGroup(*appl_group_name*) Agid(*agid*) Full Text Index Notified(*fti_notified*) Time(*time*).

Explanation

The application group failed to update full text index because it no longer uses the full text index.

User response

No action is required.

ARS0407I

Application Group Application Full Text Index Delete: ApplGroup(*appl_group_name*) Agid(*agid*) Aid(*aid*) Full Text Index Notified(*fti_notified*) Time(*time*)

Explanation

The application was deleted from the full text index.

User response

No action is required.

ARS0408E

Application Group Application Full Text Index Delete Failed: ApplGroup(*appl_group_name*) Agid(*agid*) Aid(*aid*) Full Text Index Notified(*fti_notified*) Time(*time*).

Explanation

The application failed to be deleted from the full text index.

User response

No action is required.

ARS0409E

Unable to load data because full text index is defined but no full text indexer server is specified in Application Group Name(*appl_group_name*), Agid(*agid*).

Explanation

The application failed to load because no full text indexer server name is specified.

User response

Define a server name in the application group for the full text indexer, or ensure that ARSLOAD is the same version as the Content Manager OnDemand server.

ARS0410W

Failed login: Disabled(*hostname*) Locked Out(*locked_out*) Failed Attempts(*number_of_failed_attempts*)
Last Successful Login(*date_and_time*) *additional_fields*.

Explanation

A client failed when attempting to log on to the server due to the user being disabled.

User response

The password, disable flag, or both for the user definition must be updated using a Content Manager OnDemand administrative client.

ARS0429E

TSM Error: *message*, Return Code=*return_code*, Reason=*reason_code*, File=*file_name*, Line=*line_number*

Explanation

Tivoli Storage Manager (TSM) failed.

User response

See the Tivoli Storage Manager messages and codes publication for information about the Tivoli Storage Manager error, return code, and reason.

ARS0430E

OAM Error: *message*, Return Code=*return_code*, Reason=*reason_code*, File=*file_name*, Line=*line_number*

Explanation

The storage manager failed.

User response

See the OAM messages and codes publication for information about the OAM error, return code, and reason.

ARS0431E

VSAM Error: *message*, Return Code=*return_code*, Reason=*reason_code*, File=*file_name*, Line=*line_number*

Explanation

The storage manager failed.

User response

See the VSAM messages and codes publication for information about the VSAM error, return code, and reason.

ARS0432E

V2/IAFC OAM Error: *message*, Return Code=*return_code*, Reason=*reason_code*, File=*file_name*,
Line=*line_number*

Explanation

The storage manager failed.

User response

See the OAM messages and codes publication for information about the OAM error, return code, and reason.

ARS0433E

ASM Error: *message*, File=*file_name*, Line=*line_number*

Explanation

The storage manager failed.

User response

See the server job log for specific ASM messages about this error.

ARS0434E

Database *<database_name>* not found for application group *<appl_group_name>*.

Explanation

The database associated with an application group could not be found in SYSIBM.SYSDATABASE.

User response

Verify that the database associated with the application group is correct.

ARS0436E

Unable to find an assigned user ID for the Content Manager OnDemand command or database *<cmd>* from stash file *<stash_file>*.

Explanation

Content Manager OnDemand is unable to get the necessary information from the Content Manager OnDemand stash file to proceed.

User response

Verify that the specified Content Manager OnDemand stash file contains a correct user ID for the Content Manager OnDemand command or database.

ARS0437E

The Content Manager OnDemand stash file *<stash_file>* either does not exist or is not valid. The return code is *rc*.

Explanation

Content Manager OnDemand is unable to get the necessary information from the Content Manager OnDemand stash file to proceed.

User response

Verify that the specified Content Manager OnDemand stash file exists and is correct.

ARS0438I

time DISPLAY ICSF

Explanation

This message is issued in response to a MODIFY ARSSOCKD ,D ICSF command

User response

No action is required.

ARS0439E

FTS Error: *fts_text* -- File=*file*, Line=*line*

Explanation

Content Manager OnDemand encountered an unexpected error condition when searching the full text index server.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS0443I

ODF Maintenance Processing: Date(*date*)

Explanation

The ARSODF/ARSMOINT program(s) write this message to the system log when data in the Content Manager OnDemand Distribution Facility has exceeded the configuration expiration value. This message is for your information only.

User response

No action is required.

ARS0444I

ODF Started Version *<version>* Operating System *<os>* *<os_level>* OS Userid *<userid>* Install Location *<install_loc>* *misc*

Explanation

This message is for your information only.

User response

No action is required.

ARS0445I

ODF Distribution Processed: Recipient(*recipient*) Distribution(*dist_name*) Time(*time*)

Explanation

A distribution was processed by the system. The message identifies the recipient and distribution name. This message is for your information only.

User response

No action is required.

ARS0446E

ODF Distribution Processing Failed: Recipient(*recipient*) Distribution(*dist_name*) Time(*time*)

Explanation

The load process failed.

User response

See the other messages that were generated by the ARSODF program and see messages in the OnDemand System Log to correct the problem and then resubmit the distribution. If the problem persists, contact your IBM Service Representative.

ARS0447W

ODF Distribution Processed with warnings: Recipient(*recipient*) Distribution(*dist_name*) Time(*time*)

Explanation

A distribution was processed by the system. The message identifies the recipient and distribution name. This message is for your information only.

User response

No action is required.

ARS0448E

OpenStack Object Storage (Swift) Error: *message*, Return Code=*return_code*, Reason=*reason_code*, File=*file_name*, Line=*line_number*

Explanation

OpenStack Object Storage (Swift) storage manager failed.

User response

See the OpenStack Object Storage (Swift) messages and codes publication for information about the OpenStack Object Storage (Swift) error, return code, and reason.

ARS0449E

HDFS Error: *message*, Return Code=*return_code*, Reason=*reason_code*, File=*file_name*, Line=*line_number*

Explanation

HDFS storage manager failed.

User response

See the HDFS messages and codes publication for information about the HDFS error, return code, and reason.

ARS0450E

Amazon S3 Error: *message*, Return Code=*return_code*, Reason=*reason_code*, File=*file_name*, Line=*line_number*

Explanation

Amazon S3 storage manager failed.

User response

See the Amazon S3 messages and codes publication for information about the Amazon S3 error, return code, and reason.

ARS0452E

IBM Cloud Object Storage Error: *message*, Return Code=*return_code*, Reason=*reason_code*, File=*file_name*, Line=*line_number*

Explanation

The IBM Cloud Object Storage manager failed.

User response

See the IBM Cloud Object Storage messages and codes publication for information about the IBM Cloud Object Storage error, return code, and reason.

ARS0453E

Encryption failed. File=*file_name*, Line=*line_number*

Explanation

The command failed when attempting to encrypt the data.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS0454E

Decryption failed. File=*file_name*, Line=*line_number*

Explanation

The command failed when attempting to decrypt the data.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS0455E

The tokenized query string has an invalid hex binary value at marker position *position*, value *value*. Use a valid hex binary value instead.

Explanation

The input value contains an invalid hex binary value.

User response

Provide a hex binary value for the query string and resubmit the command.

ARS0456I

Application Group Unload Database: Name(*appl_grp_name*) Agid(*agid*) Number of Loads Expired(*num_load_ids*) Rows Deleted(*rows_deleted*)

Explanation

Report(s) were deleted from the database. The message identifies the application group and the number of rows that were deleted from the database. This message is for your information only.

User response

No action is required.

ARS0457E

No master key keystore_location is specified.

Explanation

The command failed when attempting to set the Content Manager OnDemand system configuration parameter keystore_location.

User response

Reissue the command and specify the keystore_location. If the problem persists, contact your IBM Service Representative.

ARS0458E

Unable to utilize the OnDemand system configuration parameters. Please ensure that the keystore_type, keystore_location and keystore_mkl are correct and accessible. File=*file_name*, Line=*line_number*

Explanation

The command failed when attempting to utilize the Content Manager OnDemand system configuration parameters.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS0459E

File System Storage Error: *message*, Return Code=*return_code*, Reason=*reason_code*, File=*file_name*, Line=*line_number*

Explanation

File System storage failed.

User response

See the messages and codes publication for information about the Error, RC, and Reason.

ARS0777I

ASM Process to run: *process* Policy: *policy* Job name: *jobname* File:*file*

Explanation

This message denotes the ASM process that is logging this message. This message is for your information only.

User response

No action is required.

ARS0980I

Usage: arsockd [options]

Version: *version*

- d Set the OnDemand server system configuration
- D Display the OnDemand server system configuration
- h <od_inst> OnDemand instance name or host name (same as -I)
- I <od_inst> OnDemand instance name or host name (same as -h)
- p Display process usage information for the given instance
- q Display configuration and version information for the given instance
- r <iterations> Number of iterations (defaults to 1)
- s <seconds> Number of seconds between iterations (defaults to 1)
- S Start the OnDemand server for the given instance
- T Stop the OnDemand server for the given instance
- v Verbose output
- x Extended information (when used with -p)
- 1 <trace_file> Trace file
- 2 <trace_level> Trace level

Explanation

The arsockd command contains an incorrect parameter.

User response

The message text lists the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the Content Manager OnDemand Administration Guide.

ARS0981E

The specified system configuration parameters are invalid *>parameters<*.

Explanation

The system configuration parameters specified to the command are invalid.

User response

Correct the parameters and resubmit the command.

ARS1000I

arsadmin [unload | store | retrieve | import | compress | decompress | icu]

Version: *version*

Usage: arsadmin [unload | store | retrieve | import | compress | decompress | icu]

Version: *version*

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. For more information about this command, see the Content Manager OnDemand *Administration Guide*.

ARS1001I

Usage: arsadmin load [options]

Version: *version*

load Load OnDemand

-a <name> Application Name. (Not needed if 1 app in appl group)

-d <dir> If (-f), then directory to write object files into (Default current dir)

-e <res_id>

If (-r)

0, Check for duplicates. (Default)

Otherwise, Load as new resource

Else

Resource Id to use. (Defaults to 0, no resource)

-f Create Objects as files. (Default: load while processing)

-g <name> Application Group Name

-h <od_inst> OnDemand library server or instance name (same as -I)

-i <ind_file> Input Index File

-I <od_inst> OnDemand library server or instance name (same as -h)

-n <pri_nid-sec_nid> Primary/Secondary Node Identifiers

-o <out_file> Output DB File

-p <passwd> OnDemand User Login Password

-r <res_file> Input Resource File

-s <src_file> Input Doc Source File

-u <userid> OnDemand User Login Name

-y <char> Column Delimiter. (Default 'Horizontal Tab')

-Z <user_def> User defined string passed to load user exit

-1 <trace_file> Fully qualified trace file name

-2 <level> Trace level number. The values are additive. (Default: 3)

1: Errors

2: Warnings
4: Info
8: Flow

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1002I

Usage: `arsadmin load_db [options]`

Version: *version*

`load_db` Load the database from a file

-a <name> Application Name. (Not needed if 1 app in appl group)

-g <name> Application Group Name

-h <od_inst> OnDemand library server or instance name (same as -I)

-I <od_inst> OnDemand library server or instance name (same as -h)

-L <load_ID> LoadId to use for OnDemand

-p <passwd> OnDemand User Login Password

-s <db_file> Input Database File

-u <userid> OnDemand User Login Name

-y <char> Column Delimiter. (Default 'Horizontal Tab')

-Z <user_def> User defined string passed to load user exit.

-1 <trace_file> Fully qualified trace file name

-2 <level> Trace level number. The values are additive. (Default: 3)

1: Errors

2: Warnings

4: Info

8: Flow

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1003I

Usage: `arsadmin unload [options]`

Version: *version*

`unload` Unload a LoadId from OnDemand

-D <pct> Threshold of load being held before reloading
(defaults to 0% - not reloaded)

-g <name> Application Group Name

-h <od_inst> OnDemand library server or instance name (same as -I)

-I <od_inst> OnDemand library server or instance name (same as -h)

-L <load_ID> LoadId to delete from OnDemand

-N Skip looking up the LoadId in System Log

-p <passwd> OnDemand User Login Password

-Q Continue if unable to find LoadId in System Log

-u <userid> OnDemand User Login Name

-1 <trace_file> Fully qualified trace file name

-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1004I

Usage: `arsadmin store [options]`
Version: *version*
store Load file(s) into Content Manager OnDemand
-d <dir> Directory to find files. (Default current dir)
-g <name> Application Group Name
-h <od_inst> OnDemand library server or instance name (same as -I)
-I <od_inst> OnDemand library server or instance name (same as -h)
-m <loc> The location to load the data
The values are additive. (Default: 7)
1 Cache (If exists)
2 Primary Node (If exists)
4 Secondary Node (If exists)
-n <pri_nid-sec_nid> Primary/Secondary Node Identifiers
-p <passwd> OnDemand User Login Password
-u <userid> OnDemand User Login Name
-1 <trace_file> Fully qualified trace file name
-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow
<file1..n> List of files

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1005I

Usage: `arsadmin retrieve [options]`
Version: *version*
retrieve Retrieve file(s) from OnDemand
-b <off> Offset to begin at. (Default 0)
-d <dir> Directory to retrieve files into. (Default current dir)
-g <name> Application Group Name
-h <od_inst> OnDemand library server or instance name (same as -I)
-I <od_inst> OnDemand library server or instance name (same as -h)
-l <len> Length to end at. (Default object size)

-m <loc> The location to extract the data
The values are additive. (Default: 3)
1 Cache (If exists)
2 Primary Node (If exists)
4 Secondary Node (If exists)
-n <pri_nid-sec_nid> Primary/Secondary Node Identifiers
-p <passwd> OnDemand User Login Password
-u <userid> OnDemand User Login Name
-1 <trace_file> Fully qualified trace file name
-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow
<file1..n> Retrieve file(s) from OnDemand

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1006I

Usage: `arsadmin import [options]`
Version: *version*
`import` Import Database Table
-g <name> Application Group Name
-h <od_inst> OnDemand library server or instance name (same as -I)
-I <od_inst> OnDemand library server or instance name (same as -h)
-p <passwd> OnDemand User Login Password
-u <userid> OnDemand User Login Name
-1 <trace_file> Fully qualified trace file name
-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow
<table_name> Tablename to reimport

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1007I

Usage: `arsadmin res_diff [options]`
Version: *version*
`res_diff` Resource Comparison
-a <name> Application Name. (Not needed if 1 app in appl group)
-g <name> Application Group Name
-h <od_inst> OnDemand library server or instance name (same as -I)

-I <od_inst> OnDemand library server or instance name (same as -h)
-n <pri_nid-sec_nid> Primary/Secondary Node Identifiers
-p <passwd> OnDemand User Login Password
-u <userid> OnDemand User Login Name
-1 <trace_file> Fully qualified trace file name
-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow
<res_file1..n> Resource File(s) to compare to existing resources

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1008I

Usage: `arsadmin postprocess_cmd` [options]

Version: *version*

`postprocess_cmd` Write the Post Process Command on stdout

-a <name> Application Name. (Not needed if 1 app in appl group)
-g <name> Application Group Name
-h <od_inst> OnDemand library server or instance name (same as -I)
-I <od_inst> OnDemand library server or instance name (same as -h)
-p <passwd> OnDemand User Login Password
-u <userid> OnDemand User Login Name
-1 <trace_file> Fully qualified trace file name
-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1009I

Usage: `arsadmin indexer` [options]

Version: *version*

`indexer` Write the Indexer and Indexer Params on stdout

-a <name> Application Name. (Not needed if 1 app in appl group)
-g <name> Application Group Name
-h <od_inst> OnDemand library server or instance name (same as -I)
-I <od_inst> OnDemand library server or instance name (same as -h)
-p <passwd> OnDemand User Login Password
-u <userid> OnDemand User Login Name
-1 <trace_file> Fully qualified trace file name

-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1010I

Usage: `arsadmin psf_options [options]`
Version: *version*
`psf_options` Write the PSF Print Options on stdout
-a <name> Application Name. (Not needed if 1 app in appl group)
-g <name> Application Group Name
-h <od_inst> OnDemand library server or instance name (same as -I)
-I <od_inst> OnDemand library server or instance name (same as -h)
-p <passwd> OnDemand User Login Password
-u <userid> OnDemand User Login Name
-1 <trace_file> Fully qualified trace file name
-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1011I

Usage: `arsadmin msgs [options]`
Version: *version*
`msgs` Log messages to the server
-h <od_inst> OnDemand library server or instance name (same as -I)
-I <od_inst> OnDemand library server or instance name (same as -h)
-p <passwd> OnDemand User Login Password
-s <src_file> Input ASCII Text File to store with message
-u <userid> OnDemand User Login Name
-M <msg_num> OnDemand Message Number
-1 <trace_file> Fully qualified trace file name
-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow
[arg1] [arg2] [arg3] [arg4]

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1012I

Usage: `arsadmin compress` [options]

Version: *version*

`compress` Compress a file

`-b <off>` Offset to begin at. (Default 0)

`-c <type>` Document Compress Type

'D' Disable compression

'F' OD77 Lite Compression

'H' OD77HW Compression

'L' LZW12 Compression

'N' No Compression

'O' OD77 Compression (Default)

'X' OD77LiteHW Compression

'Z' LZW16 Compression

`-l <len>` Length to end at. (Default file size)

`-o <out_file>` Output File

`-s <src_file>` Input File

`-1 <trace_file>` Fully qualified trace file name

`-2 <level>` Trace level number. The values are additive. (Default: 3)

1: Errors

2: Warnings

4: Info

8: Flow

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1013I

Usage: `arsadmin decompress` [options]

Version: *version*

`decompress` Decompress a file

`-b <off>` Offset to begin at. (Default 0)

`-c <type>` Document Compress Type

'D' Disable compression

'F' OD77 Lite Compression

'H' OD77HW Compression

'L' LZW12 Compression

'N' No Compression

'O' OD77 Compression (Default)

'X' OD77LiteHW Compression

'Z' LZW16 Compression

`-l <len>` Length to end at. (Default file size)

`-o <out_file>` Output File

-s <src_file> Input File
-1 <trace_file> Fully qualified trace file name
-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. Verify and correct the command parameters and resubmit the command. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1014I

Usage: `arsadmin icu` [options]
Version: *version*
`icu` Performs codepage conversion
-F <from_codepage> Input File Codepage
-o <out_file> Output File
-s <src_file> Input File
-T <to_codepage> Output File Codepage
-1 <trace_file> Fully qualified trace file name
-2 <level> Trace level number.

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. See the *Content Manager OnDemand Administration Guide* for more information. Verify and correct the command parameters and resubmit the command.

ARS1015I

Usage: `arsadmin logid` [options]
Version: *version*
`logid` Get a log ID from the server
-h <od_inst> OnDemand library server or instance name (same as -I)
-I <od_inst> OnDemand library server or instance name (same as -h)

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. See the *Content Manager OnDemand Administration Guide* for more information. Verify and correct the command parameters and resubmit the command.

ARS1016I

Usage: `arsadmin update_defs` [options]
Version: *version*
`update_defs` Updates report definition parameters
-a <name> Application name (not required if only one app in appl group)

-g <name> Application group name
-h <od_inst> OnDemand library server or instance name (same as -I)
-I <od_inst> OnDemand library server or instance name (same as -h)
-O <obj_server_name> Name of the object server where storage node resides
-p <passwd> OnDemand user login password
-R <storage_node_name> Name of the storage node where data will be loaded
-s <src_file> Input document source file
-u <userid> OnDemand user login name
-1 <trace_file> Fully qualified trace file name
-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow

Explanation

The `arsadmin` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. See the *Content Manager OnDemand Administration Guide* for more information. Verify and correct the command parameters and resubmit the command.

ARS1017E

Storage node >node_name< on object server >obj_server_name< does not exist in storage set >set_name<

Explanation

The storage node cannot be found in the storage set that is used by the application group.

User response

Resubmit the command with a storage node that exists in the storage set that is used by the application group.

ARS1018E

The CC Type that was returned by the user exit program is not valid

Explanation

The user exit program returned an unknown CC type. The `arscsxit.h` file contains the valid values for the CC type.

User response

Change the user exit program to return a valid CC type and resubmit the command.

ARS1019E

The RECFM value that was returned by the user exit program is not valid

Explanation

The user exit program returned an unknown RECFM. The `arscsxit.h` file contains the valid values for the RECFM.

User response

Change the user exit program to return a valid RECFM and resubmit the command.

ARS1020E

The LRECL value of *>lrecl<* that was returned by the user exit program is not valid

Explanation

The user exit program returned an invalid LRECL value. Valid values for the LRECL type are integers between 1 and 32767.

User response

Change the user exit program to return an LRECL value between 1 and 32767 and resubmit the command.

ARS1023E

Userid *>userid<* does not have permission to update application *>appl_name<* in application group *>applgrp_name<*

Explanation

The specified user does not have the permissions that are required to perform the action.

User response

Update the user to provide the user with permission to perform the action and then resubmit the command. Otherwise, resubmit the command with a different user ID.

ARS1024I

Usage: *sm_expire* [options]

Version: *version*

sm_expire Unloads a list of objects

-h *<od_inst>* OnDemand library server or instance name (same as -I)

-I *<od_inst>* OnDemand library server or instance name (same as -h)

-p *<passwd>* OnDemand User Login Password

-s *<src_file>* Input file containing the list of objects to be expired

-u *<userid>* OnDemand User Login Name

-1 *<trace_file>* Fully qualified trace file name

-2 *<level>* Trace level number. The values are additive. (Default: 3)

1: Errors

2: Warnings

4: Info

8: Flow

Explanation

The *arsadmin* command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. See the *Content Manager OnDemand Administration Guide* for more information. Verify and correct the command parameters and resubmit the command.

ARS1025I

An invalid *sm_expire* object *object* was found at line *lineno* of file *file*

Explanation

An invalid *sm_expire* object was found. For more information about this command, see the *Administration Guide*.

User response

Resubmit the command with the correct parameters.

ARS1026E

The Delimiter value of `>delim<` that was returned by the user exit program is not valid.

Explanation

The user exit program returned an invalid delimiter value.

User response

Change the user exit program to return a delimiter string that contains valid hexadecimal values such as 25, 0A, or OD0A.

ARS1027E

The user exit `userexit_name` failed. The return code is rc.

Explanation

The specified user exit program failed.

User response

Verify that the user exit program functions properly outside of the Content Management OnDemand environment. Make any necessary corrections to the user exit program. Then, resubmit the command.

ARS1028I

Usage: `arsadmin trace [options]`

Version: *version*

`trace` Converts trace file into XML

`-o <out_file>` Output File

`-s <src_file>` Input File

`-1 <trace_file>` Fully qualified trace file name

`-2 <level>` Trace level number. The values are additive. (Default: 3)

1: Errors

2: Warnings

4: Info

8: Flow

Explanation

An incorrect parameter was specified for the command.

User response

The message response outlines the valid parameters for this command. See the *Content Manager OnDemand Administration Guide* for more information on the correct command parameters. Verify and correct the command parameters and resubmit the command.

ARS1029E

The input trace file is corrupt. Info=*info*, Line=*line*

Explanation

An error occurred while running this program.

User response

Contact your IBM Service Representative.

ARS1102E

Invalid option *>-option<* for command *>command<*

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS1103E

Option *>-option<* requires an argument

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS1104E

The option *>-option<* argument *>argument<* is invalid

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS1105E

Userid or password is invalid

Explanation

An incorrect user ID or password was specified.

User response

Resubmit the command with a valid user ID and password.

ARS1106E

Connection cannot be established for the *>hostname<* server

Explanation

The command could not communicate with the specified server.

User response

Resubmit the command with the valid name of a Content Manager OnDemand server. If the problem persists, verify that the server is running and is configured correctly.

ARS1107E

An error occurred. Contact your System Administrator and/or consult the System Log. File=*file*, Line=*line*

Explanation

An error occurred while this program was running. Other messages with the same log ID might provide additional information about the error.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

Note: Ensure that ARSLOAD and ARSSOCKD are at the same Version/Release/Modification level.

ARS1108E

User *>user_name<* does not have permission to perform the specified action

Explanation

The specified user does not have the permissions that are required to perform the action.

User response

Either update the user's permissions and resubmit the command or submit the command with a different user ID.

ARS1109E

Unable to allocate enough memory. File=*file*, Line=*line*

Explanation

The command failed when attempting to allocate sufficient memory to run the action.

User response

Determine why memory could not be allocated by looking at the operating system and application task status. If necessary, close other applications to free memory. Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS1110E

The application group *>appl_grp_name<* does not exist or user *>user_name<* does not have permission to access the application group

Explanation

Either the specified application group name is not correct or the specified user does not have the permissions that are required to perform the action.

User response

Verify the name of the application group, or verify the user ID and that the user has permission to perform the action. Then resubmit the command.

ARS1111E

The application *>appl_name<* does not exist within the application group *>appl_grp_name<*

Explanation

The specified application does not belong to the specified application group.

User response

Verify the name of the application and the name of the application group. Then resubmit the command.

ARS1112E

Unable to open the file: *file_name*

Explanation

The specified file does not exist or the permissions do not allow the file to be opened.

User response

Verify that the file exists and that its permissions allow the file to be opened. Then resubmit the command.

ARS1113E

Unable to seek to position *offset* in the file: *file_name*

Explanation

The command failed when attempting to find the correct position within the file. The input file might be too large. Input files for ACIF, the IBM Content Manager OnDemand PDF Indexer, and the Generic Indexer can not exceed 2 GB. There is no file size limit for the z/OS Indexer.

User response

Verify the file permissions and verify that the file size does not exceed the maximum file size for the indexing program in use. If the file does exceed the limit, take steps to reduce the size of the file. Then, resubmit the command.

ARS1114E

Unable to read from offset *offset_position* for length *length_position* from the file: *file_name*

Explanation

The command failed when attempting to read the specified file. The following is an example of a possible scenario: While loading an AFP report, ARSLOAD scans the output file that was produced by ACIF searching for page groups. The page groups are delimited by Begin Named Group (BNG) and End Named Group (ENG) AFP structured fields. ARSLOAD uses the index file produced by ACIF to determine the location and length of the page groups in the output file. If the end of the output file is encountered before the start of a page group is found or the end of a page group is found, ARSADMIN issues message ARS1114E.

User response

Verify and correct the offset and length values for the file. Then resubmit the command.

In the scenario, set the ACIF parameters CC and CCTYPE as CC=YES and CCTYPE=A. ACIF requires that the page groups in the AFP report be delimited by a BNG and ENG structured field.

ARS1115E

Unable to write the file: *file_name*

Explanation

The command failed when attempting to write to the specified file.

User response

Verify that the location for the file contains sufficient free space to write to the file. Then resubmit the command.

ARS1116E

Unable to close the file: *file_name*

Explanation

The command failed when attempting to close the specified file.

User response

Verify that the location for the file contains sufficient free space to close the file. Then resubmit the command.

ARS1117E

Unable to gather statistics about the file: *file_name*

Explanation

The command failed when attempting to get information about the specified file.

User response

Verify that the file exists and verify the file permissions. Then resubmit the command.

ARS1118E

Unable to create the file: *file_name*

Explanation

The command failed when attempting to create the specified file.

User response

Verify that the directory in which the file is being created has sufficient free space and that the directory permissions allow for the creation of files. Then resubmit the command.

ARS1119E

File *>file_name<* is empty

Explanation

The specified file contains no data.

User response

Verify that the file exists, that the name of the file is correct, and that the file contains data. Then resubmit the command.

ARS1120E

The LZW decompression only handles files with a maximum of *lzw_bits* bits

Explanation

The LZW compression algorithm can only handle from 12 to 16 bits.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the compression. If the problem persists, contact your IBM Service Representative.

ARS1121E

The input file is not in LZW compressed format

Explanation

The input file is not in the LZW format.

User response

Resubmit the command with an input file that is in the correct compression format.

ARS1122E

Unable to open the *input_codepage* to *output_codepage* icu converter

Explanation

The command failed when attempting to open the code page converter.

User response

Check to ensure that the converter codepage exists in the `cnvtrts.txt` file, and that the ICU Data Library is in the locale directory and has the correct permissions. Then try the command again. Contact your IBM Service Representative.

ARS1123E

Row *row_number*: The icu converter failed converting string *>string<*. `errno = errno`

Explanation

The command failed when attempting to convert a string. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

Verify that the data is valid within the specified code pages. See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS1124E

Row *row_number*: The value '*value*' cannot be converted to a valid small integer

Explanation

The specified value is invalid for a small integer. A small integer has a value between -32767 and 32767.

User response

Change the indexing information so that the value is valid for a small integer.

ARS1125E

Row *row_number*: The value '*value*' cannot be converted to a valid integer

Explanation

The specified value is invalid for an integer.

User response

Change the indexing information so that the value is valid for an integer.

ARS1126E

Row *row_number*: The value '*value*' cannot be converted to a valid decimal number

Explanation

The specified value is invalid for a decimal.

User response

Change the indexing information so that the value is valid for a decimal.

ARS1127E

Row *row_number*: The string "*string*" has a length of *length* and the field has a maximum length of *field_length*

Explanation

The length of the specified string exceeds the maximum length of the specified field.

User response

Increase the size of the field in the indexing information or shorten the string. Then resubmit the command.

ARS1128E

Row *row_number*: The string "*string*" has the column delimiter in it

Explanation

The command failed because the specified string contains a character that is the same as the column delimiter that is currently being used by the command.

User response

Resubmit the command with a different column delimiter.

ARS1129E

Row *row_number*: The string "*string*" could not be converted to a date from the format of *date_format*

Explanation

The string could not be converted to a date because it did not match the date format. Date formats might vary by application. Both the invalid string and the required format are shown in the message.

User response

Change the date value to match the default date format or specify a different date format.

ARS1130E

submitted_fields fields submitted by the indexer, *expected_fields* expected

Explanation

The load program cannot continue unless it receives all of the fields that are required to store the document. Field requirements might vary by application. Both the submitted fields and the required fields are shown in the message.

User response

Verify that the indexing parameters correctly identify all of the fields that are required. Then resubmit the command.

ARS1131E

The compressed object is too small to compress

Explanation

There is not enough input data for the LZW compression algorithm to compress.

User response

Resubmit the command with a different compression option.

Note: Specify the OD77 compression option.

ARS1132I

The compressed object has compressed larger than the original data

Explanation

The compressed data became larger than the original input data. This message is usually the result of trying to compress data that is already compressed.

User response

Disable compression in the application and resubmit the command.

ARS1133I

The last row successfully loaded was *row_number*

Explanation

ARSADMIN load_db finished loading. This message is for your information only.

User response

No action is required.

ARS1134E

Invalid structured field header in the file *file_name*

Explanation

The AFP data has a structured field header that was not constructed correctly.

User response

Verify that the AFP data conforms to the AFP specification. See the *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* (SC31-6802) for more information about the correct format of the structured field.

ARS1135E

Unable to find the X'*structured_field*' structured field in the file *file_name*

Explanation

The AFP data does not contain a required structured field.

User response

Verify that the AFP data conforms to the AFP specification. See the *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference*, (SC31-6802) for more information about the correct format of the structured field.

ARS1136E

Unexpected structured field X'*structured_field*' in the file *file_name*

Explanation

The AFP data contains an invalid structured field.

User response

Verify that the AFP data conforms to the AFP specification. See the *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference*, (SC31-6802) for more information about the correct format of the structured field.

ARS1137E

Unable to find the triplet X'*triplet*' for the structured field X'*structured_field*' in file *file_name*

Explanation

The AFP data does not contain a required triplet for the structured field.

User response

Verify that the AFP data conforms to the AFP specification. See the *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference*, (SC31-6802) for more information about the correct format of the structured field.

ARS1138W

Warning: Unable to find the triplet X'*triplet*' for the structured field X'*structured_field*' in the file *file_name*

Explanation

The AFP data does not contain a required triplet for the structured field, however processing can continue.

User response

Verify that the AFP data conforms to the AFP specification. See *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference*, (SC31-6802) for more information about the correct format of the structured field.

ARS1139E

Unable to find the triplet X'*triplet*' of type X'*type*' for the structured field X'*structured_field*' in the file *file_name*

Explanation

The AFP data does not contain a required triplet type for the structured field.

User response

Verify that the AFP data conforms to the AFP specification. See the *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference*, (SC31-6802) for more information about the correct format of the structured field.

ARS1140I

Resource *resource_name* matches the resource >*rid-pri_nid-sec_nid*<

Explanation

A resource that is used by a document already exists on the system. OnDemand will use the resource that exists on the system. This message is for your information only.

User response

No action is required.

ARS1141I

Resource *resource_name* does not match any existing resources

Explanation

The specified resource does not exist on the system. This message is for your information only.

User response

No action is required.

ARS1142I

Resource [*generated internally* | *resource_name*] will be added as resource *>rid-pri_nid-sec_nid<*.
Compression Type(*compress_type*) Original Size(*original_size*) Compressed Size(*compressed_size*)

Explanation

The specified resource was added to the system. This message is for your information only. If "generated internally" is issued Content Manager OnDemand has created a new resource for a value found missing.

User response

No action is required.

ARS1143I

The field name '*field_name*' found in the index file does not match any expected fields. The field will be ignored.

Explanation

The specified field was found in the index file. However, the field will not be used because it is not defined in the application group.

User response

No action is required. However, you should verify that the field is not needed to load or retrieve data.

ARS1144I

OnDemand Load Id = *>agid-pri_nid-sec_nid-name-start_date-stop_date<*

Explanation

The load ID is given for the current report load. You can use this load ID to find or unload the data from this report load. This message is for your information only.

User response

No action is required.

ARS1145E

Line *line_number*: Unable to read next column from input file

Explanation

ARSADMIN failed when attempting to read the input file. This message is usually the result of an invalid delimiter in the input file. The column delimiters are the vertical bar (|) character by default. You can specify a different delimiter on the command line with the -y parameter.

User response

Verify that the input file is properly constructed and resubmit the command.

ARS1146I

Loaded *rows* rows into the database

Explanation

The specified number of rows were loaded into the database for this report. This message is for your information only.

User response

No action is required.

ARS1147I

rows rows written to output file

Explanation

The specified number of rows were written to an output file for this report. This message is for your information only.

User response

No action is required.

ARS1148E

This application has no indexer defined

Explanation

There is no indexer associated with the Content Manager OnDemand application.

User response

In the Content Manager OnDemand administrative client, choose a valid indexer for the application. Then resubmit the command.

ARS1149E

This application has an unknown type of indexer

Explanation

The indexer that is specified for the application is not a valid indexer.

User response

In the Content Manager OnDemand administrative client, choose a valid indexer for the application. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS1150E

Row *row_number*: The value '*value*' cannot be converted to a valid binary value

Explanation

Value is not valid for a decimal.

User response

Change the indexing information so that the value is a valid binary.

ARS1154W

The password for userid *>user_name<* has expired, please change password

Explanation

The user's password expired.

User response

Change the password for the user and then resubmit the command. Passwords might be case sensitive.

ARS1155E

Unable to fork a child process. *errno=errno*, *File=file*, *Line=line*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in */usr/include/sys/errno.h* on UNIX systems, */usr/include/errno.h* on z/OS systems, and */QIBM/include/errno.h* on IBM i systems.

User response

Close other applications to free memory, or restart the Content Manager OnDemand client. Then try the command again. See the *errno.h* file for more information. If the problem persists, contact your IBM Service Representative.

ARS1156E

The command *>command<* must be run as the instance owner *>instance_owner<*

Explanation

The command must be run under the user ID of the instance owner.

User response

Resubmit the command and specify the user ID of the instance owner.

ARS1157E

Unable to store the object *>object_name<*. Object size *object_size*

Explanation

The command failed when attempting to store the specified object.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS1158E

Failed while attempting to load the database

Explanation

The command failed when attempting to load the database.

User response

Determine the log ID and search the Content Manager OnDemand System Log for other messages that are associated with the load process. If the problem persists, contact your IBM Service Representative.

ARS1159E

Unable to retrieve the object *>object_name<*

Explanation

The command failed when attempting to retrieve the specified object.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the retrieve process. If the problem persists, contact your IBM Service Representative.

ARS1160E

Unable to get resource identifier

Explanation

The command failed when attempting to get a resource identifier.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the resource. If the problem persists, contact your IBM Service Representative.

ARS1161E

Unable to get LoadId

Explanation

The command failed when attempting to get a load ID.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the load process. If the problem persists, contact your IBM Service Representative.

ARS1162E

Unable to unload data from Content Manager OnDemand - LoadId(*loadid*) Rows Deleted(*rows_deleted*)

Explanation

The command failed when attempting to unload data.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the unload process. If the problem persists, contact your IBM Service Representative.

ARS1163E

No source file was specified

Explanation

A source (input) file was not specified.

User response

Resubmit the command with a valid source (input) file.

ARS1164E

Unable to register the resource

Explanation

The command failed when attempting to register a resource.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the resource. If the problem persists, contact your IBM Service Representative.

ARS1165E

Unable to get existing resource information

Explanation

The command failed when attempting to get existing resource information.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the resource. If the problem persists, contact your IBM Service Representative.

ARS1166E

Unable to save load information

Explanation

The command failed when attempting to save load information.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the load process. If the problem persists, contact your IBM Service Representative.

ARS1167E

Warning: Resource *>resource_name<* is empty, no resource will be used for documents

Explanation

The resource file is empty.

User response

Verify that the data that is being loaded does not require resources or, if it does, specify a valid resource.

ARS1168E

Unable to determine Storage Node

Explanation

The command failed to get the storage node information.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the load process. If the problem persists, contact your IBM Service Representative.

ARS1169W

The object already exists

Explanation

The object already exists.

User response

Verify the parameters and resubmit the command, or submit the command with a different object name.

ARS1170W

The object does not exist

Explanation

The server was unable to find a requested object.

User response

Verify the name of the object and resubmit the command with the correct parameters.

ARS1171E

The client and server are incompatible. Install a version of the client that is compatible with your OnDemand server.

Explanation

The client software and server software are not compatible. They must be the same version or compatible versions.

User response

Upgrade the client software, the server software, or both to the same version or to compatible versions.

ARS1172E

The operation was unsuccessful because the database is read-only

Explanation

The command failed when attempting to process a read-only instance of OnDemand.

User response

Resubmit the command to an instance of OnDemand that is not read-only.

ARS1173E

The server connection has timed out

Explanation

The server forced the command to log off the server because the command did not perform an action on the server within the interval of time that is specified by the inactivity time out value.

User response

Log off the server and log back on to the server. Then resubmit the command. A system administrator can increase the inactivity time out value for this or any other server in the Content Manager OnDemand administrative client. See the online help in the Content Manager OnDemand administrative client for more information.

ARS1174E

Internal product logic error. File=*file*, Line=*line*

Explanation

The program encountered an internal error.

User response

Verify that the API function parameters are correct. Contact your IBM Service Representative.

ARS1175I

Document compression type used - *compress_type*. Bytes Stored = *>bytes_stored<*

Explanation

The specified compression type was used to store the specified number of bytes. This message is for your information only.

User response

No action is required.

ARS1176E

Large Object had no pages specified. Make sure data has been properly indexed.

Explanation

To load large object documents into the system, the load process requires page-level indexing information.

User response

Verify that the indexing parameters are correct and enable the collection of page-level indexing information. Then resubmit the command.

ARS1179E

ICONV Conversion failed. rc=*returnCode*

Explanation

The command failed when attempting to convert the data.

User response

Contact your IBM Service Representative.

ARS1181E

The specified LoadId is not valid for the Application Group

Explanation

The load ID is not valid for the application group.

User response

Resubmit the command with a load ID that is valid for the application group.

ARS1182E

Unable to convert multibyte character string *>string<* to wide character string

Explanation

The command failed when attempting to convert a multibyte character string.

User response

Contact your IBM Service Representative.

ARS1183E

Unable to convert wide character string *>string<* to multibyte character string

Explanation

The command failed when attempting to convert a multibyte character string.

User response

Contact your IBM Service Representative.

ARS1184I

OnDemand UnLoad Successful - LoadId(*agid-pri_nid-sec_nid-name-start_date-stop_date*) Rows Deleted(*rows_deleted*)

Explanation

A report was successfully deleted from the system. This message is for your information only.

User response

No action is required.

ARS1185W

Warning: Unable to find LoadId in System Log

Explanation

The command failed to find the load ID in the Content Manager OnDemand System Log. The requested action cannot proceed.

User response

Resubmit the command with a valid load ID.

ARS1186I

LoadId matches existing LoadId in System Log

Explanation

The command located the load ID in the Content Manager OnDemand System Log. Processing continues. This message is for your information only.

User response

No action is required.

ARS1187W

Warning: LoadId (*load_id*) partially matches existing LoadId (*existing_load_id*) in System Log

Explanation

The command located a load ID in the Content Manager OnDemand System Log that contains some of the elements of the specified load ID. The requested action cannot proceed.

User response

Verify that the load ID is valid and then resubmit the command.

ARS1188E

Unloading will not continue, specify -Q option to continue

Explanation

The command failed when attempting to find the load ID. The unload command will not continue.

User response

Resubmit the command with the -Q parameter.

ARS1189W

Unloading will continue, however you may need to resubmit this command with the correct LoadId

Explanation

The specified load ID will be deleted. However, because the load ID does not represent a complete load process, you might need to take additional action to completely remove the report from the system.

User response

Resubmit the command with the load ID that represents the complete load process.

ARS1190E

Unable to determine codepage from codeset *rc*

Explanation

OnDemand was not able to determine the code page or code set.

User response

Verify that the codeset converter exists, and is in the correct location. Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS1191E

Unable to terminate the icu conversion *rc*

Explanation

The command failed when attempting to terminate the code page conversion.

User response

Contact your IBM Service Representative.

ARS1192I

OnDemand Login:

Explanation

You must enter a user ID that is valid for the instance of OnDemand that is being processed.

User response

Type a valid user ID and press Enter.

ARS1193I

Content Manager OnDemand Password:

Explanation

The password for the user ID used to log on to the Content Manager OnDemand instance that is being processed is required.

User response

Type the password for the user ID and press Enter.

ARS1194I

OnDemand Application Group:

Explanation

The application group to be processed must be identified.

User response

Type the name of the application group and press Enter.

ARS1195I

OnDemand Folder:

Explanation

The folder to be processed must be identified.

User response

Type the name of the folder and press Enter.

ARS1196E

Invalid generic index file format: >value<

Explanation

The index file contains incorrect index data.

User response

Verify that the index file conforms to the Content Manager OnDemand generic index file format. Then resubmit the command. See the IBM Content Manager OnDemand *Indexing Reference* for information about and examples of the Content Manager OnDemand generic index file.

ARS1197E

Invalid generic index file format sequence

Explanation

The index file contains incorrect index data.

User response

Verify that the index file conforms to the Content Manager OnDemand generic index file format. Then resubmit the command. See the IBM Content Manager OnDemand *Indexing Reference* for information about and examples of the Content Manager OnDemand generic index file.

ARS1198E

Row *row_number*: The value '*value*' cannot be converted to a valid big integer

Explanation

Invalid value for a big integer

User response

Change the indexing information so that the value is a valid big integer.

ARS1199W

The `.ind` file CCSID *ccsid_cp* does not match the CODEPAGE:*val_cp* value specified in the `.ind` file. A mismatch between the `.ind` file CCSID and the CODEPAGE:*value* might cause the load to fail.

Explanation

Codepage mismatch between the file CCSID and CODEPAGE value

User response

Verify that the index file conforms to the Content Manager OnDemand generic index file format. Then resubmit the command. Refer to the IBM Content Manager OnDemand *Indexing Reference* for information about and examples of the Content Manager OnDemand generic index file.

ARS1201I

Usage: arsmaint [-c [-n <min>] [-x <max>]] [-d] [-D <pct>] [-e] [-f <full>] [-g <name>] [-i] [-I <od_inst>] [-L] [-m] [-o] [-r] [-R] [-t <internal_date>] [-u <userid>] [-p <passwd>]]

Version: *version*

-c Expire Cache

-d Expire Database

-D <pct> Threshold of load being held before reloading (defaults to 0% - not reloaded)

-e Migrate Database Tables

-f <full> Cache Full - When to send alert message (defaults to 95%)

-g <name> Application Group Name (Defaults to all)

-h <od_inst> OnDemand instance name (same as -I)

-i Expire Migrated Imported Database Tables

-I <od_inst> OnDemand instance name (same as -h)

-L Update load ID table with application ID

-m Migrate Cache

-n <min> Min cache threshold percentage (Only for -c, Defaults to 80%)

-o Expire OnDemand Distribution Facility

-p <passwd> OnDemand Passwd (Only for -t)

-r Database Statistics

-R Reload Resources

-s Cache Filesystem statistics

-t <internal_date> Internal Date To Expire/Migrate (Defaults to Today)

-u <userid> OnDemand Userid (Only for -t)

-v Verify/Validate Cache Filesystems

-x <max> Max cache threshold percentage (Only for -c, Defaults to 80%)

Explanation

The arsmaint command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. See the Content Manager OnDemand Administration Guide for more information. Verify and correct the command parameters and resubmit the command.

ARS1202E

User `>user_name<` does not have permission to expire data on Application Group `>appl_grp_name<`

Explanation

The specified user does not have permission to expire data from the specified application group.

User response

Specify a user who has permission to expire data from the application group or change the user's permissions. Then resubmit the command.

ARS1301I

Usage: `arstblsp [-a <action>] [[-g <name>] [-I <od_inst>] [-t <table>]] [-u <userid>] [-p <passwd>]`

Version: *version*

`-a <action>` Action to perform

0 - Copy tables into their own tablespace, must specify `-g`

1 - Close a table that is still open for loading, must specify `-g`

2 - List the tables that do not have their own tablespace

3 - List the tables that are still open for loading

`-d <dir>` Directory for export/import file (UNIX default uses a named pipe)

`-g <name>` Application Group Name

`-h <od_inst>` OnDemand instance name (same as `-I`)

`-I <od_inst>` OnDemand instance name (same as `-h`)

`-p <passwd>` OnDemand Passwd

`-t <table>` Table Name

`-u <userid>` OnDemand Userid

Explanation

The `arstblsp` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. See the Content Manager OnDemand Administration Guide for more information. Verify and correct the command parameters and resubmit the command.

ARS1302E

Application Group `>appl_grp_name<` is currently not configured for tablespaces

Explanation

The specified application group is not configured to use table spaces. See the *IBM Content Manager OnDemand for z/OS: Administration Guide* for information on moving existing tables into table spaces.

User response

In the Content Manager OnDemand administrative client, configure the application group to use table spaces.

ARS1303I

No Tablespace: ApplGroup(*appl_grp_name*) Agid(*agid*) Table(*table_name*)

Explanation

This message is for your information only.

User response

No action is required.

ARS1304I

Table still open for loading: ApplGroup(*appl_grp_name*) Agid(*agid*) Table(*table_name*)

Explanation

The specified table is still open for loading. A table that is open for loading cannot be migrated to a table space.

User response

Close the table with the ARSTBLSP command. The application group name and table name are required by the ARSTBLSP command, and are provided in the message text.

ARS1305I

Closed table successfully: ApplGroup(*appl_grp_name*) Agid(*agid*) Table(*table_name*)

Explanation

The ARSTBLSP program successfully closed the specified table. This message is for your information only.

User response

No action is required.

ARS1306E

Unable to close table: ApplGroup(*appl_grp_name*) Agid(*agid*) Table(*table_name*)

Explanation

The ARSTBLSP program failed when attempting to close the specified table.

User response

Verify the name of the application group and the name of the table. See the Content Manager OnDemand System Log for other messages that are associated with the task. Resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS1307I

Table Empty - Deleted: ApplGroup(*appl_grp_name*) Agid(*agid*) Table(*table_name*)

Explanation

The ARSTBLSP program successfully deleted the specified table. This message is for your information only.

User response

No action is required.

ARS1308E

Unable to delete table: ApplGroup(*appl_grp_name*) Agid(*agid*) Table(*table_name*)

Explanation

The ARSTBLSP program failed when attempting to delete the specified table.

User response

Verify the name of the application group and the name of the table. See the Content Manager OnDemand System Log for other messages that are associated with the task. Resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS1309I

Successful copy of table: ApplGroup(*appl_grp_name*) Agid(*agid*) OldTable(*old_table_name*)
NewTable(*new_table_name*)

Explanation

The ARSTBLSP command successfully copied the specified table. This message is for your information only.

User response

No action is required.

ARS1310E

Copy of table failed: ApplGroup(*appl_grp_name*) Agid(*agid*) Table(*table_name*)

Explanation

The ARSTBLSP program failed when attempting to copy the specified table.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS1311E

User *>user_name<* does not have permission to convert tablespace data on Application Group
>appl_grp_name<

Explanation

The specified user does not have permission to convert table space data for the application group.

User response

Specify a user who has permission to convert table space data for the application group or permit the specified user to have administrator authority for the application group. Then resubmit the command.

ARS1312E

The system has encountered invalid data in the file during file decompression and has reported the following return code (comp_rc).

Explanation

There is invalid data in the file being decompressed.

User response

Verify that the content of the file being decompressed is valid and resubmit the command.

ARS1313I

Table created successfully: ApplGroup(*appl_group_name*) Agid(*agid*) Table(*table_name*)

Explanation

The ARSTBLSP program successfully created a new table. This message is for your information only.

User response

No action is required.

ARS1314E

Unable to create table: ApplGroup(*appl_group_name*) Agid(*agid*) Table(*table_name*)

Explanation

The ARSTBLSP program failed when attempting to create a table.

User response

Verify the name of the application group and the name of the table. See the Content Manager OnDemand System Log for other messages that are associated with the task . Resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS1315W

Warning: The date string "*date_string*" with date format "*date_format*" does not match a specific date. The minimum date is "*min_date*" and maximum date is "*max_date*"; the minimum date will be used.

Explanation

The string does not represent a specific date.

User response

Use a date value which does match a specific date.

ARS1400E

Duplicate load of *>file<* detected. Application group *>applgrp<*, partial loadid *loadid*.

Explanation

An attempt was made to load a file that failed a prior load.

User response

Use the ARSADMIN UNLOAD program function with *-Q -L load ID* parameters to unload the failed load. On IBM i systems, use the Remove Report (RMVRPTOND) command to unload the failed load.

ARS1401I

Unified login user id(*uid*) user name(*user_name*)

Explanation

An attempt to perform unified login failed using the specified uid and user.

User response

No action is required.

ARS1403I

Usage: version -V parm_file [options] Version: %2-u <userid> OnDemand User Login Name-p<passwd>
OnDemand User Login Password Stash File

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. For more information about this command, please see the *Administration Guide* for Content Manager OnDemand.

ARS1404I

The data that was loaded was a part of a distribution in ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS1405I

The data that was loaded was not a part of a distribution in ODF.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS1406E

Unable to notify ODF of the load. The error number is (error_num).

Explanation

The system was unable to determine if the loaded data belonged to a distribution in ODF.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS1407W

A document with >number_of_pages< pages and >number_of_bytes< bytes was processed. Although data might be stored successfully, the data might not be retrieved successfully.

Explanation

A document in the load qualifies as a large object. Adding large object support to the application that contains that document can improve performance when clients retrieve that document.

User response

Update the application definition to include the use of large object support. For more information about large object support and how to update an application definition, see the Content Manager OnDemand information center.

ARS1408W

Warning: A document of size *document size* bytes was processed. It is not recommended to store documents in OnDemand greater than *max_size* MB in size. Although data may store successfully, it is possible that the data may not be able to be retrieved successfully.

Explanation

The system determined that a document in the load should be indexed differently or broken into smaller segments.

User response

Determine whether the document can be indexed differently so that it is smaller, or whether the document can be segment.

ARS1409I

It is recommended that the application compression type be updated from *compression_type* to *>%2<* in order to use more efficient and higher compression ratio algorithms.

Explanation

The system determined that better compression algorithms exists and should be considered for use for the application.

User response

The application should be updated to use the compression algorithm specified.

ARS1410W

Information about the load that is stored in order to support certain features has exceeded the recommended size. The current size is *size* bytes and the recommended maximum size is *max_size*MB. It is recommended that the load be split into a series of smaller loads.

Explanation

The system determined that the load should be broken into smaller segments.

User response

The load should be evaluated to determine if it can be broken into smaller segments.

ARS1411W

Warning: The application group does not have a storage set defined and therefore will default to cache only. It is recommended that the application group have a defined storage set.

Explanation

The system determined that the application group did not have a storage set defined.

User response

The application group should be evaluated to determine if a storage set can be assigned.

ARS1412E

The document size of *<pages>* bytes exceeds the maximum size allowed of *<document_size>* bytes.

Explanation

The system is unable to load a document due to the document size exceeding the maximum size allowed for a document.

User response

Evaluate the document in the load to determine if the document can be made smaller or split into multiple smaller documents.

ARS1413I

File *compression_type* was successfully transferred to the server. Size(%2) Time(%3)

Explanation

This message is for your information only.

User response

No action is required.

ARS1414E

Unable to transfer the file *object_name*. Size(*object_size*)

Explanation

The command failed when attempting to transfer the specified file.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS1415E

Unable to load annotations when a postprocess command is specified.

Explanation

The command failed when attempting to load data.

User response

Verify the postprocess command for the application.

ARS1416E

Unable to load holds when a postprocess command is specified.

Explanation

The command failed when attempting to load data.

User response

Verify the postprocess command for the application.

ARS1417E

Unable to load data to an application group configured as a single table.

Explanation

The command failed when attempting to load data.

User response

Verify the application group is set to store to multiple tables.

ARS1418E

UUID generation failed. File=*file_name*, Line=*line_number*

Explanation

The command failed when attempting to generate a uuid for the document.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS1419E

SHA256 hash failed. File=*file_name*, Line=*line_number*

Explanation

The command failed when attempting to hash the document.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS1420E

Encryption failed. File=*file_name*, Line=*line_number*

Explanation

The command failed when attempting to encrypt the data.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS1421E

Decryption failed. File=*file_name*, Line=*line_number*

Explanation

The command failed when attempting to decrypt the data.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. If the problem persists, contact your IBM Service Representative.

ARS1500I

Usage: arssl [options]

Version: *version_number*

- The OnDemand System Load Utility Tool --
- a Audit the OnDemand database
- c Create message table and index
- d Drop message table and index
- g Application group name (Defaults to all application groups)
- h <od_inst> OnDemand instance name (same as -I)
- I <od_inst> OnDemand instance name (same as -h)
- o Output file name (XML format)
- p Populate message table
- v Verbose
- 1 <trace_file> Fully qualified trace file name

-2 <level> Trace level number. The values are additive. (Default: 3)
1: Errors
2: Warnings
4: Info
8: Flow

Explanation

The `arssl` command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. See the *Content Manager OnDemand Administration Guide* for more information. Verify and correct the command parameters and resubmit the command.

ARS1507E

Message table *table* does not exist

Explanation

The ARSSLU program cannot find the message table. The populate parameter requires this table exist.

User response

Generate the message table using the `-c` option, and resubmit the command.

ARS1600I

Usage: `arsstash [-a <action>] [-c] -s <stash_file> -u <userid>`

Version: *version*

`-a <action>` Action to perform

1 - Store the OnDemand userid and password (default)

2 - Delete the OnDemand userid and password

3 - Store the OnDemand userid and password for ARSLOAD

4 - Store the OnDemand userid and password for ODF

6 - Store the OnDemand userid and password for PDD

7 - Store the LDAP userid and password

8 - Store the DB2 userid and password

9 - Store the Oracle userid and password

10 - Store the ZooKeeper userid and password

If no userid (`-u`) is given for actions 3 thru 10, then the currently assigned userid for the corresponding OnDemand command or database will be displayed

`-c` Create stash file

`-s <stash_file>` Stash file name

`-u <userid>` Userid

`-1 <trace_file>` Trace file

`-2 <trace_level>` Trace level

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS1601E

The file *<file_name>* already exists.

Explanation

The specified file already exists.

User response

Verify that the file does not exist. Then resubmit the command.

ARS1602E

The stash file *<file_name>* is invalid.

Explanation

The specified stash file is invalid.

User response

Verify that the file is valid. Otherwise, resubmit the command specifying the option to create a new stash file.

ARS1603I

Userid *<userid>* is currently assigned to *<command>*.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS1604E

Unable to find an assigned user ID for the Content Manager OnDemand command or database.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS1605I

Verify OnDemand Password:

Explanation

The command prompts for the password of the user ID that was specified.

User response

Type the user's password and then press Enter to continue.

ARS1606E

The passwords do not match.

Explanation

An attempt was made to set a password, but the value that was specified for the Verify Content Manager OnDemand Password does not match the value that was specified for the Content Manager OnDemand Password.

User response

Specify the exact same values for the Content Manager OnDemand Password and Verify Content Manager OnDemand Password.

ARS1607E

Unable to find an assigned userid for the Content Manager OnDemand command or database *<cmd>* from stash file *<stash_file>*.

Explanation

Content Manager OnDemand is unable to get the necessary information from the Content Manager OnDemand stash file to proceed.

User response

Verify that the specified Content Manager OnDemand stash file contains a correct userid for the Content Manager OnDemand command or database.

ARS1608E

The Content Manager OnDemand stash file *<stash_file>* either does not exist or is not valid. Return Code is *rc*.

Explanation

Content Manager OnDemand is unable to get the necessary information from the Content Manager OnDemand stash file to proceed.

User response

Verify that the specified Content Manager OnDemand stash file exists and is correct.

ARS1609W

Specifying passwords on the command line is not secure, due to the text being visible. See the Installation and Configuration Guide for your platform for information about the `arsstash` command or using Unified Login.

Explanation

Specifying a password on the command line is considered insecure as the password is displayed in plain text. You should use the `arsstash` command to generate a stash file and pass this filename to the command or use a Unified Login for Windows or z/OS.

User response

Use a password stash file or Unified Login instead of passing a clear text password on the command line.

ARS1610E

The stash file *stash_file* is full, only %2 userid/passwords can be stored.

Explanation

The Content Manager OnDemand stash file can only contain a certain number of userid/passwords, either delete a userid from the existing stash file or create a new stash file.

User response

Create a new stash file or delete an existing userid from the stash file.

ARS2061W

Change Expired Logon Password

Explanation

The user's password expired and must be changed.

User response

Change the user's password and resubmit the command. Passwords might be case sensitive.

ARS2076E

*** LOGIC ERROR: An unknown message id was returned by the Common Server

Explanation

OnDemand encountered an internal logic error.

User response

Contact your IBM Service Representative.

ARS2077E

Mapping file '*file_name*' for codepage *codepage* not found. The default will be used.

Explanation

The client was unable to locate a mapping file required for converting a code page. The default mapping file will be used instead.

User response

Verify that the client is correctly installed. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS2078E

Could not initialize Common Server. Locale path is '*path_name*'

Explanation

The command failed when attempting to initialize the client software.

User response

Verify that the client is correctly installed. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS2083E

Insufficient memory is available to perform the operation

Explanation

There was not enough free memory available to run the command.

User response

Determine why sufficient memory could not be allocated by looking at the operating system and application task status. You might need to stop other processes or reboot the workstation before resubmitting the command.

ARS2084E

The client and server are incompatible. Reinstallation of the product is required.

Explanation

The client software and server software are not compatible. They must be the same version or compatible versions.

User response

Upgrade the client software, the server software, or both to the same version or to compatible versions.

ARS2085E

The client application is unable to initialize server communications. Contact your system administrator.

Explanation

The command failed when attempting to initialize the server.

User response

Stop and restart your client application. If the problem persists, contact your IBM Service Representative.

ARS2086E

Connection cannot be established for the *hostname* server

Explanation

The client failed when attempting to connect to the specific server.

User response

Verify that the server is properly configured and that the server program is running.

ARS2087E

Dynamic Load Library '*dll_name*' could not be found

Explanation

The client failed when attempting to load the specified dynamic load library.

User response

Verify that the Content Manager OnDemand software is installed correctly. If the problem persists, contact your IBM Service Representative.

ARS2088E

The server connection has timed out. You normally need to logoff, logon, and retry the operation. In some cases, an explicit logoff is not needed before the system invites you to logon.

Explanation

The server forced the client to log off from the server because the client did not perform an action on the server within the interval of time that is specified by the Inactivity Time Out value.

User response

Log off from the server and log back on to the server. Then resubmit the command. A system administrator can increase the inactivity time out value for this or any other server in the Content Manager OnDemand administrative client. See the online help in the Content Manager OnDemand administrative client for more information.

ARS2089E

Information has been modified on the server. Please logoff, logon, and retry the operation.

Explanation

The requested data was modified on the server.

User response

You must log off from the server, log on to the server again, and then try the operation again.

ARS2090E

The server failed during a search operation

Explanation

A server program encountered an error during a search operation.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the search. If the problem persists, contact your IBM Service Representative.

ARS2091E

The server failed while accessing folder data

Explanation

A server program encountered an error when accessing a folder.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the folder operation. If the problem persists, contact your IBM Service Representative.

ARS2092E

The server failed while retrieving a named query

Explanation

A server program encountered an error when retrieving a named query.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the retrieve operation. If the problem persists, contact your IBM Service Representative.

ARS2093E

The server failed while updating a named query

Explanation

A server program encountered an error when updating a named query.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the update operation. If the problem persists, contact your IBM Service Representative.

ARS2094E

The server failed while retrieving a document

Explanation

A server program encountered an error when retrieving a document.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the retrieve operation. If the problem persists, contact your IBM Service Representative.

ARS2095E

The server failed while updating a document

Explanation

A server program encountered an error when updating a document.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the update process. If the problem persists, contact your IBM Service Representative.

ARS2096E

The server failed while storing a document

Explanation

A server program encountered an error when storing a document.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the load process. If the problem persists, contact your IBM Service Representative.

ARS2097E

The server failed while deleting a document

Explanation

A server program encountered an error when deleting a document.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the delete process. If the problem persists, contact your IBM Service Representative.

ARS2098E

The server failed while retrieving a resource group

Explanation

A server program encountered an error when retrieving a resource group.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the retrieve process. If the problem persists, contact your IBM Service Representative.

ARS2099E

The server failed while retrieving a storage set

Explanation

A server program encountered an error when retrieving a storage set.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the retrieve process. If the problem persists, contact your IBM Service Representative.

ARS2100E

The server failed while updating user information

Explanation

A server program encountered an error when updating the user information.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the update process. If the problem persists, contact your IBM Service Representative.

ARS2101E

The server failed while retrieving a note

Explanation

A server program encountered an error when retrieving an annotation.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the retrieve process. If the problem persists, contact your IBM Service Representative.

ARS2102E

The server failed while storing a note

Explanation

A server program encountered an error when storing an annotation.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2103E

The server failed while deleting a note

Explanation

A server program encountered an error when deleting an annotation.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the delete process. If the problem persists, contact your IBM Service Representative.

ARS2104E

The server failed while updating an application

Explanation

A server program encountered an error when updating an application.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the update. If the problem persists, contact your IBM Service Representative.

ARS2105E

The server failed while querying printers

Explanation

A server program encountered an error when running a query for printers.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the query. If the problem persists, contact your IBM Service Representative.

ARS2106E

The server failed while printing

Explanation

A server program encountered an error when printing.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the print process. If the problem persists, contact your IBM Service Representative.

ARS2107E

The User ID or Password is not valid for the server

Explanation

The user ID or password is not valid for the instance of OnDemand.

User response

Specify a user ID and password that are valid for the instance of OnDemand. Passwords might be case sensitive.

ARS2108E

The new password must contain at least *min_passwd_length* characters

Explanation

An attempt was made to change a password, but the new password does not contain the minimum number of characters that are required by the system. Minimum password length is a configurable system parameter for each Content Manager OnDemand server. See the Content Manager OnDemand administrative client online help for additional information.

User response

Specify a new password that contains at least the minimum number of characters required by the system.

ARS2109E

The first and second specification of the new password are not the same

Explanation

An attempt was made to change a password, but the confirmation value did not match the value that was specified for the new password.

User response

Type the same value in both password fields. Passwords might be case sensitive.

ARS2110E

The current password is not correct

Explanation

An incorrect password was used.

User response

Resubmit the command with the correct password.

ARS2111E

The user is not permitted to perform the operation

Explanation

The user ID that was specified does not have permission to perform the operation.

User response

Specify a user ID that has permission to perform the operation or permit the user to perform the operation and then resubmit the command.

ARS2112E

The operation was unsuccessful because the database is read-only

Explanation

The database cannot be updated because it is read-only. The command cannot be run against a read-only instance of OnDemand.

User response

Resubmit the command against an instance of OnDemand that is not read-only.

ARS2113I

The folder cannot be opened because it does not contain any application groups accessible to the user. Contact your system administrator.

Explanation

The user ID does not have access to any of the application groups that are contained in the folder.

User response

Verify the name of the folder and the user ID. Permit the user to access one or more of the application groups that are contained in the folder. Then try to open the folder again.

ARS2114E

No search criteria have been specified

Explanation

A search command was attempted but no search criteria were specified.

User response

Specify search criteria for at least one of the search fields and resubmit the command.

ARS2115E

A value must be specified for *'field'*

Explanation

A search command was attempted but a value for a required field was not specified.

User response

Specify a value for the field and resubmit the command.

ARS2116E

'value' is invalid for *'field'*. A maximum of *max_chars* character(s) may be entered.

Explanation

The specified search string exceeds the maximum number of characters that are allowed for the field.

User response

Specify a valid search string for the field and resubmit the command.

ARS2117E

Only one value was entered for *'field'*. Enter a second value or choose a different comparison operator.

Explanation

A search by using a range was attempted but a valid range was not specified. A valid range consists of two values: the low value and the high value.

User response

Specify a valid range for the field or select a search operator that does not require a range. Then resubmit the search.

ARS2118E

'value' is invalid for *'field'*. An integer value in the range *'min_range'* to *'max_range'* is required.

Explanation

The specified search string is not a valid integer value. The error message provides additional information about valid integer values.

User response

Specify a valid integer value for the field and resubmit the search.

ARS2119E

'value' is invalid for 'field'. A decimal value in the range 'min_decimal' to 'max_decimal' is required. A maximum of *max_digits* digits may be specified to the right of the decimal point.

Explanation

The specified search string is not a valid decimal value. The error message provides additional information about valid decimal values.

User response

Specify a valid decimal value for the field and resubmit the search.

ARS2120E

'value' is invalid for 'field'. A date/time in the range 'min_date' to 'max_date' is required. Note that 2-digit years less than 70 are interpreted as year 20nn.

Explanation

The specified search string is not a valid date value. The error message provides additional information about valid date values.

User response

Specify a valid date value for the field and resubmit the search.

ARS2121E

For 'field', the first value must not be greater than the second value

Explanation

A search by using a range was attempted but a valid range was not specified. The first value in the range must not be greater than the second value in the range.

User response

Specify a valid range for the field and resubmit the search.

ARS2122E

'value' for 'field' is incompatible with 'incompat_value' for 'incompat_field'

Explanation

The specified search string is not compatible with the field being searched. For example, ApplGrp=a and FieldX=b, but FieldX is not mapped in ApplGrp a.

User response

Specify valid search values for the field and resubmit the search.

ARS2123E

'value' cannot be used for 'field'

Explanation

The specified search string is not compatible with the field being searched.

User response

Specify a valid search value for the field and resubmit the search.

ARS2124I

Only *max_documents* documents can be listed for this folder

Explanation

A search resulted in more items that can be listed in the document list. A Content Manager OnDemand folder might have a limit on the number of items that can be listed in the document list. This limit is defined for each folder with the Maximum Hits option.

User response

Refine the query to return fewer results or increase the maximum results for this folder. Then resubmit the command.

ARS2125I

The document for '*document*' is not available at this time. It may reside on an unmounted storage volume. Contact your system administrator.

Explanation

A document cannot be retrieved because it resides on an unmounted storage volume.

User response

Ask a system administrator or system operator to mount the storage volume. Then resubmit the command.

ARS2126I

'*view*' was the default view. The public default view will be used unless another private default is set.

Explanation

The default private logical view was deleted. Documents will now be viewed using the default public logical view, unless a new default private logical view is specified.

User response

No action is required.

ARS2127E

A maximum of *max_views* views may be stored for this document

Explanation

An attempt was made to create a logical view but the maximum number of logical views was exceeded.

User response

Delete an existing logical view and then try to create the logical view again.

ARS2128E

The client and CD-ROM Mastering Dynamic Load Library are incompatible. Reinstallation of the product is required.

Explanation

The client software and server software are not compatible. They must be the same version or compatible versions.

User response

Upgrade the client software, the server software, or both to the same version or to compatible versions.

ARS2129E

Unable to obtain procedure addresses from CD-ROM Mastering DLL

Explanation

The client failed when attempting to load the CD-ROM Mastering dynamic load library.

User response

Reinstall the client application, then try the command again. If the problem persists, contact your IBM Service Representative.

ARS2130E

Only one copy of a folder may be put on a CD-ROM

Explanation

The folder already exists on the CD-ROM.

User response

Select a different folder.

ARS2131I

A staging drive must be selected

Explanation

CD-ROM production requires a staging drive, and one was not specified.

User response

Resubmit the command with a valid staging drive.

ARS2132E

Unable to clean staging area

Explanation

An error occurred while this program was running.

User response

Verify that the staging drive is valid, and that you have the correct permissions to write to it. If the problem persists, contact your IBM Service Representative.

ARS2133E

Unable to set up directories on staging drive

Explanation

An error occurred while this program was running.

User response

Verify that the staging drive is valid, and that you have the correct permissions to write to it. If the problem persists, contact your IBM Service Representative.

ARS2134E

Unable to retrieve documents

Explanation

An error occurred while this program was running.

User response

See other messages in the System Log that are associated with the CD-ROM task. If the problem persists, contact your IBM Service Representative.

ARS2135E

Unable to retrieve resources

Explanation

An error occurred while this program was running.

User response

See other messages in the System Log that are associated with the CD-ROM task. If the problem persists, contact your IBM Service Representative.

ARS2136E

Unable to open index file

Explanation

An error occurred while this program was running.

User response

Ensure that you are using a valid OnDemand CD-ROM image. If the problem persists, contact your IBM Service Representative.

ARS2137E

The client and the CD-ROM indexes are incompatible

Explanation

The client software and server software are not compatible. They must be the same version or compatible versions.

User response

Upgrade the client software, the server software, or both to the same version or to compatible versions.

ARS2138E

Unable to add items to the index

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2139E

Unknown field type encountered in the data

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2140E

Unable to retrieve annotations

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2141E

Unable to read ARS layout

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2142E

Unable to read client layout

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2143E

CD-ROM Mastering software is not defined

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2144E

Unable to obtain valid volume id

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2145E

Unable to open manifest file

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2146E

Unable to open original file for staging

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2147E

Unable to open destination file for staging

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2148E

Unable to read file for staging

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2149E

Invalid folder encountered

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2150E

External server error

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2151E

*** LOGIC ERROR: unexpected exception from External Server

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2152E

*** LOGIC ERROR: Unknown folder name

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2153E

*** LOGIC ERROR: Invalid search operator for '*field*'

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2154E

*** LOGIC ERROR: Unknown choice for CHOICE criteria

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2155E

*** LOGIC ERROR: Invalid segment number

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2156E

*** LOGIC ERROR: Invalid CDROM folder

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the CD-ROM process. If the problem persists, contact your IBM Service Representative.

ARS2157E

*** LOGIC ERROR: LogView - Unknown or public or no permission to save, update, or delete

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2158E

*** LOGIC ERROR: Named Query - Unknown or no permission to save, update, or delete

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2159E

*** LOGIC ERROR: No CsvPrtOpt name provided

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2160E

Server exit password validation failed. Contact your system administrator.

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2161E

*** LOGIC ERROR: A server operation was in progress when another was initiated

Explanation

An error occurred while this program was running.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2162E

The server failed while attempting to convert data

Explanation

An error occurred while this program was running.

User response

Check to ensure the converter code page exists in the cnvrtrs.txt file and that the ICU data library is in the locale directory and has the correct permissions. If the problem persists, contact your IBM Service Representative.

ARS2163E

The server failed while attempting to logon

Explanation

An error occurred while this program was running.

The server was unable to complete the logon.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2164I

The operation could not be completed because required data resides on unavailable archive media. Contact your system administrator to make the data available.

Explanation

The document could not be retrieved because the storage volume on which it exists is offline or not available.

User response

Ask a system administrator or system operator to mount the storage volume. Then resubmit the command.

ARS2166E

The user is not permitted to perform this operation for document '*document*'

Explanation

The user does not have permission to perform the operation on the specified document.

User response

Update the user's permissions to allow the operation and resubmit the command, or submit the command from a user ID that has the correct permissions.

ARS2167I

No documents meet the search criteria

Explanation

The query was run, however, there were no documents that matched the search criteria.

User response

Verify that this is the expected result. If it is not, change the search criteria and resubmit the query.

ARS2168E

The document for '*document*' is not displayable or printable

Explanation

The specified document cannot be viewed or printed. This message is for your information only.

User response

Select a document that can be displayed or printed.

ARS2169E

The argument '*value*' is not a valid decimal number

Explanation

The specified search value is not a valid decimal number.

User response

Specify a valid decimal number and try the search again.

ARS2170I

No arguments specified

Explanation

A search was attempted, but no search values were specified.

User response

Specify one or more search values and try the search again.

ARS2171E

The argument '*value*' was not specified

Explanation

A search was attempted, but a search value was missing from a required search field.

User response

Specify a search value for the field and try the search again.

ARS2172E

The function '*function*' was not found

Explanation

The client failed because the specified function was not found.

User response

Check the Content Manager OnDemand documentation, and ensure that the function you are calling is a valid, supported function. If the problem persists, contact your IBM Service Representative.

ARS2173E

The field '*field*' was not found in this folder

Explanation

The specified field is not a valid field for the folder.

User response

Resubmit the command with a valid folder field.

ARS2174E

No mappings exist for the specified folder fields

Explanation

The folder fields are not mapped to application group fields.

User response

Map the folder fields to the application group fields and resubmit the command.

ARS2175E

The environment variable '*environ_variable*' was not found

Explanation

The command failed because the specified environment variable was not set.

User response

Set the environment variable and then resubmit the command.

ARS2176I

The user specified does not have access to any folders

Explanation

The specified user does not have permission to access any folders.

User response

Update the user's permissions to allow access to one or more folders and resubmit the command.

ARS2177E

Unable to initialize environment. rc=*returnCode*

Explanation

The client failed when attempting to initialize the environment.

User response

Configure the server to enable logging and then resubmit the command. See the *Web Enablement Kit: Implementation Guide* for information about how to enable logging and for help with other problem determination tools that are available in this environment. If the problem persists, contact your IBM Service Representative.

ARS2184I

There are no notes associated with this document

Explanation

This message is for your information only.

User response

No action is required.

ARS2185I

Select a folder:

Explanation

This message is for your information only.

User response

No action is required.

ARS2187I

User logged off!

Explanation

This message is for your information only.

User response

No action is required.

ARS2192I

View Document

Explanation

This message is for your information only.

User response

No action is required.

ARS2193I

View Annotations

Explanation

This message is for your information only.

User response
No action is required.

ARS2194I

Add Annotation

Explanation
This message is for your information only.

User response
No action is required.

ARS2195I

Server Print

Explanation
This message is for your information only.

User response
No action is required.

ARS2196I

Private to user

Explanation
This message is for your information only.

User response
No action is required.

ARS2197I

Private to group

Explanation
This message is for your information only.

User response
No action is required.

ARS2198I

Note can be copied to another server

Explanation
This message is for your information only.

User response
No action is required.

ARS2201W

At least one document must be selected!

Explanation
A command was entered, but no documents were selected.

User response

Select one or more documents and resubmit the command.

ARS2202I

Documents sent to printer!

Explanation

This message is for your information only.

User response

No action is required.

ARS2203I

Note added successfully!

Explanation

This message is for your information only.

User response

No action is required.

ARS2207I

Document has been updated!

Explanation

This message is for your information only.

User response

No action is required.

ARS2209E

Unable to run the program *>command<*. *errno=errno*

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in */usr/include/sys/errno.h* on UNIX systems, */usr/include/errno.h* on z/OS systems, and */QIBM/include/errno.h* on IBM i systems.

User response

Check the Content Manager OnDemand installation directory and ensure that the file exists and is executable. Then try the command again. See the *errno.h* file for more information. If the problem persists, contact your IBM Service Representative.

ARS2210I

strerror_text

Explanation

The message contains the text from the *strerror()* function. This message is for your information only.

User response

No action is required.

ARS2211I

Using *temp_dir* for temporary files

Explanation

The specified directory is being used for temporary files.

User response

No action is required.

ARS2215E

The server failed while applying holds

Explanation

A server program encountered an error when applying holds.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2216E

Internal error func=func RC=rc(rsn1-rsn2) File=file, Line=line

Explanation

An internal error occurred when during processing.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the task. If the problem persists, contact your IBM Service Representative.

ARS2217E

Application group '*applgrp_name*' was not found on server '*server_name*'.

Explanation

A Server error occurred during Application Group Query.

User response

Verify the name of the application group and the name of the server. Verify that the application group exists on the server. Verify that the user has permission to access the application group. Then resubmit the command.

ARS2218E

The data type of the database field '*database_field_name*' is not supported by the client that is being used to add the document.

Explanation

The data type of the database field is not supported by the client that is being used to add the document.

User response

The client that is being used to add the document does not support the data type of the database field. Resubmit the command with a client that supports the data type.

ARS2220E

'*value*' is invalid for '*field*'.

Explanation

The specified search string is not a valid binary value.

User response

Specify a valid binary value for the field and resubmit the search.

ARS3001E

timestamp: 001: Server name parameter required

Explanation

A server name is required, but one was not specified.

User response

Resubmit the command with a valid server name.

ARS3002E

timestamp: 002: No data distribution server section defined [*server*]

Explanation

The server section for data distribution does not exist.

User response

Define and configure the servers in the server section and resubmit the command.

ARS3003E

timestamp: 003: Unable to clean directory [*directory_name*]

Explanation

An error occurred while this program was running.

User response

Verify that the directory exists, and that you have permissions to write to it. Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS3004E

timestamp: 004: Unable to copy file [*file_name*]

Explanation

An error occurred while this program was running.

User response

Verify that the directory exists, and that you have permissions to write to it. Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS3005E

timestamp: 005: Unable to obtain volume set id

Explanation

An error occurred while this program was running.

User response

Verify that the Content Manager OnDemand server definition is correct, then try the command again. If the problem persists, contact your IBM Service Representative.

ARS3006E

timestamp: 006: Unable to create control file [*file_name*]

Explanation

An error occurred while this program was running.

User response

Verify that the directory exists, and that you have permissions to write to it. Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS3007E

timestamp: 007: Unable to open control file [*file_name*]

Explanation

An error occurred while this program was running.

User response

Verify that the directory exists, and that you have permissions to write to it. Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS3008E

timestamp: 008: OnDemand password expired or invalid

Explanation

The password that was entered is not valid.

User response

Check to ensure that you entered the password correctly, and that the password is still valid. If it is no longer valid, reset it and try the command again.

ARS3009E

timestamp: 009: OnDemand login error RC [*rc*]

Explanation

An error occurred while this program was running.

User response

Ensure that you are specifying a valid OnDemand server and that you are entering valid logon information. Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS3010E

timestamp: 010: Rimage imaging directory not specified

Explanation

The name of the Rimage imaging directory was not specified.

User response

Specify the name of the Rimage imaging directory and resubmit the command.

ARS3014E

timestamp: 014: OnDemand library server logon information missing

Explanation

Either the library server was not specified or an incorrect user ID or password was supplied.

User response

Resubmit the command with a library server and a valid user ID and password.

ARS3015E

timestamp: 015: Log directory required

Explanation

A log directory is required, but one was not specified.

User response

Specify the name of the directory to be used for log and Rimage control files. Then resubmit the command.

ARS3016E

timestamp: 016: Load directory required

Explanation

A load directory is required, but one was not specified.

User response

Specify the name of the load directory and resubmit the command.

ARS3017E

timestamp: 017: Unable to open volume set id file [*file_name*]

Explanation

The ARSDD program failed when attempting to open the specified volume set ID file.

User response

Verify that the volume set ID file exists and then resubmit the command.

ARS3018E

timestamp: 018: Invalid volume set id file [*file_name*]

Explanation

The specified volume set ID file is not correct. It might be in an invalid format, be empty, or be damaged. Another possibility is that multiple users have used the same staging directory for saving image information and the volume set ID file was overwritten.

User response

Begin the image creation process again. If the problem persists, consider creating separate distribution servers for each user involved in creating CD images.

ARS3019E

timestamp: 019: Invalid parameter combination '-i' and '-g' specified

Explanation

The -i (data distribution file ID) and -g (data distribution group ID) parameters cannot be specified for the same task. Valid parameters and usage instructions are available from the command line: `arsdd -?`.

User response

Resubmit the command with the correct parameters.

ARS3020E

timestamp: 020: Could not store control file [*file_name*]

Explanation

An error occurred while this program was running.

User response

Verify that the directory exists and that you have permission to write to it. If the problem persists, contact your IBM Service Representative.

ARS3021E

timestamp: 021: Could not display load failure file [*file_name*]

Explanation

The CD-ROM creation process failed.

User response

Then try the command again. If the problem persists, contact your IBM Service Representative.

ARS3022E

timestamp: 022: Memory allocation failed [*file|line*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3023E

timestamp: 023: Unable to clean root directory

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3024E

timestamp: 024: Unable to retrieve id file [*file_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3025E

timestamp: 025: Invalid or unreadable distribution group file [*file_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3026E

timestamp: 026: Invalid or incorrectly named index file [*file_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3027E

timestamp: 027: Invalid or incorrectly named input file [*file_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3050I

timestamp: 050: CREATE [*file_name*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3051I

timestamp: 051: LIBRARY SERVER USERID [*hostname*] [*user_name*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3052I

timestamp: 052: CONTROL FILE ERROR [*file_name*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3053I

timestamp: 053: DONE LOAD DIRECTORY [*directory_name*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3054I

timestamp: 054: DONE DISTRIBUTION FILE ID [*file_id*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3055I

timestamp: 055: LOAD DIRECTORY [*directory_name*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3056I

timestamp: 056: LOAD COMPLETED FILE [*file_name*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3057E

timestamp: 057: LOAD FAILED FILE [*file_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3058I

timestamp: 058: DISTRIBUTION FILE ID FOLDER [*file_id*] [*folder_name*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3059I

timestamp: 059: DISTRIBUTION GROUP ID FOLDER [*file_id*] [*folder_name*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3060I

timestamp: 060: QUERY FOLDER NQUERY [*named_query*] [*folder*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3061I

timestamp: 061: VERIFICATION PASSED

Explanation

This message is for your information only.

User response

No action is required.

ARS3062E

timestamp: 062: VERIFICATION FAILED

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3063E

timestamp: 063: VERIFICATION NO FOLDER FOR APPLICATION GROUP [*appl_grp_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3064E

timestamp: 064: VERIFICATION NO APPLICATION GROUPS

Explanation

An error occurred while this program was running.

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3065E

timestamp: 065: VERIFICATION WARNING NO CLIENT SOFTWARE

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3066E

timestamp: 066: VERIFICATION NO APPLICATION GROUP FOR FOLDER [*folder_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3067E

timestamp: 067: VERIFICATION WARNING NO MEDIA LABEL TEMPLATE

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3068E

timestamp: 068: VERIFICATION NO USERS

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3069E

timestamp: 069: VERIFICATION WARNING NO PASSWORD

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3070I

timestamp: 070: APPLICATION GROUP [appl_grp_name]

Explanation

This message is for your information only.

User response

No action is required.

ARS3072I

timestamp: 071: CLIENT LANGUAGE [client] [language]

Explanation

This message is for your information only.

User response

No action is required.

ARS3074I

timestamp: 072: USER SUPPLIED FILE SRC DEST TYPE [source] [destination] [file_name]

Explanation

This message is for your information only.

User response

No action is required.

ARS3076I

timestamp: 073: FOLDER [folder_name]

Explanation

This message is for your information only.

User response

No action is required.

ARS3078I

timestamp: 074: GROUP [group_name]

Explanation

This message is for your information only.

User response

No action is required.

ARS3080I

timestamp: 075: LABEL TEMPLATE ID [file_id] [label]

Explanation

This message is for your information only.

User response

No action is required.

ARS3082I

timestamp: 076: USER [user_name]

Explanation

This message is for your information only.

User response

No action is required.

ARS3084I

timestamp: 077: USER PASSWORD [user_name] [passwd]

Explanation

This message is for your information only.

User response

No action is required.

ARS3086I

timestamp: 078: CFM FILE ID [value] [file_id]

Explanation

This message is for your information only.

User response

No action is required.

ARS3088I

timestamp: 079: RETRIEVED LABEL ID [label_file_name] [file_name]

Explanation

This message is for your information only.

User response

No action is required.

ARS3090E

timestamp: 080: FAILED RETRIEVING LABEL ID [label_file_name] [file_name]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3100I

timestamp: 100: DATA DISTRIBUTION PROCESSING STARTED

Explanation

Data distribution processing started. This message is for your information only.

User response

No action is required.

ARS3101E

timestamp: 101: DATA DISTRIBUTION PROCESSING FAILED

Explanation

An error occurred while this program was running.

Data distribution processing failed

User response

Look in the Rimage Image Server and Production Server logs for other errors. If the problem persists, contact your IBM Service Representative.

ARS3102I

timestamp: 102: DATA DISTRIBUTION PROCESSING COMPLETED

Explanation

Data distribution processing is complete. This message is for your information only.

User response

No action is required.

ARS3103E

timestamp: 103: DATA DISTRIBUTION PROCESSING CRITICAL FAILURE

Explanation

An error occurred while this program was running.

Data distribution processing failed.

User response

Look at the messages that precede this message for the last process that started before this error for an indication of what failed. If the problem persists, contact your IBM Service Representative.

ARS3104I

timestamp: 104: CLIENT TRANSFER STARTED

Explanation

Client transfer started. This message is for your information only.

User response

No action is required.

ARS3105E

timestamp: 105: CLIENT TRANSFER FAILED

Explanation

An error occurred while this program was running.

Client transfer failed. The Content Manager OnDemand user client might not be available on the Content Manager OnDemand library server. For AIX, the user client should be installed in /opt/IBM/ondemand/V10.1/client/windows/win32. For Solaris, the path is opt/ondemand/client/windows/win32. For Windows, the path is \client\windows\win32.

User response

Make sure that the latest Content Manager OnDemand client was installed in the proper directory on the Content Manager OnDemand Library server. If the problem persists, contact your IBM Service Representative.

ARS3106I

timestamp: 106: CLIENT TRANSFER COMPLETED

Explanation

Client transfer is complete. This message is for your information only.

User response

No action is required.

ARS3107E

timestamp: 107: CLIENT COPY FILE ERROR [*source*] [*errno*]

Explanation

An error occurred while this program was running. The *source* identifies the name of the file that failed. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS3108I

timestamp: 108: CFM TRANSFER STARTED

Explanation

This message is for your information only.

User response

No action is required.

ARS3109E

timestamp: 109: CFM TRANSFER FAILED

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3110I

timestamp: 110: CFM TRANSFER COMPLETED

Explanation

This message is for your information only.

User response

No action is required.

ARS3111E

timestamp: 111: CFM COPY FILE ERROR [*file_name*] [*errno*]

Explanation

An error occurred while this program was running. The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS3112I

timestamp: 112: USER SUPPLIED FILES TRANSFER STARTED

Explanation

Transfer of user-supplied files started. This message is for your information only.

User response

No action is required.

ARS3113E

timestamp: 113: USER SUPPLIED FILES TRANSFER FAILED

Explanation

An error occurred while this program was running.

Transfer of user-supplied files failed.

User response

If the problem persists, contact your IBM Service Representative.

ARS3114I

timestamp: 114: USER SUPPLIED FILES TRANSFER COMPLETED

Explanation

Transfer of user-supplied files is complete. This message is for your information only.

User response

No action is required.

ARS3115E

timestamp: 115: USER SUPPLIED FILES ERROR [*file_name*] [*errno*]

Explanation

An error occurred while this program was running.

The *errno* value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems.

User response

See the `errno.h` file for more information. If the problem persists, contact your IBM Service Representative.

ARS3116I

timestamp: 116: VOLUME CALCULATION STARTED

Explanation

Volume calculation started. This message is for your information only.

User response

No action is required.

ARS3117E

timestamp: 117: VOLUME CALCULATION FAILED

Explanation

An error occurred while this program was running.

Volume calculation failed.

User response

If the problem persists, contact your IBM Service Representative.

ARS3118I

timestamp: 118: VOLUME CALCULATION COMPLETED

Explanation

Volume calculation is complete.

User response

No action is required.

ARS3119I

timestamp: 119: VOLUME CALCULATION VOLUMES FILES BYTES [*volumes*] [*files*] [*total*]

Explanation

Volume calculation is complete. The volume requires *volumes* of media to hold *files* files totaling *total* bytes.

User response

No action is required.

ARS3120W

timestamp: 120: VOLUME INDEX CAPACITY EXCEEDED BYTES [*bytes*]

Explanation

The index exceeds the capacity of the media. If this is a multi-volume set, the index must fit on the first volume of the set along with the Content Manager OnDemand client and all user-supplied files.

User response

Reduce the number of user-defined files or reduce the number of documents or folders. Then resubmit the command.

ARS3121W

timestamp: 121: VOLUME DATA CAPACITY EXCEEDED VOLUME BYTES [*volumes*] [*total*]

Explanation

The data file for the specified volume exceed the capacity of the media.

User response

Reduce the size of the data file and then resubmit the command.

ARS3122I

timestamp: 122: STORAGE SET CREATION STARTED

Explanation

Storage set creation started at the specified time. This message is for your information only.

User response

No action is required.

ARS3123E

timestamp: 123: STORAGE SET CREATION FAILED

Explanation

An error occurred while this program was running.

Storage set creation failed.

User response

If the problem persists, contact your IBM Service Representative.

ARS3124I

timestamp: 124: STORAGE SET CREATION COMPLETED

Explanation

Storage set creation is complete. This message is for your information only.

User response

No action is required.

ARS3125E

timestamp: 125: STORAGE SET CREATION FAILED ADD STORAGE SET [*set_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3126I

timestamp: 126: STORAGE SET CREATION FAILED ADD STORAGE NODE [*node_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3127I

timestamp: 127: STORAGE SET APPLICATION GROUP UPDATE STARTED

Explanation

This message is for your information only.

User response

No action is required.

ARS3128E

timestamp: 128: STORAGE SET APPLICATION GROUP UPDATE FAILED

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3129I

timestamp: 129: STORAGE SET APPLICATION GROUP UPDATE COMPLETED

Explanation

This message is for your information only.

User response

No action is required.

ARS3130E

timestamp: 130: LOGIN FAILED RETURN CODE [rc]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3131I

timestamp: 131: STORAGE SET DATA FILE UPDATE STARTED

Explanation

This message is for your information only.

User response

No action is required.

ARS3132E

timestamp: 132: STORAGE SET DATA FILE UPDATE FAILED

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3133I

timestamp: 133: STORAGE SET DATA FILE UPDATE COMPLETED

Explanation

This message is for your information only.

User response

No action is required.

ARS3134E

timestamp: 134: DATA FILE UPDATE ERROR APPLICATION GROUP FILE [*appl_grp_name*] [*file_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3135E

timestamp: 135: DATA FILE UPDATE ERROR RETURN CODES [RC=*rc*] [CTRC=*ctrc*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3136I

timestamp: 136: INDEX OPTIMIZATION STARTED

Explanation

Index optimization started. This message is for your information only.

User response

No action is required.

ARS3137E

timestamp: 137: INDEX OPTIMIZATION FAILED

Explanation

An error occurred while this program was running.

Index optimization failed.

User response

If the problem persists, contact your IBM Service Representative.

ARS3138I

timestamp: 138: INDEX OPTIMIZATION COMPLETED

Explanation

Index optimization is complete. This message is for your information only.

User response

No action is required.

ARS3139E

timestamp: 139: INDEX CONVERSION ERROR FILE RETURN CODE [*file_name*] [*rc*]

Explanation

An error occurred while this program was running.

An error occurred during index conversion.

User response

If the problem persists, contact your IBM Service Representative.

ARS3140I

timestamp: 140: DATA DISTRIBUTION WRITING STARTED

Explanation

This message is for your information only.

User response

No action is required.

ARS3141E

timestamp: 141: DATA DISTRIBUTION WRITING FAILED

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3142I

timestamp: 142: DATA DISTRIBUTION WRITING COMPLETED

Explanation

This message is for your information only.

User response

No action is required.

ARS3143E

timestamp: 143: DATA DISTRIBUTION WRITING TIMEOUT

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3144E

timestamp: 144: WRITING VOLUME FILE FAILED [*volume_number*|*rc*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3145I

timestamp: 145: RIMAGE EDITLIST CREATION STARTED VOLUME [*rc*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3146E

timestamp: 146: RIMAGE EDITLIST CREATION FAILED VOLUME [*rc*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3147I

timestamp: 147: RIMAGE EDITLIST CREATION COMPLETED VOLUME [*rc*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3148E

timestamp: 148: EDITLIST CREATION ERROR FILE RETURN CODE [*file_name*] [*rc*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3149I

timestamp: 149: RIMAGE IMAGE CREATION STARTED VOLUME [*volume*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3153I

timestamp: 153: RIMAGE IMAGE CREATION REQUEST ACCEPTED VOLUME [*volume*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3158I

timestamp: 158: RIMAGE IMAGE PRODUCTION REQUEST ACCEPTED VOLUME [*volume*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3159E

timestamp: 159: UNABLE TO REMOVE ENTRY FROM RIMAGE IOF FILE [*file_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3160E

timestamp: 160: UNABLE TO REMOVE ENTRY FROM RIMAGE POF FILE [*file_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3161I

timestamp: 161: LABEL PROCESSING STARTED

Explanation

This message is for your information only.

User response

No action is required.

ARS3162E

timestamp: 162: LABEL PROCESSING FAILED

Explanation

An error occurred while this program was running.

Label processing failed.

User response

If the problem persists, contact your IBM Service Representative.

ARS3163I

timestamp: 163: LABEL PROCESSING COMPLETED

Explanation

Label processing is complete. This message is for your information only.

User response

No action is required.

ARS3164W

timestamp: 163: NO DOCUMENTS RETURNED NQUERY [named_query]

Explanation

The named query ran, but did not find any documents that match.

User response

Verify that this is the expected result. If it is not, verify that the named query is correct.

ARS3165E

timestamp: 164: UNABLE TO CREATE LABEL MERGE FILE [file_name] [rc]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3166E

timestamp: 165: UNABLE TO OPEN USER-SUPPLIED MERGE FILE [file_name]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3167I

timestamp: 165: LABEL TEMPLATE AVN [file_name] [avn_file_name]

Explanation

This message is for your information only.

User response

No action is required.

ARS3169I

timestamp: 166: LABEL TEMPLATE ID FILE [*file_id*] [*label*] [*merge_file*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3171I

timestamp: 167: LABEL TEMPLATE ID FIELD CONTENTS [*file_id*] [*label*] [*merge_field_number*] [*merge_field*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3173E

timestamp: 168: Unable to identify client type in file [*type*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3174E

timestamp: 169: Unable to replace client directory [*directory_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3175E

timestamp: 170: Unable to install client files in directory [*directory_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3176E

timestamp: 171: File does not exist or is inaccessible [*file_name*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3178I

timestamp: 173: Installing OnDemand 32-bit client files

Explanation

This message is for your information only.

User response

No action is required.

ARS3179I

timestamp: 174: Definition removed for server [server]

Explanation

This message is for your information only.

User response

No action is required.

ARS3180E

timestamp: 175: Server definition is not for data distribution [server]

Explanation

A server was specified that is not configured for data distribution.

User response

Update the server definition for data distribution and resubmit the command.

ARS3182E

timestamp: 176: Definition not created or updated for server [server]

Explanation

The server definition could not be created or updated. This message is usually the result of a permission problem. On Windows, the user must be an administrator. On a UNIX system, the user must have at least read-write permissions for the ars.ini file.

User response

Verify the permissions and resubmit the command.

ARS3183I

timestamp: 177: Data distribution definition created for server [server]

Explanation

This message is for your information only.

User response

No action is required.

ARS3184I

timestamp: 178: LOAD STARTED FILE [*name*]

Explanation

This message is for your information only.

User response

No action is required.

ARS3185E

timestamp: 179: RIMAGE IMAGE SERVER ERROR [*rc*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3186E

timestamp: 180: RIMAGE PRODUCTION SERVER ERROR [*rc*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3300E

timestamp: 028: Could not clean IOF file [*rc*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3301E

timestamp: 029: Could not clean POF file [*rc*]

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS3302I

Usage: *arsdd* [*options*]

Version: *version*

-a <*dir*> Directory in which to run indexer (Default: Load Directory)

-c Clean and reset staging directory

-d <*dir*> Load directory (Required)

-e Warnings as errors

-g <*id*> Data distribution group id

-h <server> OnDemand library server name
 -i <id> Data distribution file id
 -j <name> Network name of data distribution machine
 -k Keep load and status files
 -l <dir> Control file directory (Required)
 -m <n> Make n number of media sets
 -n <cp> Codepage for data and indexes (Default: 819)
 -o Show stored options
 -p <password> OnDemand library server password
 -r <dir> Rimage imaging directory (e.g. e:\rimage\images\
 -s <server> OnDemand data distribution server name (Required)
 -u <userid> OnDemand library server userid
 -v Verbose output
 -w Store configuration options
 -x <[580]/[640]/[700]/[DVD]> Media capacity (Default: 640)
 580: = ~580 Mbytes
 640: = ~640 Mbytes
 700: = ~700 Mbytes
 DVD: = ~4300 Mbytes
 -y <file> Rimage image order file name (Default: ondemand.iof)
 -z <file> Rimage production order file name (Default: ondemand.pof)
 -C <zipfile> (UNIX) Install OnDemand client files
 -N Named queries may return no documents
 -R (UNIX) Remove OnDemand data distribution server definition
 -S <dir> (UNIX) Assign or change data distribution staging directory
 -Y <seconds> Rimage image order timeout (Default: 3600)
 -Z <seconds> Rimage production order timeout (Default: 3600)
 -1 <trace_file> Fully qualified trace file name
 -2 <level> Trace level number. The values are additive. (Default: 3)
 1: Errors
 2: Warnings
 4: Info
 8: Flow

Explanation

An incorrect parameter was specified for the command. The valid parameters for the command are given in the message.

User response

Resubmit the command with the correct parameters.

ARS3303I

Current Options for [server]:
 Control and definition file folder ... *folder_name*
 [-n] Codepage for data and indexes..... *codepage*
 [-S] Staging directory..... *directory_name*

Explanation

This message is for your information only.

User response

No action is required.

ARS3304I

[-a] Indexer directory..... *index_directory*
 [-d] Load directory..... *load_directory*

[-l] Log directory..... *log_directory*
[-h] OnDemand library server..... *server*

Explanation

This message is for your information only.

User response

No action is required.

ARS3305I

[-u] OnDemand library server userid..... *userid*
[-p] OnDemand library server password..... *password*
[-x] Media capacity..... *~capacity* bytes
[-j] Network name..... *network*

Explanation

This message is for your information only.

User response

No action is required.

ARS3306I

[-r] Rimage imaging directory..... *imaging_directory*
Rimage staged files directory..... *staged_directory*
Rimage order file directory..... *order_directory*
[-y] Rimage image order file name..... *order_directory*

Explanation

This message is for your information only.

User response

No action is required.

ARS3307I

[-Y] Rimage image order timeout..... *image_timeout* seconds
[-z] Rimage production order file name..... *file_name*
[-Z] Rimage production order timeout..... *production_timeout* seconds

Explanation

This message is for your information only.

User response

No action is required.

ARS3309E

timestamp: 181: Shared log directory UNC name required

Explanation

The name of the log directory was not specified.

User response

Specify the UNC name of the shared log directory and try the command again.

ARS3310E

timestamp: 182: Shared staging directory UNC name required

Explanation

The UNC name of the staging directory was not specified.

User response

Specify the UNC name of the shared load directory and try the command again.

ARS3313E

timestamp: 185: UNABLE TO CREATE PROPERTIES FILE [file_name] [rc]

Explanation

An error occurred while running this program.

User response

If the problem persists, contact your IBM Service Representative.

ARS3314E

timestamp: 186: Rimage Web Service URI required

Explanation

The URI of the Rimage Web Service was not specified.

User response

Specify the URI of the Rimage Web Service and try the command again.

ARS3315E

timestamp: 187: Java binaries directory name required

Explanation

The directory containing the Java binaries is needed and was not specified.

User response

Specify the name of the directory where the Java binaries are located and try the command again.

ARS3317E

timestamp: 189: Call to Java™ command [*java_cmd*] failed with return code [*rc*].

Explanation

An error occurred while running this program.

User response

If the problem persists, contact IBM Software Support.

ARS4010I

Usage: arbdb [options] [table(s)]

Version: *version*

-- The OnDemand Database Configuration Tool --

Defaults to all tables

-d Drop Tables

-e Drop Indexes

-f Ignore DB Failures

-g (DB2/MSSQL) Start the Database
-h (DB2/MSSQL) Stop the Database
-i Import Data
-I <od_inst> OnDemand Instance Name
-k (DB2) Activate the Database
-l (DB2) For Import/Export use IXF Format
(MSSQL) For Import/Export use Native Format
-m (DB2/MSSQL) Maintenance
-o <filename> Output File name
-r Create Configuration Indexes
-s Run Statistics
-t Create Configuration Tables
-u Update Configuration Tables
-v Verbose
-x Export Data
-X (DB2) If -Y or -Z, don't backup Tablespace USERSPACE1
-y <device> (DB2) Backup the Database Offline to the device
(MSSQL) Complete Database backup to the device
-Y <device> (DB2) Backup the Database Tablespace(s) Offline to the device
-z <device> (DB2) Backup the Database Online to the device
(MSSQL) Differential Database backup to the device
-Z <device> (DB2) Backup the Database Tablespace(s) Online to the device

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS4011E

The *database_engine database_name* database action failed due to an unexpected interrupt

Explanation

The ARSDB program failed or was stopped. This message is expected if program was interrupted, such as by pressing Ctrl+C, or if the database canceled the session. Other messages in the Content Manager OnDemand System Log might help determine the cause of external problems, such as database errors. You might need to refer to the documentation for the database manager product that you are using with OnDemand for an explanation of messages and codes provided by the database.

User response

If the command was canceled from the keyboard, no action is necessary. Otherwise, look at previous messages to determine the problem. If necessary, refer to your database documentation. If the problem persists, contact your IBM Service Representative.

ARS4012E

Unable to initialize environment. rc=-1

Explanation

An error occurred while this program was running.

An error occurred at program startup. This message is usually the result of a path or permission problem with a configuration file or an invalid parameter in a configuration file.

User response

Verify that the instance owner has at least read permission for the configuration files (`ars.ini`, `ars.cfg`, `ars.cache`, and `ars.dbfs`). Verify that all parameters used in the configuration files are valid. Verify that the paths to other configuration files in the `ars.ini` file are correct. If the problem persists, contact your IBM Service Representative.

Note: If you are running the `arsdb` configuration utility during initial setup, you receive the following message:

```
ARS4012E
```

In this case, receiving the error message is normal and informational.

Remember: If this instance was created in 8.5 or above for z/OS, then define `ARS_ORIGINAL_CODEPAGE=37` in `ars.cfg`. If this instance was created before 8.5 define `ARS_ORIGINAL_CODEPAGE=nnnn` in `ars.cfg`. After `ARS_ORIGINAL_CODEPAGE` is set it must never change.

ARS4013E

Unable to determine the database engine

Explanation

The Content Manager OnDemand database engine parameter is not specified correctly or there is a permission problem. There are three valid values for the database engine parameter: DB2, ORACLE, and MSSQL. The instance owner must have at least read permission for the database.

User response

Correct the Content Manager OnDemand database configuration and verify that the permissions are correct. Then resubmit the command.

ARS4014E

Unable to load `>dll_name<`

Explanation

The ARSDB program failed when attempting to load the specified dynamic load library. The instance owner needs at least read-execute permission for the dynamic load library.

User response

Verify that the dynamic load library exists and that the file permissions are correct. Then resubmit the command.

ARS4015I

Starting the `database_engine database_name` database instance

Explanation

The ARSDB command successfully started the database. This message is for your information only.

User response

No action is required.

ARS4016E

Unable to start the `database_engine database_name` database instance

Explanation

The ARSDB program failed when attempting to start the specified instance of OnDemand.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the instance could not be started. Correct the problem and then resubmit the command.

ARS4017I

Activating the *database_engine database_name* database

Explanation

The ARSDB command successfully activated the database. This message is for your information only.

User response

No action is required.

ARS4018I

Creating the *database_engine database_name* database

Explanation

The ARSDB command is attempting to create the Content Manager OnDemand database. This message is for your information only.

User response

No action is required.

ARS4019E

Unable to create the *database_engine database_name* database

Explanation

The ARSDB program failed when attempting to create the database.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the database could not be created. Correct the problem and then resubmit the command.

ARS4020E

Unable to configure data source *database_engine*

Explanation

The ARSDB program failed when attempting to configure the database.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the database could not be configured. Correct the problem and then resubmit the command.

ARS4021I

Backing up the *database_engine database_name* database online

Explanation

The ARSDB command is attempting an online back up of the Content Manager OnDemand database. This message is for your information only.

User response

No action is required.

ARS4022I

Backing up the *database_engine database_name* database offline

Explanation

The ARSDB command is attempting an offline back up of the Content Manager OnDemand database. This message is for your information only.

User response

No action is required.

ARS4023E

Unable to connect to *database_engine database_name* database

Explanation

The ARSDB program failed when attempting to connect to the database.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not connect to the database. Correct the problem and then resubmit the command.

ARS4024I

Are you sure you wish to drop the database tables and/or indexes:

Explanation

The ARSDB program issues a prompt before attempting to drop database tables or indexes.

User response

Specify y (yes) to drop the database tables or indexes or n (no) to keep the database tables or indexes.

ARS4025E

Unknown table *table_name*

Explanation

The specified table is not defined to the system.

User response

Verify the name of the table and resubmit the command.

ARS4026I

Creating table *table_name*

Explanation

The ARSDB command is creating a table in the Content Manager OnDemand database. This message is for your information only.

User response

No action is required.

ARS4027E

Unable to create table *table_name*

Explanation

The ARSDB program failed when attempting to create the specified table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not create the table. Correct the problem and then resubmit the command.

ARS4028I

Inserting default values into table *table_name*

Explanation

The ARSDB command is initializing a table with default values. This message is for your information only.

User response

No action is required.

ARS4029E

Unable to insert into table *table_name* the values (*values*)

Explanation

The ARSDB program failed when attempting to insert the specified default values into the specified table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not insert the default values into the table. Correct the problem and then resubmit the command.

ARS4030I

Dropping index *index_name*

Explanation

The ARSDB command is dropping the specified index. This message is for your information only.

User response

No action is required.

ARS4031E

Unable to drop index *index_name*

Explanation

The ARSDB program failed when attempting to drop the specified index.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not drop the index. Correct the problem and then resubmit the command.

ARS4032I

Dropping table *table_name*

Explanation

The ARSDB command is dropping the specified table. This message is for your information only.

User response

No action is required.

ARS4033E

Unable to drop table *table_name*

Explanation

The ARSDB program failed when attempting to drop the specified table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not drop the table. Correct the problem and then resubmit the command.

ARS4034I

Creating index *index_name*

Explanation

The ARSDB command is creating the specified index. This message is for your information only.

User response

No action is required.

ARS4035E

Unable to create index *index_name*

Explanation

The ARSDB program failed when attempting to create the specified index.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not create the index. Correct the problem and then resubmit the command.

ARS4036I

Exporting table *table_name*

Explanation

The ARSDB command is exporting the specified table. This message is for your information only.

User response

No action is required.

ARS4037E

Unable to export table *table_name*

Explanation

The ARSDB program failed when attempting to export the specified table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not export the table. Correct the problem and then resubmit the command.

ARS4038I

Importing table *table_name*

Explanation

The ARSDB command is importing the specified table. This message is for your information only.

User response

No action is required.

ARS4039E

Unable to import table *table_name*

Explanation

The ARSDB program failed when attempting to import the specified table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not import the table. Correct the problem and then resubmit the command.

ARS4040I

Reorganizing table *table_name*

Explanation

The ARSDB command is reorganizing the specified table. This message is for your information only.

User response

No action is required.

ARS4041E

Unable to reorganize table *table_name*

Explanation

The ARSDB program failed when attempting to reorganize the specified table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not reorganize the table. Correct the problem and then resubmit the command.

ARS4042I

Updating runstat statistics for table *table_name*

Explanation

The ARSDB command is updating the statistics for the specified table. This message is for your information only.

User response

No action is required.

ARS4043E

Unable to update runstat statistics on table *table_name*

Explanation

The ARSDB program failed when attempting to update statistics on the specified table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not update the statistics on the table. Correct the problem and then resubmit the command.

ARS4044I

Stopping the *database_engine database_name* instance

Explanation

The ARSDB command is stopping the database. This message is for your information only.

User response

No action is required.

ARS4045E

Unable to commit the *database_engine database_name* database work

Explanation

The ARSDB program failed when attempting to commit the transaction.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not commit the transaction. Correct the problem and then resubmit the command.

ARS4046E

Unable to terminate the *database_engine database_name* database connection

Explanation

The ARSDB program failed when attempting to disconnect from the database.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not disconnect from the database. Correct the problem and then resubmit the command.

ARS4048I

Backing up the *database_engine database_name* tablespace *tablespace_name* at *timestamp*

Explanation

The ARSDB command started backing up the specified OnDemand table space at the indicated time. This message is for your information only.

User response

No action is required.

ARS4049E

Unable to back up *database_engine database_name* tablespace to *tablespace_name*. *rc=returnCode*

Explanation

The ARSDB program failed when attempting to back up the specified table space.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not back up the table space. Correct the problem and then resubmit the command.

ARS4051I

Backing up the *database_engine database_name* database at *timestamp*

Explanation

The ARSDB command started backing up the specified OnDemand database at the indicated time. This message is for your information only.

User response

No action is required.

ARS4052E

Unable to back up *database_engine database_name* database to *directory_name*. *rc=returnCode*

Explanation

The ARSDB program failed when attempting to back up the database.

User response

Resubmit the command with the -v(verbose) option. Use the information from the additional messages to correct the problem. Then resubmit the command.

ARS4053I

The *database_engine database_name* database was deactivated. Please use -k to activate the database

Explanation

The database was successfully deactivated.

User response

Submit the ARSDB program with the -k parameter to activate the database.

ARS4054E

DB Error: *text* -- SQLSTATE=*sqlstate*, SQLCODE=*sqlcode*

Explanation

The database failed. The information in the message is provided by the database.

User response

See the messages and codes publication of the database manager product that you are using with OnDemand for information about database errors and SQL return codes.

ARS4055E

Unable to activate database *database_name*. SQLCODE = *sqlcode*

Explanation

The ARSDB program failed when attempting to activate the database.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command.

ARS4056E

Database activation is not supported under *database_engine*

Explanation

The ARSDB program cannot be used to activate the database.

User response

To activate the database, use an activation function that is provided with the database manager product that you are using with OnDemand.

ARS4057I

Timestamp for back up image is: *timestamp*

Explanation

The ARSDB command completed backing up the database. The back up was marked with the specified timestamp. This message is for your information only.

User response

No action is required.

ARS4058E

Unable to back up database *database_name*. err=*err*

Explanation

The ARSDB program failed when attempting to back up the specified database.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command.

ARS4059E

Database back up is not supported under *database_engine*

Explanation

The ARSDB program cannot be used to back up the database.

User response

To back up the database, use a back up function that is provided with the database manager product that you are using with OnDemand.

ARS4060E

Database clean logs is not supported under *database_engine*

Explanation

The ARSDB program cannot be used to clean the logs for the database.

User response

To clean the logs for the database, use a log function that is provided with the database manager product that you are using with OnDemand.

ARS4062I

Using Locale '*locale*' and Codeset '*codeset*'

Explanation

The ARSDB command is creating the Content Manager OnDemand database with specified locale and code set. This message is for your information only.

User response

No action is required.

ARS4063E

The '*directory_name*' directory does not exist

Explanation

The ARSDB program could not locate the specified directory. The database owner needs read-write-execute permissions for the directory.

User response

Create the directory and set the directory permissions for a database directory. Then resubmit the command.

ARS4064E

The *database_name* database already exists

Explanation

The specified database already exists.

User response

Make sure the database specified is unique and does not already exist, then resubmit the command.

ARS4065E

The database name '*database_name*' is invalid

Explanation

The name specified for the database is not correct or supported by the database. It might be too long or contain invalid characters.

User response

Refer to your database documentation for naming restrictions. Then resubmit the command with a valid database name.

ARS4067E

Unable to create the *database_name* database. *err=err*

Explanation

The ARSDB program failed when attempting to create the database.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command.

ARS4068I

Updating the *database_name* database configuration

Explanation

The ARSDB command is configuring database parameters for the Content Manager OnDemand database. This message is for your information only.

User response

No action is required.

ARS4069E

The new path to the log is not valid

Explanation

The path name for the database log files is not a valid name. The path must be given as an absolute path and the database owner must have read-write-execute permissions on the directory.

User response

Verify the permissions and the path. Then resubmit the command.

ARS4070E

Unable to update the *database_name* database configuration. *SQLCODE = sqlcode*

Explanation

The ARSDB program failed when attempting to update the database configuration.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command.

ARS4071I

Backing up the *database_name* database so that the updates can take effect

Explanation

The ARSDB command is backing up the newly created database to save the updated parameters. This message is for your information only.

User response

No action is required.

ARS4072E

Database creation is not supported under *database_engine*

Explanation

The ARSDB program cannot be used to create the database.

User response

To create the database, use a create function that is provided with the database manager product that you are using with OnDemand.

ARS4073I

Deactivating database *database_name*

Explanation

The ARSDB command is deactivating the Content Manager OnDemand Database in preparation for a back up. This message is for your information only.

User response

No action is required.

ARS4074E

The DB2 instance has not been started

Explanation

The ARSDB program failed because the DB2 instance was not started.

User response

Start the DB2 instance and resubmit the command.

ARS4075W

The *database_name* database was not activated

Explanation

This message is for your information only.

User response

No action is required.

ARS4076E

Unable to deactivate database *database_name*. SQLCODE = *sqlcode*

Explanation

The ARSDB program failed when attempting to deactivate the database.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS4077E

Database deactivate is not supported under *database_engine*

Explanation

The ARSDB program cannot be used to deactivate the database.

User response

To deactivate the database, use a deactivate function that is provided with the database manager product that you are using with OnDemand.

ARS4078I

The *database_instance* instance has already been started

Explanation

The database instance is already started. This message is for your information only.

User response

No action is required.

ARS4079E

Unable to start database *database_name*. SQLCODE = *sqlcode*

Explanation

The ARSDB program failed when attempting to start the database.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS4080E

Database start is not supported under *database_engine*

Explanation

The ARSDB program cannot be used to start the database.

User response

To start the database, use a start function that is provided with the database manager product that you are using with OnDemand.

ARS4081E

Unable to deactivate database *database_name*

Explanation

The ARSDB program failed when attempting to deactivate the database.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS4082E

Unable to stop *database_engine*. SQLCODE = *sqlcode*

Explanation

The ARSDB program failed when attempting to stop the database.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS4083E

Database stop is not supported under *database_engine*

Explanation

The ARSDB program cannot be used to stop the database.

User response

To stop the database, use a stop function that is provided with the database manager product that you are using with OnDemand.

ARS4084E

Unable to export table *table_name*. *err=err*

Explanation

The ARSDB program failed when attempting to export a table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS4086E

Unable to import table *table_name*. *err=err*

Explanation

The ARSDB program failed when attempting to import a table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS4088E

Unable to reorganize table *table_name*. SQLCODE = *sqlcode*

Explanation

The ARSDB program failed when attempting to reorganize a table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS4089E

Reorganization is not supported under *database_engine*

Explanation

The ARSDB program cannot be used to reorganize the database.

User response

To reorganize the database, use a reorganization function that is provided with the database manager product that you are using with OnDemand.

ARS4090E

Unable to do a runstats on table *table_name*. *err=err*

Explanation

The ARSDB program failed when attempting to update the statistics for a table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS4092E

The *database_name* database was deactivated, however there is still a connection to one or more nodes

Explanation

Only one node was deactivated, however, multiple nodes exist.

User response

Verify that all nodes are deactivated before proceeding.

ARS4094E

Unable to connect to database

Explanation

An error occurred while this program was running.

The ARSDB command was unable to connect to the specified OnDemand database. There might be database-related messages in the Content Manager OnDemand System Log.

User response

Verify the name of the database. Check the Content Manager OnDemand System Log for related messages. If the problem persists, contact your IBM Service Representative.

ARS4095E

Filegroup back ups for MSSQL should be done using the Database Maintenance Planner

Explanation

The ARSDB program cannot be used to run filegroup back ups for SQL Server.

User response

Use the Database Maintenance Planner in SQL Server to run filegroup back ups.

ARS4096E

Differential back ups for MSSQL should be done using the Database Maintenance Planner

Explanation

The ARSDB program cannot be used to run differential back ups for SQL Server.

User response

Use the Database Maintenance Planner in SQL Server to run differential back ups.

ARS4097E

CoCreate instance failed

Explanation

An error occurred while this program was running.

The ARSDB command is unable set up the Microsoft COM environment. Microsoft SQL Server might not be installed or might not be installed correctly.

User response

Verify that Microsoft SQL Server is installed and operational. If the problem persists, contact your IBM Service Representative.

ARS4098E

CoInitialize failed

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS4112E

Unable to start *database_name*. HRESULT=*hresult*

Explanation

The database failed. HRESULT is an error code provided by Microsoft SQL Server.

User response

See the messages and codes documentation for the version of Microsoft SQL Server that you are using for information about database errors.

ARS4113W

database_name has already been started

Explanation

The database is already started, so you do not need to specify the start database parameter.

User response

No action is required.

ARS4114E

Unable to stop *database_name*. HRESULT=*hresult*

Explanation

The database failed. HRESULT is an error code provided by Microsoft SQL Server.

User response

See the messages and codes documentation for the version of Microsoft SQL Server that you are using for information about database errors.

ARS4115I

Number of rows exported = *rows_exported*

Explanation

This message is for your information only.

User response

No action is required.

ARS4116I

Number of rows imported = *rows_imported*

Explanation

This message is for your information only.

User response

No action is required.

ARS4118E

action for library *database_name* failed with exception *rc*

Explanation

The database failed.

User response

See the messages and codes publication of the database manager product that you are using with OnDemand for information about database errors.

ARS4119I

Creating links for the following file:

file_name

Do you wish to use DISK(1) or ADSM(2)?

Please specify 1 or 2:

Explanation

The ARSDB program issues a prompt to specify the type of archived log file user exit.

User response

Specify 1 (one) to maintain the log files on disk. Specify 2 (two) to use Tivoli Storage Manager to maintain the log files.

ARS4120E

SET RULES=STD failed

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS4121I

Altering table *table_name*

Explanation

This message is for your information only.

User response

No action is required.

ARS4122E

Unable to alter table *table_name*

Explanation

The ARSDB program failed when attempting to alter the specified table.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to determine why the ARSDB program could not alter the table. Correct the problem and then resubmit the command.

ARS4123I

Table *table_name* has already been updated

Explanation

This message is for your information only.

User response

No action is required.

ARS4124I

Unable to complete OD update - User Id *uid* is also used by a group definition. Please contact IBM support in order to proceed with update.

Explanation

This message is for your information only.

User response

No action is required.

ARS4125I

Failed while processing sql statement *<sql>*

Explanation

This message is for your information only.

User response

No action is required.

ARS4126W

Table already exists *table_name*

Explanation

This message is for your information only.

User response

No action is required.

ARS4127I

Index already exists *index*

Explanation

This message is for your information only.

User response

No action is required.

ARS4128I

Table *table* does not exist

Explanation

This message is for your information only.

User response

No action is required.

ARS4129W

Index does not exist *index*

Explanation

This message is for your information only.

User response

No action is required.

ARS4130I

Found *index* rows in ARSSYS table, only expected 1 row. Contact the IBM Support Center

Explanation

This message is for your information only.

User response

Search the problem reporting database for a fix for the problem. If no fix exists, please contact the IBM Support Center.

ARS4131I

Usage: arsdm [options] [table(s)] Version: version -d Drop the OnDemand system tables -e Drop the OnDemand system indexes -f Ignore DB Failures -F Do not prompt -i Import data to the OnDemand system tables -I <od_inst> OnDemand instance name -m Run Maintenance for the OnDemand system

tables -o <filename> Output file name -O OnDemand Distribution Facility (ODF) -r Create indexes for the OnDemand system tables -s Run statistics on the OnDemand system tables -t Create the OnDemand system tables -u Update the OnDemand system tables -v Verbose -x Export data from the OnDemand system tables

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. For more information about this command, please see the *Administration Guide* for Content Manager OnDemand.

ARS4132I

Usage: arsdm [options] [table(s)] Version: version -c Create the OnDemand database -d Drop the OnDemand system tables -e Drop the OnDemand system indexes -f Ignore DB Failures -F Do not prompt -i Import data to the OnDemand system tables -I <od_inst> OnDemand instance name -o <filename> Output file name -r Create indexes for the OnDemand system tables -t Create the OnDemand system tables -u Update the OnDemand system tables -v Verbose -x Export data from the OnDemand system tables

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. For more information about this command, please see the Content Manager OnDemand administration guide.

ARS4200E

Creation of *system_folder* information failed due to an unexpected interrupt

Explanation

The ARSSYSCR program failed or was canceled. This message is expected if program was interrupted, such as by pressing Ctrl+C.

User response

If the command was canceled from the keyboard, no action is necessary. Otherwise, look at previous messages to determine the problem and resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS4201I

Deleting folder with fid = *fid*

Explanation

This message is for your information only.

User response

No action is required.

ARS4203I

Deleting application group with agid = *agid*

Explanation

This message is for your information only.

User response

No action is required.

ARS4204I

Updating *owner.table_name*, may result in no updates

Explanation

This message is for your information only.

User response

No action is required.

ARS4206I

Updating *owner.table_name*

Explanation

This message is for your information only.

User response

No action is required.

ARS4207I

Adding to *owner.table_name* with Storage Set Id = *sid*

Explanation

This message is for your information only.

User response

No action is required.

ARS4208I

Adding to *owner.table_name*

Explanation

This message is for your information only.

User response

No action is required.

ARS4209I

Creation of *system_folder* information was successful

Explanation

This message is for your information only.

User response

No action is required.

ARS4211E

Failed while creating the Content Manager OnDemand *system_folder*

Explanation

The ARSSYSCR program failed when attempting to create the system definitions.

User response

See the other messages that were generated by the ARSSYSCR program to determine the cause of the problem. Resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS4212I

Usage: arssyscr [-I <od_inst>] [-l | -m | -p]

Version: *version*

-a System Load

-h <od_inst> OnDemand instance name (same as -I)

-I <od_inst> OnDemand instance name (same as -h)

-l System Log

-m System Migration

-o <filename> Output file name

-p OnDemand Publications

Explanation

An error occurred during program startup.

User response

This error can occur when a configuration file has an invalid file path or when a user has insufficient permission to access this file. This error can also result from an invalid parameter in the configuration file. Verify that all parameters used in the configuration files are valid. Verify that the paths to other configuration files in the ars.ini file are correct. If the problem persists, contact your IBM Service Representative.

ARS4213I

The definitions being defined will make use of the new database style date/time field(s)

Explanation

This message is for your information only.

User response

No action is required.

ARS4300I

Usage: arslod [options] [load_file]

Version: *version*

-a <appl> The application within the application group

Defaults to filename conventions

-A <field> MVS™ filename component to use for OnDemand application

-b <field> Field identifier for filename index parameter

-B <filename_format> Format of input filename for parsing

WRI WRITER

MVS MVS

JOB JOBNAME

DAT DATASET

FOR FORMS

YY YYDDD

HH HHMMM

AG Application Group

APP Application

IDX Index (Note: Can prepend to one field above to identify for load indexing)

IGN Ignore

.EXT Extension

Example: For files in the default format

MVS.JOBNAME.DATASET.FORMS .YYDDD.HHMMM.ARD
format could be written as
MVS.JOB.DAT.FOR.YY.HH.EXT
or format could be written as
MVS.JOB.IDXDAT.FOR.YY.HH.EXT
to associate the DAT part of the filename as a load index

- c <idx_dir> The directory to run the indexer
Defaults to current directory
- C <class> (OD390) jes class to monitor
- d <dl_dir> The download directory
Can be specified more than once
- E Execute the arsuupdt user exit program
- f If load fails, unload the data
- F <form> (OD390) jes form to monitor
- g <appl_grp> The application group
Defaults to filename conventions
- G <field> MVS filename component to use for OnDemand application group
(OD390) WRITER.MVS.JOBNAME.DATASET .FORMS
– or –
MVS.JOBNAME.DATASET.FORMS
(Otherwise) MVS.JOBNAME.DATASET.FORMS
Defaults to FORMS
- h <od_inst> OnDemand library server or instance name (same as -I)
- i Run the Indexer Only
- I <od_inst> OnDemand library server or instance name (same as -h)
- j <parm_file> Additional indexing parameters
- n Do not remove files
- p <passwd> Password
- s <input>
(OD390) JCL ddname to use as input (i.e., INPUT)
- t <seconds> Time interval to sleep
Defaults to *seconds* seconds
- u <userid> Userid
- U <file> File to find default userid/passwd
Defaults to *file_name*
- v Verbose
- W <writer> (OD390) jes writer to monitor
- Z <user_def> User-defined string passed to load user exit
- 1 <trace_file> Fully qualified trace file name
- 2 <level> Trace level number, The values are additive. (Default: 3)

1: Errors
2: Warnings
4: Info
8: Flow

Explanation

An incorrect parameter was specified for the `arsload` command. The valid parameters are given in the message and are explained in the OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS4302I

timestamp -- Indexing started, *bytes* bytes to process

Explanation

This message is for your information only.

User response

No action is required.

ARS4303I

--INDEXING ONLY--

Explanation

This message is for your information only.

User response

No action is required.

ARS4304W

---->Remaining indexer messages are being ignored<----

Explanation

This message is for your information only.

User response

No action is required.

ARS4305E

Generic Indexer requires the data to have already been indexed. Index the data or verify your input file and resubmit the job

Explanation

The ARSLOAD program attempted to use the Content Manager OnDemand generic indexer. However, an index file does not exist or the indexing records in the index file are not valid for the generic indexer.

User response

Verify that the indexing records in the index file are valid for the generic indexer. Then resubmit the command. See the IBM Content Manager OnDemand *Indexing Reference* for more information about the generic indexer.

ARS4306E

Unknown Indexer >*indexer*<

Explanation

The indexer that is specified for the application is not a valid indexing program.

User response

Verify that the data is of the format expected by the defined indexer or specify a different indexer for the application in the Content Manager OnDemand administrative client. Then resubmit the command.

ARS4307E

Output/Indexer file was not created

Explanation

The indexing program did not create the output file or the index file.

User response

Verify and correct the indexing parameters and resubmit the command.

ARS4308I

timestamp Indexing completed

Explanation

This message is for your information only.

User response

No action is required.

ARS4309E

timestamp Indexing failed

Explanation

The indexing program failed.

User response

Verify and correct the indexing parameters and then resubmit the command.

ARS4310I

timestamp Loading completed

Explanation

This message is for your information only.

User response

No action is required.

ARS4311E

timestamp Loading failed

Explanation

The ARSLOAD program failed.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command.

ARS4312I

timestamp -- Loading started, *bytes* bytes to process

Explanation

This message is for your information only.

User response

No action is required.

ARS4313E

The postprocessor command `>command<` failed on the DB file `>db_file_name<` for the file `>file_name<`

Explanation

The ARSLOAD program failed when attempting to run the specified postprocessor command.

User response

Verify the full path name of the command. Verify that the command runs successfully outside of the Content Manager OnDemand environment. Then resubmit the command with the `-v` (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command.

ARS4314E

File `>file_name<` cannot be processed because the Application Group cannot be determined

Explanation

The ARSLOAD program failed because the name of the application group to load was not specified or could not be derived from the input file name.

User response

Resubmit the command with the name of the application group or verify that the name of the input file contains the name of the application group and then resubmit the command. See the *Administration Guide* for more information about how the ARSLOAD program can derive the name of the application group from the input file name.

ARS4315I

Processing file `>file_name<`

Explanation

This message is for your information only.

User response

No action is required.

ARS4316E

File `>file_name<` cannot be found for processing

Explanation

The ARSLOAD program could not find the specified file. If you are using the generic indexer, the paths to the data files in the index might be incorrect. Unlike other indexers, the generic indexer requires the use of an absolute path to the data files referenced in the index.

User response

Verify that the file exists and that the user has at least read permission for the file and directory. Verify that the path is given as an absolute, rather than a relative, path. Then resubmit the command.

ARS4317I

Processing successful for file `>file_name<`

Explanation

This message is for your information only.

User response

No action is required.

ARS4318E

Processing failed for file >*file_name*<

Explanation

The ARSLOAD program failed when processing the specified file.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command.

ARS4319W

Unloading of data was NOT performed

Explanation

The ARSLOAD program failed. However, the ARSLOAD program did not unload the data.

User response

Either unload the data by submitting the ARSADMIN program with the UNLOAD function or use the unload parameter when you submit the ARSLOAD program. On IBM i systems, use the Remove Report (RMVRPTOND) command to unload the data.

ARS4320I

timestamp -- Unloading started

Explanation

This message is for your information only.

User response

No action is required.

ARS4321I

timestamp -- Unloading of data was successful

Explanation

This message is for your information only.

User response

No action is required.

ARS4322E

timestamp -- Unloading of data failed

Explanation

The ARSLOAD program failed when attempting to unload data.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command.

ARS4323E

Unable to log load information

Explanation

The ARSLOAD program failed when attempting to obtain the log load information.

User response

Resubmit the command with the -v (verbose) parameter. Use the information from the additional messages to correct the problem. Then resubmit the command.

ARS4324E

File >file_name< renamed to >file_name.Failed<. Correct problems and resubmit file.

Explanation

The ARSLOAD program failed and renamed the specified file.

User response

See the other messages that the ARSLOAD program generated. Correct any problems and then resubmit the command.

ARS4325E

The -n option should not be used when running this command as a daemon. This will cause the files to be recursively loaded.

Explanation

An attempt was made to start the ARSLOAD program as a daemon, however, the -n parameter was specified. The -n parameter is not valid when running the ARSLOAD program as a daemon. See the *Administration Guide* for a complete list of ARSLOAD parameters.

User response

Resubmit the command without the -n parameter.

ARS4326E

Could not connect to server to establish log id

Explanation

The ARSLOAD program failed when attempting to obtain the log ID.

User response

Verify that the server on which you want to load the data is running. Then resubmit the command.

ARS4327E

Processing has stopped. The remaining files will NOT be processed.

Explanation

The ARSLOAD program failed while loading files. Some files might not have been loaded, and will need to be submitted again. If the daemon was used to process files, failed files will have `.failed` appended to the file name.

User response

See the messages that were generated by the ARSLOAD program. Resubmit the ARSLOAD program to load the files that were not loaded.

ARS4328E

ARSSAPIR failed: rc = rc sapi_rc(sapi_rsn)

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS4329E

SVC 99 failed for file *file_name*: S99ERROR = *error*, S99INFO = *info*

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS4330E

Field index format may be specified incorrectly on the command line. Check usage information.

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS4331E

Unable to add another index field to the data. Data maybe fully composed or otherwise already indexed.

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS4332E

The maximum number of fields are already in use for this data type.

Explanation

An error occurred while this program was running.

User response

If the problem persists, contact your IBM Service Representative.

ARS4333I

ARSLoad is running in direct mode. (ARSMVS_ARADMIN_USETCPIP=0).

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4335I

Server Version <%1\$s> Operating System <%2\$s> <%3\$s> Database <%4\$s> <%5\$s>

Explanation

This message is for your information only.

User response

No action is required.

ARS4336I

The program instance *instance* is ready

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4337I

The program instance *instance* is terminating

Explanation

The command is ending. This message is for informational purposes only.

User response

No action is required.

ARS4338E

Filename indexing parameter formats cannot be mixed.

Explanation

An error occurred while running this program.

User response

If the problem persists, contact your IBM Service Representative.

ARS4339I

Application Group *appl_grp_name*

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4340I

Application <appl_name>

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4341I

Storage Set *sset_name*

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4342I

Storage Node *snode_name*

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4343I

Postprocess Command *snode_name*

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4344I

Postprocess command completed successfully

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4345E

Input file cannot contain mixed document indexing nodes.

Explanation

An error occurred while running this program.

User response

The XML indexer requires that all document indexing nodes within a single input file be of the same type. The two types are `<oddateref>` and `<odxmldata>`.

ARS4346I

Adding file *file_name* to resource

Explanation

This message is for your information only.

User response

No action is required.

ARS4347I

Encryption >*encryption_type*<

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4348I

Load Statistics: Index In >*index_input_size*< Load In >*load_input_size*< Load Out >*load_output_size*<
Rows >*rows*< Pages >*total_pages*< Time >*time*< Resource In >*res_input_size*< Resource Out
>*res_output_size*<

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4349I

Load Statistics: Index In >*index_input_size*< Load In >*load_input_size*< Load Out >*load_output_size*<
Rows >*rows*< Pages >*total_pages*< Time >*time*<

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4400I

Usage: arsxafp [-c] [-l] [-w] [-h] [-o] [-r] [-f] [-t] [-x] [-y] inputfile

Version: *version*

-c <chars> Characters per inch (horizontal) (default: 18)

-l <lines> Lines per inch (vertical) (default: 12)

-w <inches> Page width (default: 8.5)

-h <inches> Page height (default: 11.0)

-o <rot> Page orientation (0 | 90 | 180 | 270)

-r <file> Resource group file

-f <dir> Font directory

-t <file> AFP viewer trace file

-x Suppress rules/lines

-y Character space reset

-1 <trace_file> Trace file

-2 <trace_level> Trace level

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS4401E

Error opening input file - *file_name*

Explanation

The ARSXAFP program failed when attempting to open the specified input file. The user must have at least read permissions on the file.

User response

Verify that the file exists and verify the name of the file. Verify the file permissions. Then resubmit the command.

ARS4402I

Usage: arsvview -n [-d] [-i] [-j] [-p] [-m] [-f] [-l] [-g] [-c] [-r]

Version: *version*

- i <file> Input file
- j <file> Output file (default: standard output)
- p <pages> Number of pages (default: all)
- m <prmode> Mode (default: none)
- f <record format> format (default: stream)
- l <record length> length (default: 133)
- d <record delimiter> delimiter (default: 0A)
- g <trc present> (default: false)
- c <code page> code page (default: 850)
- r <cc type> cc type (default:ansi)

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. For more information about this command, please see the Content Manager OnDemand Administration Guide.

ARS4403I

Usage: arsxline [options]

Version: *version*

- a <cctype> carriage control (default A - ANSI, M - Machine, N - None)
- c <cp> input data code page (default: 500)
- d <rec_delim> record delimiter (default: 0A)
- f <rec_fmt> record format (default F - Fixed, V - Variable, S - Stream)
- F <font_name> font name (default: Courier)
- g <pdf_image_file> pdf image file
- G <pdf_image_position> pdf image file position (default: 0,0 left,top)
- h <page_neight> page height (default: 792)
- i <inp_file> input file
- k <overstrike_mode> overstrike mode (default M - Merge, S - Separate, F - Full)
- K <pdf_image_mode> pdf image mode (default A - All, F - First, L - Last)
- l <rec_len> fixed record length (default: 133)
- m <margin> margin (default: 36,36,36,36 top,bottom,left,right)

-n <font_size> font size (default: 12)
-o <out_file> output file
-O <orientation> (P - Portrait, L - Landscape)
-p <prmode> prmode (default N - None, 1 - SOSI1, 2 - SOSI2, 3 - SOSI3)
-P <parm_file> parameter file
-q <lines_per_page> lines per page (default: 0)
-Q <line_per_print_page> - lines per print page (default: 0)
-s <line_spacing_factor> line spacing factor (default: 1.6)
-t <trc> trc (default 0 - No, 1 - Yes)
-w <page_width> page width (default: 612)
-x <transform_type> transform type (default U - UTF8, P - PDF)
-1 <trace_file> Trace file
-2 <trace_level> Trace level

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. For more information about this command, see the Content Manager OnDemand Administration Guide.

ARS4500I

Usage: arsddate [-a|-i|-z] [-A|-I|-Z] [-C] [-d] [-D] [-f] [-F] [-g] [-h] [-m] [-n] [-s] [-t] [-y] (value | number)

Version: *version*

-a Input date type (default)
-A Output date type (defaults to input type)
-C Convert to/from OD internal type and database type
-d <days> Days to add
-D Database type (default is OnDemand internal type)
-f <input_fmt> Input format string
-F <output_fmt> Output format string
-g Get today's date
-h <hours> Hours to add
-i Input date/time type (without timezone)
-I Output date/time type (without timezone)
-m <months> Months to add
-n <mins> Minutes to add
-s <secs> Seconds to add
-t time format
-y <years> Years to add
-z Input date/time (with timezone)
-Z Output date/time (with timezone)
-1 <trace_file> Trace file
-2 <trace_level> Trace level

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS4501I

Today: *timestamp*

Explanation

This message is for your information only.

User response

No action is required.

ARS4502E

Failed

Explanation

The ARSDATE program could not perform the requested date conversion. Valid date formats are listed in the *Administration Guide*.

User response

Verify that the date value or the date and time value is correct. Then resubmit the command.

ARS4601I

Usage: arsdoc [get | query | add | update | delete | print]

Version: *version*

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS4602E

Unknown command >*command*<

Explanation

Unable to run the specified command. The user must have at least read-execute permission for the file.

User response

Verify that the command exists and that the file permissions are correct. Then resubmit the command.

ARS4700I

OnDemand Command Prompt

Explanation

This message is for your information only.

User response

No action is required.

ARS4703E

Unable to run command `>command<`, `errno=errno`

Explanation

The Content Manager OnDemand server was unable to run the specified command. The `errno` value, which might provide additional information, resides in `/usr/include/sys/errno.h` on UNIX systems, `/usr/include/errno.h` on z/OS systems, and `/QIBM/include/errno.h` on IBM i systems. The user must have at least read-execute permission for the command.

User response

Verify that the command exists and verify the file permissions, then resubmit the command. See the `errno.h` file for more information.

ARS4800I

Received index data `>text<`

Explanation

This message is for your information only.

User response

No action is required.

ARS4801I

Returned index data `>text<`

Explanation

This message is for your information only.

User response

No action is required.

ARS4802I

All index data has been returned.

Explanation

This message is for your information only.

User response

No action is required.

ARS4803E

The length of the database value for field '`name`' is `value_len`. The maximum allowable string length is `max_len` for a database field.

Explanation

The string length of the database value exceeds the maximum allowable string length for a database field.

User response

Use a different database value or change the value so that it does not exceed the maximum allowable length.

ARS4804I

Return Code = '*rc*', Number of bytes received = '*num_bytes*', hex value = '*hex_value*'

Explanation

This message is for your information only.

User response

No action is required.

ARS4805I

Number of bytes received = '*num_bytes*', hex value = '*hex_value*'

Explanation

This message is for your information only.

User response

No action is required.

ARS4806I

Initializing arscmnst. Version: *version*

Explanation

This message is for your information only.

User response

No action is required.

ARS4807E

Unable to convert UTF-8 character string *char_string* to a UTF-16 character string

Explanation

The command failed when attempting to convert a UTF-8 character string.

User response

Contact your IBM Service Representative.

ARS4808E

Unable to convert UTF-16 character string *char_string* to a UTF-8 character string

Explanation

The command failed when attempting to convert a UTF-16 character string.

User response

Contact your IBM Service Representative.

ARS4809I

Server information for server '*server*' ... SERVER VERSION: *version* OPERATING SYSTEM: *os* OPERATING SYSTEM VERSION: *os_version* DATABASE: *db* DATABASE VERSION: *db_version* STORAGE MANAGER: *sm* STORAGE MANAGER VERSION: *sm_version*

Explanation

This message is for your information only.

User response

No action is required.

ARS4900I

Usage: arspdoci [parmdd filename]

Version: *version*

Coordinates: Metrics (units X and Y are specified in)

Inches | Centimeters | Millimeters

Fontlib: Font directory

Inputdd: Input filename

Msgdd: Message filename - default is stdout

Outputdd: Output filename pattern

TraceDD: Trace file - default is stderr

Tracelevel: PDF=15

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS4901I

parameter

Explanation

This message is for your information only.

User response

No action is required.

ARS4902I

Number of input pages = *pages*

Explanation

This message is for your information only.

User response

No action is required.

ARS4903E

keyword keyword contains non-numeric identifier

Explanation

The identifier for the specified keyword must be a number from 1 to 16 (TRIGGER parameter) or 1 to 32 (INDEX or FIELD parameter).

User response

Correct the identifier and resubmit the command.

ARS4904E

Error allocating *bytes* bytes memory

Explanation

The IBM Content Manager OnDemand PDF Indexer was unable to allocate the requested amount of memory.

User response

Decrease the load on the system or increase the amount of memory available to the IBM Content Manager OnDemand PDF Indexer and resubmit the command.

ARS4905E

parameter parameter syntax incorrect

Explanation

The syntax for the TRIGGER, FIELD, or INDEX parameter is not correct.

User response

Correct the parameter and resubmit the command.

ARS4906E

Unknown parameter: *parameter*

Explanation

The specified string is not a valid IBM Content Manager OnDemand PDF Indexer parameter.

User response

Correct the parameter and resubmit the command.

ARS4907E

Incorrect index file definition

Explanation

The file specified for the INDEXDD file definition parameter cannot be created. The user must have read-write permissions for the directory. If the file does not exist, it will be created. If it does exist, it will be replaced.

User response

Verify that the file name and path in the parameter file are correct. Verify that the directory exists and that the permissions are correct. Then resubmit the command.

ARS4908E

Incorrect input file definition

Explanation

The file specified for the INPUTDD file definition parameter cannot be read. The user must have read permission for the directory and the file.

User response

Verify that the file name and path in the parameter file are correct. Verify that the directory and the file exist and that the permissions are correct. Then resubmit the command.

ARS4909E

Incorrect output file definition

Explanation

The file specified for the OUTPUTDD file definition parameter cannot be created. The user must have read-write permissions for the directory. If the file does not exist, it will be created. If it does exist, it will be replaced.

User response

Verify that the file name and path in the parameter file are correct. Verify that the directory exists and that the permissions are correct. Then resubmit the command.

ARS4910E

Incomplete indexing parameters supplied

Explanation

The current set of indexing parameters does not permit the IBM Content Manager OnDemand PDF Indexer to create index data. There might be a syntax error in the TRIGGER parameter. The parameter file must exist, and it must contain at least one set of TRIGGER, FIELD, and INDEX parameters. The IBM Content Manager OnDemand *Indexing Reference* provides a sample parameter file.

User response

Correct the parameters and resubmit the command.

ARS4911E

Error opening INDEX file *file_name*

Explanation

The specified file does not exist or the file permissions do not allow the file to be opened.

User response

Verify that the file exists and verify that the file permissions allow the file to be opened. Then resubmit the command.

ARS4912E

Error opening Input file *file_name*

Explanation

The specified file does not exist or the file permissions do not allow the file to be opened.

User response

Verify that the file exists and verify that the file permissions allow the file to be opened. Then resubmit the command.

ARS4913E

Error opening Parameter file *file_name*

Explanation

The specified file does not exist or the file permissions do not allow the file to be opened.

User response

Verify that the file exists and verify that the file permissions allow the file to be opened. Then resubmit the command.

ARS4914E

Trigger(s) not found by page *page*

Explanation

The IBM Content Manager OnDemand PDF Indexer did not find a trigger by the specified page number. The INDEXSTARTBY parameter determines the page number by which the IBM Content Manager OnDemand PDF Indexer must find a trigger and begin indexing.

User response

Verify the page number that is specified in the INDEXSTARTBY parameter. If the page number is correct, verify the TRIGGER parameters. Then resubmit the command.

ARS4915E

Field(s) not found by page *page*

Explanation

The IBM Content Manager OnDemand PDF Indexer did not find a field by the specified page number. The INDEXSTARTBY parameter determines the page number by which the IBM Content Manager OnDemand PDF Indexer must find a trigger and begin indexing for a field.

User response

Verify the page number that is specified in the INDEXSTARTBY parameter. If the page number is correct, verify the FIELD parameters. Then resubmit the command.

ARS4916E

Failed Adobe Toolkit Initialization rc=*returnCodeError* string : *string*

Explanation

The Adobe toolkit returned an error. There might be a problem with the permissions on the directories specified for the FONTLIB and TEMPDIR parameters, the directories might be incorrect, or the disk might not have enough space. The user must have read-write permissions for the directories. Images usually require more space than text.

User response

Verify the directories that are specified for the FONTLIB and TEMPDIR parameters. Verify the permissions for the directories named in these parameters. Verify that the FONTLIB directories provide access to the fonts that are required by the IBM Content Manager OnDemand PDF Indexer. Verify that the TEMPDIR directory contains sufficient free space to process the input file. If the problem persists, contact your IBM Service Representative.

ARS4917E

Create of new Document Segment failed

Explanation

The Adobe toolkit returned an error when trying to create a new document segment. There might be a problem with the permissions on the directories specified for the FONTLIB and TEMPDIR parameters, the directories might be incorrect, or the disk might not have enough space. The user must have read-write permissions for the directories. Images usually require more space than text.

User response

Verify the directories that are specified for the FONTLIB and TEMPDIR parameters and the files and directories that are named in the INPUTDD and OUTPUTDD parameters. Verify the permissions for the files and directories named in these parameters. Verify that the FONTLIB directories provide access to the fonts that are required by the IBM Content Manager OnDemand PDF Indexer. Verify that the TEMPDIR and

OUTPUTDD directories contain sufficient free space to process the input file. If the problem persists, contact your IBM Service Representative.

ARS4918E

Page extraction failed!

Explanation

The Adobe toolkit returned an error when trying to extract pages for a new segment. The original PDF might be damaged. There might be a problem with the permissions on the directories specified for the FONTLIB and TEMPDIR parameters, the directories might be incorrect, or the disk might not have enough space. The user must have read-write permissions for the directories. Images usually require more space than text.

User response

Verify that the PDF is not damaged by viewing in Adobe Acrobat. Verify the directories that are specified in the FONTLIB and TEMPDIR parameters. Verify the permissions for the directories named in these parameters. Verify that the FONTLIB directories provide access to the fonts that are required by the IBM Content Manager OnDemand PDF Indexer. Verify that the TEMPDIR directory contains sufficient free space to process the input file. If the problem persists, contact your IBM Service Representative.

ARS4919E

Word search or extraction error

Explanation

The Adobe toolkit returned an error while searching the PDF document. The original PDF might be damaged. There might be a problem with the permissions on the directories specified in the FONTLIB and TEMPDIR parameters, the directories might be incorrect, or the disk might not have enough space. The user must have read-write permissions for the directories. Images usually require more space than text.

User response

Verify the directories that are specified in the FONTLIB and TEMPDIR parameters. Verify the directory permissions. Verify that the directories that are named in the FONTLIB parameter provide access to the fonts that are required by the IBM Content Manager OnDemand PDF Indexer. Verify that the directory named in the TEMPDIR parameter contains sufficient free space to process the input file. If the problem persists, contact your IBM Service Representative.

ARS4920E

Error during Distil rc =rc Error string :*string* Check the Distiller messages

Explanation

Acrobat Distiller returned an error while trying to distill the input file.

User response

Use the Distiller output messages to determine the cause and resolution of the error. After correcting the error, resubmit the command.

ARS4921E

The Input file contains an unsupported data type

Explanation

The input file does not contain PostScript or PDF data.

User response

Verify that the correct file is named in the INPUTDD parameter. Verify that the file named in the INPUTDD parameter contains PostScript or PDF data. Then resubmit the command.

ARS4922I

ARSPDOCI *version* completed code *rc*

Explanation

The IBM Content Manager OnDemand PDF Indexer completed processing the input data with the completion code listed.

User response

No action is required.

ARS4923E

action version error code *string*

Explanation

The Adobe toolkit returned an error. The message displays the toolkit function being used when the error occurred, the error code, and the error message

User response

See the user response for message 4924.

ARS4924E

Error running *action* API rc =*rc* Error string: *string*

Explanation

The Adobe toolkit returned an error. The *rc* (reason code) and *string* are provided by the Adobe toolkit.

User response

Verify the directories that are specified in the FONTLIB and TEMPDIR parameters. Verify the permissions for the directories named in these parameters. Verify that the FONTLIB directories provide access to the fonts that are required by the IBM Content Manager OnDemand PDF Indexer. Verify that the TEMPDIR directory contains sufficient free space to process the input file. If the problem persists, contact your IBM Service Representative.

ARS4925I

ARS4925 Usage: arspdump -f filename [-F font_dir] [-h] [-o output file]
[-p page number] [-t temp dir]
Version: *version*
-f: PDF file name
-F: Font directory
-h: This message
-o: Output file (default is stdout)
-p: Specifies the page number (default is all pages)
-t: Temp directory

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. For more information about this command, see the IBM Content Manager OnDemand *Indexing Reference*.

ARS4926I

– Page *page* –

Explanation

This message is for your information only.

User response

No action is required.

ARS4927I

– Rotated 90 degrees –

Explanation

This message is for your information only.

User response

No action is required.

ARS4928I

----- Rotated 180 degrees -----

Explanation

This message is for your information only.

User response

No action is required.

ARS4929I

– Rotated 270 degrees –

Explanation

This message is for your information only.

User response

No action is required.

ARS4930I

WordFinder version: *version*

Explanation

This message is for your information only.

User response

No action is required.

ARS4931I

Number of Pages = *page*

Explanation

This message is for your information only.

User response

No action is required.

ARS4936E

The resource extraction failed.

Explanation

The Adobe toolkit returned an error.

User response

See response for message 4924.

ARS4937E

Incorrect resource file definition

Explanation

The file specified for the RESOBJDD file definition parameter is not a valid file name.

User response

Correct the file name specified in the file definition parameter and resubmit the command.

ARS4938E

Error opening RESOURCE file *file_name* error code *error_code*

Explanation

The specified file does not exist, or the file permissions do not allow the file to be opened.

User response

Verify that the file exists, and that the file's permissions allow it to be opened. Then resubmit the command.

ARS4939E

Copy of file *file_name* to *file_name* was unsuccessful.

Explanation

An attempt to copy the input file to the temporary directory failed.

User response

Verify that the file exists and verify that the file permissions allow the file to be copied. Verify the space in the temporary directory.

ARS4940E

Index not found by page *page number*

Explanation

The IBM Content Manager OnDemand PDF Indexer did not find an index by the specified page number. The INDEXSTARTBY parameter determines the page number by which the IBM Content Manager OnDemand PDF Indexer must find an index.

User response

Verify the page number that is specified on the INDEXSTARTBY parameter. If the page number is correct, verify that the document contains Metadata indexes and resubmit the command.

ARS4941I

The Content Manager OnDemand PDF feature has not been installed. Please ensure that the feature has been purchased and properly installed.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS4942E

TRIGGER1 must be GROUP type.

Explanation

TRIGGER1 must be TYPE=GROUP, which is the default. TYPE=FLOAT is not valid for TRIGGER1.

User response

Verify the TRIGGER1 parameter. Then resubmit the command.

ARS4943E

At least one index must contain fields which are not based on a floating trigger.

Explanation

If the index contains multiple fields, none of the fields can be based on floating triggers.

User response

Verify the INDEX parameters. Then resubmit the command.

ARS4944E

Error in field *field*. A field based on a floating trigger must contain a default value.

Explanation

A field which is based on a trigger of TYPE=FLOAT must contain a default value.

User response

Verify the FIELD parameters. Then resubmit the command.

ARS4945E

Error in index *index*. Indexes which contain a field based on a floating trigger cannot be combined with other fields in the same index.

Explanation

The index must contain only the single field.

User response

Verify the INDEX parameters. Then resubmit the command.

ARS4946E

Referenced page *page* is outside the range of pages in the document.

Explanation

FIELD parameters can contain a page offset from the current page. The page referenced by a FIELD parameter is outside of the range of pages in the document.

User response

Verify the FIELD parameters. Then resubmit the command.

ARS4947E

The number of Page Piece indexes in the PDF document is greater than the supported maximum of *maximum*

Explanation

The Page Piece Dictionary in the input file contains more indexes than are supported or are specified on the INDEXMODE parameter.

User response

The default number of indexes supported with the Page Piece Dictionary is 32. If the document contains more than 32 indexes, specify the number of indexes on the INDEXMODE parameter. The PDF Indexer can support 128 indexes.

ARS4948E

The regular expression buffer size was exceeded.

Explanation

When using a regular expression, the buffer size is limited to 2000 characters, including the spaces between words. The number of characters inside the bounding box for the trigger exceeds 2000 characters.

User response

Make the bounding box size for the TRIGGER parameter smaller. Then resubmit the command.

ARS4949E

A logic error occurred in the ArspSearchPageRegex function.

Explanation

A logic error occurred when a regular expression was used to search for a trigger.

User response

Verify that the PDF file is correct. You can repair minor syntax errors in the PDF file by adding the REMOVERES parameter. If the problem persists, contact your IBM service representative.

ARS4950E

TRIGGER *trigger number* regular expression is not correct.

Explanation

The expression is not correct.

User response

Correct the regular expression and resubmit the command.

ARS4951E

A mask and a regular expression can not both be specified for Field *field*.

Explanation

A mask and a regular expression can not both be specified on a field parameter at the same time.

User response

Correct the field parameter and resubmit the command.

ARS5001I

program accepts no parameters

Explanation

The specified program does not expect any parameters to be passed on the JCL PARM parameter.

User response

Remove the parameters and rerun the program.

ARS5002I

The path to *program* could not be determined

Explanation

An attempt was made to run the specified program, but the path to the program could not be determined.

User response

Search the problem reporting database for a fix for the problem. If no fix exists, contact your IBM Service Representative.

ARS5004I

fldata() failed for *file_name* (RC:int_rc (X'hex_rc))

Explanation

An error occurred while OnDemand was attempting to determine the file information for the file.

User response

Search the problem reporting database for a fix for the problem. If no fix exists, contact your IBM Service Representative.

ARS5005I

Syntax error - keyword delimiter not found

Explanation

A keyword delimiter was not provided.

User response

Correct the error and resubmit the command.

ARS5006I

Unrecognized keyword: *keyword*

Explanation

A keyword was found that was not valid.

User response

Verify the spelling of the keyword, and that it is valid for the utility. Then resubmit the command.

ARS5007I

Keyword operand not supplied

Explanation

The keyword requires an operand, but one was not provided.

User response

Supply the missing operand and resubmit the command.

ARS5008I

Operand rightside delimiter not found

Explanation

The rightside delimiter for a keyword operand was not found. For example, KEYWORD=(a , b was entered instead of KEYWORD=(a , b).

User response

Supply the missing delimiter and resubmit the command.

ARS5009I

Operand leftside delimiter not found

Explanation

The leftside delimiter for a keyword operand was not found. For example, KEYWORD=a , b) was entered instead of KEYWORD=(a , b).

User response

Supply the missing delimiter and resubmit the command.

ARS5010I

Invalid operand length

Explanation

The operand for a keyword was too long for the keyword.

User response

Shorten the operand and resubmit the command.

ARS5011I

True/False operand expected

Explanation

A true (true, yes, or 1) or false (false, no, or 0) was expected as the operand of the keyword.

User response

Correct the operand and resubmit the command.

ARS5012I

Operand does not consist of all decimal digits

Explanation

The operand must be an integer.

User response

Correct the operand and resubmit the command.

ARS5013I

Control statements processing completed - RC=*int_rc* (X'*hex_rc*)

Explanation

Parameter file processing completed. The maximum return code is displayed.

User response

No action is required.

ARS5014I

Unable to initialize environment for *instance*. RC=*rc*

Explanation

The environment could not be initialized for the specified instance.

User response

Verify that the instance name is correct and corresponds to an instance in the *ars.ini* file. Then resubmit the command.

ARS5015I

ODINSTANCE must be specified

Explanation

The ODINSTANCE keyword is required as control statement for ARSEXPIR.

User response

Specify the ODINSTANCE keyword and resubmit the command.

ARS5016I

Storage sets *sset1* and *sset2* contain the same storage node *nodename*

Explanation

The same node name appears in two storage sets. ARSEXPIR cannot determine which node ID to use.

User response

Remove the duplicate node from one of the storage sets.

ARS5017I

Invalid message id *msgid*

Explanation

An attempt was made to issue a message for which no message template exists.

User response

Search the problem reporting database for a fix for the problem. If no fix exists, contact your IBM Service Representative.

ARS5018I

Error occurred processing ARSMVSSR. RC = *rc1* (*rc2-rsn*)

Explanation

The ARSMVSSR function was called to extract the system management facilities (SMF) records, however it encountered a problem. *rc1* indicates the type of error:

Value of <i>rc1</i>	Description
1	ATTACH failed
2	SORT failed
3	BPX1OPN failed
4	BPX1WRT failed

rc2 and *rsn* contain error related return and reason codes.

User response

Search the problem reporting database for a fix for the problem. If no fix exists, contact your IBM Service Representative.

ARS5019I

Arsadm returned invalid node on line *linenum*. Text=*text*

Explanation

The ARSADM program was called to retrieve a list of the Content Manager OnDemand storage nodes, but the list that was returned was not formatted correctly. The message contains the line number and the first 200 characters of the line.

User response

Search the problem reporting database for a fix for the problem. If no fix exists, contact your IBM Service Representative.

ARS5020I

SORT returned no data

Explanation

The sort process indicated that objects were found that were to be deleted. However, the file that was supposed to contain the data either does not exist or contains zero bytes.

User response

Search the problem reporting database for a fix for the problem. If no fix exists, contact your IBM Service Representative.

ARS5021I

text

Explanation

The message text is produced when requested under the direction of the IBM Support Center.

User response

Provide the message text to the Support Center.

ARS5022I

Sort complete. *num_objs* objects returned.

Explanation

The sort step completed reading all the SMF records. *num_objs* were found that are candidates for unloading.

User response

No action is required.

ARS5023I

cmd returned *rc*. Params=>*parms*<

Explanation

A non-zero return value was provided by the *cmd*. This message provides the parameters that were used to invoke the command.

User response

Search the problem reporting database for a fix for the problem. If no fix exists, contact your IBM Service Representative.

ARS5024I

ARSEXPIR *version* invoked on *tstamp*

Explanation

ARSEXPIR was invoked at the specified time.

User response

No action is required.

ARS5025I

Storage Manager Resource Expiration: Application group(*applgrp_name*) Agid(*agid*)

Explanation

Resources were deleted for the specified application group.

User response

No action is required.

ARS5026I

Storage Manager Resource Expiration failed: Application group(*applgrp_name*) Agid(*agid*)

Explanation

Resource failed to be deleted for the specified application group.

User response

No action is required.

ARS5027I

Nid(*pri_nid*) Resource(*rid*)

Explanation

The node identifier and resource identifier involved in the action

User response

No action is required.

ARS5028I

Storage Manager Document Expiration: Application group *application group* Rows Deleted *rows*

Explanation

Rows were deleted from the application group data table(s) for the specified application group.

User response

No action is required.

ARS5029I

Storage Manager Document Expiration failed: Application group (*applgrp_name*) Agid(*agid*)

Explanation

Rows could not be deleted from the application group data table(s) for the specified application group.

User response

No action is required.

ARS5030I

LoadIdloadid

Explanation

The partial load id was involved in the action.

User response

No action is required.

ARS5031I

func_name failed reason code (X' *rsn*')

Explanation

An error occurred invoking the specified function

User response

Search the problem reporting database for a fix for the problem. If no fix exists, please contact the IBM Support Center.

ARS5100I

Usage: `arsrpt -h od_inst -u userid -p password -t <date> [-d<output_dir.>] [-f<date_format.>] [-o <filename_prefix.>] [-r <report_selection.>] [-x<report_format.>]` Version: version -c <cp> codepage for output files (defaults to system codepage) -d <output_dir> Output directory for report files -f <fmt> Format string for -t date value (Assumes yyyy-mm-dd) -h <od_inst> OnDemand Instance Name (same as -I) -I <od_inst> OnDemand OnDemand Instance Name (same as -h) -o <filename> Output file name prefix -p <password> OnDemand password stash file -r <report_selection> Report on selected activity (Defaults to all activities) 1 Logins 2 Loads 3 Query and retrieves -t <date> Date to generate report for -u <userid> OnDemand userid -x<report_format> Limit report output (Defaults to both outputs) 1 Summary output only 2 XML output only

Explanation

The `arsrpt` command contains an incorrect parameter

User response

The message response outlines the valid parameters for this command. See the appropriate OnDemand white-paper. Verify and correct the command parameters and resubmit the command.

ARS5101E

The date '*date*' is invalid or incorrect for the default format.

Explanation

The specified string is not a valid date value or the date format is invalid.

User response

Specify a valid date for the default format for the field and resubmit the command.

ARS5102E

The date '*date*' is invalid or the specified format '*format*' is incorrect.

Explanation

The specified string is not a valid date value or the date format is invalid.

User response

Specify valid date and/or format values for the fields and resubmit the command.

ARS5103E

Unable to open file '*file_name*'.

Explanation

The command failed when attempting to open the specified file.

User response

Verify that the file permissions are correct. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS5400E

ACIF Parm parser did not return any values

Explanation

The indexing parameters did not result in any Triggers, Fields, or Index values. The set of index instructions is invalid.

User response

Specify a valid set of indexing parameters.

ARS5401E

Input Parm string is empty

Explanation

No indexing parameters were found.

User response

Specify a valid set of indexing parameters.

ARS5403E

Use of multiple fields for INDEX *index-number* is not supported

Explanation

The OS/390® indexer does not support the use of multiple fields to construct the index value.

User response

Specify a single field for the Index.

ARS5404E

More than 32 sets of segmentation instructions were identified

Explanation

The OS/390 indexer supports up to 32 sets of segmentation instructions. More than 32 index instructions specified BREAK=YES.

User response

Redefine the indexing parameters to use a maximum of 32 BREAK=YES instructions.

ARS5405E

Field default values are not supported

Explanation

The OS/390 indexer does not support the use of "default values" on the Field parameter.

User response

Redefine the indexing parameters to not use "default values."

ARS5406E

Field constant values are not supported

Explanation

The OS/390 indexer does not support the use of "constant values" on the Field parameter for indexes 1 and 3 of NODX reports or index 3 of PAGE reports.

User response

Redefine the indexing parameters to not use "constant values."

ARS5407E

Invalid DOC SIZE specified *size*

Explanation

The document size returned from the ANYSTORE exit was invalid. The value must be between 1 and 1048320.

User response

Correct any errors in your ANYSTORE exit.

ARS5408E

ANYSTORE - INDEX call with no or an incomplete preceding segment

Explanation

The ANYSTORE exit returned with the ANY-INDEX return code, but was not preceded by a completed document.

User response

Correct any errors in your ANYSTORE exit.

ARS5409E

ANYSTORE - EOF call with no or an incomplete preceding segment

Explanation

The ANYSTORE exit returned with the ANY-EOF return code, but was not preceded by a completed document.

User response

Correct any errors in your ANYSTORE exit.

ARS5410E

NULL file read. Processing stopped.

Explanation

End of file was found, but no documents have been stored.

User response

If using the ANYSTORE exit, correct any errors in your ANYSTORE exit. Verify that the report file contains valid data. Contact your IBM Service Representative for further assistance.

ARS5411E

Severe error returned from ANYSTORE exit. Processing stopped.

Explanation

The ANYSTORE exit returned with the ANY-ERR return code.

User response

Look for additional messages generated by the ANYSTORE exit, and correct any errors in your ANYSTORE exit.

ARS5412E

ARSASTOR - Invalid doc size specified: *size*

Explanation

An AFP document was returned with an invalid document size. The value must be between 1 and 1048320.

User response

Verify that the AFP report contains valid data. Contact your IBM Service Representative for further assistance.

ARS5413E

ARSASTOR - Index call with no or an incomplete preceding segment

Explanation

The ARSASTORE exit returned with the AFP-INDEX return code, but was not preceded by a completed document.

User response

Verify that the AFP report contains valid data. Contact your IBM Service Representative for further assistance.

ARS5414E

ARSASTOR - EOF call with no or an incomplete preceding segment

Explanation

The ARSASTORE exit returned with the AFP-EOF return code, but was not preceded by a completed document.

User response

Verify that the AFP report contains valid data. Contact your IBM Service Representative for further assistance.

ARS5415E

Severe error returned from ARSASTOR exit. Processing stopped.

Explanation

A severe error was found while processing an AFP report.

User response

Look for additional messages generated by the store routine. Verify that your report file contains valid data. Contact your IBM Service Representative for further assistance.

ARS5417E

Invalid AFP record, 5A not found in pos 1

Explanation

A line was found in the AFP file which did not contain a X'5A' in column 1.

User response

Verify that your report file contains valid data.

ARS5418I

ANYSTORE document not recognized as being either Line Print or AFP, no Large Object processing performed

Explanation

A report captured through an ANYSTORE exit was not recognized as being either "line print" or "AFP." No attempt will be made to capture it as a Large Object.

User response

No action is required.

ARS5419E

No documents found - input exhausted

Explanation

The "start of report," based on trigger instructions, was not found before reaching end of file.

User response

Verify that your report file contains valid data, and verify that the indexing instructions are correct.

ARS5430E

Structured field length does not match record length. Record count: *record_count*. Input DDNAME *ddname*

Explanation

The AFP record's structured field length value (columns 2-3) does not match the record length of the variable length record. The variable length record must be one byte longer than the structured field length value.

User response

Ensure that the AFP report data set contains valid AFP data.

ARS5431E

Premature EOF for DDNAME *ddname*

Explanation

An End of File condition was found before it was expected. This can occur if the file does not contain both a BDT and an EDT record.

User response

Ensure that the AFP report data set contains valid AFP data.

ARS5432I

Match not found for value in TLE record, record number *record_num*. Input DDNAME *ddname*

Explanation

A TLE record was found which could not be matched with any index.

User response

No action required. This message is for informational purposes only.

ARS5433E

AFPDSIN data set was empty

Explanation

An input AFP data set does not contain any records.

User response

Ensure that the AFP report data set contains valid AFP data.

ARS5435E

TLE invalid structure, NAME triplet not found, record number *record_num*. Input DDNAME *ddname*

Explanation

A TLE record was found which did not contain a valid Name triplet.

User response

Ensure that the AFP report data set contains valid AFP data.

ARS5436E

TLE invalid structure, VALUE triplet not found, record number *record_num*. Input DDNAME *ddname*

Explanation

A TLE record was found which did not contain a valid Value triplet.

User response

Ensure that the AFP report data set contains valid AFP data.

ARS5438I

Truncated records fixed for AFP file *ddname*, count *record_count*

Explanation

The program identified one or more records as having a record length value within the AFP record that was larger than the physical record length. The program adds trailing blanks to the record to make it agree with the length in the AFP record.

User response

No action is required. The assumption is that JES removed the trailing blanks, so the program puts them back in.

ARS5439I

Truncated records fixed for Resource file *ddname*, count *record_count*

Explanation

The program identified one or more records as having a record length value within the resource record that was larger than the physical record length. The program adds trailing blanks to the record to make it agree with the length in the resource record.

User response

No action is required. The assumption is that JES removed the trailing blanks, so the program puts them back in.

ARS5440E

Invalid NOP record format, invalid length

Explanation

A NOP record with either an OD390 or ODZOS id value was found, but its record length was not valid. OD390 NOP records have a record length of 1048. ODZOS NOP records have a record length of 8208.

User response

Ensure that the AFP report data set contains valid AFP data.

ARS5441E

Open failed for input file - *ddname*

Explanation

An error occurred when opening the input report data set.

User response

Check the JES log for additional messages.

ARS5442E

Invalid RECFM (F) for AFP datastream. *ddname*

Explanation

The record format for the AFP input data set was "fixed." A "variable" record format is expected.

User response

Ensure that the AFP report data set contains valid AFP data.

ARS5443E

Open failed for AFP file – *ddname*

Explanation

An error occurred when opening the input AFP report data set.

User response

Check the JES log for additional messages.

ARS5444E

Close failed for *ddname* for AFP file

Explanation

An error occurred when closing the input AFP report data set.

User response

Check the JES log for additional messages.

ARS5445E

AFP read failed for file *ddname*

Explanation

An error occurred when reading the input AFP report data set.

User response

Check the JES log for additional messages.

ARS5446I

Open failed for AFP resource file – *ddname*

Explanation

An error occurred when opening the input AFP resource data set.

User response

Check the JES log for additional messages.

ARS5447E

Close failed for *ddname* for AFP resource file

Explanation

An error occurred when closing the input AFP resource data set.

User response

Check the JES log for additional messages.

ARS5448E

Resource read failed for file *ddname* after record *#record_count*

Explanation

An error occurred when reading the input AFP resource data set.

User response

Check the JES log for additional messages.

ARS5449I

Bad BREAKYES value, 'AND' assumed

Explanation

Valid values for the BREAKYES parameter are "AND" and "OR". Some other value was found. "AND" is used as the default.

User response

Check the INDEX INFORMATION tab of the application definition and verify the value specified for the BREAKYES parameter.

ARS5450E

Triggers with TYPE=GROUP were not satisfied within the page range specified by the INDEXSTARTBY parameter

Explanation

The OS/390 indexer did not find the TYPE=GROUP triggers by the specified page number. The INDEXSTARTBY parameter determines the page number by which the z/OS indexer must find the TYPE=GROUP trigger and begin indexing.

User response

Verify the page number that is specified in the INDEXSTARTBY parameter. If the page number is correct, verify the TRIGGER parameters. Then rerun the load

ARS5454E

Offset value on a FIELD or TRIGGER exceeds 255

Explanation

The valid range of values for the offset on the FIELD and TRIGGER parameters is 0 through 255.

User response

Verify the indexing parameters. Correct and rerun the load.

ARS5455E

Maximum size of DJDE Buffer exceeded

Explanation

The maximum number of DJDE records supported by the processing logic was exceeded.

User response

Contact your IBM Service representative for assistance.

ARS5456E

DJDECNT value must be between 0 and 256

Explanation

The range of valid values for the DJDECNT parameter is 0 through 256.

User response

Verify the indexing parameters. Correct and rerun the load.

ARS5457E

DJDECOL value must be between 1 and LRECL

Explanation

The range of valid values for the DJDECOL parameter is 1 through the input file's logical record length.

User response

Verify the indexing parameters. Correct and rerun the load.

ARS5458E

Global DJDE records not found.

Explanation

A DJDECNT value greater than zero was specified, but the global DJDE records could not be found.

User response

Verify the indexing parameters. Correct and rerun the load.

ARS5459E

Close failed for input file - *ddname*

Explanation

An error occurred when closing the input report dataset.

User response

Check the JES log for additional messages.

ARS5460E

Read failed for input file - *ddname*

Explanation

An error occurred when reading the input report dataset.

User response

Check the JES log for additional messages.

ARS5461E

Input file RECFM not \"F\" or \"V\"

Explanation

The report input file must have a record format that starts with F or V.

User response

Correct the record format of the input file, and rerun the load.

ARS5462E

The INPEXITNEW parameter must be Y or N.

Explanation

The value specified for the INPEXITNEW parameter was invalid. Specify either Y or N. The default is N.

User response

Specify a value of Y or N for the INPEXITNEW parameter.

ARS5463E

The INDEXSTYLE parameter is not valid.

Explanation

The value specified for the INDEXSTYLE parameter is not valid. Valid values are DOC, PDOC, PAGE, NODX, and AFP. The default value is DOC.

User response

Specify a valid value for the INDEXSTYLE parameter.

ARS5464E

[TYPE=FLOAT] cannot be specified for TRIGGER1.

Explanation

The TYPE=FLOAT datatype is not valid for TRIGGER1. Use 'TYPE=GROUP'.

User response

Use 'TYPE=GROUP' for TRIGGER1.

ARS5465E

An incorrect relative record number was entered for TRIGGER1.

Explanation

The record number associated with the TRIGGER1 parameter was not an asterisk.

User response

Enter an asterisk (*) for the record number for TRIGGER1.

ARS5466E

The length, *masklen*, of the mask value for field *field* does not equal the length *fieldlen*, specified for this field.

Explanation

The length of the mask value and the field length value must be the same.

User response

Correct the mask value or the field length value, as appropriate.

ARS5467E

The length, *offlen*, of offset pair *pair* for field *field* does not equal the length, *fieldlen*, specified for this field.

Explanation

The length of a begin-end pair, specified by the offset keyword of a field, does not match the length of the field. These lengths must be equal.

User response

Correct the offset start and end values so the length matches the field value length.

ARS5468E

Invalid channel command at record *linenum* of the input file.

Explanation

An invalid machine code carriage return control character was found, and could not be converted to an ANSI carriage return control character.

User response

Correct the input data, and try the command again

ARS5469E

The MCC2NSI parameter must be Y or N.

Explanation

The value specified for the MCC2ANSI parameter is invalid. Specify either Y or N. The default value is N.

User response

Specify either a Y or an N for the MCC2ANSI parameter, and then try the command again

ARS5470E

The AFPINDEXBUF parameter must have a value between 1 and 10000.

Explanation

The value specified for the AFPINDEXBUF parameter was invalid. Specify a value between 1 and 10000. The default is 10.

User response

Specify a value between 1 and 10000 for the AFPINDEXBUF parameter.

ARS5471E

The following message was returned from the OS/390 indexer (ARSZSTDR error_message = msg_text).

Explanation

See the message text.

User response

Review the message text. If necessary, correct the problem indicated by the message text. For more information on OS/390 indexer, see the OS/390 indexer reference section in the IBM Content Manager OnDemand *Indexing Reference*.

ARS5472E

There were no indexing instructions in the indexing parameters. (ARSZSTDR returned 0 fields).

Explanation

The indexing parameters did not include valid INDEX instructions. Field names are based on information in the INDEX instructions. No field names were found.

User response

Review the index parameters. Check for invalid or missing values. Correct and resubmit the command.

ARS5473E

The internal function disk2mem received invalid parameters for either length (length) or offset (offset). (disk2mem invalid length=length or offset=offset).

Explanation

An error occurred in the disk2mem function.

User response

Check the z/OS console log and OnDemand server for additional information. Resubmit the command. If the problem persists, contact IBM Software Support.

ARS5474E

The internal function mem2disk received invalid parameters for file mode (file_mode) and line (line). (mem2disk invalid fileMode file_mode, line=line).

Explanation

An error occurred in the mem2disk function.

User response

Check the z/OS console log and OnDemand server for additional information. Resubmit the command. If the problem persists, contact IBM Software Support.

ARS5475E

The temporary files directory (directory) does not exist.

Explanation

Various temporary internal files are used during the load process. These files are placed in the temporary files directory. This directory could not be found. It is specified through any of the following environment variables: ARS_HFS, ARSMVS_ARSLOAD_INDEX_DIR, ARS_TMP, TEMP or TMP. If none of these environment variables are set, the default temporary directory name is /tmp.

User response

Create the directory and set the appropriate environment variable. Resubmit the command.

ARS5476E

The OS/390 indexer failed with the specified return code. (Arsl390 rc = rc).

Explanation

The report failed to load. See previous messages for additional information.

User response

Check the CMOD system log for additional messages related to this problem. Correct the problem as indicated by the additional messages.

ARS5477E

The ArcADMIN_Field function failed with the specified return code while processing the specified fields and value. (ArcADMIN_Field rc = rc, field = field, value = value)

Explanation

The report failed to load. Review the field value with the application group field definition to be sure that they are compatible.

User response

Correct the problems. If the problems persist, contact IBM Software Support.

ARS5478E

A BEGIN RESOURCE GROUP (BRG) record was not found in the RESOURCE DD input.

Explanation**User response**

Verify that the RESOURCE DD input contains BEGIN RESOURCE GROUP / END RESOURCE GROUPa pair (BRG/ERG).

ARS5479E

INVALID INDEXING PARM. NUMERIC VALUE EXPECTED AT COL *col*. FOUND >*value*< INSTEAD. PARM STARTS WITH *parm*

Explanation

The value found in the indexing parameter could not be converted to an integer.

User response

Correct the indexing parameter.

ARS5480E

NEGATIVE RECORD LENGTH FOUND: *len*.

Explanation

The record length returned by the input exit was negative.

User response

Correct the input exit.

ARS5481I

parameter=value

Explanation

For this run, the parameter listed has been used with the associated value.

The original indexing parameters from the Application Definition may have been modified by any of the following actions:

- removing all comments
- removing imbedded banks that are not part of a quoted string
- renumbering the TRIGGER, FIELD, and INDEX parameters to remove gaps in the sequence numbers

System action

None.

User response

No action is required.

Programmer response

No action is required.

ARS5482E

The FILEFORMAT is missing or not correct. The format must be RECORD or STREAM.

Explanation

The value specified for the FILEFORMAT parameter was not correct. Specify either RECORD or STREAM.

User response

Specify a value for the FILEFORMAT parameter.

ARS5483E

A NEWLINEvalue was not specified with the FILEFORMAT=STREAM parameter.

Explanation

When FILEFORMAT=STREAM is specified, the parameter must include a NEWLINE sub-parameter.

User response

Specify a NEWLINE sub-parameter on the FILEFORMAT parameter.

ARS5484E

The space needed for consecutive lines with overstrike carriage control exceeds what is available when the LINEOFFSET=ASPRINTED parameter is used.

Explanation

The load file contains too many consecutive records with an overstrike carriage control character. When you use the LINEOFFSET=ASPRINTED indexing parameter, these lines exceed the available space allotted to hold them in memory.

User response

Adjust the indexing parameters so that the LINEOFFSET=ASREAD parameter can be specified.

ARS5485E

Severe error returned from INDEXIT exit. Processing stopped.

Explanation

The INDEXIT exit returned with the ERR status. Look for additional messages generated by the INDEXIT Exit.

User response

Correct any errors in your INDEXIT exit.

ARS5486E

Severe error returned from INPEXIT exit. Processing stopped.

Explanation

The INPEXIT exit returned with the ERR status. Look for additional messages generated by the INPEXIT Exit.

User response

Correct any errors in your INPEXIT exit.

ARS5487E

INVALID INDEXING PARM. *parm* MUST BE IN THE RANGE *min-max*. FOUND *>value<* INSTEAD

Explanation

The value found in the indexing parameter was not within a required range.

User response

Correct the indexing parameter.

ARS5488E

INVALID INDEXING PARM. ERROR OCCURS NEAR *parm*

Explanation

A value found in the indexing parameters was not valid.

User response

Correct the indexing parameter.

ARS5489E

INVALID INDEXING PARM FOR *statement*. VALUE *value* IS INVALID FOR *keyword*

Explanation

The indicated statement contains an invalid value for the keyword.

User response

Correct the indexing parameter.

ARS6000I

Usage: arsdoc add -h hostname [-u <userid>] [-p <passwd>] [-v] (-F <parmfile> | ([-i <sql_query> | -q <namedquery> | -o <filename>] [-f <foldername>] -a <name> (-g <name> | -G <name>) -n field1=value1 [-O][[-S <startdate,enddate[,format]>]]) [-1 <trace_file>] [-2 <trace_level>]
Version: *version*

-a <name> Application Name
 -f <foldername> OnDemand folder (required in parm file)
 -g <name> Application Group Name
 -h <hostname> OnDemand Hostname (command line only)
 -i <sql_query> SQL query string
 -n <field1=value1> One or more database field names and values
 -o <filename> Data file name
 -p <passwd> OnDemand User Login Password (command line only)
 -q <namedquery> Public named query
 -u <userid> OnDemand User Login Name (command line only)
 -v Verbose (command line only)
 -F <parmfile> Requests parameter file (command line only)
 -G <name> Application Group Name
 -O Database fields values are not required
 -S <startdate,enddate[,format]> Segment date range
 -1 <trace_file> Trace file (command line only)
 -2 <trace_level> Trace level (command line only)
 Flags in a parameter file must be delimited by brackets EX: [-f foldername]

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS6001I

Usage: arsdoc update -h hostname [-u <userid>] [-p <passwd>] [-U <user_alias>] [-v]
 (-F <parmfile> | ((-i <sql_query> | -l <holdname> | -q <namedquery> | -t <search_str> | -T <search_str> |
 -X <load_id> | -x <load_id>)
 [-f <foldername>] (-g <name> | -G <name>)) -n field1=value1
 [-S <startdate,enddate[,format]>])) [-1 <trace_file>] [-2 <trace_level>]
 Version: *version*
 -f <foldername> OnDemand folder (required in parm file)
 -g <name> Application Group Name
 -h <hostname> OnDemand Hostname (command line only)
 -i <sql_query> SQL query string
 -l <holdname> OnDemand hold
 -n <field1=value1> One or more database field names and values
 -p <passwd> OnDemand User Login Password (command line only)
 -q <namedquery> Public named query
 -t <search_str> Server text search
 -u <userid> OnDemand User Login Name (command line only)
 -v Verbose (command line only)
 -x <load_id> LoadId to use for OnDemand
 -F <parmfile> Requests parameter file (command line only)
 -G <name> Application Group Name
 -S <startdate,enddate[,format]> Segment date range
 -T <search_str> Full text search
 -U <user_alias> User alias that appears in System Log messages
 -X <load_id> LoadId to use for OnDemand
 -1 <trace_file> Trace file (command line only)
 -2 <trace_level> Trace level (command line only)
 Flags in a parameter file must be delimited by brackets EX: [-f foldername]

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS6002I

Usage: arsdoc delete -h hostname [-u <userid>] [-p <passwd>] [-v] (-F <parmfile> | ((-i <sql_query> | -q <namedquery>) [-f <foldername>] [-G <name>] [-S <startdate,enddate[,format]>])) [-1 <trace_file>] [-2 <trace_level>]
Version: *version*

-f <foldername> OnDemand folder (required in parm file)
-h <hostname> OnDemand Hostname (command line only)
-i <sql_query> SQL query string
-p <passwd> OnDemand User Login Password (command line only)
-q <namedquery> Public named query
-u <userid> OnDemand User Login Name (command line only)
-v Verbose (command line only)
-F <parmfile> Requests parameter file (command line only)
-G <name> Application Group Name
-S <startdate,enddate[,format]> Segment date range
-1 <trace_file> Trace file (command line only)
-2 <trace_level> Trace level (command line only)
Flags in a parameter file must be delimited by brackets EX: [-f foldername]

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS6003I

Usage: arsdoc get -h <hostname> [-u <userid>] [-p <passwd>] [-s] [-v] (-F <parmfile> | ((-i <sql_query> | -Q <sql_filename> | -q <namedquery> | -X <load_id>) [-x <load_id>] [-f <foldername>] [-G <name>] [-a] [-c] [-g] [-A <type>] [-N] [-n] [-o <filename>] [-d <dir>] [-L <max_docs>] [-S <startdate,enddate[,format]>])) [-1 <trace_file>] [-2 <trace_level>]
Version: *version*

-a Include resource group
-c Store documents in one file
-d <dir> Directory to store files
-f <foldername> OnDemand folder (required in parm file)
-g Create generic indexer file
-h <hostname> OnDemand hostname (command line only)
-i <sql_query> SQL query string
-n Do not use bulk retrieve
-o <filename> Output file name (required in parm file)
-p <passwd> OnDemand User Login Password
-q <namedquery> Public named query
-s <seconds> Delay time between requests (command line only)
-u <userid> OnDemand User Login Name
-x <load_id> LoadId to use for OnDemand
-v Verbose (command line only)
-A <type> Retrieve annotations

The values are additive.

0 Include public text annotations

1 Include private annotations

2 Include annotations that cannot be copied to another server

4 Include graphic annotations

-F <parmfile> Requests parameter file (command line only)

-G <name> Application Group Name

-L <max_docs> Maximum documents to retrieve

-N Use Application group and application names in file name

-Q <sql_filename> SQL query strings file name

-S <startdate,enddate[,format]> Segment date range

-X <load_id> LoadId to use for OnDemand

-1 <trace_file> Trace file (command line only)

-2 <trace_level> Trace level (command line only)

Flags in a parameter file must be delimited by brackets EX: [-f foldername]

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. Valid parameters are provided in the message. For more detailed information about this command, see the Content Manager OnDemand *Administrator's Guide*.

ARS6004I

Usage: arsdoc query -h hostname [-u <userid>] [-p <passwd>] [-v]

(-F <parmfile> | ((-i <sql_query> | -q <namedquery> |

-X <load_id>) [-x <load_id>] [-B <dbname>] [-f <foldername>] [-G <name>]

[-e <delim>] [-H] [-I] [-N <(field1)>][-n] [-o <filename>]

[-d <dir>] [-L <max_hits>] [-S <startdate,enddate[,format]>])) [-1 <trace_file>] [-2 <trace_level>]

Version: *version*

-d <dir> Directory to write output file

-e <delim> separator between database values

-f <foldername> OnDemand folder (required in parm file)

-h <hostname> OnDemand Hostname (command line only)

-i <sql_query> SQL query string

-n Add line numbers in output file

-o <filename> Output file name (required in parm file)

-p <passwd> OnDemand User Login Password

-q <namedquery> Public named query

-u <userid> OnDemand User Login Name

-x <load_id> LoadId to use for OnDemand

-v Verbose (command line only)

-B <dbname> Name of a database field used to sort the data in ascending order

-F <parmfile> Requests parameter file (command line only)

-G <name> Application Group Name

-D Append the document handle to each record in the file

-H Build a header record

-I Append the LoadId to each record in the file

-L <max_hits> Maximum hits to process

-N <(field1)> One or more database field names; defines order in file

-S <startdate,enddate[,format]> Segment date range

-X <load_id> LoadId to use for OnDemand

-1 <trace_file> Trace file (command line only)

-2 <trace_level> Trace level (command line only)

Flags in a parameter file must be delimited by brackets EX: [-f foldername]

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS6005I

Usage: arsdoc print -h hostname [-u <userid>] [-p <passwd>] [-v]
(-F <parmfile> | ((-i <sql_query> | -q <namedquery>)
[-B <dbname>] [-f <foldername>] [-G <name>] [-P <prtr>] [-L <max_docs>]
[-S <startdate,enddate[,format]>])) [-1 <trace_file>] [-2 <trace_level>]
Version: *version*
-f <foldername> OnDemand folder (required in parm file)
-h <hostname> OnDemand Hostname (command line only)
-i <sql_query> SQL query string
-p <passwd> OnDemand User Login Password (command line only)
-q <namedquery> Public named query
-u <userid> OnDemand User Login Name (command line only)
-v Verbose (command line only)
-B <dbname> Name of a database field used to sort the data in ascending order
-F <parmfile> Requests parameter file (command line only)
-G <name> Application Group Name
-L <max_docs> Maximum documents to retrieve
-P <prtr> System printer name
-S <startdate,enddate[,format]> Segment date range
-1 <trace_file> Trace file (command line only)
-2 <trace_level> Trace level (command line only)
Flags in a parameter file must be delimited by brackets EX: [-f foldername]

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS6006E

Unable to get folder information. The folder does not exist or the user does not have permission to access the folder.

Explanation

The command failed when attempting to find the specified folder on the specified server.

User response

Verify that the folder exists on the server and that the user has permission to access the folder. Then resubmit the command.

ARS6007E

The server failed during a search operation. View the System Log for additional messages.

Explanation

The command failed when attempting a query for documents.

User response

Verify that the SQL string is a valid SQL query and that the database field names that are specified in the SQL string are valid. Then resubmit the command.

ARS6009E

A cancel request was received during a server request.

Explanation

An error occurred.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. Use the information in the messages to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS6010E

The server operation failed.

Explanation

The command failed when attempting a query or retrieval request.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. Use the information in the messages to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS6011E

The error occurred on line number *line_number*.

Explanation

The command failed with an error on the specified line number.

User response

See the Content Manager OnDemand System Log for other messages that are associated with the command. Use the information in the messages to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS6012E

Unable to read parameter file '*file_name*'.

Explanation

The command failed when attempting to read a record from the specified parameter file.

User response

Verify and correct the parameter file. Then resubmit the command.

ARS6013E

The host name or address must be provided to continue the operation.

Explanation

The host name or IP address was not provided on the command line.

User response

Resubmit the command with the -h parameter and the host name or IP address of the server.

ARS6014E

The folder name must be provided to continue the operation.

Explanation

The folder name was not provided.

User response

Resubmit the command with the -f parameter and the name of the folder.

ARS6015E

Printer '*printer_name*' was not found.

Explanation

The specified printer was not found on the server.

User response

Verify that the printer exists on the server and that the user has permission to access the printer. Then resubmit the command.

ARS6016E

The output file name '*file_name*' exceeds a maximum length of *length*.

Explanation

The number of characters in the output file name exceeds the maximum allowable length.

User response

Change the name of the output file so that the length of the file name does not exceed the maximum allowable length. Then resubmit the command.

ARS6017E

The user does not have authority to add documents.

Explanation

The application group document permissions for the user do not include the authority to add documents.

User response

Resubmit the command with a user ID that has permission to add documents or change the application group document permissions to include the authority to add documents and resubmit the command.

ARS6018E

The user does not have authority to delete documents.

Explanation

The application group document permissions for the user does not include the authority to delete documents.

User response

Resubmit the command with a user ID that has permission to delete documents or change the application group document permissions to include the authority to delete documents and resubmit the command.

ARS6019E

The user does not have authority to update documents.

Explanation

The application group document permissions for the user does not include the authority to update documents.

User response

Resubmit the command with a user ID that has permission to update documents or to change the application group document permissions to include the authority to update documents and resubmit the command.

ARS6020E

The database field '*database_name*' was not found in the application group.

Explanation

The database field name was not found in the application group.

User response

Verify that the name of the database field is the same as a database field in the application group. Then resubmit the command.

ARS6021E

The application group name must be provided to continue the operation.

Explanation

The application group name was not provided.

User response

Resubmit the command with a valid application group name.

ARS6022E

Application group '*applgrp_name*' was not found in folder '*folder_name*'.

Explanation

The specified application group was not found in the specified folder. Either the folder does not contain the application group, or the user does not have permission to access the application group.

User response

Verify that the application group can be searched from the folder and that the user has permission to access the application group. Then resubmit the command.

ARS6023E

The -s flag can only be used when a parameter file name is provided using the -F flag.

Explanation

The -s parameter specifies the amount of time to delay between requests to the server. The -s parameter is not applicable when only one request is sent to the server. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command without the -s parameter.

ARS6024E

The -N and -c flags must be specified when the -g flag is used.

Explanation

The -g parameter, the -N parameter, and the -c parameter are used together to generate a generic index file and the output file. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command with the -g, -N, and -c parameters.

ARS6025E

The -c or -g flag cannot be used when an output file name contains database field names.

Explanation

The output file name will be generated from the database field names. Documents must be written to separate files if this option is used. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command without the -c or -g parameters.

ARS6026I

arsdoc completed.

Explanation

This message is for your information only.

User response

No action is required.

ARS6027E

The application name must be provided to continue the operation.

Explanation

The application name was not specified.

User response

Resubmit the command with a valid application name.

ARS6028E

Application '*appl_name*' was not found in application group '*applgrp_name*'.

Explanation

The specified application was not found in the specified application group.

User response

Verify the names of the application and the application group. Verify that the application belongs to the application group. Then resubmit the command.

ARS6029E

The syntax for the value of flag -n '*value*' is not valid. Valid syntax is 'dbfield=*value*'.

Explanation

The value that was specified with the -n parameter did not have the correct syntax. The correct syntax is provided in the message, and all ARSDOC parameters are explained in the *Administration Guide*.

User response

Change the value of the -n parameter to the format 'dbfield=*value*' and resubmit the command.

ARS6030E

The -o flag and the -S flag cannot be used together.

Explanation

A segment date cannot be specified if a data file name is specified. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command with either the -o parameter or the -S parameter.

ARS6031E

The -i flag or the -q flag cannot be specified when the -o flag is used.

Explanation

An SQL query or a named query cannot be specified if a data file name is specified. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command without the -i and -q parameters.

ARS6032E

At least one field=*value* pair must be provided to continue the operation.

Explanation

A request was made to add or update a document but the field values for the document were not specified.

User response

Resubmit the command with at least one field=*value* pair.

ARS6033E

An SQL query string (-i \"WHERE database_name = *value*\") must be provided to continue the operation.

Explanation

An SQL query string was not provided.

User response

Resubmit the command with a valid SQL query string.

ARS6034W

No hits were found that matched search criteria.

Explanation

No documents matched the search criteria.

User response

Verify that this is the expected result. If it is not, submit the command with different search criteria.

ARS6035E

The named query '*named_query*', does not exist in folder '*folder_name*'.

Explanation

The specified named query was not found in the specified folder.

User response

Verify that the named query exists in the folder, that the named query is a public named query, and that the user has authority to view the named queries for the folder. Then resubmit the command.

ARS6036E

The -i, -t, -T, or -X flag cannot be used with the -q flag.

Explanation

An incorrect parameter was specified.

User response

Resubmit the command without the invalid parameters.

ARS6037E

The -q flag and the -S flag cannot be used together.

Explanation

A segment date cannot be specified if a named query is specified. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command without the -S parameter.

ARS6038E

The syntax for the value of flag -S '*segment_dates*' is not valid. Valid syntax is *segdate1,segdate2* or *segdate1,segdate2,format*.

Explanation

The value specified with the -S parameter is not valid. The dates might not match the format, or the specified format might be invalid. Valid date formats and all ARSDOC parameters are explained in the *Administration Guide*.

User response

Verify that the value is in the following format: *segdate1, segdate2, format* and that the date format is valid. Then resubmit the command.

ARS6039E

The only options that can be specified with the -F option are -u, -p, -h, and -v.

Explanation

The -F parameter was specified and one or more other parameters that are not valid on the command line were also specified. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command with the correct parameters.

ARS6040E

The only options that can be specified with the -F option are -u, -p, -h, -s, and -v.

Explanation

The -F parameter was specified and one or more other parameters that are not valid on the command line were also specified. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command with the correct parameters.

ARS6041E

The -o flag must be specified when using the -d flag.

Explanation

A directory name was provided without an output file name. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command without the -d parameter or with the -d and -o parameters.

ARS6043E

The -L, -n, and -N flags cannot be used when requesting only database field names.

Explanation

When requesting only the database field names, the -L, -n, and -N parameters cannot be specified. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command without the -L, -n, and -N parameters.

ARS6044E

The output file name '*outfile_name*' and the directory path '*dir_path*' exceeds a maximum length of *path_size*.

Explanation

The number of characters in the output file name and the directory exceeds the maximum allowable length.

User response

Change the file name or directory path so that the length of the file name does not exceed the maximum allowable length. Then resubmit the command.

ARS6045E

The output file name '*file_name*' exceeds a maximum length of *length*.

Explanation

The number of characters in the output file name exceeds the maximum allowable length.

User response

Change the file name so that the length of the file name does not exceed the maximum allowable length.

ARS6046E

A value has not been provided for field '*field_name*'.

Explanation

A value for the specified field is missing. By default, when adding a document, values must be provided for all fields. You can specify the -O parameter to indicate that some field values are optional, but you must always provide date and time fields. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command with a value for the field or resubmit the command with the -O parameter.

ARS6047E

Data is from application '*appl_name1*', application group '*applgrp_name1*' and must be from application '*appl_name2*', application group '*applgrp_name2*'.

Explanation

An attempt was made to add a document that points to an existing document, but the two documents were not from the same application. When adding a document that points to an existing document, both documents must be in the same application. Application names must be unique within an application group, but multiple application groups can have similarly named applications. The specified applications must belong to the same application group.

User response

Determine whether the document or the application was misidentified. Then resubmit the command with documents that belong to the same application and application group.

ARS6048E

The name of the system printer is required to continue the operation.

Explanation

The system printer name is required but was not specified with the -P parameter. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command with the -P parameter and specify the name of the system printer.

ARS6049E

The -c flag must be specified when the -N flag is used.

Explanation

Documents must be concatenated into one file when the -N parameter is specified. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command with the -c parameter.

ARS6050E

The -o flag must be specified when either the -c or -g flag is specified.

Explanation

An output file name must be specified when the -c or -g parameters are specified. All ARSDOC parameters are explained in the *Administration Guide*.

User response

Resubmit the command with the -o parameter.

ARS6052E

The length of the delimiter is invalid. The delimiter can only be 1 character.

Explanation

The value that was specified for the delimiter contains more than one character.

User response

Resubmit the command with a valid, one-character delimiter.

ARS6053E

The output filename format is invalid.

Syntax is as follows. (Parentheses are required.)

(ag_name1)(ag_name2)(ag_name3)

Explanation

The output file name is not in the correct format. The correct format is shown in the message text.

User response

Resubmit the command with a valid output file name.

ARS6054E

The header format is invalid. Syntax is as follows (Parentheses are required):

(ag_name1)(ag_name2)(ag_name3)

Explanation

The header is not in the correct format. The correct format is shown in the message text.

User response

Resubmit the command with a valid header string.

ARS6055E

A maximum of '*max_hits*' hits(s) were requested for this query. The number of matching hits found was '*num_hits*'.

Explanation

The SQL query matched more items than the number requested.

User response

Change the SQL query string to match fewer items or increase the maximum number of items to return. Then resubmit the command.

ARS6056E

Unable to retrieve resource group for '*file_name*'.

Explanation

The command failed when attempting to retrieve a resource group.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6057E

'LoadId could not be found'

Explanation

The Content Manager OnDemand System Log was searched but the load ID could not be found.

User response

Resubmit the command with a valid load ID.

ARS6058E

Invalid option '*option*'.

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS6059W

The number of hits returned has been limited to the maximum number of hits defined in the folder.

Explanation

The folder has a limit on the number of items that can be returned, and the query exceeded the maximum limit.

User response

Verify that this is the expected result. If it is not, submit the command with different search criteria.

ARS6061I

Querying for printers on server '*server_name*'...

Explanation

This message is for your information only.

User response

No action is required.

ARS6062I

Searching for folder '*folder_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6063I

Searching for documents in '*folder_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6064I

Deleting *num_documents* documents

Explanation

This message is for your information only.

User response

No action is required.

ARS6065I

Deleting document *document_name*

Explanation

This message is for your information only.

User response

No action is required.

ARS6066I

Waiting *seconds* seconds ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6067I

Sending *num_documents* documents to printer '*printer_name*' on server '*server_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6068I

Updating *num_documents* documents with *field_values*

Explanation

This message is for your information only.

User response

No action is required.

ARS6069I

Updating document *field_values_string* ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6070I

Adding document with fields: *field_values* ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6071I

Writing *num_hits* hits in file '*file_name*'...

Explanation

This message is for your information only.

User response

No action is required.

ARS6072I

Writing database field names in file '*file_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6073I

Retrieving document for userid '*userid*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6080I

Login successful

Explanation

This message is for your information only.

User response

No action is required.

ARS6081E

Login unsuccessful

Explanation

The command failed when attempting to log on to the server.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6082I

Query successful

Explanation

This message is for your information only.

User response

No action is required.

ARS6083E

Query unsuccessful

Explanation

The command failed when attempting to query the database.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6084I

Search successful

Explanation

This message is for your information only.

User response

No action is required.

ARS6085E

Search unsuccessful

Explanation

The command failed when attempting to query the database.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6086I

Add successful

Explanation

This message is for your information only.

User response

No action is required.

ARS6087E

Add unsuccessful

Explanation

The command failed when attempting to add a document.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6088I

Update successful

Explanation

This message is for your information only.

User response

No action is required.

ARS6089E

Update unsuccessful

Explanation

The command failed when attempting to update a document.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6090I

Delete successful

Explanation

This message is for your information only.

User response

No action is required.

ARS6091E

Delete unsuccessful

Explanation

The command failed when attempting to delete a document.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6092I

Write successful

Explanation

This message is for your information only.

User response

No action is required.

ARS6093E

Write unsuccessful

Explanation

The command failed when attempting to write a document.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6094I

Document successfully retrieved.

Explanation

This message is for your information only.

User response

No action is required.

ARS6095I

Document successfully retrieved and stored in file '*file_name*'

Explanation

This message is for your information only.

User response

No action is required.

ARS6096E

Retrieve unsuccessful

Explanation

The command failed when attempting to retrieve a document.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6097I

Print request successful

Explanation

This message is for your information only.

User response

No action is required.

ARS6098E

Print request unsuccessful

Explanation

The command failed when attempting to print a document.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6099E

The folder field value of '*field_value*' is not valid for field '*field_name*'.

Explanation

The specified value is not valid for the specified folder field.

User response

Resubmit the command with a value that is valid for the folder field.

ARS6100E

The -f, -i, -l, -q, -t, -x, -B, -Q, -S, or -T flag cannot be used with the -X flag.

Explanation

An incorrect parameter was specified.

User response

Resubmit the command without the invalid parameters.

ARS6101E

Application group '*applgrp_name*' was not found on server '*server_name*'.

Explanation

The specified application group could not be found on the specified server.

User response

Verify the name of the application group and the name of the server. Verify that the application group exists on the server and that the user has permission to access it. Then resubmit the command.

ARS6102E

Unable to restore hit from record '*rec_number*' in file '*file_name*'.

Explanation

The record contains missing information or incorrect values and cannot be processed.

User response

Resubmit the command with a valid record.

ARS6106E

The add operation cannot be performed because the application group's expiration type is Load or the Database Organization is single load per database table.

Explanation

To add a document, the application group expiration type must be Segment or Document and the Database Organization must be multiple loads per database table.

User response

Change the expiration type to Segment or Document or change the Database Organization to multiple loads per database table.

ARS6107I

hits_queried document(s) have been queried. Retrieving *hits_retrieved* document(s).

Explanation

This message is for your information only.

User response

No action is required.

ARS6108I

Starting arsdoc. Version: *version*

Explanation

This message is for your information only.

User response

No action is required.

ARS6109E

The -g, -N and -c flags must be specified when the -A flag is used.

Explanation

Annotations cannot be retrieved unless a generic indexer file is used.

User response

Resubmit the command with the -g parameter, the -N parameter and the -c parameter.

ARS6110I

Writing generic indexer file(s).

Explanation

This message is for your information only.

User response

No action is required.

ARS6111I

Generic indexer file *filename* has been successfully created.

Explanation

This message is for your information only.

User response

No action is required.

ARS6112I

numNotes annotations were written to file *filename*.

Explanation

This message is for your information only.

User response

No action is required.

ARS6113E

Unable to convert large object string *string*.

Explanation

A failure occurred when attempting to convert a large object string.

User response

See the other messages that were generated by the command, and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6114E

Unable to initialize string conversion routines using code page *codePage1* and *codePage2*.

Explanation

A failure occurred when attempting to initialize the string conversion process.

User response

See the other messages that were generated by the command, and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6116E

The -i, -q, -x, or -X flag cannot be used with the -Q flag.

Explanation

An incorrect parameter was specified.

User response

Resubmit the command without the -i, -q, -x, or -X parameter.

ARS6117I

Querying database with SQL string *string*.

Explanation

This message is for your information only.

User response

No action is required.

ARS6118I

numDocs document(s) have been queried.

Explanation

This message is for your information only.

User response

No action is required.

ARS6119I

A total of *num_notes* annotations were written to file '*file_name*'.

Explanation

This message is for your information only.

User response

No action is required.

ARS6120E

Tokenized query string format failed at marker *position*, input value *str_value*: A type string is expected; the value must be enclosed in single quotes.

Explanation

A string value is not enclosed in single quotes. For example:

SQL string:

```
2;balance,name;777.77,A & A%';WHERE balance = ? AND name LIKE ?
```

System log message:

```
Tokenized query string format failed at marker (2),  
input value (A & A%'): A type string is expected;  
the value must be enclosed in single quotes.
```

User response

Enclose the string value in single quotes and resubmit the command.

ARS6121W

Tokenized query string format warning: non-numeric value was found at marker *position*, input value *str_value*: A numeric value is expected.

Explanation

An invalid numeric value was specified. For example:

SQL string:

```
2;balance,name;777.77abc,'A & A%';WHERE balance = ? AND name LIKE ?
```

System log message:

```
Tokenized query string format warning:  
non-numeric value was found at marker (1),  
input value (777.77abc):  
A numeric value is expected.
```

User response

Check that the value is numeric and resubmit the command.

ARS6122E

Tokenized query string format failed:

The number of parameter markers (*numMarkers*) is not equal to the number of parameter names (*numNames*).

Explanation

The number of parameters is not the same as the number of parameter names. For example:

SQL string:

```
3;balance,name;777.77,'A & A%';WHERE balance = ? AND name LIKE ?
```

System log message:

```
Tokenized query string format failed:  
The number of parameter markers (3) is  
not equal to the number of parameter names (2).
```

User response

Resubmit the command with a valid SQL query string.

ARS6123E

Tokenized query string format failed:
Missing parameter values; the number of parameter markers was specified as (*numMarkers*).

Explanation

Fewer parameter values were specified than were expected. For example:

SQL string:

```
2;balance,name;777.77;WHERE balance = ? AND name LIKE ?
```

System log message:

```
Tokenized query string format failed:  
Missing parameter values;  
the number of parameter markers was  
specified as (2).
```

Note: If more parameter values are specified than are expected, OnDemand will map the parameter names and values from left to right, and discard the extra value (or values).

User response

Correct the number of values in the parameter value string and resubmit the command.

ARS6124I

```
Usage: arsdoc hold_add -h hostname [-u <userid>] [-p <passwd>] [-U <user_alias>] [-v]  
(-F <parmfile> | ((-i <sql_query> | -q <namedquery> | -X <load_ID>) -l <holdname>  
[-f <foldername>] [-G <name>] [-S <startdate,enddate[,format]>]))  
[-1 <trace_file>] [-2 <trace_level>]
```

Version: *version*

-f <foldername> OnDemand folder (required in parm file)
-h <hostname> OnDemand Hostname (command line only)
-i <sql_query> SQL query string
-l <holdname> OnDemand hold
-p <passwd> OnDemand User Login Password (command line only)
-q <namedquery> Public named query
-u <userid> OnDemand User Login Name (command line only)
-v Verbose (command line only)
-F <parmfile> Requests parameter file (command line only)
-G <name> Application Group Name
-S <startdate,enddate[,format]> Segment date range
-U <user_alias> User alias that appears in System Log messages
-X <load_ID> LoadId to use for OnDemand
-1 <trace_file> Trace file (command line only)
-2 <trace_level> Trace level (command line only)

Flags in a parameter file must be delimited by brackets

Explanation

The arsdoc command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. See the Content Manager OnDemand Administration Guide for more information. Verify and correct the command parameters and resubmit the command.

ARS6125I

Usage: arsdoc hold_release -h hostname [-u <userid>] [-p <passwd>] [-U <user_alias>] [-v] (-F <parmfile> | ((-i <sql_query> | -q <namedquery> | -t <search_str> | -T <search_str> | -X <load_ID>) -l <holdname> [-f <foldername>] [-G <name>] [-S <startdate,enddate[,format]>])) [-1 <trace_file>] [-2 <trace_level>]

Version: *version*

-f <foldername> OnDemand folder (required in parm file)
-h <hostname> OnDemand Hostname (command line only)
-i <sql_query> SQL query string
-l <holdname> OnDemand hold
-p <passwd> OnDemand User Login Password Stash File (command line only)
-q <namedquery> Public named query
-u <userid> OnDemand User Login Name (command line only)
-v Verbose (command line only)
-F <parmfile> Requests parameter file (command line only)
-G <name> Application Group Name
-S <startdate,enddate[,format]> Segment date range
-T <search_string> Full text search
-U <user_alias> User alias that appears in System Log messages
-X <load_ID> LoadId to use for OnDemand
-1 <trace_file> Trace file (command line only)
-2 <trace_level> Trace level (command line only)
Flags in a parameter file must be delimited by brackets

Explanation

The arsdoc command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. See the Content Manager OnDemand Administration Guide for more information. Verify and correct the command parameters and resubmit the command.

ARS6126I

Usage: arsdoc cfsod_fed -h hostname [-u <userid>] [-p <passwd>] [-U <user_alias>] [-v] (-F <parmfile> | ((-i <sql_query> | -l <holdname> | -q <namedquery> | -t <search_str> | -T <search_str> | -X <load_ID>) [-f <foldername>] [-G <name>] [-S <startdate,enddate[,format]>])) [-1 <trace_file>] [-2 <trace_level>]

Version: *version*

-f <foldername> OnDemand folder (required in parm file)
-h <hostname> OnDemand Hostname (command line only)
-i <sql_query> SQL query string
-l <holdname> OnDemand hold
-p <passwd> OnDemand User Login Password Stash File (command line only)
-q <namedquery> Public named query
-u <userid> OnDemand User Login Name (command line only)
-v Verbose (command line only)
-F <parmfile> Requests parameter file (command line only)

-G <name> Application Group Name
-S <startdate,enddate[,format]> Segment date range
-T <search_string> Full text search
-U <user_alias> User alias that appears in System Log messages
-X <load_ID> LoadId to use for OnDemand
-1 <trace_file> Trace file (command line only)
-2 <trace_level> Trace level (command line only)
Flags in a parameter file must be delimited by brackets

Explanation

The arsdoc command contains an incorrect parameter.

User response

The message response outlines the valid parameters for this command. See the Content Manager OnDemand Administration Guide for more information. Verify and correct the command parameters and resubmit the command.

ARS6128E

Hold add unsuccessful

Explanation

The command failed when attempting to add a document to a hold.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6129I

Adding *num_documents* documents to hold %2

Explanation

This message is for your information only.

User response

No action is required.

ARS6130E

The hold name must be provided to continue the operation.

Explanation

The hold name was not provided.

User response

Resubmit the command and specify the -l parameter and the name of the hold.

ARS6131I

Searching for hold '*folder_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6132E

Enhanced Retention Management is not supported on server '*server_name*'.

Explanation

The server does not support Enhanced Retention Management.

User response

Resubmit the command with a server name that supports Enhanced Retention Management.

ARS6133E

Unable to get hold information. The hold does not exist or the user does not have permission to access the hold.

Explanation

The command failed when attempting to find the specified hold on the specified server.

User response

Verify that the hold exists on the server. Verify that the user has permission to access the hold. Then resubmit the command.

ARS6134I

Releasing *num_documents* documents from hold %2

Explanation

This message is for your information only.

User response

No action is required.

ARS6135I

Hold release successful

Explanation

This message is for your information only.

User response

No action is required.

ARS6136E

Hold release unsuccessful

Explanation

The command failed when attempting to release a document from a hold.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6137I

Sending documents to CFS-OD successful

Explanation

This message is for your information only.

User response

No action is required.

ARS6138E

Sending documents to CFS-OD unsuccessful

Explanation

The command failed when attempting to send documents to CFS-OD.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6139I

Sending *num_documents*documents to CFS-OD

Explanation

This message is for your information only.

User response

No action is required.

ARS6140E

Content Federation Services (CFS-OD) is not supported on server '*server_name*'.

Explanation

The server does not support Content Federation Services (CFS-OD).

User response

Resubmit the command with a server name that supports Content Federation Services (CFS-OD).

ARS6141E

Index values that have been stored in database field '*field_name*' cannot be changed.

Explanation

Index values that have been stored in the database field cannot be changed because the database field has been identified as a field that cannot be updated.

User response

Resubmit the command with field values that can be that updated.

ARS6142E

The -f, -i, -l, -q, -t, -x, -S, or -T flag cannot be used with the -X flag.

Explanation

An incorrect parameter was specified.

User response

Resubmit the command without the invalid parameters.

ARS6143E

Unable to open the file: *file_name* (ERRNO = *err_no*)

Explanation

The specified file does not exist or the permissions do not allow the file to be opened.

User response

Verify that the file exists. Verify that the file permissions allow the file to be opened. Then resubmit the command.

ARS6144E

The Common Store API cannot read the file (*file_name*) starting from offset position (*offset_position*) for a length of (*length_position*): *file_name* (ERRNO = *err_no*)

Explanation

The Common Store API failed when attempting to read the file.

User response

Verify and correct the offset and length values for the file.

ARS6145E

The command is unable to write to the file: *file_name* (ERRNO = *err_no*)

Explanation

The command failed when attempting to write to the file.

User response

See your operating platform documentation for more information on the ERRNO. Verify that the location for the file contains sufficient free space to write to the file. Resubmit the command.

ARS6146E

The directory *dirpath* does not exist or cannot be accessed. *file_name* (ERRNO = *err_no*)

Explanation

The specified directory does not exist on the server or can not be accessed.

User response

See your operating platform documentation for more information on the ERRNO. Verify that the directory exists and that the user has access to the directory and resubmit the command.

ARS6147E

Full Text Search is not supported on server '*server_name*'.

Explanation

The server does not support Full Text Search.

User response

Resubmit the command with a server name that supports Full Text Search.

ARS6148I

Usage: arsdoc fti_add -h hostname [-u <userid>] [-p <passwd>] [-U <user_alias>] [-v] (-F <parmfile> | ((-i <sql_query> | -q <namedquery> | -t <search_str> | -T <search_str> | -X <load_id>) -l <holdname> [-f <foldername>] [-G <name>] [-S <startdate,enddate[,format]>])) [-1 <trace_file>] [-2 <trace_level>]

Version: *version*

-f <foldername> OnDemand folder (required in parm file)
-h <hostname> OnDemand Hostname (command line only)
-i <sql_query> SQL query string
-l <holdname> OnDemand hold
-p <passwd> OnDemand User Login Password (command line only)
-q <namedquery> Public named query
-t <search_string> Server text search
-u <userid> OnDemand User Login Name (command line only)
-v Verbose (command line only)
-F <parmfile> Requests parameter file (command line only)
-G <name> Application Group Name
-S <startdate,enddate[,format]> Segment date range
-T <search_string> Full text search
-U <user_alias> User alias that appears in System Log messages
-X <load_id> LoadId to use for OnDemand
-1 <trace_file> Trace file (command line only)
-2 <trace_level> Trace level (command line only)
Flags in a parameter file must be delimited by brackets EX: [-f foldername]

Explanation

The arsdoc command contains an incorrect parameter.

User response

The message text lists the valid parameters for this command. For more information, see the *Content Manager OnDemand Administration Guide*. Verify and correct the command parameters and resubmit the command.

ARS6149I

Usage: arsdoc fti_release -h hostname [-u <userid>] [-p <passwd>] [-U <user_alias>] [-v] (-F <parmfile> | ((-i <sql_query> | -q <namedquery> | -t <search_str> | -T <search_str> | -X <load_id>) -l <holdname> [-f <foldername>] [-G <name>] [-S <startdate,enddate[,format]>])) [-1 <trace_file>] [-2 <trace_level>]

Version: *version*

-f <foldername> OnDemand folder (required in parm file)
-h <hostname> OnDemand Hostname (command line only)
-i <sql_query> SQL query string
-l <holdname> OnDemand hold
-p <passwd> OnDemand User Login Password (command line only)
-q <namedquery> Public named query
-t <search_string> Server text search
-u <userid> OnDemand User Login Name (command line only)
-v Verbose (command line only)
-F <parmfile> Requests parameter file (command line only)
-G <name> Application Group Name
-S <startdate,enddate[,format]> Segment date range
-T <search_string> Full text search
-U <user_alias> User alias that appears in System Log messages
-X <load_id> LoadId to use for OnDemand
-1 <trace_file> Trace file (command line only)
-2 <trace_level> Trace level (command line only)

Flags in a parameter file must be delimited by brackets EX: [-f foldername]

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. For more information about this command, see the *Administration Guide* for Content Manager OnDemand.

ARS6150I

Full Text Index add was successful.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS6151E

Full Text Index add was unsuccessful.

Explanation

The command failed when attempting to add a document to the Full Text Index.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Software Support.

ARS6152I

Adding *num_documents* documents to Full Text Index.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS6153I

Releasing *num_documents* documents from Full Text Index.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS6154I

Full Text index release was successful.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS6155E

Full Text Index release was unsuccessful.

Explanation

The command failed when attempting to release a document from the Full Text Index.

User response

For more information, see the other messages that were generated by the command and additional messages in the Content Manager OnDemand System Log. If the problem persists, contact IBM Software Support.

ARS6167W

The application group '*applgrp_name*' contains a segment date. For better performance, a segment date range should be specified by using the -S parameter.

Explanation

An application group has a date field that has been designated as a segment field. For better performance, a segment date range should be provided.

User response

Resubmit the command with the -S parameter.

ARS6500I

Usage: `arsadm user -h hostname [-u <userid>] [-p <passwd>] [-v] (-F <parmfile> | ([-a <action>] [-d <desc>] [-e <expire_date>] [-f <format>] [-g <[+]-group1>] -i <userid> [-s <time_out>] [-t <type>] [-w <passwd>] [-A <account>] [-B <bldg>] [-C <company>] [-D <dept>] [-G <cover_page>] [-L <dflt_prtr>] [-N <name>] [-P <phone_no>] [-R <room>] [-T <title>] [-U <uid>] [-X <fax_no>] [-E <email>] [-1 <addr1>] [-2 <addr2>] [-3 <addr3>] [-4 <addr4>]))`

Version: *version*

-a <action>

a Add user

d Delete user

u Update user

-d <desc> Description

-e <expire_date> Date used to delete users

-f <format> Format of date string

-g <[+]-group1> list of userids separated by spaces

+ add user to group

- remove user from group on update

-h <hostname> OnDemand Hostname (command line only)

-i <userid> New or existing userid

-p <passwd> OnDemand User Login Password (command line only)

-s <time_out> Inactivity Time out

-t <type>

a Create appl/appl grps

b Create appl/appl grps & folders

c Create users

d Appl group/folder administrator

e Create groups

f Create folders
 g User administrator
 s System administrator
 u User
 -u <userid> OnDemand User Login Name (command line only)
 -v Verbose (command line only)
 -w <passwd> Password of user being processed
 -A <account> Account information
 -B <bldg> Building
 -C <company> Company
 -D <dept> Department
 -E <email> E-Mail Address
 -F <parmfile> Requests parameter file (command line only)
 -G <cover_page> Cover page
 -L <dflt_prtr> Default printer
 -N <name> Name
 -P <phone_no> Phone number
 -R <room> Room
 -T <title> Title
 -U <uid> UID
 -X <fax_no> Fax number
 -1 <addr1> Address line 1
 -2 <addr2> Address line 2
 -3 <addr3> Address line 3
 -4 <addr4> Address line 4
 Flags in a parameter file must be delimited by brackets EX: [-i userid]

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS6501I

Usage: `arsadm group -h hostname [-u <userid>] [-p <passwd>] [-v] (-F <parmfile> | ([-a <action>] [-d <desc>] -g <groupname> [-i <[+-]user1>] [-o <owner>] [-G <gid>]))`
 Version: *version*
 -a <action>
 a Add group
 d Delete group
 u Update group
 -d <desc> Description
 -g <groupname> New or existing group name
 -h <hostname> OnDemand Hostname (command line only)
 -i <[+-]user1> list of userids separated by spaces
 + add user to group
 - remove user from group on update
 -o <owner> Userid or Group name that owns the group
 -p <passwd> OnDemand User Login Password (command line only)
 -u <userid> OnDemand User Login Name (command line only)
 -v Verbose (command line only)
 -F <parmfile> Requests parameter file (command line only)
 -G <gid> GID
 Flags in a parameter file must be delimited by brackets EX: [-g groupname]

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS6502I

Usage: `arsadm printer -h hostname [-u <userid>] [-p <passwd>] [-v] (-F <parmfile> | ([-a <action>] [-d <desc>] -n <printername> -q <queue> [-t <type>]))`
Version: *version*
-a <action>
a Add printer
d Delete printer
u Update printer
-d <desc> Description
-h <hostname> OnDemand Hostname (command line only)
-n <printername> New or existing printer name
-p <passwd> OnDemand User Login Password (command line only)
-q <queue> Name of PSF printer queue
-t <type>
p Printer
f Fax
i Printer with information
-u <userid> OnDemand User Login Name (command line only)
-v Verbose (command line only)
-F <parmfile> Requests parameter file (command line only)
Flags in a parameter file must be delimited by brackets EX: [-n printername]

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS6503E

The server failed while attempting to get user information.

Explanation

The command failed when attempting to get user information from the server.

User response

See the other messages that the command generated and see messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6504E

The server failed while attempting to get group information.

Explanation

The command failed when attempting to get group information from the server.

User response

See the other messages that the command generated and see messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6505E

The server failed while attempting to get printer information.

Explanation

The command failed when attempting to get printer information from the server.

User response

See the other messages that the command generated and see messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6524E

Userid '*userid*' does not exist.

Explanation

The specified user ID could not be found on the server.

User response

Verify that the user ID exists on the server. Then resubmit the command.

ARS6525E

Group name '*group_name*' does not exist.

Explanation

The specified group name could not be found on the server.

User response

Verify the name of the group and that the group exists on the server. Then resubmit the command.

ARS6538I

Querying for user '*userid*' on server '*server_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6539I

Querying for group '*group_name*' on server '*server_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6700I

Usage: arsexprt -h hostname [-u <userid>] [-p <passwd>] [-v]
(-F <parmfile> | ([-c] [-e <user_group_list>] -i <import_userid>
-s <import_srvr> -t <type> -w <import_passwd> -N <name>))

Version: *version*

-c Ignore warnings

-e <user_group_list> List of users and groups to exclude permissions
(e.g. -e \"user1 +group1 user2 +group2\")

(group names must be preceded by the plus sign)

-h <hostname> OnDemand Hostname (command line only)

-i <import_userid> Import server login userid

-p <passwd> OnDemand User Login Password (command line only)

-s <import_srvr> Server where object will be added

-t <type>

u User

g Group

a Application group

s Storage set

f Folder

p Printer

-u <userid> OnDemand User Login Name (command line only)

-w <import_passwd> Import server login passwd

-v Verbose (command line only)

-F <parmfile> Requests parameter file (command line only)

-N <name> Name of object to export

Flags in a parameter file must be delimited by brackets EX: [-u userid] arsexprt -h hostname [-u *userid*] [-p *passwd*] [-v] (-F *parmfile*) ([-c] [-e *user_group_list*] -i *import_userid*-s *import_srvr*-t *type*-w *import_passwd*-N <name>))

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS6703E

The name of the exported item must be provided to continue the operation.

Explanation

The name is missing from the request.

User response

Resubmit the command with the name of the item to be exported.

ARS6707I

The server operation failed with an 'Unknown' return code.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS6708I

arsexprt completed.

Explanation

This message is for your information only.

User response

No action is required.

ARS6712E

The only options that can be specified with the -F option are -u, -p, -h, -c, -v, -i, -s, and -w.

Explanation

One or more parameters that are not valid with the -F parameter were specified.

User response

Resubmit the command with the correct parameters.

ARS6720E

'*name*' was not found on the '*server_name*' server.

Explanation

The specified name could not be found on the specified server.

User response

Verify that the object exists on the server and that the user has the authority to access the object. Then resubmit the command.

ARS6815E

The import userid must be provided to continue the operation.

Explanation

The user ID for the target server was not specified.

User response

Resubmit the command with a user ID for the target server.

ARS6816E

The import password must be provided to continue the operation.

Explanation

The password for the target server was not specified.

User response

Resubmit the command with a password for the target server.

ARS6817E

The import host name must be provided to continue the operation.

Explanation

The host name of the target server was not specified.

User response

Resubmit the command with the host name of the target server.

ARS6819E

The export type must be provided to continue the operation.

Explanation

The type of export to perform was not specified.

User response

Resubmit the command with the type of export to perform.

ARS6822I

Attempting login for userid '*userid*' on server '*server_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6825I

Processing *object* ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6826I

Querying for users on server '*server_name*'...

Explanation

This message is for your information only.

User response

No action is required.

ARS6827E

A user or group with id '*id*' could not be found on server '*server_name*'.

Explanation

The UID of the user ID or the GID of the group could not be found on the specified server.

User response

Verify the user ID and the name of the group and the name of the server and resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS6828I

Querying for groups on server '*server_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6829I

Querying for storage sets on server '*server_name*'...

Explanation

This message is for your information only.

User response

No action is required.

ARS6830E

'*name*' already exists on server '*server_name*'.

Explanation

The specified object already exists on the specified server.

User response

Resubmit the command with a different object name.

ARS6831E

The server failed while adding a storage set.

Explanation

The command failed when attempting to add a storage set.

User response

See the other messages that were generated by the command and see messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6832E

The server failed while adding a storage node to a storage set.

Explanation

The command failed when attempting to add a storage node to a storage set.

User response

See the other messages that were generated by the command and see messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6833E

The server host names must be different to continue the operation.

Explanation

The source server name and the target server name are the same.

User response

Resubmit the command and specify a name for the source server that is different than the name of the target server.

ARS6834E

Unable to identify the name of the default printer.

Explanation

The name of the default printer cannot be determined.

User response

Verify that the user has access to the printer so that the printer name can be determined. Then resubmit the command.

ARS6835E

The application group '*applgrp_name*' does not exist or the user does not have permission to access the application group.

Explanation

The specified application group could not be found on the server or the user does not have permission to access the application group.

User response

Verify the name of the application group and that the application group exists on the server. Verify that the user has permission to access the application group. Then resubmit the command.

ARS6836I

Querying for application group '*applgrp_name*' on server '*server_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6837E

A storage set with id '*sid*' could not be found on server '*server_name*'.

Explanation

The command failed because a storage set could not be found on the specified server.

User response

Verify the name and ID of the storage set and the name of the server. Resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS6838E

A printer with id '*pid*' could not be found on server '*server_name*'.

Explanation

The command failed because a printer could not be found on the specified server.

User response

Verify the name and ID of the printer and the name of the server. Verify that the user ID performing the export has permission to see the printer. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS6839I

Querying for folder '*folder_name*' on server '*server_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS6840E

The folder '*folder_name*' does not exist or the user does not have permission to access the folder.

Explanation

The command failed because the specified folder could not be found on the server.

User response

Verify the name of the folder and that the folder exists on the server. Verify that the user has permission to access the folder. Then resubmit the command. If the problem persists, contact your IBM Service Representative.

ARS6841E

The server failed while deleting a storage set.

Explanation

The server operation failed when attempting to delete a storage set.

User response

See the other messages that were generated by the command and see messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6842E

The server failed while updating a storage set.

Explanation

The server operation failed when attempting to update a storage set.

User response

See the other messages that were generated by the command and see messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6843E

The server failed while deleting a storage node from a storage set.

Explanation

The server operation failed when attempting to delete a node from a storage set.

User response

See the other messages that were generated by the command and see messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS6844E

The server failed while updating a storage node in a storage set.

Explanation

The server operation failed when attempting to update a storage node.

User response

See the other messages that were generated by the command and see messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS7000I

Usage: arsmdmgr -h hostname [-u <userid>] [-p <passwd>] [-v]
[-c <out_dir>] -d <in_dir> [-e <delim>] [-f <foldername>]
[-l] -m <min_nbr> [-n <nbr_drives>] [-t <seconds>] [-F <ext>]
-T <max_wait_time> [-r] [-H] [-I]

Version: *version*

-c <out_dir> Output directory
-d <in_dir> Input directory
-e <delim> Character separator between index values
-f <foldername> OnDemand folder
-h <hostname> OnDemand Hostname
-l Write messages to log file
-m <min_nbr> Minimum # of entries present before retrieval begins
-n <nbr_drives> Maximum # of drives per OnDemand Object server
-p <passwd> OnDemand User Login Password
-r Perform reconciliation processing
-t <seconds> # of seconds to wait before looking for requests
-u <userid> OnDemand User Login Name
-v Verbose
-F <ext> File extension of the input parameter files
-H Request file is in hit list format
-I Write hits to a file
-R <name> Request file name
-T <max_wait_time> # of seconds to wait before processing a request

Explanation

An incorrect parameter was specified for the command. The valid parameters are given in the message and are explained in the Content Manager OnDemand Administrator's Guide.

User response

Resubmit the command with the correct parameters.

ARS7001I

arsmdmgr completed.

Explanation

This message is for your information only.

User response

No action is required.

ARS7002E

The input directory must be provided to continue the operation.

Explanation

The input directory was not specified.

User response

Resubmit the command with a valid input directory.

ARS7003E

The directory '*dirpath*' does not exist or cannot be accessed.

Explanation

The specified directory could not be found or accessed.

User response

Verify that the directory exists and that the user has access to the directory. Then resubmit the command.

ARS7004E

The minimum number of requests to process must be provided to continue the operation.

Explanation

The minimum number of requests to process was not specified.

User response

Resubmit the command with the minimum number of requests to process.

ARS7005E

The maximum amount of time to wait to process a request must be provided to continue the operation.

Explanation

The maximum amount of time to wait was not specified.

User response

Resubmit the command with the maximum amount of time to wait.

ARS7006E

The folder field value of '*field_value*' is not valid for field '*field_name*' in request '*request_identifier*'.

Explanation

The specified value is not valid for the specified field.

User response

Resubmit the command with a valid value for the field.

ARS7008E

The file doesn't contain any records.

Explanation

The request file does not contain any records.

User response

Resubmit the command with a file that contains request records.

ARS7009E

Unable to submit requests with command '*command*'.

Explanation

The specified command failed.

User response

Verify that the environment variable ARS_MEDMGR is set correctly and that the command exists on the system. Then resubmit the command.

ARS7010I

The -d, -F, -I, -n, -m, -r, -t, and -T flags are being ignored in this session.

Explanation

This message is for your information only.

User response

No action is required.

ARS7011I

Logging off the server.

Explanation

This message is for your information only.

User response

No action is required.

ARS7012I

File '*file_name*' renamed to '*file_name_new*'.

Explanation

This message is for your information only.

User response

No action is required.

ARS7013I

Building hit list for '*folder_name*' ...

Explanation

This message is for your information only.

User response

No action is required.

ARS7014I

Hit list successful

Explanation

This message is for your information only.

User response

No action is required.

ARS7015E

Hit list unsuccessful

Explanation

The command failed when attempting to generate the document list.

User response

See the other messages that were generated by the command and see additional messages in the Content Manager OnDemand System Log for more information. If the problem persists, contact your IBM Service Representative.

ARS7016E

The -r flag and the -H flag cannot be used together.

Explanation

Reconciliation processing (-r) cannot be performed when the request file is in hit list format (-H).

User response

Resubmit the command with either the -r parameter or the -H parameter.

ARS7100I

Usage: arsafpd [-d [-t] [-w] | -s] -i <file> [-1 <trace_file>] [-2 <trace_level>]

Version: *version*

-d Display of AFP structured fields

-i <in_file> Input filename

-s Document sniffer

-t Process structure field triplets (only for -d)

-w Disable warning messages (only for -d)

-1 <trace_file> Trace file

-2 <trace_level> Trace level

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. For more information about this command, see the *Content Manager OnDemand Administration Guide*.

ARS7101W

Warning: Structured field length was incorrect in record *#number*, attempting to continue...

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7102W

Warning: Prefix length does not match the structured field length in record *#number*, attempting to continue...

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7103E

The AFP data contains a structured field header in record *#number* that is not correct.

Explanation

The AFP data contains a structured field header that is not correct.

User response

Verify that the AFP data conforms to the AFP specification. For more information about the correct format of the structured field, see *Mixed Object Document Content Architecture Reference*.

Related information

[Mixed Object Document Content Architecture Reference](#)

ARS7104I

Document type: *doc_type*.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7105W

Warning: No TLE structured fields were found for the group ending with record *#number*.

Explanation

The AFP Begin Named Group was created without group TLE structured fields. Group TLE structured fields are required to load the file into Content Manager OnDemand.

User response

Talk to your AFP producer about regenerating the file with group TLE structured fields.

ARS7106W

Warning: No group TLE structured fields were found in the file.

Explanation

The AFP file was created without group TLE structured fields. Group TLE structured fields are required to load the file into Content Manager OnDemand.

User response

Talk to your AFP producer about regenerating the file with group TLE structured fields.

Note: TLEs are not required when loading into Content Manager OnDemand for i.

ARS7107I

Group TLE structured fields were found.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7108I

AFP structured fields were found; however, the file might be mixed mode (AFP and line data) or be invalid AFP.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7109I

File contains a two byte prefix before each record.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7110I

Carriage control type appears to be: *type*.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7111I

Pages appear to be delimited with a formfeed (0x0C). If using ACIF, the asciinp and asciinpe user exit might be required.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7112W

Warning: The last record does not contain the delimiter character(s).

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7113I

Records appear to be fixed length: *number_of_bytes*.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7114I

Records appear to be delimited by hex character(s): *hex_character*.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7115I

Codepage appears to be: *code_page_number*.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7116W

Warning: No page information was found.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7117W

Warning: A triplet with a length of zero was found in record # *number*.

Explanation

The AFP triplet was not correctly generated.

User response

Verify that the AFP data conforms to the AFP specification. Refer to the *Mixed Object Document Content Architecture Reference* for more information about the correct format of the triplet.

ARS7118W

The maximum number of warning messages were issued.

Explanation

This message is for informational purposes only. The `arsafpd` command issues no more than 10 messages.

User response

No action is required.

ARS7514E

Unable to delete the storage set. The storage set contains application groups.

Explanation

The command failed when attempting to delete the storage set because one or more application groups are assigned to the storage set. A storage set cannot be deleted if one or more application groups are assigned to the storage set.

User response

Delete the application groups that are assigned to the storage set. Then resubmit the command to delete the storage set.

ARS7525E

Node information must be specified when updating a storage node.

Explanation

Information that is required to update a storage node was not specified.

User response

Resubmit the command with the required storage node information.

ARS7526E

One primary node on each server must be identified as the node where data will be loaded.

Explanation

You must specify a primary node on which to load data. If you are loading data on multiple servers, you must specify the primary node for each one.

User response

For each server, set the load data option on the primary node to which data will be loaded.

ARS7527E

More than one primary node on server '*server_name*' has been identified as the node where data will be loaded.

Explanation

More than one primary node on a server was identified as the node to which data will be loaded.

User response

Set the load data option on only one primary node on each server.

ARS7528E

More than one node has been identified as the node where data will be loaded.

Explanation

When the load type is fixed, only one storage node can be identified as the node to which data will be loaded.

User response

Set the load data option on only one storage node in the storage set.

ARS7529E

The storage node password must be at least one non-blank character.

Explanation

The storage node password was blank.

User response

Resubmit the command with a valid storage node password.

ARS7530E

The storage node host name cannot be all blank characters.

Explanation

The host name contains all blank characters.

User response

Resubmit the command with a valid host name.

ARS7531I

Adding node '*node_name*' in storage set '*set_name*' ...

Explanation

The specified node is being added to the specified storage set. This message is for your information only.

User response

No action is required.

ARS7532I

Deleting node '*node_name*' in storage set '*set_name*' ...

Explanation

The specified node is being deleted from the specified storage set. This message is for your information only.

User response

No action is required.

ARS7533I

Updating node '*node_name*' in storage set '*set_name*' ...

Explanation

The specified node is being updated in the specified storage set. This message is for your information only.

User response

No action is required.

ARS7571E

Storage set '%1' was not found.

Explanation

The specified storage set does not exist on the server.

User response

Verify the name of the storage set and that the storage set exists on the server. Correct the Batch Admin input XML file and resubmit the command.

ARS7572E

Storage node '%1' was not found.

Explanation

The specified storage node does not exist on the server.

User response

Verify the name of the storage node and that the storage node exists on the server. Correct the Batch Admin input XML file and resubmit the command.

Chapter 2. OAM support services ABEND codes

ABEND code U-0039 (X'0027') is issued by the OAM support services when a failure or error condition occurs for which normal program running cannot continue.

An associated reason code (usually contained in general register 15 at the time of ABEND) further describes the condition. The reason code is an 8-digit hexadecimal value of the form *mmmmrrrr* where:

mmmm (the high order 4-digits)

is the binary coded decimal representation of an associated message number. If these digits are 0000 then no message was issued.

rrrr (the low order 4-digits)

is a reason code that identifies the failure or error condition. The reason code descriptions that are listed in [“OAM support services reason codes”](#) on page 295 correspond to the *rrrr* digits.

Unless indicated otherwise, the following items apply to all reason codes:

System Action:

The system might create LOGREC records and might also produce an SVC dump.

System Programmer Response:

Search problem reporting databases for a fix for the problem. If no fix exists, please have the following diagnostic and problem determination materials available and contact your IBM Service Representative:

- Binary machine readable dump data sets (for example, SVC dump and SYSMDUMP data sets). Note that print image formatted dumps written to data sets referenced by the SYSUDUMP and SYSABEND DD statements are, in general, inadequate when performing problem determination.
- Formatted LOGREC records related to the failure. See the *Environmental Record Editing and Printing Program (EREP) User's Guide*, GC35-0151 and the *Environmental Record Editing and Printing Program (EREP) Reference*, GC35-0152 for information regarding the selection and formatting of LOGREC records.
- Relevant sections of the z/OS system log.
- All related job logs and JCL listings.

OAM support services reason codes

The following reason codes are associated with ABEND code U-0039 (X'0027') that is issued by the OAM support services when a failure or error condition occurs for which normal program running cannot continue. See [Chapter 2, “OAM support services ABEND codes,”](#) on page 295 for general information about the reason codes, including the system action and the system programmer response.

0250

Queueing services request error: An invalid combination of storage attributes has been specified on a queue or queue element BUILD request.

Module

ARS3QMGR

0251

Queueing services request error: The caller is not running in task mode and is not properly authorized.

Module

ARS3QMGR

0252

Queueing services error: An unexpected return code was received from the z/OS lock manager when attempting to obtain a lock.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Indicates which lock was being manipulated.

1:

LOCAL

2:

CMS

R14

Contains the lock manager (SETLOCK) return code.

Module

ARS3QMGR

0253

Queueing services error: An unexpected return code was received from the z/OS lock manager when attempting to release a lock.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Indicates which lock was being manipulated.

1:

LOCAL

2:

CMS

R14

Contains the lock manager (SETLOCK) return code.

Module

ARS3QMGR

0254

Queueing services error: A queue validity error was detected. An element was expected to reside on a queue, however, it appears that the element is not properly queued.

Module

ARS3QMGR

0255

Queueing services error: A queue validity error was detected. An element was found that was expected to not reside on a queue, however, its queue header pointer was non-zero.

Module

ARS3QMGR

0256

Queueing services error: The queue serialization level value within the queue header was invalid.

Module
ARS3QMGR

0257

Queueing services request error: An attempt was made to destroy an element that still resided on a queue.

Module
ARS3QMGR

0258

Queueing services request error: An attempt was made to destroy a queue header that described a non-empty queue.

Module
ARS3QMGR

0259

Queueing services request error: The service was invoked by an unauthorized caller through a mechanism other than the workstation instruction.

Module
ARS3QMGR

025A

Queueing services request error: The caller is not running in task mode and has not supplied a TCB pointer to associate with VSM requests.

Module
ARS3QMGR

025B

Queueing services error: An unexpected return code was received from the TCBTOKEN service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the TCBTOKEN plist.

R14

Contains the TCBTOKEN service return code.

Module
ARS3QMGR

0270

Initialization failure: One or more support modules could not be loaded.

Module
ARS3OCT

0271

Explanation

An unexpected return code was received from ATTACH. At the time of ABEND registers are loaded as follows:

R0

Contains the address of the ATTACH plist.

R14

Contains the ATTACH service return code.

Module

ARS3OCT

0272

Explanation

An unexpected return code was received from the z/OS lock manager when attempting to obtain a lock. At the time of ABEND registers are loaded as follows:

R0

Indicates which lock was being manipulated.

1:

LOCAL

2:

CMS

R14

Contains the lock manager (SETLOCK) return code.

Module

ARS3OCT

0273

An unexpected return code was received from the z/OS lock manager when attempting to release a lock.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Indicates which lock was being manipulated.

1:

LOCAL

2:

CMS

R14

Contains the lock manager (SETLOCK) return code.

Module

ARS3OCT

0274

The end-of-task exit program was entered for a TCB that did not have a corresponding element on the ARS3CAS_TCBQH subtask queue.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the ARS3QMP structure.

R2

Contains the TCB pointer presented to the ETRX.

R14

Contains the ARS3QMGR service return code.

Module

ARS3OCT

0275

Initialization error: An unacceptable value was specified for the number of ARS3OSR tasks to be attached.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the specified task count.

Additional Problem Determination Information: OAM services initialization parameters are contained in the `ars.cfg` file, which resides in the `/usr/lpp/ars/V10R1M0/config` directory. The number of ARS3OSR tasks to be attached is specified as the operand of the `ARS_NUM_OAMSRVR` statement. The value specified must be non-negative and less than or equal to 30.

Module

ARS3OCT

0276

The attempt to establish an ESTAEX recovery environment was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the ESTAEX reason code.

R14

Contains the ESTEAX reason code.

Module

ARS3OCT

027A

An unexpected return code was received from the ARS3QMGR service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the ARS3QMP struct.

R14

Contains the ARS3QMGR service return code.

Module

ARS3OCT

027B

An unexpected return code was received from the TCBTOKEN service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the TCBTOKEN plist.

R14

Contains the TCBTOKEN service return code.

Module

ARS3OCT

027D

An unexpected return code was received from an IEANTxx service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Indicates which service was being requested.

4:

IEANTCR

8:

IEANTRT

C:

IEANTDL

R14

Contains the IEANTxx return code.

Module

ARS3OCT

027E

A subtask did not terminate when requested to do so. The subtask is being forcibly terminated using CALLRTM.

Module

ARS3OCT

027F

During subsystem shutdown, not all subtasks could be terminated.

Module

ARS3OCT

0292

An unexpected return code was received from the z/OS lock manager when attempting to obtain a lock.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Indicates which lock was being manipulated.

1:

LOCAL

2:

CMS

R14

Contains the lock manager (SETLOCK) return code.

Module

ARS3OSR

0293

An unexpected return code was received from the z/OS lock manager when attempting to release a lock.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Indicates which lock was being manipulated.

1:

LOCAL

2:

CMS

R14

Contains the lock manager (SETLOCK) return code.

Module

ARS3OSR

0296

The attempt to establish an ESTAEX recovery environment was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the ESTAEX reason code.

R14

Contains the ESTEAX reason code.

Module

ARS3OSR

029A

An unexpected return code was received from the ARS3QMGR service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the ARS3QMP structure.

R14

Contains the ARS3QMGR service return code.

Module

ARS3OSR

029B

An unexpected return code was received from the TCBTOKEN service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the TCBTOKEN plist.

R14

Contains the TCBTOKEN service return code.

Module

ARS3OSR

037A

An unexpected return code was received from the ARS3QMGR service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the ARS3QMP structure.

R14

Contains the ARS3QMGR service return code.

Module

ARS3ORI

Chapter 3. ABEND codes for the JES spool data capture facility

ABEND code U-0039 (X'0027') is issued when a failure or error condition occurs for which normal program running cannot continue. An associated reason code (usually contained in general register 15 at the time of ABEND) further describes the condition.

The reason code is an eight-digit hexadecimal value of the form *mmmmrrrr* where:

mmmm (the high order four digits)

is the binary coded decimal representation of an associated message number. If these digits are 0000 then no message was issued.

rrrr (the low order four digits)

is a reason code that identifies the failure or error condition. The reason code descriptions that are listed beginning on page “JES spool data capture facility reason codes” on page 303 correspond to the *rrrr* digits.

Unless indicated otherwise, the following items apply to all reason codes:

System Action:

The system might create LOGREC records and might also produce an SVC dump.

System Programmer Response:

Search problem reporting data bases for a fix for the problem. If no fix exists, collect the following diagnostic and problem determination information and then contact the IBM support center:

- Binary machine readable dump data sets (for example, SVC dump and SYSMDUMP data sets). Note that print image formatted dumps written to data sets referenced by the SYSUDUMP and SYSABEND DD statements are, in general, inadequate when performing problem determination.
- Formatted LOGREC records related to the failure. See the *Environmental Record Editing and Printing Program (EREP) User's Guide*, GC35-0151 and the *Environmental Record Editing and Printing Program (EREP) Reference*, GC35-0152 for information regarding the selection and formatting of LOGREC records.
- Relevant sections of the z/OS system log.
- All related job logs and JCL listings.

Reason code X'029C' is issued when the internal procedure which prepares OAM Query Response data structures for use was presented an insufficiently sized structure construction area. At the time of ABEND, registers are loaded as follows:

R0

Contains the length of the construction area.

R14

Contains the address of the construction area.

JES spool data capture facility reason codes

The following reason codes are associated with ABEND code U-0039 (X'0027') that is issued by the JES spool data capture facility (ARSYSFIN) when a failure or error condition occurs for which normal program running cannot continue. See Chapter 3, “ABEND codes for the JES spool data capture facility,” on page 303 for general information about the reason codes, including the system action and the system programmer response.

025C

Explanation

Queue header or queue element validation failed for one of the following reasons:

- The structure pointer was either null or was not on a doubleword boundary.
- The expected ID string was not found in the structure.

Module

ARS3QMGR

025D

Explanation

Queue header validation failed for one of the following reasons:

- One, but not both, of the top or bottom of queue pointers was null.
- One, but not both, of the top or bottom of queue pointers pointed to the queue header.

Module

ARS3QMGR

025E

During queue verification, a serialization error was detected while attempting to restore the queue element chain.

Module

ARS3QMGR

025F

During queue verification, a serialization error was detected while attempting to remove the queue element chain.

Module

ARS3QMGR

0260

During queue verification, an element chaining or element condition error was detected.

Module

ARS3QMGR

0261

A request has been received to dequeue a specific element, however, the element was not found on the specified queue.

Module

ARS3QMGR

0401

The attempt to OPEN a DCB was not successful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Points to an area consisting of the DDNAME immediately followed by the DCB.

R14

Contains the OPEN return code.

Module

ARSYSPIN

0402

The attempt to create a capture data space was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the DSPSERV reason code.

R2

Points to the DSPSERV interface plist.

R14

Contains the DSPSERV return code.

Module

ARSYSPIN

0403

The attempt to create an access list entry for the capture data space was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the ALESERV reason code.

R2

Points to the ALESERV interface plist.

R14

Contains the ALESERV return code.

Module

ARSYSPIN

0404

The attempt to delete the capture data space was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the DSPSERV reason code.

R2

Points to the DSPSERV interface plist.

R14

Contains the DSPSERV return code.

Module

ARSYSPIN

0405

The attempt to delete the access list entry for the capture data space was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the ALESERV reason code.

R2

Points to the ALESERV interface plist.

R14

Contains the ALESERV return code.

Module

ARSYSPIN

0470

One or more support modules could not be loaded.

Module

ARSYSPIN

0471

An unexpected return code was received from ATTACH.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the ATTACH plist.

R14

Contains the ATTACH service return code.

Module

ARSYSPIN

0472

An unexpected return code was received from the MVS lock manager when attempting to obtain a lock.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Indicates which lock was being manipulated.

- 1:**
LOCAL
- 2:**
CMS

R14

Contains the lock manager return code.

Module
ARSYSPIN

0473

An unexpected return code was received from the MVS lock manager when attempting to release a lock.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Indicates which lock was being manipulated.

- 1:**
LOCAL
- 2:**
CMS

R14

Contains the lock manager return code.

Module
ARSYSPIN

0474

The end-of-task exit program was entered for a TCB that did not have a corresponding element on the ARSYCAS_TCBQH subtask queue.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the ARS3QMP structure.

R2

Contains the TCB pointer presented to the ETXR.

R14

Contains the ARS3QMGR service return code.

Module
ARSYSPIN

0476

The attempt to establish an ESTAEX recovery environment was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the ESTAEX reason code.

R14

Contains the ESTAEX return code.

Module

ARSYSPIN

047A

An unexpected return code was received from the ARS3QMGR service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the ARS3QMP structure.

R14

Contains the ARS3QMGR service return code.

Module

ARSYSPIN

047B

An unexpected return code was received from the TCBTOKEN service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the TCBTOKEN plist.

R14

Contains the TCBTOKEN service return code.

Module

ARSYSPIN

047D

An unexpected return code was received from an IEANTxx service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Indicates which service was being requested:

4:

IEANTCR

8:

IEANTRT

C:

IEANTDL

R14

Contains the IEANTxx return code.

Module

ARSYSPIN

047E

A subtask did not terminate when requested to do so. The subtask is being forcibly terminated using CALLRTM.

Module
ARSYSPIN

047F

During subsystem shutdown, not all subtasks could be terminated.

Module
ARSYSPIN

0480

An IEALSQRY request was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R14

Contains the IEALSQRY return code.

Module
ARSYSPIN

0490

A request has been made to interact with the JES3 subsystem, however, the current unit of work is not running under the control of JES3.

Module
ARSYSSI

0491

An unexpected return code was received from the MVS subsystem request router.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the IEFSSREQ return code.

R14

Contains the address of the ARSYCBSI structure.

Module
ARSYSSI

0492

An unexpected return code was received from the MVS lock manager when attempting to obtain a lock.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Indicates which lock was being manipulated.

- 1:**
LOCAL
- 2:**
CMS

R14

Contains the lock manager return code.

Module
ARSYSSI

0493

An unexpected return code was received from the MVS lock manager when attempting to release a lock.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Indicates which lock was being manipulated.

- 1:**
LOCAL
- 2:**
CMS

R14

Contains the lock manager return code.

Module
ARSYSSI

0494

An unexpected return code was received from JES in response to a SAPI request.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the SSOBRETN value.

R14

Contains the address of the ARSYCBSI structure.

Module
ARSYSSI

0496

The attempt to establish an ESTAEX recovery environment was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the ESTAEX reason code.

R14

Contains the ESTAEX return code.

Module
ARSYSSI

049A

An unexpected return code was received from the ARS3QMGR service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the ARS3QMP structure.

R14

Contains the ARS3QMGR service return code.

Module
ARSYSSI

049B

An unexpected return code was received from the TCBTOKEN service.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the TCBTOKEN plist.

R14

Contains the TCBTOKEN service return code.

Module
ARSYSSI

049C

An unexpected return code was received from the DSPSERV service when attempting to release data space pages.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the DSPSERV reason code.

R2

Contains the DSPSERV interface plist.

R14

Contains the DSPSERV return code.

Module
ARSYSSI

049D

An unexpected return code was received from ATTACH.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the address of the ATTACH plist.

R14

Contains the ATTACH service return code.

Module

ARSYSSI

04A9

A request to deallocate a transfer data set was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the DYNALLOC request block S99RSC field.

R14

Contains the S99RB address.

Module

ARSYSSI

04AA

An attempt to OPEN a transfer file DCB was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R14

Contains the DCB address.

Module

ARSYSSI

04AB

A request to dynamically allocate (DYNALLOC) a transfer data set was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the DYNALLOC request block S99RSC field.

R14

Contains the S99RB address.

Module

ARSYSSI

04AC

A request to deallocate a spool file was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the DYNALLOC request block S99RSC field.

R14

Contains the S99RB address.

Module

ARSYSSI

04AD

An attempt to close a spool file ACB was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R14

Contains the ACB address.

Module

ARSYSSI

04AE

An attempt to open a spool file ACB was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R14:

Contains the ACB address.

Module

ARSYSSI

04AF

A request to dynamically allocate (DYNALLOC) a spool file was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the DYNALLOC request block S99RSC field.

R14

Contains the S99RB address.

Module

ARSYSSI

04B0

An IEALSQRY request was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R14

Contains the IEALSQRY return code.

Module

ARSYSSI

04B3

The attempt to create an access list entry for the capture data space was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0:

Contains the ALESERV reason code.

R2:

Points to the ALESERV interface plist.

R14:

Contains the ALESERV return code.

Module

ARSYSSI

04B5

The attempt to delete the access list entry for the capture data space was unsuccessful.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the ALESERV reason code.

R2

Points to the ALESERV interface plist.

R14

Contains the ALESERV return code.

Module

ARSYSSI

04D0

An invalid user exit interface driver action code was specified.

Explanation

At the time of ABEND registers are loaded as follows:

R0

Contains the ARSYUXIP address.

Module

ARSYUXI

JES spool data capture facility messages

The following messages are associated with the JES spool data capture facility (ARSYSPIN).

ARSY0100E

Unable to open <filename> (errno: <integer> (x'<hexdigits>'))

Explanation

The attempt to open the specified file was unsuccessful. The C runtime errno value (shown in decimal and hexadecimal) is described in the C++ runtime reference.

The most likely cause of the failure is a missing DD statement.

Module

ARSYPXP

Related information

[OS/390 C++ Run-Time Library Reference \(SC28-1663\)](#)

ARSY0101E

fldata() failed for <filename> (RC: <integer> (x'<hexdigits>'))

Explanation

The attempt to retrieve descriptive information for the specified file was unsuccessful. For a description of the fldata() function return values, see the C++ runtime reference.

Module

ARSYPXP

Related information

[OS/390 C++ Run-Time Library Reference \(SC28-1663\)](#)

ARSY0102E

Error on fread() of file <filename>

Explanation

An attempt to read a logical record from the specified file was unsuccessful. This message is usually followed by a message beginning with EDC, which further describes the error.

Module

ARSYPXP

ARSY0103I

<<options statement text>>

Explanation

This message echoes the text of a given control statement.

Module

ARSYPXP

ARSY0104E

Syntax error - keyword delimiter not found

Explanation

The equal sign (=) delimiter that separates a keyword from its operand was not found on the current control statement. (That is, the statement identified by the most recent preceding ARSY0103I message.)

Module
ARSYPXP

ARSY0105E

Unrecognized keyword: <string>

Explanation

The current control statement keyword (that is, the text to the left of the equal sign) is not valid.

Module
ARSYPXP

ARSY0106E

Keyword operand not supplied

Explanation

No text was found following the keyword delimiter on the current control statement.

Module
ARSYPXP

ARSY0107E

Operand rightside delimiter not found

Explanation

The operand for the current control statement did not contain the expected delimiter on the right. For example, if the operand for the current control statement keyword is expected to be contained within parentheses, the right parenthesis character was not found. See the ARSYSPIN program reference in the *IBM Content Manager OnDemand for z/OS: Administration Guide* for the expected operand characteristics of a given keyword.

Module
ARSYPXP

ARSY0108E

Operand leftside delimiter not found

Explanation

The operand for the current control statement did not contain the expected delimiter on the left. For example, if the operand for the current control statement keyword is expected to be contained within parentheses, the left parenthesis character was not found. See the ARSYSPIN program reference in the *IBM Content Manager OnDemand for z/OS: Administration Guide* for the expected operand characteristics of a given keyword.

Module
ARSYPXP

ARSY0109E

Invalid operand length

Explanation

The supplied operand for the current control statement keyword is either too short or too long. See the ARSYSPIN program reference in the *IBM Content Manager OnDemand for z/OS: Administration Guide* for the expected operand characteristics of a given keyword.

Module

ARSYPXP

ARSY0110E

True/False operand expected

Explanation

A Boolean operand is expected for the current control statement keyword. See the ARSYSPIN program reference in the *IBM Content Manager OnDemand for z/OS: Administration Guide* for the valid Boolean operand values.

Module

ARSYPXP

ARSY0111E

Operand does not consist of all decimal digits

Explanation

The operand for the current control statement keyword is expected to consist solely of a string of decimal digits.

Module

ARSYPXP

ARSY0112E

Invalid suboperand length

Explanation

When processing an operand that can be specified as a parenthesized list of suboperands, one or more of these suboperands is either too short or too long. See the ARSYSPIN program reference in the *IBM Content Manager OnDemand for z/OS: Administration Guide* for the expected operand characteristics of a given keyword.

Module

ARSYPXP

ARSY0113I

Control statements processing completed - RC= <integer> (x'<hexdigits>')

Explanation

Processing of the control statement stream has completed. If the RC value is non-zero, then at least one syntax error has been detected and ARSYSPIN terminates.

Module

ARSYPXP

ARSY0114E

Unrecognized subparameter: <string>

Explanation

The operand or suboperand for the current control statement keyword is expected to be a member of a set of specific character strings. For example, the ERROPT keyword expects its operand to be either ABEND, ACCEPT, or HOLD. See the ARSYSPIN program reference in the *IBM Content Manager OnDemand for z/OS: Administration Guide* for the allowable operand values for a given control statement keyword.

Module

ARSYPXP

ARSY0115E

Improper number of subparameters

Explanation

An improper number of subparameters (either too many or too few) was specified for the current control statement. See the ARSYSPIN program reference in the *IBM Content Manager OnDemand for z/OS: Administration Guide* for the expected operand characteristics of a given keyword.

Module

ARSYPXP

Chapter 4. ACIF messages

ACIF prints a message list at the end of each compilation. A return code of 0 means that ACIF completed processing without any errors. ACIF supports the standard return codes.

Note:

1. ACIF messages contain instructions for the PSF or Infoprint Manager system programmer. Please show your system programmer these messages, because they might not be contained in the PSF or Infoprint Manager messages publications.
2. AIX and Windows users can invoke the PSF MSG command on the server to view or print messages online.

Message identifiers

ACIF issues the same messages for AIX, Solaris, Windows, and z/OS. The format of the message identifier is `APKnnnt`, where the following list describes the variables:

APK

Identifies an ACIF message.

nnn or nnnn

Specifies the three-digit or four-digit message number.

t

Specifies one of the following error conditions:

Error Type	Description
S	Severe error that causes ACIF to terminate processing the current print file. The exact method of termination can vary. For certain severe errors, ACIF abends with a return code and reason code. This is generally the case when some system service fails. In other cases, ACIF terminates with the appropriate error messages written to the message file specified when you invoked ACIF. Most error conditions detected by ACIF fall into the severe category.
W	Warning error that ACIF issues when the fidelity of the document (assuming it is reprinted) might be in question.
I	Informational error that ACIF issues when it processes a print file to let the operator or application programmer determine if the correct processing parameters have been specified. These messages can assist in providing an audit trail.

The terms used in the messages and explanations are those used for z/OS, even though the messages and explanations also apply to AIX, Solaris, and Windows. The following list shows some of the terms used in the messages in this publication and what those terms refer to in AIX, Solaris, and Windows:

Term	AIX, Solaris, Windows
print data set	input file
data set	input file
data stream	file

Term	AIX, Solaris, Windows
PSF	PSF or Infoprint Manager
record	data set

Multiple message scenarios

ACIF can issue more than one error message as a result of a single error condition. These situations are limited to the area of parsing the ACIF (for example, determining the length and type of the ACIF). Some possible scenarios include these message numbers:

- 105, 108, 109, 103
- 105, 108, 110, 103
- 106, 108, 109, 103
- 106, 108, 110, 103

Any subset of the listed message numbers is also possible, provided you start with the first one (for example, 105, 108, 109 or 105, 108, or 105, 110, and so on). The first message accurately describes the error condition; any subsequent messages provide additional information. Additional error messages might not always be accurate.

Message number 101 can occur after many error conditions, because ACIF attempts to locate the end of the resource containing the error as part of its recovery procedure.

ACIF messages

APK104S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: *structuredfield* STRUCTURED FIELD IS NOT ALLOWED OR FORMS AN INVALID SEQUENCE.

Explanation

The structured field identified in this message is either out of sequence or not valid in an object. The record might be line data. If inline resources are used with data-set header pages, multiple resource groups might be present.

This message is issued if your AFP input file contains IM1 image with no Image Raster Data (IRD) structured field. This type of AFP file might be built by DCF when creating shaded text with a shading percentage of zero.

If this message is preceded by message APK420S, the error is caused by a missing resource object.

System action

ACIF stops processing the print data set.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information on the correct format of the referenced structured field. If the structured fields are in the

correct order, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APK105I

THE ERROR REPORTED ABOVE OCCURRED IN LOGICAL RECORD NUMBER *recordnumber*, WHOSE SEQUENCE NUMBER IS *sequencenumber*.

Explanation

This message is given in addition to the message that describes the error. It identifies the specific input record that is not valid. The object (if any) that contains the not valid record is identified in either message APK108I or message APK109I.

The record number specified is relative to the user data stream and is different for multiple transmissions of the data set. However, the record number might be inaccurate if the data set is using a page definition that performs conditional processing.

The sequence number might print as NOT AVAILABLE in the message. For example, a line-data record does not have a sequence number.

System action

The disposition of the file depends upon the error described in the accompanying messages.

System programmer response

See the specific error conditions described in the accompanying messages to determine an appropriate response.

User response

See the specific error conditions described in the accompanying messages to determine an appropriate response.

APK106I

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: NAME *tokenname* IN *begintypestructuredfield* DOES NOT MATCH NAME *tokenname* IN *endtypestructuredfield*.

Explanation

The TOKEN NAME parameters in the Begin-type and End-type structured fields identified in this message do not match. Structured fields might be out of sequence in the input data stream.

When token names are specified, the TOKEN NAME parameters in the associated Begin-type and End-type structured fields must match.

System action

Processing continues, and ACIF issues a message identifying the position of the structured field in the input data stream or resource. ACIF issues additional messages identifying the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an

ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK108I

THE ERROR REPORTED ABOVE WAS DETECTED WITHIN OBJECT TYPE *objecttype* WITH TOKEN NAME *tokenname*.

Explanation

This message is issued in addition to the message that describes the error. The objects that were being processed are listed to identify the location of the error in the input data stream or in a resource.

System action

The disposition of the file depends on the error described in the accompanying messages.

System programmer response

See the specific error conditions described in the accompanying messages to determine an appropriate response.

User response

See the specific error conditions described in the accompanying messages to determine an appropriate response.

APK109I

THE ERROR REPORTED ABOVE WAS CAUSED BY THE RESOURCE *resourcename* IN AN EXTERNAL LIBRARY OR AN INLINE RESOURCE.

Explanation

This message is issued in addition to the message that describes the error. The object identified in the accompanying message was either a resource being processed from an external library or an inline resource. Error message APK108I identifies the member as a page definition, form definition, font, code page, font character set, page segment, or an overlay. The combined information from these two messages can be used to identify the library defined to ACIF on the *typeLIB* parameter, where *type* is the type of resource, such as OVLY for overlay. In the case of an inline form definition or page definition, the resource is not a member of an external library but is included at the beginning of the user's data set.

System action

The disposition of the file depends on the error described in the accompanying messages.

System programmer response

See the specific error conditions described in the accompanying messages to determine an appropriate response.

User response

See the specific error conditions described in the accompanying messages to determine an appropriate response.

APK110S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: THE LENGTH SPECIFIED IN THE SELF-DEFINING PARAMETER *identifier* OF THE STRUCTURED FIELD *structuredfield* IS INCORRECT.

Explanation

Insufficient data was present in the structured field for the length given in the self-defining parameter or triplet. If the self-defining parameter or triplet ID is 0, the length of the self-defining parameter or triplet might have been 0 or 1, which means that no ID was available for use in this message.

System action

If the error occurred in a structured field in a page or resource, PSF attempts to find the end of the page or resource. If PSF can find the end of the page, it prints any data accumulated for the current page. If PSF cannot find the end of the page, the data set is terminated. If the error occurred in a form definition, a page definition, or non-presentation object container resource (for example, COMSETUP), the form definition, page definition, or non-presentation object container resource is not used, and one of these occurs:

- PSF is not started for any of these:
 - The default form definition
 - A form definition specified for printing messages or separator pages
 - A page definition specified for printing messages or separator pages
- PSF cannot begin printing the data set for a form definition or non-presentation object container resource (or page definition if printing line date) specified on a user's OUTPUT JCL statement; PSF tries to print the next data set. PSF issues a message identifying the position of the structured field in the data stream or resource. PSF issues additional messages identifying the processing environment in which the error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the object, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the object, contact your system programmer.

APK112S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: RECORD CONTAINS NO DATA, EVEN THOUGH AT LEAST A CONTROL CHARACTER IS EXPECTED.

Explanation

ACIF read an input record without a control character following the record descriptor word (RDW). A minimum of 1 byte of control-character data is needed to make the record valid.

System action

ACIF stops processing the print data set.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK113S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: STRUCTURED FIELD LENGTH IS LESS THAN THE INTRODUCER LENGTH.

Explanation

A structured field must have at least 8 bytes of data, the minimum length necessary for a structured-field introducer. The Extension Indicator flag in the structured-field introducer indicates whether the minimum length of the structured field can be greater than 8 bytes.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK114S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: RECORD LENGTH DOES NOT AGREE WITH LENGTH IN STRUCTURED FIELD INTRODUCER.

Explanation

All structured fields are preceded by a record length that specifies the entire length of the record, including four bytes in the record length and a one byte control character. However, the record length specified does not match the sum of the LENGTH parameter in the structured field introducer and the five other bytes.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, ensure that the record length specified is valid for the structured field, and resubmit the print request. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APK116S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: PADDING LENGTH OR EXTENSION LENGTH IS INCORRECT FOR STRUCTURED FIELD.

Explanation

The length of padding or extension specified in the LENGTH or EXTENSION parameter in the structured-field introducer indicates more data than was found in the structured field.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, ensure that the Extension Indicator flag is set correctly and that the LENGTH parameter in the structured-field introducer specifies the actual length of padding for the structured field that is not valid. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured-field introducer. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APK117S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: LENGTH INDICATED IN THE STRUCTURED FIELD INTRODUCER IS INCORRECT FOR *structuredfield* STRUCTURED FIELD.

Explanation

The length indicated by the structured-field introducer specifies an incorrect number of bytes for the structured field identified in this message. This error is caused by one of these :

- The Extension or Padding Indicator flags in the structured-field introducer are set incorrectly.
- One or more of the parameters in the structured field that is not valid contain too many bytes of data.

In some cases, the length of a structured field is specified in a parameter located in another structured field. For example, the length of Fixed Data Text (FDX) structured field is specified in the SIZE parameter of the Fixed Data Size (FDS) structured field.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, ensure that the LENGTH parameter in the structured-field introducer specifies a valid length for the structured field. Also ensure that the number of bytes in the structured-field parameter matches the length specified in the structured-field introducer. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture*

Reference or Advanced Function Presentation: Programming Guide and Line Data Reference for more information about the structured-field introducer.

If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APK118W

UNSUPPORTED STRUCTURED FIELD *code* WAS IGNORED, AND, IF IT BEGAN AN OBJECT, THE OBJECT WAS IGNORED.

Explanation

The IDENTIFIER parameter in the structured-field introducer for the incorrect structured field specified a structured-field code that was not recognized as a valid structured-field code.

System action

If the structured field began an object, the object was ignored. Otherwise, only the structured field was ignored, and processing of the rest of the data set continues as usual.

ACIF issues a message identifying the position of the structured field in the input data stream or containing resource. ACIF issues additional messages identifying the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If the printed output was unacceptable, and you created the structured fields for the print data set or resource, give the incorrect structured field a valid code for its structured-field type. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for a list of valid structured-field types.

If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured field for the print data set or resource, contact your system programmer.

APK120S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: *structuredfield1* STRUCTURED FIELD CONTAINS AN INCORRECT VALUE FOR THE SIZE OF THE *structuredfield2* REPEATING GROUP.

Explanation

Structuredfield1 specifies the length of each repeating group found in *structuredfield2*. Either the value specified in *structuredfield1* for the size of the repeating group is too small, or the actual length of the repeating-group data is not a multiple of the size specified.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

None.

User response

Use the accompanying messages to determine if the structured field causing the error is in the print data set or in a resource. Correct the process used to create the print data set or resource. If you used an IBM

licensed program to create the data stream with the error, use local problem-reporting procedures to report this message.

APK130S

DATA IN AN INPUT RECORD IS INVALID: *structuredfield* STRUCTURED FIELD IS NOT ACCEPTABLE AT THE START OF A DATA STREAM.

Explanation

The structured-field type identified in this message is not valid at the start of the data stream. Subsequent error messages give additional information about the processing environment when the error occurred.

System action

ACIF stops processing the print data set.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set, contact your system programmer.

APK135I

DATA IN A FORMDEF RESOURCE IS INVALID: DUPLICATE OVERLAY LOCAL IDENTIFIER WAS FOUND IN THE *structuredfield* STRUCTURED FIELD.

Explanation

The same local identifier was found assigned to more than one OVERLAY LOCAL IDENTIFIER parameter in the Map Medium Overlay (MMO) or Map Page Overlay (MPO) structured field repeating groups. The MMO structured field is contained in the form definition. The MPO is contained in the page definition or the print data set.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK138S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: OVERLAY LOCAL IDENTIFIER VALUE IS NOT ACCEPTABLE IN THE *structuredfield* STRUCTURED FIELD.

Explanation

An incorrect OVERLAY LOCAL IDENTIFIER was encountered in the Map Medium Overlay (MMO), Map Page Overlay (MPO), or Medium Modification Control (MMC) structured field repeating groups. The MMO and MMC structured fields are contained in the form definition. The MPO is contained in the page definition or the print data set.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK139S

DATA IN A FORMDEF RESOURCE IS INVALID: SUPPRESSION LOCAL IDENTIFIER VALUE IS NOT ACCEPTABLE IN THE MSU STRUCTURED FIELD.

Explanation

The SUPPRESSION LOCAL IDENTIFIER parameter in the Map Suppression (MSU) structured field is not valid. The MSU structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK140S

DATA IN A FORMDEF RESOURCE IS INVALID: TWO MMC STRUCTURED FIELDS ARE DEFINED WITH THE SAME IDENTIFIER, *identifier*.

Explanation

Two Medium Modification Control (MMC) structured fields in a single form environment group have the same value in their MEDIUM MODIFICATION CONTROL IDENTIFIER parameters. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MMC has no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK141S

DATA IN A FORMDEF RESOURCE IS INVALID: MEDIUM SUPPRESSION TOKEN NAME IS REPEATED IN MSU STRUCTURED FIELD.

Explanation

The TOKEN NAME parameters in two repeating groups in a Map Suppression (MSU) structured field have the same value. The MSU structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK143S

DATA IN A FORMDEF RESOURCE IS INVALID: COPY SPECIFICATIONS IN THE MCC STRUCTURED FIELD ARE NOT ACCEPTABLE.

Explanation

Either a gap or an overlap exists in the Starting and Stopping Copy Numbers, or the maximum number of copies for one set of modifications has been exceeded. The COPY NUMBER parameters are specified in the Medium Copy Count (MCC) structured field. The MCC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, ensure that the Starting Copy Number and Stopping Copy Number parameters in a repeating group in an MCC structured field have valid values that correlate. Also, verify that fewer than 255 copies have been requested. If 255 or more copies with the same modifications are needed, define two or more MCC structured fields. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information on the MCC structured field. If the MCC has no errors, the error might be an ACIF logic error.

If you used a program to create the structured fields for the form definition, contact your system programmer.

APK145S

DATA IN A FORMDEF RESOURCE IS INVALID: THE FORMS-FLASH VALUE IN MMC STRUCTURED FIELD, ID *identifier*, IS NOT ACCEPTABLE.

Explanation

The Medium Modification Control (MMC) structured field contains an incorrect value for the repeating group that contains forms-flash modification. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MMC has no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK146S

DATA IN A FORMDEF RESOURCE IS INVALID: MORE THAN 8 OVERLAYS ARE SPECIFIED IN MMC STRUCTURED FIELD, ID *identifier*.

Explanation

In a Medium Modification Control (MMC) structured field, the maximum number of overlays allowed in one set of modifications has been exceeded. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MMC has no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK147S

DATA IN A FORMDEF RESOURCE IS INVALID: MORE THAN 8 SUPPRESSIONS ARE SPECIFIED IN MMC STRUCTURED FIELD, ID *identifier*.

Explanation

In a Medium Modification Control (MMC) structured field, the maximum number of suppressions allowed in one set of modifications has been exceeded. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MMC has no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK152S

DATA IN A FORMDEF RESOURCE IS INVALID: MMC STRUCTURED FIELD WAS NOT FOUND TO COMPARE WITH IDENTIFIER *identifier* IN MCC STRUCTURED FIELD.

Explanation

The MEDIUM MODIFICATION CONTROL IDENTIFIER parameter in the Medium Copy Count (MCC) structured field contains a value that did not match the MEDIUM MODIFICATION CONTROL IDENTIFIER parameter in any Medium Modification Control (MMC) structured field in the form environment group. The MCC and MMC structured fields are contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MCC or MMC structured field. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MCC and MMC have no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK154S

DATA IN A FORMDEF RESOURCE IS INVALID: OVERLAY LOCAL IDENTIFIER IN MMC STRUCTURED FIELD, ID *identifier*, WAS NOT FOUND IN MMO STRUCTURED FIELD.

Explanation

The overlay modification in the Medium Modification Control (MMC) structured field was not present in the Map Medium Overlay (MMO) structured field. The MMC and MMO structured fields are contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK155S

DATA IN A FORMDEF RESOURCE IS INVALID: TOO MANY COPY CONTROLS WERE SPECIFIED FOR THE CURRENT FORM ENVIRONMENT GROUP.

Explanation

For a given physical page, up to 256 bytes of data can be specified for the printer command that describes the copies and modifications to be made. The current form environment group causes the data for the command to exceed 256 bytes. ACIF builds the printer command from data contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, either reduce the number of copy groups in the Medium Copy Count (MCC) structured field or reduce the number of modifications specified in the Medium Modification Control (MMC) structured field. Otherwise, split these functions between two or more form environment groups in two or more medium maps. Then, include in your input two or more identical copies of the same page that each select an appropriate copy group by use of the Invoke Medium Map (IMM) structured field. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the MMC and MMO structured fields.

If you used a program to create the structured fields for the form definition, contact your system programmer.

APK156S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: NULL NAME IS NOT ACCEPTABLE IN *structuredfield* STRUCTURED FIELD.

Explanation

All Begin-type and End-type structured fields can include an 8-byte token name. A null token name is not allowed for the listed structured field.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK157S

MISMATCH BETWEEN PRINT DATA SET AND FORMDEF RESOURCE: MEDIUM MAP *mediummap* SPECIFIED IN IMM STRUCTURED FIELD WAS NOT FOUND IN FORMDEF *formdefinition*.

Explanation

The TOKEN NAME parameter in the Invoke Medium Map (IMM) structured field specifies the token name used to locate a medium map in the form definition. This parameter must match the TOKEN NAME parameter specified in bytes 0–7 in one of the Begin Medium Map (BMM) structured fields in the current form definition. The IMM structured field is contained in the print data set.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

No action is required

User response

Ensure that the correct form definition was specified. If it was, and if you added the Invoke Medium Map structured field to the print data set, change the TOKEN NAME in the IMM structured field and run ACIF. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the BMM and IMM structured fields. If the correct form definition was specified, and if you used a program to embed the IMM structured field in the print data set, verify that the copy group name that you gave the program is valid for the form definition you have specified.

APK158I

PAGEDEF PARAMETER MUST BE SPECIFIED IN ORDER TO PRINT THIS DATA SET. DETERMINE THE PERMISSIBLE VALUES USED IN YOUR INSTALLATION FOR THE PAGEDEF PARAMETER.

Explanation

The current data set contains line data, XML data, or structured fields that do not form a MO:DCA-P page. This kind of data set cannot be printed without an active page definition. No PAGEDEF keyword was provided for this job.

This error can also occur if MO:DCA-P data in the print data set contains a record without the required X'5A' control character preceding the structured-field introducer. The missing control character makes the record appear to be line data. A page definition is necessary to process line data. Therefore, ACIF detects an error.

System action

ACIF stops processing the print data set.

System programmer response

No action is required

User response

If you intended to print line data or XML data, you must specify the PAGEDEF keyword when starting ACIF.

If you intended to print line data or XML data, you must specify the PAGEDEF keyword when starting ACIF.

APK159S

THE END OF THE DATA STREAM WAS ENCOUNTERED BEFORE THE LOGICAL END OF AN OBJECT WITHIN THE DATA STREAM.

Explanation

ACIF was processing an object that began with a Begin-type structured field. However, the input data stream ended before a corresponding End-type structured field was found. The message can also occur if the system operator prematurely interrupts or ends a print request by issuing an INTERRUPT, RESTART, or CANCEL Job Entry Subsystem (JES) command.

System action

ACIF stops processing the print data set.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set, contact your system programmer.

APK162S

MISMATCH BETWEEN PRINT DATA SET AND PAGEDEF RESOURCE: DATA MAP *datamap* SPECIFIED IN IDM STRUCTURED FIELD WAS NOT FOUND IN PAGEDEF *pagedefinition*.

Explanation

The TOKEN NAME parameter in the Invoke Data Map (IDM) structured field specifies the token name used to locate a data map in the page definition. The name must match the value specified in the TOKEN NAME parameter in the Begin Data Map (BDM) structured field in the current page definition. The IDM structured field is contained in the print data set.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

No action is required

User response

Ensure that the correct page definition was specified. If it was, and if you added the Invoke Data Map structured field to the print data set, change the TOKEN NAME in the IDM structured field and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the BDM and IDM structured fields. If the correct page definition was specified, and if you used a program to embed the IDM structured field in the print data set, verify that the data map name that you supplied the program is one that is valid for the page definition you have specified.

APK163S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: THE SCALE FACTOR VALUE IN THE IOC STRUCTURED FIELD IS NOT ACCEPTABLE.

Explanation

The IMAGE BLOCK SCALE FACTOR parameter in the Image Output Control (IOC) structured field is not valid. The image block or image cell might be contained in an overlay, a page segment, or a composed-text print data set. It might also be embedded in a data set containing line data, using a Begin Image (BIM) structured field.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APK166S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: AN ENTRY IN A MCF STRUCTURED FIELD CONTAINS AMBIGUOUS IDENTIFICATION.

Explanation

A font in the Map Coded Font (MCF) structured field can be identified with a CODED FONT NAME parameter, with a combination of the FONT CHARACTER SET NAME parameter and the CODE PAGE NAME parameter, or with a CODED FONT parameter (also known as a GRID parameter). One of the repeating groups in an MCF structured field specified more than one of these ways to specify a font or specified a CODED FONT (GRID) and a section number other than 0. The MCF structured field is in the MO:DCA-P data, an overlay, or a page definition.

System action

If the error is contained in a page definition, PSF terminates processing of the data set and continues processing with the next data set. Otherwise, PSF terminates the page or overlay containing the structured field in error. PSF attempts to locate the end of the current page and resumes processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message identifying the position of the structured field in the input data stream or resource. PSF issues additional messages identifying the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK167S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: AN ENTRY IN AN MCF STRUCTURED FIELD CONTAINS INCOMPLETE IDENTIFICATION.

Explanation

One of the repeating groups in a Map Coded Font (MCF) structured field does not contain enough information to identify a coded font. Two ways to identify a font in the Map Coded Font (MCF) structured field are either with a CODED FONT NAME parameter or with a combination of the FONT CHARACTER SET NAME parameter and the CODE PAGE NAME parameter. An entry contains only a FONT CHARACTER SET NAME parameter or a CODE PAGE NAME parameter. The MCF structured field is contained in a composed-text print data set, an overlay, or a page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK169S

INSUFFICIENT VIRTUAL STORAGE PREVENTED FURTHER PROCESSING. INCREASE REGION SIZE, AND RESUBMIT THE PRINT REQUEST.

Explanation

Insufficient storage is available in the ACIF address space to contain the internal control block needed to read an object.

System action

ACIF stops processing the print data set.

System programmer response

The value of the REGION parameter used for the ACIF job should be increased.

User response

Inform your system programmer that this error occurred.

APK170S

DATA IN A FORMDEF RESOURCE IS INVALID: THE SIMPLEX/DUPLEX VALUE IN MMC STRUCTURED FIELD, ID *identifier*, IS NOT ACCEPTABLE.

Explanation

In the Medium Modification Control (MMC) structured field with the specified identifier, either the simplex or the duplex keyword-parameter value is not valid. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MMC has no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK171S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: FONT LOCAL IDENTIFIER VALUE IS NOT ACCEPTABLE IN THE *structuredfield* STRUCTURED FIELD.

Explanation

The Map Coded Font (MCF) structured field consists of repeating groups. In one of the groups, the value of the CODED FONT LOCAL IDENTIFIER parameter for the font (section) being mapped is not valid. The MCF structured field is contained in a composed-text print data set, an overlay, or a page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK172S

DATA IN A FORMDEF RESOURCE IS INVALID: THE SET OF MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INCLUDES BOTH NORMAL AND TUMBLE DUPLEX.

Explanation

The Medium Copy Count (MCC) structured field refers to one or more Medium Modification Control (MMC) structured fields, which include requests for both normal duplex and tumble duplex. You cannot request both normal duplex and tumble duplex within the same medium map. The MCC and MMC structured fields are contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MCC or MMC structured field. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MCC and MMC have no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK178S

DATA IN A FORMDEF RESOURCE IS INVALID: THE MCC STRUCTURED FIELD HAS AN ODD NUMBER OF COPY GROUPS, BUT SPECIFIES DUPLEX.

Explanation

The Medium Copy Count (MCC) structured field specifies an odd number of copy groups, but the copy group modifications specified in the Medium Modification Control (MMC) structured field include duplex, which requires an even number of copy groups. The MCC and MMC structured fields are contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MCC or MMC structured field. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MCC and MMC have no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK179S

DATA IN A FORMDEF RESOURCE IS INVALID: THE SET OF MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INCLUDES BOTH SIMPLEX AND DUPLEX.

Explanation

The Medium Copy Count (MCC) structured field refers to two or more Medium Modification Control (MMC) structured fields, which include requests for both simplex and duplex printing. You cannot specify both simplex and duplex printing within the same medium map. The MCC and MMC structured fields are contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MCC or MMC structured field. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MCC and MMC have no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK181S

DATA IN A FORMDEF RESOURCE IS INVALID: UNEQUAL COPY COUNTS FOR DUPLEX SHEETS ARE SPECIFIED IN THE MCC STRUCTURED FIELD.

Explanation

The set of modifications referred to by the Medium Copy Count (MCC) structured field includes duplexing, but the numbers of copies in two corresponding repeating groups are not equal. The repeating groups are defined in the Medium Map Control structured field (MMC). The MCC and MMC structured fields are contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MCC or MMC structured field. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MCC and MMC have no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK188S (removed)

This message is no longer issued by ACIF.

APK190S

DATA IN A FORMDEF RESOURCE IS INVALID: THE BIN-SELECTION VALUE IN MMC STRUCTURED FIELD, ID *identifier*, IS NOT ACCEPTABLE.

Explanation

In the Medium Modification Control (MMC) structured field with the identifier specified in the message text, the bin-selection parameter value was not valid. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MMC has no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK191S

DATA IN A FORMDEF RESOURCE IS INVALID: THE SUPPRESSION LOCAL IDENTIFIER VALUE IN MMC STRUCTURED FIELD, ID *identifier*, IS NOT ACCEPTABLE.

Explanation

The MEDIUM MODIFICATION CONTROL IDENTIFIER parameter in a Medium Modification Control (MMC) structured field is not valid. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MMC has no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK210S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: A REQUIRED TRIPLET OR SELF-DEFINING PARAMETER WITH ID *identifier* WAS MISSING FROM A *structuredfield* STRUCTURED FIELD.

Explanation

The triplet or self-defining parameter specified in the message was not found in the structured field indicated. This is a required triplet or self-defining parameter.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the input data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields, correct the error and resubmit the print request. Refer to *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APK212S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: THE UNIT BASE PARAMETER IN THE *structuredfield* STRUCTURED FIELD IS INVALID.

Explanation

An incorrect Unit Base value was encountered in the structured field identified in this message.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

None.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APK217S

DATA IN AN INPUT RECORD IS INVALID: PARAMETER IN A BR STRUCTURED FIELD CONTAINS UNACCEPTABLE DATA.

Explanation

One of the parameters in the Begin Resource (BR) structured field is not valid. The BR structured field is contained in the print data set.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to place the BR structured field in the print data set, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you placed the BR structured field in the print data set, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If you used a program to place the BR structured field in the print data set, contact your system programmer.

APK221S

DATA IN A FORMDEF RESOURCE IS INVALID: THE ORIENTATION VALUE *value* IN THE MDD STRUCTURED FIELD IS UNACCEPTABLE.

Explanation

The Medium Descriptor (MDD) structured field has an incorrect orientation value. The MDD structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK223I

A FORMDEF RESOURCE REQUIRED ENHANCED N_UP AND A CONFLICTING VALUE FOR THE DUPLEX PARAMETER WAS SPECIFIED.

Explanation

When enhanced N_UP is requested, the DUPLEX parameter cannot be used to change from duplex (specified in the form definition) to simplex or vice versa. The reason is that with enhanced N_UP, the Page Position (PGP) Format two structured field specified the partition number and sheet side for each page placed on a sheet. If the duplex value is changed from duplex to simplex or vice versa, ACIF does not have the information it needs to place the pages. The only valid options for the DUPLEX parameter when enhanced N_UP is specified in the form definition are:

- If the form definition requests normal or tumble duplex, you can specify either NORMAL or TUMBLE on the DUPLEX parameter.
- If the form definition requests simplex, you can specify NO on the DUPLEX parameter.

System action

ACIF stops processing the input file and issues a message identifying the position of the structured field in the file or resource.

System programmer response

No action is required.

User response

Resubmit the job without specifying the DUPLEX parameter.

APK244I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE *structuredfield* STRUCTURED FIELD CONTAINS TOO MANY REPEATING GROUPS.

Explanation

The structured field contains more repeating groups than are allowed. The structured field in which the error appears can be in a resource environment group, a composed text page, an overlay, or a page definition.

System action

If this error occurs in a resource, PSF stops processing the data set. If this error occurs in a resource environment group, PSF stops processing the resource environment group and continues processing the data set.

If this error occurs in a composed text page, PSF stops processing the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the current page, PSF stops printing the data set.

PSF issues additional messages identifying the processing environment in which the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK245I

A COMPLEX IM IMAGE OBJECT CONTAINS INVALID OR INCORRECT DATA. THE COMPLEX IM IMAGE OBJECT CANNOT BE CONVERTED TO AN IO IMAGE OBJECT.

Explanation

This message is issued when ACIF converts a complex IM image object to an IO image object and the image size is not large enough to contain the image raster data from the IRD structured fields. This message is issued when the default IMAGEOUT=IOCA parameter is specified. This message is issued if either of these are true:

- The XCSIZE or YCSIZE parameter value of the ICP structured field is larger than the calculated image X size or Y size, respectively.
- The XCOSET plus XFILSIZE parameter values or the YCOSET plus YFILSIZE parameter values of the ICP structured field are larger than the calculated image X size or Y size, respectively.

When ACIF converts a complex IM image object to an IO image object, ACIF calculates the image size by subtracting the X and Y image origins from the X and Y page sizes. The X and Y image origins are from the Xoa0set and Yoa0set parameter values of the IOC structured field. The X and Y page sizes are from the XpgSize and YpgSize parameter values of the PGD structured field, if the image object is contained in a MO:DCA-P file or overlay, or is embedded in a file containing line data. For an image object in a page segment, the X and Y page sizes used by ACIF are 2040 and 2640 respectively. The IOC and ICP structured fields are contained in a MO:DCA-P file, overlay, or page segment, or are embedded in a file containing line data. The PGD structured field is contained in a MO:DCA-P file, overlay, or page definition.

System action

ACIF terminates.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

Specify EXTENSIONS=CELLED and IMAGEOUT=ASIS to see if the error is corrected. Otherwise, if you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK250S

DATA IN A PAGE OR RESOURCE IS MISSING: THE REQUIRED STRUCTURED FIELD *structuredfield* COULD NOT BE FOUND TO COMPLETE THE PROCESSING OF A PAGE OR RESOURCE.

Explanation

The structured field identified in this message is required to complete the processing of a page or resource. This structured field was not found before the end of the page or resource was encountered.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK251S

DATA IN A FORMDEF RESOURCE IS MISSING: THE FORMDEF DOES NOT CONTAIN ANY MEDIUM MAPS.

Explanation

The form definition did not specify any medium maps; however, a medium map is required to print a page.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK253S

DATA IN A FORMDEF RESOURCE IS INVALID: THE PRINT QUALITY VALUE IN MMC STRUCTURED FIELD, ID *identifier*, IS NOT ACCEPTABLE.

Explanation

The Medium Modification Control (MMC) structured field specified a print quality value of 0, which is outside the valid range. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MMC has no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK254S

DATA IN A FORMDEF RESOURCE IS INVALID: THE OFFSET STACKING VALUE IN MMC STRUCTURED FIELD, ID *identifier*, IS NOT ACCEPTABLE.

Explanation

The Medium Modification Control (MMC) structured field specified an offset stacking value other than 0 or 1. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MMC has no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK258S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: *structuredfield* STRUCTURED FIELD IS NOT ALLOWED BETWEEN OBJECTS.

Explanation

The structured field identified in this message is not allowed at the point in the input data stream or resource at which it was found.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured fields are in the correct order, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APK259I

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: THE X-DIRECTION AND Y-DIRECTION L-UNITS PER UNIT BASE VALUES SPECIFIED IN STRUCTURED FIELD *structuredfield* DO NOT MATCH.

Explanation

The X-direction and Y-direction L-Units per Unit Base values in the structured field identified in the message are not identical.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

None.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content*

Architecture Reference or Advanced Function Presentation: Programming Guide and Line Data Reference for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK260S

THE OBJECT SPECIFIED WITH THE *structuredfield* STRUCTURED FIELD IS NOT SUPPORTED ON THIS PRINTER.

Explanation

PSF has encountered a valid AFP object that is not supported by the printer. The object is identified either by its Begin structured field, by an Invoke structured field, such as Include Page Overlay (IPO), or by an OTH record (object container without MO:DCA-P structured fields wrapping the data).

System action

If the object or Invoke structured field is embedded in a page or overlay, PSF ignores the object and continues processing the current page or overlay.

If the Begin structured field, the Invoke structured field, or the OTH record is in a resource included by a page or overlay, PSF terminates the page or overlay. PSF attempts to locate the end of the current page and resume processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set.

System programmer response

Delete the unsupported object type from the separator page data set for this printer.

User response

To print the object type indicated in the message, submit the print job to a printer that supports the object type. For more information about what object types are supported by your printer, refer to your printer documentation.

APK261S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: STRUCTURED FIELD *structuredfield* CONTAINED A CODED-FONT- LOCAL-IDENTIFIER VALUE THAT WAS USED IN A PREVIOUS FONT MAPPING STRUCTURED FIELD.

Explanation

One or more font mapping structured fields in the same active environment group or object environment group used the same coded font local identifier for different coded fonts. The Map Coded Font (MCF) structured field that attempted to use the already-mapped coded font local identifier is identified in the message. The MCF structured field can be contained in a composed-text print data set, an overlay, or a page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

None.

User response

If you were printing a composed-text print data set or an overlay, and you created the structured fields in the object containing the error, check the Coded Font Local Identifiers in the MCF structured field for duplicates. If the MCF structured field has no error, the error might be an ACIF logic error. If you used a

program to create the structured fields in the object containing the error, contact your system programmer.

If you were printing a data set containing line data using a page definition, and if you created the structured fields for the page definition, check the Coded Font Local Identifiers in the MCF structured field for duplicates. If the MCF structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field.

APK262S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: STRUCTURED FIELD *structuredfield* CONTAINS AN INVALID ROTATION VALUE.

Explanation

The rotation value specified in the named structured field was not valid.

System action

ACIF stops processing the print data set. ACIF issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK263S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: OVERLAY *overlayname* NAMED IN AN IPO STRUCTURED FIELD IS NOT NAMED IN AN MPO STRUCTURED FIELD.

Explanation

An Include Page Overlay (IPO) structured field names a page overlay, but the overlay was not previously defined in the Map Page Overlay (MPO) structured field in the Active Environment Group (AEG) of the page, which contains the IPO. The MPO might be contained in the AEG of a composed-text page or a page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If the MPO indicates that this overlay is for annotation only, create another MPO structured field in the AEG that defines the page overlay. If you are using the input data to define the name of your page overlay and your input data is ASCII, this error can occur because the resource name in the MPO is EBCDIC. If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you use a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK264S

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A RESOURCE MAPPED BY A *structuredfield* STRUCTURED FIELD IN AN OBJECT ENVIRONMENT GROUP IS NOT NAMED IN THE ACTIVE ENVIRONMENT GROUP OF THE PAGE OR RESOURCE.

Explanation

A structured field in an object environment group names a resource. However, that resource is not defined in the structured field in the active environment group of the page or resource containing the object environment group.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource. ACIF stops processing and printing the data set.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK267S

EITHER NO ENVIRONMENT GROUP WAS SPECIFIED FOR THE PAGE OR AN ERROR OCCURRED IN THE ENVIRONMENT GROUP.

Explanation

Either no environment group was specified, or an error occurred in one of the structured fields in the environment group. If an environment group was present but contained an error, a previous ACIF message identifies the error. The environment group causing this error might be contained in an overlay, a page definition, or a composed-text print data set.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK268S

AN ENTRY IN AN MCF STRUCTURED FIELD DOES NOT CONTAIN CODE PAGE INFORMATION.

Explanation

One of the repeating groups in a Map Coded Font Format 2 (MCF-2) structured field specifies a font character set but no code page information. This error was detected while processing a graphics object within a page or overlay.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the object, correct the error and resubmit the print request. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the object, contact your system programmer.

APK269S

A VALUE OF ZERO WAS SPECIFIED AS THE L-UNITS PER UNIT BASE IN THE *structuredfield* STRUCTURED FIELD.

Explanation

Several structured fields specify an L-Units per Unit Base value: Medium Descriptor (MDD), Page Descriptor (PGD), Presentation Text Descriptor (PTD-2), Object Area Descriptor (OBD), Graphics Data Descriptor (GDD), Image Data Descriptor (IDD), Barcode Data Descriptor (BDD), and Image Input Descriptor (IID). The value of zero is not valid for the L-Units per Unit Base.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

None.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for information about the structured fields. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set, contact your system programmer.

APK270S

DATA IN A PAGEDEF RESOURCE IS MISSING: THE PAGEDEF DOES NOT CONTAIN ANY DATA MAPS.

Explanation

The page definition did not specify any data maps and a data map is required to print a data set containing line data.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK271S

DATA IN A FORMDEF RESOURCE IS INVALID: THE DUPLEX SPECIFICATION IN THE PGP STRUCTURED FIELD IS NOT ACCEPTABLE.

Explanation

The duplex specification value in the Page Position (PGP) structured field is not acceptable. The PGP structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK272S

DATA IN A FORMDEF RESOURCE IS INVALID: THE PGP STRUCTURED FIELD DOES NOT CONTAIN A PAGE ORIGIN POSITION FOR THE FRONT SIDE OF A SHEET.

Explanation

The Page Position format-2 (PGP) structured field must contain a repeating group that defines the Page Origin Position for the front side. This value will also be used for the back side of a duplex sheet unless the

PGP structured field contains a repeating group that specifies the Page Origin Position for the back side of the sheet. The PGP structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK273S

DATA IN A FORMDEF RESOURCE IS INVALID: THE CONSTANT FORMS CONTROL VALUE IN THE MMC STRUCTURED FIELD ID *identifier*, IS NOT ACCEPTABLE.

Explanation

The Constant Forms Control modification in the Medium Modification Control (MMC) structured field contained an unsupported value. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK274S

DATA IN A FORMDEF RESOURCE IS INVALID: THE MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INCLUDE CONFLICTING CONSTANT FORMS CONTROL VALUES FOR THE SAME SIDE OF THE SHEET.

Explanation

All Medium Modification Control (MMC) structured fields referenced by the Medium Copy Count (MCC) structured field must use the same Constant Forms Control value for the same side of a sheet. The MMC and MCC structured fields are contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK275S

DATA IN A FORMDEF RESOURCE IS INVALID: A MEDIUM MAP SPECIFIES ONLY CONSTANT DATA FOR A PAGE.

Explanation

An attempt was made to process a page using a medium map specifying Constant Forms Control for both the front and back sides of a duplexed page or for the front side of a simplex page. Another medium map must be invoked to allow processing of the remaining line or page data. The Constant Forms Control is contained in a Medium Modification Control (MMC) structured field. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK278S

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE MAPPING OPTION SPECIFIED IN THE *structuredfield* IS INCORRECT OR UNSUPPORTED.

Explanation

The structured field in error contained an incorrect Mapping Option value or the printer does not support the Mapping Option value. The structured field could be contained in a bar code object, graphics object, image object, or object container object, or it could be an IOB structured field with a bad mapping option triplet. The bar code object, graphics object, image object, or IOB can be contained in an overlay, MO:DCA-P page, or embedded in line data. The graphics object can be contained in a composed-text print data set or an overlay, or embedded in a data set containing line data. The image object can be contained

in a composed-text print data set, an overlay, or a page segment, or embedded in a data set containing line data.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the object, correct the error and resubmit the print request. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the object, contact your system programmer.

APK289I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE FONT SCALING SIZE VALUE SPECIFIED IN AN MCF STRUCTURED FIELD IS NOT ACCEPTABLE.

Explanation

The value specified for either the font vertical scale factor, the horizontal scale factor, or the font width is not within the acceptable range of 0 to 32767.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program is valid. If the input is valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK299I

AN IM IMAGE OBJECT CONTAINS INVALID OR INCORRECT DATA. THE IM IMAGE OBJECT CANNOT BE CONVERTED TO AN IO IMAGE OBJECT.

Explanation

This message is issued when ACIF converts an IM image object to an IO image object and one of the image size values is zero. For a simple IM image object, this message is issued if either the XSize or YSize parameter value of the Image Input Descriptor (IID) structured field is zero. For a complex IM image object, this message is issued if one of the XCSize, YCSize, XFileSize, or YFileSize parameter values of the Image Cell Position (ICP) structured field is zero. When ACIF processes a page segment in an inline resource group, the resource is converted from an IM1 image to an IOCA image unless the IMAGEOUT=ASIS parameter is specified. This message is issued if the application later includes the page segment in a page or overlay with a non-zero orientation or with L-units other than 1440 per inch.

System action

ACIF stops processing the print data set.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program is valid. If the input is valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

Correct the error and resubmit the request.

APK300I

DATA IN A PAGEDEF RESOURCE IS INVALID: THE NEXT LINE DESCRIPTOR IF SKIPPING PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER *number* IS 0.

Explanation

The current record contains a control character that indicates a skip to a Line Descriptor (LND) structured field with a specific channel control. However, the LND structured field identified in this message had a value of 0 in its NEXT LINE DESCRIPTOR IF SKIPPING parameter. The LND structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK301S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE NEXT LINE DESCRIPTOR IF SKIPPING PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER *number* IS *parametervalue*. THIS EXCEEDS THE LNC STRUCTURED FIELD COUNT VALUE OF *parametervalue*.

Explanation

In the Line Descriptor (LND) structured field identified in this message, the value of the next LND IF SKIPPING parameter is greater than the total number of LND structured fields in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK307S

DATA IN A PAGEDEF RESOURCE IS INVALID: IN LND STRUCTURED FIELD NUMBER *number*, THE REUSE RECORD FLAG WAS SET BUT THE NEXT LINE DESCRIPTOR IF REUSING DATA PARAMETER WAS 0.

Explanation

In the Line Descriptor (LND) structured field identified in this message, the Reuse Record flag had a value of B'1', indicating that the data being processed in this LND structured field should be reused and processed. The NEXT LINE DESCRIPTOR IF REUSING DATA parameter should point to the LND structured field used to continue processing. However, the value for the REUSING DATA parameter was X'0000', indicating the end of the chain. The LND structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK309S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE REPEATING GROUP LENGTH PARAMETER VALUE IN CCP STRUCTURED FIELD *ccpidentifier* IS INVALID.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. Either the LENGTH OF REPEATING GROUPS parameter is zero, or the length of the repeating group data is not a multiple of the size specified in that parameter. The CCP structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more

information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK310S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE COUNT PARAMETER VALUE IN THE LNC STRUCTURED FIELD WAS 0.

Explanation

The COUNT parameter in the Line Descriptor Count (LNC) structured field had a value of zero. The LNC structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK312S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE SIZE PARAMETER VALUE IN THE FDS STRUCTURED FIELD WAS 0.

Explanation

The SIZE parameter in the Fixed Data Size (FDS) structured field has a value of 0. The FDS structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK314S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE NUMBER OF REPEATING GROUPS PARAMETER VALUE IN CCP STRUCTURED FIELD *ccpidentifier* IS INVALID.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. Either the NUMBER OF REPEATING GROUPS parameter contained in the CCP structured field is zero, or the number of repeating groups does not match the number specified in the parameter. The CCP structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK315S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE NEXT LINE DESCRIPTOR IF SPACING PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER *number* IS 0.

Explanation

The logical-record control character indicates that the NEXT LINE DESCRIPTOR IF SPACING parameter should be followed. However, in the Line Descriptor (LND) structured field identified in this message, the NEXT LINE DESCRIPTOR IF SPACING parameter value was zero. The LND structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK316S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE NEXT LINE DESCRIPTOR IF SPACING PARAMETER IN LND STRUCTURED FIELD NUMBER *number* IS *parametervalue*. THIS VALUE IS TOO LARGE.

Explanation

The logical record control character indicates that the NEXT LINE DESCRIPTOR IF SPACING parameter in the Line Descriptor (LND) structured field should be followed. However, in the Line Descriptor (LND) structured field identified in this message, the NEXT LINE DESCRIPTOR IF SPACING parameter value was greater than the total number of line descriptors in the data map. The LND structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK317S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE LENGTH OF COMPARISON STRING PARAMETER VALUE IN CCP STRUCTURED FIELD *ccpidentifier* IS INVALID.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. Either the LENGTH OF COMPARISON STRING parameter is zero, or the length of the comparison string data does not match the length of a repeating group minus the fixed lengths of the remaining fields of the repeating group. The CCP structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK319I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: LND, RCD, OR XMD STRUCTURED FIELD NUMBER *number* HAS A NULL VALUE SPECIFIED IN THE SUPPRESSION TOKEN NAME PARAMETER. A NULL VALUE IS NOT VALID.

Explanation

The SUPPRESSION TOKEN NAME parameter in the Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field in the page definition has a null value. A null value is any value that contains X'FFFF' in the first two bytes.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK320S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE IDENTIFIER *identifier1* SPECIFIED IN THE NEXT CCP IDENTIFIER PARAMETER IN CCP STRUCTURED FIELD *identifier2* WAS NOT FOUND.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The NEXT CONDITIONAL PROCESSING CONTROL IDENTIFIER parameter in the CCP structured field specifies the identifier used to locate a CCP, if the CCP structured fields are chained. The identifier must match a value specified in the CCP IDENTIFIER parameter of another CCP within the same page definition. The identifier specified in the NEXT CCP IDENTIFIER parameter did not match the CCP IDENTIFIER of any CCPs in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK321S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE TIMING OF ACTION PARAMETER VALUE *value* IN CCP STRUCTURED FIELD *ccpidentifier* IS INVALID.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The TIMING OF ACTION parameter in one of the repeating groups of the CCP structured field contains an incorrect value. The CCP structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK322S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE MEDIUM MAP ACTION PARAMETER VALUE *value* IN CCP STRUCTURED FIELD *ccpidentifier* IS INVALID.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The MEDIUM MAP ACTION parameter in one of the repeating groups of the CCP structured field contains an incorrect value. The CCP structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK323S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE DATA MAP ACTION PARAMETER VALUE *value* IN CCP STRUCTURED FIELD *ccpidentifier* IS INVALID.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The DATA MAP ACTION parameter in one of the repeating groups of the CCP structured field contains an incorrect value. The CCP structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK324S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE COMPARISON PARAMETER VALUE *value* IN CCP STRUCTURED FIELD *ccpidentifier* IS INVALID.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The COMPARISON parameter in one of the repeating groups of the CCP structured field contains an incorrect value. The CCP structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK326S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE DATA MAP *dataname* SPECIFIED IN THE DATA MAP NAME PARAMETER OF CCP STRUCTURED FIELD *ccpidentifier* WAS NOT FOUND.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The DATA MAP NAME parameter in one of the repeating groups of the CCP structured field specifies the token name of a data map used to locate a data map in the page definition. The name must match the value specified in the TOKEN NAME parameter in one of the Begin Data Map (BDM) structured fields in the current page definition. No data map with name *dataname* was found in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK327S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE NEXT LINE DESCRIPTOR IF REUSING DATA PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER *number* WILL CAUSE AN INFINITE LOOP.

Explanation

The NEXT LINE DESCRIPTOR IF REUSING DATA parameter in the Line Descriptor (LND) structured field identified in this message caused an infinite-loop condition. The LND structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK329S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE NEXT LINE DESCRIPTOR IF REUSING DATA PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER *number* IS *parametervalue1*. THIS EXCEEDS THE LNC STRUCTURED FIELD COUNT VALUE OF *parametervalue2*.

Explanation

The NEXT LINE DESCRIPTOR IF REUSING DATA parameter in the Line Descriptor (LND) structured field identified in this message has an incorrect value. The value is greater than the COUNT parameter in the Line Descriptor Count (LNC) structured field in the current data map. The LNC and LND structured fields are contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK330I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: WHEN THE DATA START POSITION VALUE IS ADDED TO THE DATA LENGTH VALUE IN LND, RCD, OR XMD STRUCTURED FIELD NUMBER *number*, IT EXCEEDS THE FDS STRUCTURED FIELD SIZE VALUE OF *parametervalue*.

Explanation

The Use Fixed Data flag in byte 0 in the Line Descriptor (LND) structured field, in byte 11 in the Record Descriptor (RCD) structured field, or in byte 1 in the XML Descriptor (XMD) structured field was set to B'1'. This indicates that data from Fixed Data Text (FDX) structured fields is to be added to the data placed within the page by the LND, RCD, or XMD structured field. The FDX, XMD, RCD, and LND structured fields are in the page definition.

The DATA START POSITION parameter in the LND, RCD, or XMD structured field indicates the offset of the first byte of data. The DATA LENGTH parameter specifies how many bytes of FDX are to be placed within the page. This error was caused when these two parameters specified more data than the FDX structured fields contain. The number of bytes of data in the FDX structured fields can be found in the SIZE parameter of the Fixed Data Size (FDS) structured field.

System action

PSF stops processing the current data set, and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the infomation provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK334S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE AMOUNT OF FIXED DATA RECEIVED DID NOT AGREE WITH THE VALUE SPECIFIED IN THE FDS STRUCTURED FIELD SIZE PARAMETER.

Explanation

The Fixed Data Text (FDX) structured field contained more bytes of data than what was indicated in the SIZE parameter of the Fixed Data Size (FDS) structured field. The FDS and FDX structured fields are contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK335S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE MEDIUM MAP *mediummapname* SPECIFIED IN THE MEDIUM MAP NAME PARAMETER OF CCP STRUCTURED FIELD *ccpidentifier* WAS NOT FOUND.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The MEDIUM MAP NAME parameter in one of the repeating groups of the CCP structured field specifies the token name of a medium map used to locate a medium map in the form definition. The name must match the value specified in the TOKEN NAME parameter in one of the Begin Medium Map (BMM) structured fields in the current form definition. No medium map with name *mediummapname* was found in the form definition. The CCP structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK337I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: IN LND, RCD, OR XMD STRUCTURED FIELD NUMBER *number*, THE CONDITIONAL PROCESSING FLAG WAS SET BUT THE CONDITIONAL PROCESSING CONTROL IDENTIFIER WAS ZERO.

Explanation

In the Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field, the Conditional Processing flag had a value of B'1', indicating that the line data to be processed by this LND, RCD, or XMD structured field is to be compared with a value specified in a Conditional Processing Control (CCP) structured field. The CCP IDENTIFIER parameter in the LND, RCD, or XMD structured field is used to find one of the CCP structured fields in the current page definition. This parameter was set to 0, which is not a valid value if the Conditional Processing flag is on. The LND, RCD, XMD, and CCP structured fields are in the page definition.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK339I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE IDENTIFIER *identifier* SPECIFIED IN THE CONDITIONAL PROCESSING CONTROL IDENTIFIER PARAMETER IN LND, RCD, OR XMD STRUCTURED FIELD NUMBER *number* WAS NOT FOUND.

Explanation

In the Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field, the Conditional Processing flag had a value of B'1', indicating that the line data to be processed by this LND, RCD, or XMD structured field is to be compared with a value specified in a Conditional Processing Control (CCP) structured field. The CCP IDENTIFIER parameter in the LND, RCD, or XMD structured field is used to find one of the CCP structured fields in the current page definition. However, the identifier specified in the LND, RCD, or XMD structured field identified in this message does not match the value specified in the CCP IDENTIFIER parameter in any of the CCP structured fields in the current page definition. The LND, RCD, XMD, and CCP structured fields are in the page definition.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK340I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NEXT LINE DESCRIPTOR IF CONDITIONAL PROCESSING PARAMETER VALUE IN LND, RCD, OR XMD STRUCTURED FIELD NUMBER *number* IS *value1*. THIS EXCEEDS THE LNC STRUCTURED FIELD COUNT VALUE OF *value2*.

Explanation

The NEXT LINE DESCRIPTOR IF CONDITIONAL PROCESSING parameter in the Line Descriptor (LND), Record Format Descriptor (RCD), or XML Descriptor (XMD) structured field has an incorrect value. The value is greater than the COUNT parameter in the Line Descriptor Count (LNC) structured field in the current data map. The LNC, LND, RCD, and XMD structured fields are contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK342I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NEXT LINE DESCRIPTOR IF CONDITIONAL PROCESSING PARAMETER VALUE IN LND, RCD, OR XMD STRUCTURED FIELD NUMBER *number* WILL CAUSE AN INFINITE LOOP.

Explanation

The NEXT LINE DESCRIPTOR IF CONDITIONAL PROCESSING parameter in the Line Descriptor (LND), Record Format Descriptor (RCD), or XML Descriptor (XMD) structured field caused an infinite-loop condition. The LND, RCD, and XMD structured fields are in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK343I

DATA IN AN INPUT RECORD OR PAGEDEF RESOURCE IS NOT VALID: RELATIVE POSITIONING PLACED DATA OUTSIDE THE LOGICAL PAGE IN THE NEGATIVE Y DIRECTION. THE PRIOR AND CURRENT LND, RCD, OR XMD STRUCTURED FIELD NUMBERS ARE: *priornumber* AND *currentnumber*.

Explanation

When relative positioning is being used on a Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field, the relative position specified for the Y direction can be a negative value. The current LND, RCD, or XMD position (*priornumber*) defines the baseline position from which the relative offset of the current LND, RCD, or XMD is measured.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK344S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE NUMBER OF LND STRUCTURED FIELDS DOES NOT MATCH THE VALUE SPECIFIED IN THE LNC STRUCTURED FIELD.

Explanation

The number of Line Descriptor (LND) or Record Descriptor (RCD) structured fields found in a page definition is either greater than or less than the value specified in the Line Descriptor Count (LNC) structured field. The LND, RCD, and LNC structured fields are in the page definition.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment in which the error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK346W

DATA IN AN INPUT RECORD OR PAGEDEF RESOURCE IS INVALID: A SKIP TO A NONEXISTENT CHANNEL = *channel* ON RECORD NUMBER = *recordnumber* WAS DETECTED WITHIN THE LND STRUCTURED FIELDS. OUTPUT WAS FORCED TO SINGLE SPACING, WHICH MAY CAUSE BLANK PAGES.

Explanation

An attempt was made to skip to a channel not defined in the current data map. The Line Descriptor (LND) structured fields in the page definition are incorrect. During scanning, the entire NEXT LINE DESCRIPTOR IF SKIPPING parameter could not be followed because an LND had the End Page If Skipping flag set. This created an infinite loop on the same input record. The LND structured field is contained in the page definition.

System action

The record containing the error was forced to single spacing. When forced single spacing occurs, the carriage control character on the record is ignored. The record is treated as if a X'09' machine control character or a X'40' ANSI control character was specified in the record that caused the error.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to *Advanced Function Presentation: Diagnosis Guide* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK350S

DATA IN A PAGEDEF RESOURCE IS INVALID: IN LND STRUCTURED FIELD NUMBER *number*, THE SHIFT-OUT CODED FONT LOCAL IDENTIFIER WAS NON-ZERO BUT THE GENERATE FONT CHANGE FLAG WAS NOT SET.

Explanation

In the Line Descriptor (LND) or Record Descriptor (RCD) structured field identified in this message, the Shift-Out Coded Font Identifier was non-zero. The Generate Font Change flag should be set to indicate

that the Primary Coded Font Local Identifier should be used whenever a shift-in code is processed. However, the Generate Font Change flag had a value of B'O'. The LND or RCD structured field is contained in the page definition.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK352I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: BAR CODE GENERATION WAS REQUESTED ON LND, RCD, OR XMD STRUCTURED FIELD NUMBER *number*, BUT THE PRINTER DOES NOT SUPPORT BAR CODE OBJECTS.

Explanation

A Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field in a page definition has requested PSF to generate a bar code object from the line data, but the printer does not support bar code objects.

System action

PSF ignores the request and continues processing the data set.

System programmer response

If the page definition is for a separator page, the message data set, or the default page definition for the user print data sets defined in the PSF startup procedure, delete the option from the page definition that requests that a bar code be generated.

User response

To print the data set and have PSF generate bar code objects, submit the print job to a printer that supports bar code objects. For more information about AFP printers that support bar code objects, refer to *Advanced Function Presentation: Printer Information*.

APK353S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE DATA LENGTH PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER *number* DOES NOT MATCH THE LENGTH OF COMPARISON STRING PARAMETER VALUE IN CCP STRUCTURED FIELD *ccpidentifier*.

Explanation

In the Line Descriptor (LND) structured field, the value of the DATA LENGTH parameter is used in identifying the field of the current input record for which conditional processing is to be performed. This field is to be compared with the Comparison String specified in the Conditional Processing Control (CCP) structured field. The length specified in the DATA LENGTH parameter in the LND structured field does not

match the length specified in the LENGTH OF COMPARISON STRING parameter of the CCP structured field. The LND and CCP structured fields are contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK355S

DATA IN A PAGEDEF RESOURCE IS INVALID: A PAGE OVERLAY WAS REQUESTED IN LND OR RCD STRUCTURED FIELD *structuredfield*, BUT THE PRINTER DOES NOT SUPPORT PAGE OVERLAYS.

Explanation

An overlay has been requested by a Line Descriptor (LND) or Record Descriptor (RCD) structured field within the page definition, but the printer does not support page overlays.

System action

PSF terminates the page and continues processing the data set.

System programmer response

If the page definition is for a separator page, the message data set, or the default page definition for the user print data sets defined in the PSF startup procedure, delete the page overlay from the page definition.

User response

To print the data set containing the page overlay, submit the print job to a printer that supports page overlays. For more information about AFP printers that support page overlays, refer to *Advanced Function Presentation: Printer Information*.

APK356S

DATA IN A PAGEDEF RESOURCE IS INVALID: A PAGE SEGMENT OR OVERLAY WAS REQUESTED IN THE LND OR RCD STRUCTURED FIELD *structuredfield*, BUT THE INLINE OR BASELINE POSITION VALUES WERE SPECIFIED FOR THE LND OR RCD.

Explanation

If any resource object-include triplets are specified in the LND structured field, bits 2 and 3 of bytes 0–1 in the LND structured field must both be set. If any resource object-include triplets are specified in the RCD structured field, bits 2 and 3 of bytes 11–13 in the RCD structured field must both be set.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment in which an error occurred.

System programmer response

If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK359I

AN INLINE MEDIUM MAP WAS ENCOUNTERED IN THE DATASET, BUT INLINE MEDIUM MAPS ARE NOT SUPPORTED.

Explanation

A Begin Medium Map (BMM) structured field was encountered in the data stream after resources for the data set had been processed. ACIF does not support inline medium maps between pages. The data set might have been created by a program that creates inline medium maps, but a data set that contains inline medium maps cannot be printed.

System action

ACIF stops processing the print data set.

System programmer response

See the I/O error message to determine an appropriate action.

User response

Correct the error and resubmit the request.

APK364I

THE SET OF MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INDICATES DIFFERENT SELECT INPUT SOURCE VALUES FOR THE FRONT AND BACK SIDES OF A DUPLEX SHEET.

Explanation

The Medium Modification Control (MMC) structured field referenced by the Medium Copy Count (MCC) structured field repeating groups specify different input source or media type local ID values, along with either tumble or normal duplex. This is an attempt to print the front and back sides of a sheet from different input bins.

System action

The form definition containing the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition specified on the user's OUTPUT JCL statement, PSF cannot begin printing the data set; it tries to print the next data set. PSF issues a message identifying the position of the structured field in the form definition. PSF issues additional messages identifying the processing environment when the error was found.

System programmer response

If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK366I

DATA IN AN INPUT RECORD OR PAGEDEF RESOURCE IS NOT VALID: THE ORIENTATION USED WITH RELATIVE POSITIONING IS DIFFERENT THAN THE LAST ORIENTATION USED FOR PRINTING. THE PRIOR AND CURRENT LND, RCD, OR XMD STRUCTURED FIELD NUMBERS ARE: *priornumber* AND *currentnumber*.

Explanation

When relative positioning is being used on a Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field, the text orientation field of the current LND, RCD, or XMD (*currentnumber*) must match the text orientation field of the LND, RCD, or XMD (*priornumber*) that was last used for positioning data. The prior LND, RCD, or XMD position defines the baseline position from which the relative offset of the current LND, RCD, or XMD is measured.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment in which the error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK367I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE OUTPUT OPTION SPECIFIED IN AN IOB STRUCTURED FIELD WITH RESOURCE LOCAL ID *identifier* IS NOT VALID OR IS UNSUPPORTED. THE IOB IS INCLUDED WITH LND, RCD, OR XMD STRUCTURED FIELD NUMBER *number*.

Explanation

The Include Object (IOB) structured field in error contained an Output Option value that is not valid, or the printer does not support the Output Option value. The IOB is included using the Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field identified in this message. The IOB, LND, RCD, and XMD structured fields are contained in the page definition.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment in which an error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK368S

DATA IN A PAGEDEF RESOURCE IS INVALID: THE RESOURCE LOCAL ID *identifier* SPECIFIED IN THE EXTENDED RESOURCE LOCAL ID TRIPLET ON LND STRUCTURED FIELD NUMBER *number* WAS NOT FOUND.

Explanation

In the Line Descriptor (LND) or Record Descriptor (RCD) structured field, and Extended Resource Local Identifier triplet specifies a local ID (*identifier*) of an Include Object (IOB) structured field that is to be used to include an object when this LND or RCD is used for printing. The identifier specified on the LND or RCD does not match any of the IOB structured fields in the page definition.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment in which an error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK369S

STRUCTURED FIELD *structuredfield* HAS AN INCORRECT OBJECT CLASS VALUE IN AN OBJECT CLASSIFICATION TRIPLET.

Explanation

The Object Classification (X'X'10") triplet in the structured field specified in the message has an incorrect object class value. Possible incorrect class values for each structured field are:

- Map Data Resource (MDR)
 - Non-presentation object container is included in a repeating group.
 - Object container or IOCA embedded in a page or overlay has a data object font mapped in the Object Environment Group.
- Include Object (IOB) or Preprocess Presentation Object (PPO)
- Non-presentation object container, data object font (DOF), or non-DOF secondary resource is specified.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program is valid. If the input is valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource, correct the error and resubmit the print request. Refer to Mixed Object Document Content Architecture Reference and Advanced Function Presentation: Programming Guide and Line Data Reference for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK380S

THE REGISTRATION ID (*identifier*) OF AN OBJECT CONTAINER RESOURCE, NAME *resourcename* OR OBJECT OID *objectoid*, DOES NOT MATCH THE CORRESPONDING REGISTRATION ID FOR THE INVOKING JCL KEYWORD OR STRUCTURED FIELD.

Explanation

An object container resource was requested through a JCL keyword or an IOB or MDR structured field, but the object classification triplet in the Begin Object Container structured field did not have the corresponding registration ID. For a list of registration IDs and their assumed functions, refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference*. A value of *** means that the resource name or object OID was not specified.

System action

If the object container was called out by JCL, PSF stops processing the current data set and issues additional messages that identify the processing environment in which an error occurred. If the object container was included by an IOB or MDR structured field, PSF terminates the page or overlay. PSF attempts to locate the end of the current page and resume processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set.

System programmer response

If an IBM licensed program was used to create the structured fields for the object container that contains the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the object container resource, ensure that the registration ID corresponds to the keyword used to invoke the resource or the registration ID specified in the object classification triplet specified on the IOB or MDR structured field.

APK381S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: THE REGISTERED OBJECT ID IN THE OBJECT CLASSIFICATION TRIPLET ON A *structuredfield* STRUCTURED FIELD IS NOT SPECIFIED.

Explanation

The registered object ID is 0 in the object classification triplet. Object containers require a registered ID to be specified.

System action

If the structured field is included in an object embedded in a page or overlay, or the structured field is in a resource included by a page or overlay, PSF terminates the page or overlay. PSF attempts to locate the end of the current page and resume processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. For non-presentation object containers, PSF stops printing the data set.

If the error is contained in a page definition, PSF terminates processing of the data set and continues processing with the next data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues additional messages identifying the processing environment in which the error occurred.

System programmer response

If an IBM licensed program was used to create the structured field with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK384S

DATA IN A FORMDEF RESOURCE IS INVALID: THE SET OF MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INCLUDES CONFLICTING PRESENTATION SYSTEM SETUP ID VALUES.

Explanation

Multiple MMC structured fields referenced by the MCC structured field do not use the exact same set of Presentation System Setup ID values.

System action

ACIF stops processing the print data set.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MCC structured field. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MCC has no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK385S

DATA IN A FORMDEF RESOURCE IS INVALID: THE MODIFICATIONS SPECIFIED IN THE MMC STRUCTURED FIELD *structuredfield* INCLUDE UNPAIRED *keyword1* AND *keyword2* KEYWORDS.

Explanation

The keywords must be paired in the Medium Modification Control (MMC) structured field. This form definition has one or the other keyword but not both, or the keyword pairs are not adjacent. The MMC structured field is contained in the form definition.

System action

The form definition containing the error is not used, and one of these occurs:

- PSF is not started if the form definition containing the error is defined in the PSF startup procedure. The form definition resources defined in the PSF startup procedure are for separator pages, for the message data set, and for the default form definition resource for user print data sets.
- If the error is in a form definition specified on the user's OUTPUT JCL statement, PSF cannot begin printing the data set; it tries to print the next data set. PSF issues a message identifying the position of the structured field in the form definition. PSF issues additional messages identifying the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK386S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: A REQUIRED TRIPLET with ID *identifier* WAS MISSING FROM AN IOB STRUCTURED FIELD.

Explanation

When identifier is:

X'4C'

The x- or y-axis origin for object content or an object area size (X'4C') triplet was specified on an IOB, but no measurement unit (X'4B') triplet was specified. The structured field is contained in a print data set or overlay.

X'22'

The Extended Resource Local Identifier (X'22') triplet is required when the IOB structured field is contained in a page definition.

System action

If the error is contained in a page definition, PSF terminates processing of the data set and continues processing with the next data set. Otherwise, PSF terminates the page or overlay containing the structured field in error. PSF attempts to locate the end of the current page and resumes processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message identifying the position of the structured field in the input data stream or resource. PSF issues additional messages identifying the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to place the IOB structured field in the print data set or overlay, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you placed the IOB structured field in the print data set or overlay, correct the error and resubmit the ACIF job. If you used a program to place the IOB structured field in the print data set or overlay, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK387S

DATA IN AN INPUT RECORD IS INVALID: A PARAMETER IN AN IOB STRUCTURED FIELD CONTAINS UNACCEPTABLE DATA.

Explanation

One of the parameters in the Include Object (IOB) structured field is not valid. The object type specified is not supported or is not valid or the x or y offset of the object area or the rotation value are not explicitly specified when the reference coordinate system is set to X'00'. The IOB structured field is contained in the print data set or an overlay.

System action

ACIF stops processing the input data set.

System programmer response

No action is required

User response

If you placed the IOB structured field in the input data set or overlay, correct the error and resubmit the ACIF job. If you used a program to place the IOB structured field in the print data set or overlay, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK388S

DATA IN A PAGE SEGMENT IS INVALID: *structuredfield* STRUCTURED FIELD IS NOT ALLOWED IN A PAGE SEGMENT INCLUDED WITH AN IOB.

Explanation

Only MO:DCA-P page segments are allowed to be included with an IOB structured field. MO:DCA-P page segments cannot contain IM1 image or PTOCA data.

System action

ACIF stops processing the input data set.

System programmer response

No action is required

User response

If you placed the IOB structured field in the input data set or overlay, correct the error and resubmit the ACIF job. If you used a program to place the IOB structured field in the print data set or overlay, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK389S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: THE FONT RESOLUTION AND METRIC TECHNOLOGY TRIPLET SPECIFIES AN INCORRECT VALUE.

Explanation

There is an incorrect value specified for the metric technology, the unit base, or the units per unit base field in the Font Resolution and Metric Technology triplet (X'84'). The triplet is specified on a Map Coded Font (MCF) structured field, which can be in a print data set or overlay.

System action

ACIF stops processing the print data set.

System programmer response

If an IBM licensed program was used to create the structured fields with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the job to ACIF. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK390S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: THE *structuredfield* STRUCTURED FIELD CONTAINS A *triplet* TRIPLET THAT HAS AN INVALID VALUE. THE INVALID VALUE STARTS IN BYTE *byte* OF THE TRIPLET.

Explanation

An incorrect value was specified for a field that starts in byte offset of the triplet identified in this message. The triplet is specified on the structured field identified in this message.

System action

If the error occurred in a form definition, a page definition, or a non-presentation object container resource (for example, COMSETUP), the form definition, page definition, or non-presentation object container resource is not used, and one of these occurs:

- PSF is not started for any of these:
 - The default form definition
 - A form definition specified for printing messages or separator pages
 - A page definition specified for printing messages or separator pages
- PSF cannot begin printing the data set for a form definition or non-presentation object container resource (or page definition if printing line data) specified on a user's OUTPUT JCL statement; PSF tries to print the next data set. If the error occurred in a structured field in a page or another type of resource, PSF attempts to find the end of the page or resource. If PSF can find the end of the page or resource, it prints any data accumulated for the current page. If PSF cannot find the end of the page or resource, the data set is terminated.

PSF issues a message identifying the position of the structured field in the data stream or resource. PSF issues additional messages identifying the processing environment in which the error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in

determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the object, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the object, contact your system programmer.

APK392I

DATA IN A FORMDEF RESOURCE IS NOT VALID: THE SCOPE VALUE IN THE MFC IS NOT VALID. EITHER DOCUMENT LEVEL OR PRINT FILE LEVEL FINISHING WAS SPECIFIED IN THE MEDIUM MAP OR MEDIUM LEVEL FINISHING WAS SPECIFIED IN THE DEG.

Explanation

Either a Document Environment Group (DEG) or a medium map in the current form definition contains a Medium Finishing Control (MFC) structured field with an incorrect value specified for the scope.

System action

The MFC is ignored and processing continues. ACIF might issue additional messages identifying the processing environment in which the error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program is valid. If the input is valid, report the problem to your service representative.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the problem might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK393I

THE INPUT BIN SPECIFIED IN THE MMC STRUCTURED FIELD OR ON THE OUTPUT STATEMENT IS AN INSERTER BIN AND IS DISABLED. AN ALTERNATIVE BIN WAS SUBSTITUTED.

Explanation

The Medium Modification Control (MMC) structured field or the output statement requested an input bin that is supported by the printer but is disabled. This bin is an inserter bin. The MMC structured field is contained in the form definition. The output statement is in the JCL.

System action

ACIF continues processing, selecting paper from an alternative bin. The inserter pages are blank sheets from the alternative bin.

System programmer response

No action is required

User response

If the output is not acceptable, submit the print request to a printer that has the specified bin available, or ensure that the bin is enabled on the original printer before resubmitting the print request.

APK395I

A FORMDEF RESOURCE REQUESTED A MEDIA EJECT CONTROL TO THE NEXT BACK-SIDE AND DUPLEX=NO WAS SPECIFIED ON THE OUTPUT STATEMENT.

Explanation

When a media eject control to the next back-side is specified in a form definition, the DUPLEX=NO keyword on the OUTPUT statement cannot be used to change from duplex (specified in the form definition) to simplex. The reason is that an incompatible request is being made; you cannot eject to the next back-side when simplexing.

When a media eject control to the next back-side is specified in the form definition and the form definition requests normal or tumble duplex, the only valid option for the duplex keyword is to specify either DUPLEX=NORMAL or DUPLEX=TUMBLE on the OUTPUT statement.

System action

ACIF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

None.

User response

Resubmit the job without requesting the duplex keyword on the OUTPUT statement.

APK396I

DATA IN A FORMDEF RESOURCE IS INVALID: THE OUTPUT BIN SELECTION VALUE IN MMC STRUCTURED FIELD, ID *identifier*, IS NOT ACCEPTABLE.

Explanation

In the Medium Modification Control (MMC) structured field whose identifier is specified in the message text, the output bin selection parameter value was not valid. The MMC structured field is contained in the form definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK397I

THE SET OF MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INDICATES DIFFERENT OUTPUT BIN VALUES FOR THE FRONT AND BACK SIDES OF A DUPLEX SHEET.

Explanation

The Medium Modification Control (MMC) structured fields referenced by the Medium Copy Count (MCC) structured field repeating groups specify different output bin values along with either tumble or normal duplex. This is an attempt to place the front and back sides of a sheet into different output bins.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK398I

DATA IN A FORMDEF RESOURCE IS INVALID: THE SET OF MODIFICATIONS SPECIFIED IN THE MMC STRUCTURED FIELD, ID *identifier*, INCLUDES DUPLICATE CONFLICTING VALUES FOR THE *keyword* KEYWORD.

Explanation

The Medium Modification Control (MMC) structured field contains duplicate conflicting values for the keyword identified in the message text. The MMC structured field is in the form definition.

System action

ACIF issues this message and continues processing, ignoring the duplicate keyword.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MMC has no errors, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK400S

THE *parameter* NUMBER VALUE IS NOT NUMERIC.

Explanation

A numeric value must be specified after the parameter.

System action

ACIF terminates.

System programmer response

No action is required

User response

Use a numeric value after the parameter and resubmit the job.

APK401S

THE *parameter* NAME MUST BE DELIMITED WITH QUOTES.

Explanation

The attribute name of the parameter must begin and end with single quotes.

System action

ACIF terminates.

System programmer response

No action is required

User response

Use single quotes before and after the attribute name in the parameter.

APK402S

THE PARAMETER *parameter* IS INVALID.

Explanation

A parameter that is not valid for ACIF was specified.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameter and resubmit the job.

APK403S

THE REQUESTED RESOURCE *number* IS UNKNOWN.

Explanation

A resource I/O has been requested, but the resource type is unknown to ACIF. This condition is caused by an ACIF logic error. The resource type codes are listed below:

Type	Resource
1	Print input file
2	FORMDEF file
3	PAGEDEF file

Type	Resource
4	OVERLAY file
5	SEGMENT file
6	Coded FONT file
7	Coded PAGE file
8	FONT Character Set file
9	FONT Metric file
10	FONT Shape file
20	Print output file
21	Messages output file
22	SPOOL file
23	Dummy input file
24	Dummy output file
25	Parameter file
26	Resource Object file

System action

ACIF terminates.

System programmer response

No action is required

User response

Contact IBM Service.

APK404S

THE ATTRIBUTE NAME USED IN *indexn* HAS AN IMPROPER USE OF QUOTES.

Explanation

An unpaired set of quotes was found in the attribute name for an INDEX n parameter.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the INDEX n parameter and resubmit the job.

APK405S

A VALUE OF *value* IS INVALID FOR PARAMETER *parameter*.

Explanation

The value supplied for a parameter is not valid.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameter value and resubmit the job.

APK406S

PARAMETER *parameter* HAS TOO MANY DATA SETS SPECIFIED.

Explanation

More than eight data sets have been supplied for the parameter.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the number of data sets and resubmit the job.

APK407S

A RESTYPE PARAMETER OF *value* IS NOT VALID.

Explanation

A resource type of NONE was found with another value in the RESTYPE parameter. Examples of other values are: FONT, OVLY, FDEF, or PSEG. A resource type of NONE cannot be specified with another value.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the RESTYPE parameter and resubmit the job.

APK408S

A VIRTUAL STORAGE REQUEST WAS UNSUCCESSFUL - REQUEST SIZE *storagerequestsize* RETURN CODE *returncode*.

Explanation

A GETMAIN macro made an unsuccessful attempt to obtain virtual storage. This message indicates the storage size and the return code from the system GETMAIN macro.

System action

ACIF terminates.

System programmer response

To interpret the GETMAIN return code, refer to the documents about application development macros for your operating system.

User response

Increase the REGION size and resubmit the job.

APK409S

A DDNAME FOR *parameter* WAS NOT SUPPLIED. *default* WAS USED.

Explanation

No DD name was specified for either the MSGDD or the PARMDD parameter.

System action

If the missing DD name was MSGDD, the DD name assigned to SYSPRINT was used. If the missing DD name was PARMDD, the DD name assigned to SYSIN was used.

System programmer response

No action is required

User response

If the DD name used was not acceptable, specify a DD name for the parameter and submit the job again.

APK410S

AN ACIF STORAGE REQUEST WAS UNSUCCESSFUL - REQUEST SIZE *storagerequestsize requesttype*
RETURN CODE *returncode*.

Explanation

An unsuccessful attempt was made to obtain or free ACIF subpool storage. This error message returns the following information:

- Storage request size
- Request type
- Return code

This error usually occurs when the system runs out of memory for one of the following reasons:

- There is insufficient memory to store page data. If the page size exceeds the total amount of storage, the conditional GETMAIN fails. The page size is determined by the number of print lines between two ASA "skip to line 1" carriage control characters.
- EXTENSIONS=RESORDER is specified, and there are too many inline resources for the amount of internal memory available.

Example:

```
AN ACIF STORAGE REQUEST WAS UNSUCCESSFUL -  
REQUEST SIZE 295, GETMAIN RETURN CODE 255.
```

System action

ACIF terminates.

System programmer response

Use the information that is provided in the message to correct the error and resubmit the job.

Note: Check that the carriage control and carriage control type are correctly specified in the input parameters.

User response

No action is required

APK411S

AN ERROR OCCURRED WHILE ATTEMPTING TO *action* THE DDNAME *ddname*, RETURN CODE *returncode*.

Explanation

The file I/O macro made an unsuccessful attempt to read from, write to, or close the named DD. The return codes are:

Return Code

Description
0 Successful
1 Permanent I/O error
2 Specified number of bytes is zero or negative
3 Incorrect data buffer address
4 Address not word aligned
6 Incorrect FILE_CB@
7 Incorrect MODE parameter
8 Data record longer than LRECL or buffer
9 File is not supported type
10 Storage allocation/deallocation failed
11 Incorrect record number
12 End of file detected
13 Disk is full
14 RECFM not valid
20 Incorrect file ID
28 File not found
51 Length exceeds maximum
310 File format not valid

System action

ACIF terminates.

System programmer response

No action is required

User response

Use the information provided in the return code to correct the problem.

APK412W

MODULE *modulename* HAS RETURNED WITH RETURN CODE *returncode*.

Explanation

A non-zero return code has been returned from the called module. This message indicates that an abnormal occurrence has taken place in the called module. This message is informational and further action takes place in higher level modules if required.

System action

None; this message is for information only.

System programmer response

No action is required

User response

See the accompanying message to determine a response.

APK413S

ATTEMPTED *action* RESOURCE FILE *ddname*, RESOURCE MEMBER NAME *membername* FAILED. RETURN CODE *returncode*.

Explanation

An attempt to open, close, read, or write a resource failed. This message indicates that an abnormal occurrence has taken place in the called module. This message is informational and further action takes place in higher level modules if required.

Return Code	Description
0	Successful
1	Permanent I/O error
2	Specified number of bytes is zero or negative
3	Incorrect data buffer address
4	Address not word aligned
6	Incorrect FILE_CB@
7	Incorrect MODE parameter
8	Data record longer than LRECL or buffer
9	File is not supported type
10	Storage allocation/deallocation failed
11	Incorrect record number
12	End of file detected
13	Disk is full
14	RECFM not valid

Return Code	Description
20	Incorrect file ID
28	File not found
51	Length exceeds maximum
310	File format not valid

System action

None; this message is for information only.

System programmer response

No action is required

User response

See the accompanying message to determine a response.

APK414I

THE FOLLOWING PARAMETERS WILL BE USED FOR THIS RUN:

Explanation

This message is issued before APK415I to begin the listing of the parameters to be used for this run.

System action

None.

System programmer response

No action is required

User response

No action is required

APK415I

parameter = value.

Explanation

For this run, the parameter listed has been used with the associated value.

System action

None.

System programmer response

No action is required

User response

No action is required

APK416I

THESE PATHS HAVE BEEN SPECIFIED FOR *libraryname*.

Explanation

This message is issued before message APK417I and shows the resource type the data set or file type is specified for.

System action

None.

System programmer response

No action is required

User response

No action is required

APK417I

REQUEST FOR UNKNOWN MESSAGE

Explanation

ACIF tried to display an undefined message.

System action

ACIF stops.

System programmer response

No action is required

User response

Report the problem to your service representative.

APK418S

THE MAXIMUM RECORD ID WAS EXCEEDED.

Explanation

The current job contains more than 999999999 documents.

System action

ACIF terminates.

System programmer response

No action is required

User response

Break the job up into a smaller number of documents.

APK419S

USER *exittype* EXIT *programname* RETURNED CODE *returncode*.

Explanation

An input, output, or resource user exit program has returned a non-zero return code.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the error in the exit program and resubmit the job.

APK420S

AN ERROR OCCURRED WHILE ATTEMPTING TO OPEN *dataset* RETURN CODE *returncode*.

Explanation

An attempt to open a data set failed. This message is informational and further action takes place in higher level modules if required.

Return Code	Description
0	Successful
1	Permanent I/O error
2	Specified number of bytes is zero or negative
3	Incorrect data buffer address
4	Address not word aligned
6	Incorrect FILE_CB@
7	Incorrect MODE parameter
8	Data record longer than LRECL or buffer
9	File is not supported type
10	Storage allocation/deallocation failed
11	Incorrect record number
12	End of file detected
13	Disk is full
14	RECFM not valid
20	Incorrect file ID
28	File not found
32	ACIF message catalog not found in paths specified by NLSPATH environment variable. ACIF uses default message catalog file /usr/lib/nls/msg/en_US/acif.cat
36	Default message catalog not accessible. Check permissions
51	Length exceeds maximum
310	File format not valid

System action

ACIF terminates.

System programmer response

No action is required

User response

Use the information provided in the return code to correct the problem.

APK421S

AN ERROR OCCURRED WHILE ATTEMPTING TO CLOSE *dataset* RETURN CODE *returncode*.

Explanation

An attempt to close a data set failed. This message is informational and further action takes place in higher level modules if required.

Return Code	Description
0	Successful
1	Permanent I/O error
2	Specified number of bytes is zero or negative
3	Incorrect data buffer address
4	Address not word aligned
6	Incorrect FILE_CB@
7	Incorrect MODE parameter
8	Data record longer than LRECL or buffer
9	File is not supported type
10	Storage allocation/deallocation failed
11	Incorrect record number
12	End of file detected
13	Disk is full
14	RECFM not valid
20	Incorrect file ID
28	File not found
32	ACIF message catalog not found in paths specified by NLSPATH environment variable. ACIF uses default message catalog file /usr/lib/nls/msg/en_US/acif.cat
36	Default message catalog not accessible. Check permissions
51	Length exceeds maximum
310	File format not valid

System action

ACIF terminates.

System programmer response

No action is required

User response

Use the information provided in the return code to correct the problem.

APK422S

AN ERROR OCCURRED WHILE ATTEMPTING TO READ *dataset* RETURN CODE *returncode*.

Explanation

An attempt to read a data set failed. This message is informational and further action takes place in higher level modules if required.

Return Code	Description
0	Successful
1	Permanent I/O error
2	Specified number of bytes is zero or negative
3	Incorrect data buffer address
4	Address not word aligned
6	Incorrect FILE_CB@
7	Incorrect MODE parameter
8	Data record longer than LRECL or buffer
9	File is not supported type
10	Storage allocation/deallocation failed
11	Incorrect record number
12	End of file detected
13	Disk is full
14	RECFM not valid
20	Incorrect file ID
28	File not found
32	ACIF message catalog not found in paths specified by NLSPATH environment variable. ACIF uses default message catalog file /usr/lib/nls/msg/en_US/acif.cat
36	Default message catalog not accessible. Check permissions
51	Length exceeds maximum
310	File format not valid

System action

ACIF terminates.

System programmer response

No action is required

User response

Use the information provided in the return code to correct the problem.

APK423S

AN ERROR OCCURRED WHILE ATTEMPTING TO WRITE *dataset* RETURN CODE *returncode*.

Explanation

An attempt to write a data set failed. This message is informational and further action takes place in higher level modules if required.

Return Code	Description
0	Successful
1	Permanent I/O error
2	Specified number of bytes is zero or negative
3	Incorrect data buffer address
4	Address not word aligned
6	Incorrect FILE_CB@
7	Incorrect MODE parameter
8	Data record longer than LRECL or buffer
9	File is not supported type
10	Storage allocation/deallocation failed
11	Incorrect record number
12	End of file detected
13	Disk is full
14	RECFM not valid
20	Incorrect file ID
28	File not found
32	ACIF message catalog not found in paths specified by NLSPATH environment variable. ACIF uses default message catalog file /usr/lib/nls/msg/en_US/acif.cat
36	Default message catalog not accessible. Check permissions
51	Length exceeds maximum
310	File format not valid

System action

ACIF terminates.

System programmer response

No action is required

User response

Use the information provided in the return code to correct the problem.

APK424I

PARAMETER 'RESFILE=PDS' IS ONLY VALID UNDER z/OS, DEFAULTING TO 'RESFILE=SEQ'.

Explanation

The supplied value for the RESFILE parameter is valid only for z/OS; it is incorrect for the UNIX, or Windowsoperating system.

System action

ACIF produces a sequential resource file.

System programmer response

No action is required

User response

No action is required

APK425S

USER *type* EXIT *program* WAS NOT FOUND.

Explanation

The input, output, or resource user exit program named on the exit's DD parameter does not exist.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct your exit program and resubmit the job.

APK426S

PARAMETER MISMATCH: RESTYPE *type* SPECIFIED, BUT NO SUPPORTING LIBRARY DEFINITIONS WERE SUPPLIED.

Explanation

The resource type *type* was specified on the RESTYPE parameter, but no DD parameter for that resource type was supplied in the ACIF parameter file.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameters and resubmit the job.

APK427I

AN ERROR OCCURRED WITH FILEDEF *filename*, RETURN CODE = rc, THE DEFAULT OF *filename filetype filemode* FOR *ddname* WILL BE USED.

Explanation

An incorrect *filename* was supplied. The defaults listed are used instead.

System action

ACIF continues.

System programmer response

No action is required

User response

No action is required

APK428S

A *resource* HAS BEEN REQUESTED, BUT NO NAME WAS GIVEN.

Explanation

The resource listed in the message was requested to be handled by ACIF, but the name to get was not passed to ACIF. This condition is caused by an ACIF logic error.

System action

ACIF terminates.

System programmer response

No action is required

User response

Contact IBM Service.

APK431S

INDEXING WITH MASK PARAMETER IS NOT SUPPORTED WITH UNICODE CODEPAGE *codepage*

Explanation

The user specified the MASK parameter for indexing, and also specified a Unicode code page with the CPGID parameter. Indexing with a MASK and Unicode data is not supported.

System action

ACIF terminates.

System programmer response

No action is required.

User response

Specify indexing without the MASK, or use an ASCII or EBCDIC code page instead of Unicode. This may also require a change to your application data.

APK432S

INVALID VALUE SPECIFIED FOR TRIGGER COLUMN RANGE

Explanation

When you specify a column range in the trigger parameter, the beginning and ending columns cannot be zero, and the ending column must be greater than the beginning column. Both column values must be in the range 1–32756.

System action

ACIF terminates.

System programmer response

No response is necessary.

User response

Enter correct values for the parameter and rerun ACIF.

APK435W

THE *ddname* DD STATEMENT SPECIFIED FOR *parameter* IS MISSING.

Explanation

An ACIF DD parameter specified a DD name that was not specified in the JCL (z/OS or VSE) or FILEDEF statement (VM).

System action

ACIF terminates.

System programmer response

No action is required

User response

Ensure that the ACIF parameter specifies a DD name that is defined in the job commands.

APK436S

THE GROUPNAME VALUE *value* IS NOT WITHIN THE ALLOWABLE RANGE.

Explanation

ACIF processing has encountered the GROUPNAME parameter with an incorrect INDEX number specified. The INDEXn range is 1–128.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the resource and resubmit the job.

APK437S

'(TYPE=FLOAT)' MAY NOT BE SPECIFIED FOR TRIGGER1.

Explanation

The 'TYPE=FLOAT' subparameter is not valid for TRIGGER1.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameter and rerun ACIF.

APK438S

THE VALUE SPECIFIED FOR *parameter1* CONFLICTS WITH THE VALUE SPECIFIED FOR *parameter2*.

Explanation

The value specified for the first parameter conflicts with the value specified for the second parameter.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameters and rerun ACIF.

APK440I

ACIF AT <APAR#> HAS COMPLETED NORMALLY WITH A RETURN CODE 0.

Explanation

ACIF processing has completed with a return code of zero. The message includes the current APAR number. For example: ACIF at PQ63028 has completed normally with a Return Code 0.

System action

This message is for information only.

System programmer response

No action is required

User response

See any accompanying messages to determine a response.

APK441I

ACIF AT <APAR#> HAS COMPLETED ABNORMALLY WITH A RETURN CODE *returncode*.

Explanation

ACIF at the maintenance level indicated by the APAR number has completed with one of these return codes:

Code	Description
4	Warning; processing continues
8	Error; processing stops
12	Severe error; processing stops
16	Fatal error; processing stops

System action

This message is for information only.

System programmer response

No action is required

User response

See any preceding messages to determine a response. If TRACE=YES is specified on z/OS and Generalized Trace Facility (GTF) is running, you might receive a return code 4 with no other messages, which you can ignore.

APK442S

ACIF HAS BEEN INVOKED WITHOUT ANY PARAMETERS.

Explanation

ACIF needs a minimum number of parameters in order to function.

System action

ACIF terminates.

System programmer response

No action is required

User response

Specify the INPUTDD, FORMDEF, CC, and PAGEDEF parameters.

APK443S

A BEGIN COLUMN SPECIFICATION FOR FIELD n IS ≤ 0 . SUCH A SPECIFICATION IS ONLY VALID WHEN (BASE=TRIGGER) IS ALSO SPECIFIED.

Explanation

FIELD n was specified with a column offset less than or equal to zero, but (BASE=TRIGGER) was not also specified. Negative column offsets in a FIELD specification are only valid when (BASE=TRIGGER) is also specified.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the ACIF FIELD n parameter specification and resubmit the job.

APK444S

MULTIPLE COLUMNS WERE SPECIFIED FOR FIELD n WHICH IS DEFINED WITH (BASE=TRIGGER). ONLY ONE COLUMN MAY BE SPECIFIED WHEN A FIELD IS DEFINED WITH (BASE=TRIGGER).

Explanation

FIELD n was specified with multiple columns and (BASE=TRIGGER). Only one column can be specified for a field that is also specified with (BASE=TRIGGER).

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the ACIF FIELD n parameter specification and resubmit the job.

APK445S

INDEX n WHICH IS DEFINED AS EITHER (TYPE=PAGERANGE) OR (TYPE=GROUPRANGE) INCLUDES FIELD n WHICH IS DEFINED AS (BASE=TRIGGER). THIS COMBINATION IS INVALID.

Explanation

INDEX n was specified as (TYPE=PAGERANGE) or (TYPE=GROUPRANGE) and with a FIELD n that was defined as (BASE=TRIGGER). This combination is not supported.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the ACIF parameters and resubmit the job.

APK446S

USE OF FIELD n BY INDEX n IS INVALID. ONLY ONE FIELD IS ALLOWED IN AN INDEX DEFINED AS (TYPE=PAGERANGE) OR (TYPE=GROUPRANGE).

Explanation

More than one field was specified for INDEX n , which is defined as either (TYPE=PAGERANGE) or (TYPE=GROUPRANGE). This is not valid.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the ACIF parameters and resubmit the job.

APK447S

THE LENGTH, *length1*, OF OFFSET PAIR *pair* FOR FIELD n DOES NOT EQUAL THE LENGTH, *length2*, SPECIFIED FOR FIELD n .

Explanation

The length of a begin-end pair, specified by the offset keyword of a field, does not match the length of the field. This is not valid; the lengths must be equal.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the ACIF parameters and resubmit the job.

APK448S

INDEXING WAS REQUESTED, BUT NO GROUP *TRIGGER n* NOR ANY *FIELD* BASED ON IT WAS SATISFIED WITHIN THE PAGE RANGE SPECIFIED BY THE INDEXSTARTBY PARAMETER.

Explanation

Indexing was requested, but the first group INDEX n satisfier was outside the range of pages specified in the INDEXSTARTBY parameter. A group INDEX is an index whose field or fields are based on a group or recordrange trigger.

If the message return code is 16, that means that the ACIF indexer process ended and did not find a group trigger to index. The default INDEXSTARTBY value is 1 (one). The INDEXSTARTBY condition is satisfied only by group triggers, and not by floating triggers. In other words, if you want RC=0 for empty files or for other files that do not contain your specified group trigger for indexing, you must add INDEXSTARTBY=0 to allow that.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameters and resubmit the job.

APK449S

INDEX FIELDS REFERENCE OUTSIDE OF THE RECORD, FIELD# *number* INPUT RECORD# *number*

Explanation

The FIELD n value specified on the INDEX n parameter references an area that is outside the length of the requested record.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameters and resubmit the job.

APK450S

A REQUIRED ACIF PARAMETER *parametername* WAS NOT FOUND IN THE PARAMETER FILE.

Explanation

A required ACIF parameter was not found in the parameter file.

System action

ACIF terminates.

System programmer response

No action is required

User response

Add the missing parameter to the parameter file and resubmit.

APK451S

FILE *action* ERROR DURING *ddname* PROCESSING. SVC 99 ERROR *error* INFORMATION CODE *code*.

Explanation

An error occurred during the allocation, concatenation, or outadd (for z/OS) of AFP resource libraries.

System action

ACIF terminates.

System programmer response

Use the return code and reason code to determine the cause of the error and information code; then, determine the appropriate response. Refer to your operating system's authorized assembler language programs document for information about the SVC 99.

User response

Inform your system programmer that this error occurred.

APK452S

A *trigger* NUMBER OF *number* IS INVALID FOR *parameter*.

Explanation

The trigger or record number specified in the FIELD*n* or INDEX*n* parameter is not valid.

System action

ACIF terminates.

System programmer response

No action is required

User response

Triggers used in field definitions must be defined. Correct the parameter and rerun ACIF.

APK453S

THE *fields* LENGTH OF *length* IS GREATER THAN THE ALLOWED MAXIMUM OF *maxlength*.

Explanation

The combined length of all of the FIELD n values on an INDEX n parameter is too long.

System action

ACIF terminates.

System programmer response

No action is required

User response

Check the FIELD n and INDEX n parameters to find where this happens. Correct the parameter and resubmit the job.

APK454S

A VALUE OF *value* IS INVALID FOR FIELD n .

Explanation

A FIELD n parameter value contains incorrect characters.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameter value and resubmit the job.

APK455S

FIELD n USED BY INDEX n WAS NOT DEFINED.

Explanation

An INDEX n parameter referred to a FIELD n that was not defined in the parameter file.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameters and resubmit the job.

APK456S

THE TRIGGER1 RELATIVE RECORD NUMBER IS NOT EQUAL TO ASTERISK.

Explanation

The record number associated with the TRIGGER1 parameter was not an asterisk.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameter and resubmit the job.

APK457S

TRIGGER1 WAS NOT DEFINED, BUT SECONDARY TRIGGERS ARE PRESENT.

Explanation

TRIGGER1 must be specified if secondary TRIGGER n parameters are present.

System action

ACIF terminates.

System programmer response

No action is required

User response

If no indexing is required, delete all TRIGGER n parameters from the parameter file; otherwise, supply a TRIGGER1 parameter for this run of ACIF.

APK458S

A NON-LITERAL VALUE OF *value* HAS BEEN SUPPLIED FOR TRIGGER n .

Explanation

The supplied TRIGGER n value was not a literal.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameters and resubmit the job.

APK459S

INDEX NEEDED FOR THE GROUPNAME WAS NOT FOUND.

Explanation

The index used for the GROUPNAME contained a field that was based on a floating trigger; however, the trigger was not found. Therefore, there is no value for the GROUPNAME. INDEX1 is used for the GROUPNAME by default.

System action

ACIF terminates.

System programmer response

No action is required

User response

Use the GROUPNAME parameter to specify an index that does not contain a field based on a floating trigger.

APK460S

TRIGGERS SATISFIED, BUT INDEXES WERE INCOMPLETE AT END-OF-FILE.

Explanation

The TRIGGER n parameters specified in the parameter file were met, but the end of the file was reached before the INDEX n parameters were located.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameters and resubmit the job.

APK461S

TRIGGER SUPPLIED, BUT ALL INDEX VALUES WERE LITERALS.

Explanation

A value for TRIGGER n has been supplied, but all INDEX n values were literals.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameters and resubmit the job.

APK462S

A TRIGGER PARAMETER WAS SPECIFIED, BUT THE INPUT FILE IS ALREADY INDEXED.

Explanation

The parameter file included a TRIGGER n parameter, but the input file contains indexing structured fields. ACIF cannot index a file that is already indexed.

System action

ACIF terminates.

System programmer response

No action is required

User response

If you want to create an index object file for the input file, remove all TRIGGER n parameters from the ACIF parameter file and resubmit the job.

APK463S

INDEX n USED BY THE GROUPNAME PARAMETER WAS NOT DEFINED OR WAS INVALID.

Explanation

The INDEX n specified by the GROUPNAME parameter was not defined or the index contained a field that was based on a floating trigger. When the GROUPNAME parameter is not used, INDEX1 is used by default.

System action

ACIF terminates.

System programmer response

No action is required

User response

Correct the parameters and resubmit the job.

APK464S

token1 WAS SPECIFIED WHEN *token2* EXPECTED.

Explanation

The syntax of the parameter printed above this message was incorrect.

System action

ACIF continues processing the parameter file, but does not process the report file.

System programmer response

None.

User response

Correct the value of the parameter and rerun ACIF.

APK465S

INVALID TOKEN *token* RECEIVED.

Explanation

The token identified in the message was not expected in the parameter listed above the message.

System action

ACIF continues processing the parameter file, but does not process the report file.

System programmer response

None.

User response

Correct the value of the parameter and rerun ACIF.

APK466S

A SUB-PARAMETER OF *subparameter* IS NOT SUPPORTED ON THE *parameter* PARAMETER.

Explanation

The named sub-parameter is not supported on the parameter listed above the message.

System action

ACIF continues processing the parameter file, but does not process the report file.

System programmer response

None.

User response

Correct the value of the parameter and rerun ACIF.

APK467S

THE NUMBER *number* IS NOT SUPPORTED FOR *parameter*.

Explanation

An incorrect number was specified on a FIELD*n*, INDEX*n*, or TRIGGER*n* parameter keyword.

System action

ACIF continues processing the parameter file, but does not process the report file.

System programmer response

None.

User response

Correct the parameter keyword so that the number is within the allowed range for that parameter and rerun ACIF.

APK468S

THE INPUT BUFFER IS TOO SMALL FOR THE PARAMETER VALUE *value*.

Explanation

The named value was too long for the ACIF internal input buffer.

System action

ACIF terminates.

System programmer response

None.

User response

Use your local problem reporting system to report the error.

APK469S

THE LENGTH OF THE VALUE *value* EXCEEDS THE MAXIMUM ALLOWED LENGTH FOR THE *parameter* PARAMETER.

Explanation

The length of the named value exceeds the maximum length.

System action

ACIF continues processing the parameter file, but does not process the report file.

System programmer response

None.

User response

Correct the value so that its length is within the maximum for that parameter and rerun ACIF.

APK470S

WHICH BEGINS AT OFFSET *offset* FOR A LENGTH OF *length*.

Explanation

This message is issued following a message that contains the cause of the error.

System action

ACIF continues processing the parameter file, but does not process the report file.

System programmer response

None.

User response

Correct the value so that its length is within the maximum for that parameter and rerun ACIF.

APK471S

THE NUMBER OF FIELD VALUES ON THE INDEX PARAMETER EXCEEDED THE MAXIMUM ALLOWED.

Explanation

There were too many FIELD*n* values specified for the INDEX*n* parameter printed above this message.

System action

ACIF continues processing the parameter file, but does not process the report file.

System programmer response

None.

User response

Remove the extra FIELD*n* values from the INDEX*n* parameter and rerun ACIF.

APK472S

THE NUMBER OF VALUES SPECIFIED FOR THE *parameter* PARAMETER EXCEEDED THE MAXIMUM ALLOWED.

Explanation

Too many values were specified for the named parameter, or the file specified with the PARMDD parameter contains more than 100 records.

System action

ACIF continues processing the parameter file, but does not process the report file.

System programmer response

None.

User response

Consult the ACIF manual for the maximum number of values for this parameter, correct the parameter, and rerun ACIF.

APK473S

RECORDRANGE SUB-PARAMETER ALLOWED ONLY IF RECORD VALUE IS '*'.

Explanation

The RECORDRANGE sub-parameter is only valid on a TRIGGER n parameter if the record value was specified as '*'.

System action

ACIF terminates.

System programmer response

None.

User response

Either specify an '*' for the record value or remove the RECORDRANGE sub-parameter from the TRIGGER parameter.

APK474S

END-OF-FILE ENCOUNTERED BEFORE CLOSING QUOTE FOUND FOR *value*.

Explanation

The end of the parameter file was found before the closing quote for a literal value.

System action

ACIF terminates.

System programmer response

None.

User response

Ensure the literal value is enclosed in quotes and rerun ACIF.

APK475S

THE HEX STRING *hexstring* IS NOT VALID.

Explanation

The value specified was not a valid hex string.

System action

ACIF continues processing the parameter file, but does not process the report file.

System programmer response

None.

User response

Correct the hex string and rerun ACIF.

APK476S

THE LENGTH OF THE NUMERIC VALUE *value* IS INVALID.

Explanation

ACIF attempted to write a message that is not defined in the message catalog.

System action

ACIF processing continues depending upon the significance of undefined message.

System programmer response

None.

User response

Inform your service representative that ACIF attempted to write an undefined message, which needs to be corrected.

APK478I

UNABLE TO SAVE DATA OBJECT *filename* TO RESOURCE FILE.

Explanation

Data objects resources, such as color management resources (CMRs), or font resources are being saved, but the object shown in the message has the embed flag set “off” in the resource access table (RAT). Objects with an embed flag set “off” cannot be placed inline or saved in the output resource library.

System action

ACIF skips the specified data object and continues processing the page.

System programmer response

In the resource installer product, find the specified object in its library. Select "embed" for the object, and then rerun the resource installer to update the RAT. If embed was already selected for the object, make sure that the RAT is updated in the directory where ACIF is searching for fonts or objects. If the data object is still not saved to the resource file, contact IBM Software Support for assistance.

User response

This message is informational and is based on the embed flag setting in the RAT that is created when the data object is installed. If you need to save this object in the resource file, contact your system programmer to set the embed flag “on”.

APK479I

REQUESTED DATA OBJECT *filename* NOT FOUND, RETURN CODE *nn*.

Explanation

A data object was requested with a Map Data Resource (MDR) structured field in the input file or page definition, but resource access table (RAT) could not access the object.

System action

ACIF stops processing.

System programmer response

Make sure that both the object and the RAT are installed in the correct directory. If not, use a resource installer product to install the data object in the correct directory and build the RAT entry. If the data object files and the RAT are installed correctly, contact IBM Software Support for assistance.

User response

The requested data object needs to be installed on the system in one of the directories specified with the USERPATH, FONTPATH, or OBJCPATH parameter. The return code indicates why the object was not found and gives the action to perform:

Code	Description and action
10	Attempt to assign storage failed.

Code	Description and action
20	No RAT was found in the paths specified with the USERPATH, FONTPATH, or OBJCPATH parameter. Make sure that a correct set of paths is specified for these parameters. Contact your system programmer to verify that the object is installed on your system.
30	RAU handle is null. Contact your service representative.
40	Font is not found. There was no entry for the requested font in the RAT. Make sure that you have specified the correct set of paths to search. If the correct paths are specified, contact your system programmer to install the font in the correct directory and update the RAT.
50	<p>Conversion information is missing. The object might not be found for one of the following reasons:</p> <ul style="list-style-type: none"> • The MDR structured field specifies the object encoding by CPGID/GCSGID names that cannot be mapped to a CCSID. • The object file name cannot be converted to ASCII or EBCDIC for access on your system. <p>If the object name cannot be converted or mapped, the name is presented as a hexadecimal string. Contact your system programmer for assistance in analyzing this return code.</p>
70	Unable to convert code page or character set to CCSID. Same action as return code 50.
90	RAU handle is missing. Contact your service representative.
100	Path name is missing on AddPath. Contact your service representative.
110	RAT contains incorrect entries. Contact your service representative.
120	ICU open request has an error. Same action as return code 50 (z/OS).
130	ICU conversion has an error. Same action as return code 50 (z/OS).
140	RAT type does not match the Find call. Contact your service representative.
150	RAT type is incorrect. Contact your service representative.

Code	Description and action
160	Requested color management resource (CMR) is not found in the RAT. Make sure that you have specified the correct set of paths to search. If the correct paths are specified, contact your system programmer to install the CMR into the correct directory and update the RAT.
170	Requested data object is not found in the RAT. Make sure that you have specified the correct set of paths to search. If the correct paths are specified, contact your system programmer to install the object into the correct directory and update the RAT.
180	CMR name is incorrect. Contact your service representative.
190	RAT contains incorrect entries. Contact your service representative.
200	Resource access table (RAT) not valid. For example, RAT uploaded as a text file instead of a binary file.
210	Font not found inline. An MDR setting requires that the requested data object font is inline in the input file resource group (RESTYPE=ALL or RESTYPE=FONT). The MDR repeating group flag does not apply to any code page named on a Fully Qualified Name (FQN) triplet with an FQNTYPE of X'85' that is used with the data object font (such as T1V10500). ACIF does not search external libraries when the MDR repeating group flag requires that the data object font is inline.

APK484S

INVALID REGULAR EXPRESSION *regular expression*, OFFSET *offset*, RETURN CODE *return code*.

Explanation

ACIF failed trying to compile the regular expression. The offset indicates the location within the regular expression of the error.

Return Codes

- x10301 - Syntax error in pattern
- x10302 - Invalid state for requested operation
- x10303 - Unrecognized escape sequence
- x10304 - Incorrect unicode property
- x10305 - Use of feature not yet implemented
- x10306 - Incorrectly nested parentheses
- x10307 - Decimal number too large
- x10308 - Error in {min,max} interval
- x10309 - In {min,max}, max is less than min
- x1030F - Missing closing bracket
- x10310 - In a character range [x-y], x is greater than y

x10312 - Maximum allowed match time exceeded
For other return codes contact IBM Support.

System action

ACIF stops processing.

System programmer response

Ensure that the ICU libraries are properly installed.

User response

Correct the regular expression.

APK485S

UREGEX_FIND FAILED, RETURN CODE *return code*.

Explanation

ACIF failed while using a regular expression to match text. See the return codes for message 484.

System action

ACIF stops processing.

System programmer response

Ensure that the ICU libraries are properly installed.

User response

Correct the regular expression.

APK486S

SEARCHABLE LENGTH OF *length* OF RECORD NUMBER *record number* IS GREATER THAN MAXIMUM ALLOWED SIZE OF *size*.

Explanation

ACIF failed while using a regular expression trigger to match text. The maximum allowed length of the text to search on a single record is 2048 bytes.

System action

ACIF stops processing.

System programmer response

None.

User response

Use a trigger column range.

APK487S

MASK AND REGEX CANNOT BOTH BE SPECIFIED FOR A FIELD.

Explanation

ACIF failed while processing a field parameter. The MASK and REGEX sub-keywords cannot both be specified on a field parameter.

System action

ACIF stops processing.

System programmer response

None.

User response

Use either the MASK or REGEX sub-parameter on the field parameter.

APK488S

FIELD NOT FOUND, FIELD# *field number*, INPUT RECORD# *record number*.

Explanation

ACIF failed while trying to collect a field based on a group trigger, because the field did not match the regular expression. Fields based on group triggers must be found.

System action

ACIF stops processing.

System programmer response

None.

User response

Correct the field location, change the regular expression, base the field on a floating trigger, or specify a default value for the field.

APK489S

A MASK OR REGULAR EXPRESSION IS REQUIRED FOR FIELD# *field number*.

Explanation

ACIF failed while trying to collect a field for an index which was defined as GROUPRANGE or PAGERANGE. A field for a GROUPRANGE or PAGERANGE index must use a mask or regular expression.

System action

ACIF stops processing.

System programmer response

None.

User response

Add a mask or regular expression to the FIELD parameter.

APK490S

THE ASPRINTED VALUE FOR THE LINEOFFSET PARAMETER CAN ONLY BE USED WITH INPUT DATA THAT CONTAINS ANSI CARRIAGE CONTROLS.

Explanation

ACIF failed while trying to process the LINEOFFSET parameter. The ASPRINTED value for the LINEOFFSET parameter can only be used with input data that contains ANSI carriage controls. To indicate ANSI carriage controls, specify the ACIF parameters CC=YES and CCTYPE=A or CCTYPE=Z.

System action

ACIF stops processing.

System programmer response

None.

User response

Correct the CCTYPE parameter.

APK491S

ATTEMPT TO INDEX A NON-EXISTENT RECORD ASSOCIATED WITH INPUT RECORD# <number> IS NOT ALLOWED, FIELD# <number>.

Explanation

ACIF failed while trying to collect an index field. The relative record number in the FIELD parameter referenced a record that does not exist in the input file, but is used only for line spacing. When the ASPRINTED value for the LINEOFFSET parameter is specified, the relative record numbers in the FIELD parameters must refer to real records in the input file.

System action

ACIF stops processing.

System programmer response

None.

User response

Correct the FIELD parameter.

APK499I

INTERNAL ERROR IN MODULE *module* AT FUNCTION *function*.

Explanation

An internal error occurred.

System action

ACIF stops.

System programmer response

None.

User response

Contact IBM Software Support and inform them that you received this message. Make note of the module and function specified in the message.

APK532S

A *resource* WITH A MEMBER NAME (*membername*) WAS NOT FOUND OR WAS INVALID - RETURN CODE *returncode*.

Explanation

The requested form definition, page definition, page segment, medium overlay, or setup file does not exist in any of the available paths. If the form definition member name is blank, the default is DUMMY.

Return Code	Description
0	Successful
1	Permanent I/O error
2	Specified number of bytes is zero
3	Incorrect data buffer address

Return Code	Description
4	Address not word aligned
6	Incorrect FILE_CB@
7	Incorrect MODE parameter
8	Data record longer than LRECL or buffer
9	File is not supported type
10	Storage allocation/deallocation failed
11	Incorrect record number
12	End of file detected
13	Disk is full
14	RECFM not valid
20	Incorrect file ID
28	File not found
36	Default message catalog not accessible. Check permissions
51	Length exceeds maximum
310	File format not valid

Reason Code	Description
1	Resource name missing
2	File system open error
3	File system close error
4	File system read error
6	Resource type error
7	File system write error
8	Indexer error
9	Message write error

System action
ACIF terminates.

System programmer response
None.

User response
Correct the parameters and rerun ACIF.

APK610I

GTF RETURN CODE = *rc*.

Explanation

Generalized Trace Facility (GTF) has returned a nonzero return code from the GTRACE request. The return code *rc* and *error text* explain the error. The return codes and error text are:

RC	Error Text
04	Inactive z/OS GTF
08	Incorrect length = xxxx
0C	Incorrect data address = xxxx
10	Incorrect FID = xx
14	Incorrect EID = xx
18	No GTF buffer space
1C	Incorrect parameter address = xxxx
20	Data paged out
xx	Unknown GTF return code

System action

The action depends on the return code; ACIF might or might not continue tracing. For return codes 18 and 20, GTF tracing continues. For the other return codes listed, GTF tracing stops. For unknown return codes, GTF tracing stops.

System programmer response

Refer to your operating system's service aids logic documents for more information about the return codes.

User response

No action is required

APK900S

MISSING DAT POINTER IN CCM.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK901S

MISSING FORMDEF POINTER IN CCM.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK902S

MISSING PAGEDEF POINTER IN CCM.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK903S

MISSING OBJECT STACK POINTER IN CCM.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK904S

MISSING CODE PAGE POINTER IN CCM.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK905S

MISSING FONT METRIC POINTER IN CCM.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK906S

UNEXPECTED OTHERWISE STATEMENT ENCOUNTERED.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK907S

CCM CANNOT FIND REQUESTED MEDIUM MAP.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK908S

CCM CANNOT FIND REQUESTED DATA MAP.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK909S

CCM CANNOT FIND REQUESTED MEG.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK910S

INPUT BIN LIST CHANGED DURING PROCESSING.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK911S

DAT DID NOT SPECIFY ANY INPUT BIN INFORMATION.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK912S

OVERLAY LOCAL ID HAS BEEN CHANGED IN LIST.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK913S

STARTING COPY COUNT EXCEEDS TOTAL COPIES IN MM.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK914S

CONDITIONAL PROCESSING INFORMATION PASSED TO CCM AT DOCUMENT INTERFACE BUT PAGEDEF DOES NOT REQUEST CONDITIONAL PROCESSING.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK915S

ACIF REQUESTED CODE PAGE DEALLOCATION AS WELL AS CODE PAGE PROCESSING.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK916S

ACIF REQUESTED ACTIVATION OF AN OUTLINE FONT CHARACTER SET, BUT DOES NOT SUPPORT OUTLINE FONTS.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK917S

ACIF REQUESTED ACTIVATION OF A FONT RESOURCE, BUT THE GLOBAL NAME WAS NOT PROVIDED OR HAD AN INCORRECT LENGTH.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK918S

NO FREQUENT FONT TABLE OR FGID LOOK ASIDE TABLE WAS PROVIDED TO *modulename*.

Explanation

An internal error has occurred in ACIF.

System action

ACIF terminates.

System programmer response

None.

User response

Contact IBM Service and inform them that you have received this message indicating an internal error.

APK919S

THE CCM COMPONENT OF ACIF HAS USED UP ITS OBJECT STACK IN *modulename*.

Explanation

The CCM component of ACIF has run out of its object stack area. This could be a data stream error or a logic error. A begin structured field must have a matching end structured field following it in the data stream. If this requirement is not met, the CCM can run out of its object stack area.

System action

ACIF terminates.

User response

Check the data stream to make sure each begin structured field has a matching end structured field following it. If this is not true, correct the data stream and resubmit the job to ACIF. If the data stream meets the begin structured field requirement, this message indicates an internal logic error. Inform your service representative that you have received this message indicating an internal error.

APK920S

ALL THE INPUT BINS ON YOUR PRINTER ARE EITHER DISABLED OR ARE INSERTER BINS. PSF NEEDS TO SUBSTITUTE A BIN BUT NO BINS ARE AVAILABLE TO SUBSTITUTE.

Explanation

This abend is issued by module APKMSGEX. All bins reported back from the printer are either disabled or are inserter bins. As a result, there are no bins available for printing and the current data set cannot be printed.

System action

ACIF processing terminates abnormally.

APK921S

NO RECORD LENGTH WAS PASSED TO CCM WHEN PROCESSING AN OBJECT CONTAINER RESOURCE.

Explanation

This abend is issued by module APRMSGEX. No record length was passed to CCM when processing an object container resource. This is a logic error.

System action

PSF attempts to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This ACIF abend reason code indicates a logic error. Contact your service representative for assistance regarding this error code.

User response

None.

APK2000S

THE REGISTERED OBJECT TYPE ID (*identifier*) OF AN OBJECT CONTAINER RESOURCE, NAME *resourcename* OR OBJECT OID *objectoid*, IS NOT VALID OR IS NOT SUPPORTED BY PSF OR THE PRINTER.

Explanation

The registration ID specified for an object container is not supported by the printer. The registration ID is specified in the object classification triplet on an IOB, BOC, or BR structured field. A value of *** for the resource name or object OID means that it was not specified.

System action

PSF terminates the page or overlay. PSF attempts to locate the end of the current page and resume processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the object container resource, ensure that the registration ID is correct. If the registration ID is correct, submit the print job to a printer that supports this object type. For more information about what object types are supported by your printer, refer to your printer documentation.

APK2003S

DATA IN AN INPUT RECORD OR RESOURCE IS INVALID: STRUCTURED FIELD *structuredfield* CONTAINED AN EXTENDED RESOURCE LOCAL IDENTIFIER VALUE THAT WAS USED IN A PREVIOUS STRUCTURED FIELD OF THE SAME TYPE.

Explanation

More than one structured field used the same Extended Resource Local Identifier value for different resources of the same type. The Extended Resource Local Identifier is specified by using the Extended Resource Local Identifier (X'22') triplet on the structured field. The structured field that attempted to use the same Extended Resource Local Identifier value is identified in the message.

System action

PSF stops processing the current data set and issues messages identifying the position of the structured field and the processing environment when the error was found.

Operator response

If you see this message on the operator's console, it indicates that the resource containing the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Contact your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

APK2004S

DATA IN A FORMDEF RESOURCE IS INVALID: MEDIA TYPE LOCAL IDENTIFIER IN MMC STRUCTURED FIELD, ID *identifier*, WAS NOT FOUND IN THE MMT STRUCTURED FIELD.

Explanation

The Media Type local ID in the Medium Modification Control (MMC) structured field was not present in the Map Media Type (MMT) structured field. The MMC and MMT structured fields are in the form definition.

System action

The form definition containing the error is not used, and one of the following occurs:

- If the error is in the default form definition, or a form definition specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition specified on the user's OUTPUT JCL statement, PSF cannot begin printing the data set; it tries to print the next data set.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK2005S

DATA IN AN INPUT RECORD OR PAGEDEF RESOURCE IS NOT VALID: RECORD IDENTIFIER *identifier* COULD NOT BE FOUND WITHIN THE RCD STRUCTURED FIELDS.

Explanation

The record identifier specified in an input record could not be matched to a Record Descriptor (RCD) structured field in the current data map. The RCD structured field is in the page definition.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis

reference for assistance in determining the source of the problem. If the error involves separator pages, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2006S

DATA IN A PAGEDEF RESOURCE IS NOT VALID: GRAPHICS GENERATION WAS REQUESTED ON RCD STRUCTURED FIELD *structuredfield*, BUT THE PRINTER DOES NOT SUPPORT GRAPHICS OBJECTS.

Explanation

A Record Descriptor (RCD) structured field in a page definition has requested PSF to generate a graphics object from the line data, but the printer does not support graphics objects.

System action

PSF ignores the request and continues processing the data set.

System programmer response

If the page definition is for a separator page, the message data set, or the default page definition for the user print data sets defined in the PSF startup procedure, delete the option from the page definition that requests that a graphics object be generated.

User response

To print the data set and have PSF generate graphics objects, submit the print job to a printer that supports graphics objects. For more information about AFP printers that support graphics objects, refer to *Advanced Function Presentation: Printer Information*

APK2007S

DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE FIELD RCD POINTER VALUE IN RCD STRUCTURED FIELD NUMBER *number* WILL CAUSE AN INFINITE LOOP.

Explanation

The FIELD RECORD DESCRIPTOR POINTER parameter in the Record Descriptor (RCD) structured field identified in this message caused an infinite-loop condition. The RCD structured field is contained in the page definition.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more

information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2008I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: RCD OR XMD STRUCTURED FIELD NUMBER *number* SPECIFIES A VALUE THAT IS NOT VALID AS A POINTER TO A FIELD RCD OR XMD. THE VALUE *rcdvalue*. THIS EXCEEDS THE LNC STRUCTURED FIELD COUNT VALUE OF *incvalue*.

Explanation

The Record Descriptor (RCD) or XML Descriptor (XMD) structured field identified in this message specifies a value as a pointer to a Field RCD or XMD. The value specified is not valid. The value is greater than the COUNT value in the Line Descriptor Count (LNC) structured field in the current data map. The LNC, RCD, and XMD structured fields are in the page definition.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2009S

DATA IN A PAGEDEF RESOURCE IS NOT VALID: RIGHT ALIGNMENT WAS REQUESTED ON RCD STRUCTURED FIELD *structuredfield*, BUT THE PRINTER DOES NOT SUPPORT RIGHT ALIGNMENT.

Explanation

A Record Descriptor (RCD) structured field in a page definition has requested that PSF right align a field from the line data, but the printer does not support the controls necessary for PSF to perform this function.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If the page definition is for a separator page, the message data set, or the default page definition for the user print data sets defined in the PSF startup procedure, delete the option from the page definition that requests that a field be right aligned.

User response

To print the data set and have PSF right align fields, submit the print job to a printer that supports all four inline print directions and all four character rotations. For more information about inline print directions

and character rotations supported by AFP printers, refer to *Advanced Function Presentation: Printer Information*.

APK2010S

RECORD FORMATTING WAS REQUESTED BY THE PAGE DEFINITION BUT THAT FUNCTION IS NOT SUPPORTED BY THIS RELEASE OF PSF.

Explanation

The record formatting function is not supported by this release of PSF.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If the page definition is for a separator page, the message data set, or the default page definition for the user print data sets defined in the PSF startup procedure, remove this page definition and select one that does not use the record formatting function.

User response

To use the record formatting function, submit this job to a version of print PSF that supports record formatting.

APK2011I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: DATA MAP *datamap1* AND DATA MAP *datamap2* ARE FOR PROCESSING DIFFERENT TYPES OF DATA. ALL DATA MAPS IN THE PAGE DEFINITION MUST SPECIFY THE SAME DATA FORMATTING.

Explanation

A page definition can only be used for one type of data. A single page definition cannot be used to mix the processing of traditional line data, record-format line data, and XML data.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2012S

DATA IN A PAGEDEF RESOURCE IS NOT VALID: A NON-ZERO RECORD IDENTIFIER PARAMETER VALUE *value* WAS SPECIFIED IN RCD STRUCTURED FIELD NUMBER *number*.

Explanation

For Record Descriptor (RCD) structured fields that are marked as either a field or a conditional processing RCD, the RECORD IDENTIFIER parameter value must be all zeros. The RCD structured fields are in the page definition.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2013S

DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE SAME RECORD IDENTIFIER *identifier* WAS SPECIFIED IN RCD STRUCTURED FIELD NUMBERS *number1* AND *number2*. ALL RECORD IDENTIFIERS MUST BE UNIQUE IN THE SAME DATA MAP.

Explanation

With the exception of the default Page Header Record Descriptor (RCD) structured field, the default Page Trailer RCD structured field, Field RCD structured fields, and Conditional Processing RCD structured fields, all other RCD structured fields in a data map must have a unique record identifier parameter value specified.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic

error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2014I

DATA IN AN INPUT RECORD OR PAGEDEF RESOURCE IS NOT VALID: THE PAGE SIZE IS NOT LARGE ENOUGH TO PLACE THE FIRST RECORD OF THE PAGE BY USING RCD OR XMD STRUCTURED FIELD NUMBER *number* AND ITS ASSOCIATED FIELD RCD OR XMD STRUCTURED FIELDS.

Explanation

The Body Record Descriptor (RCD) or XML Descriptor (XMD) structured field selected for placing the first body record of the page does not fit within the area of the page defined by the bottom margin. If Field RCD or XMD structured fields are being used, one of the Field RCD or XMD structured fields might be positioning data beyond the bottom margin. This error prevents PSF from being able to place the record and continuing.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2015S

DATA IN A PAGEDEF RESOURCE IS NOT VALID: AN RCD STRUCTURED FIELD SPECIFIED A GRAPHICS DESCRIPTOR TRIPLET TO END ALL STARTED GRAPHICS DESCRIPTOR TRIPLETS THAT HAVE A MATCHING GRAPHID PARAMETER VALUE *value*, BUT A MATCH COULD NOT BE FOUND.

Explanation

A graphics object can be started by one Record Descriptor (RCD) structured field and ended with another RCD structured field. When this is done, the Graphics Descriptor triplets that start and end a graphics object must have matching GRAPHID parameter values specified and the RCD structured fields must have matching orientations. PSF could not find a match between the start and end Graphics Descriptor triplets using the GRAPHID parameter from the end Graphics Descriptor triplet and the TEXT ORIENTATION parameter value from the RCD structured field.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2016S

DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE USE RECORD IDENTIFIER FLAG WAS SET BUT THE SUM OF THE DATA START POSITION AND THE DATA LENGTH PARAMETER VALUES IN RCD STRUCTURED FIELD NUMBER *number* SELECTS DATA BEYOND THE RECORD IDENTIFIER FIELD.

Explanation

For Record Descriptor (RCD) structured fields that are marked to use only the record identifier portion of an input record, only the record identifier can be accessed by the RCD. The DATA START parameter plus the DATA LENGTH parameter of this RCD accesses data beyond the 10-byte record identifier area of the input record.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2017S

DATA IN A PAGEDEF RESOURCE IS NOT VALID: A FONT IS NEEDED FOR AN RCD IN DATA MAP *datamap* BUT NO FONTS WERE MAPPED IN THE DATA MAP.

Explanation

Fonts needed for printing record-format line data must be selected in the data map. The CHARS JCL parameter cannot be used to select fonts. The data map identified in this message contained a Record Descriptor (RCD) structured field that requires a font, but no fonts were specified in the data map.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2018S

DATA IN A PAGEDDEF RESOURCE IS NOT VALID: RCD STRUCTURED FIELD *structuredfield* REQUESTED THAT THE PAGE NUMBER BE RESET, BUT THE PAGE NUMBER PARAMETER CONTAINS ZERO.

Explanation

The PAGE NUMBER parameter in a Record Descriptor (RCD) structured field cannot be zero when the RCD requests that PSF reset the page number.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2019S

DATA IN A PAGEDDEF RESOURCE IS NOT VALID: THE FONT SELECTED FOR PRINTING THE PAGE NUMBER ON RCD OR XMD STRUCTURED FIELD NUMBER *number* CANNOT BE A DOUBLE-BYTE FONT WHEN USING THE ASCII ENCODING SCHEME.

Explanation

PSF cannot determine the correct code points to generate when a double-byte font is used to print the page number using the ASCII encoding scheme. The structured field identified in this message selected a double-byte ASCII font for printing the page number. This is not allowed.

System action

PSF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APK2020I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE OBJECT OID SPECIFIED IN A FULLY QUALIFIED NAME TRIPLET ON AN *structuredfield* STRUCTURED FIELD IS INCORRECT.

Explanation

An object OID being specified in a Fully Qualified Name triplet must not contain all zeros and must be less than 130 bytes in length.

System action

ACIF stops processing the input file and issues a message identifying the position of the structured field in the file or resource.

System programmer response

If a licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2021I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE *structuredfield* STRUCTURED FIELD CONTAINS UNPAIRED FQN X'BE' & FQN X'DE' TRIPLETS.

Explanation

If this is an Include Object (IOB) structured field, the Fully Qualified Name (FQN) triplet with an FQNType of Data Object Internal Resource Reference (X'BE') must immediately follow an FQN triplet with an FQNType of Data Object External Resource Reference (X'DE'). If this is a Map Data Resource (MDR) structured field, a repeating group with an FQN triplet type X'BE' must also include an FQN triplet type X'DE'.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set.

Operator response

If you see this message on the operator's console, it indicates that the resource containing the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Contact your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APK2022I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SECONDARY RESOURCE IDENTIFIED ON STRUCTURED FIELD *structuredfield* IS NOT NAMED IN THE ACTIVE ENVIRONMENT GROUP.

Explanation

An Include Object (IOB), Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field calls for a secondary resource. This secondary resource must be named in a Map Data Resource (MDR) in the Active Environment Group (AEG) of the page, overlay, or data map containing the structured field. A color management resource (CMR) is a secondary resource that must be mapped in the AEG. If the CMR name is mapped but the scope or processing mode on the MDR does not match the IOB, LND, RCD, or XMD structured field, this message is issued.

System action

If the object is in a page, PSF terminates the page and continues processing the data set. If the object is in a resource, PSF stops processing and printing the data set.

Operator response

If you see this message on the operator's console, it indicates that the resource containing the error is defined for a separator page or for the message data set in the PSF startup procedure. Contact your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error. If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. Refer to *Data Stream and Object Architectures Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APK2023I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE FORMAT SPECIFIED IN AN FQN TRIPLET IS NOT VALID. The STRUCTURED FIELD *structuredfield* is in error.

Explanation

The FQNfmt specified in a Fully Qualified Name (FQN) triplet on the structured field specified in the message is not valid.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2024I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A FULLY QUALIFIED NAME TRIPLET MAPPED AN OBJECT THAT IS NOT ALLOWED IN AN MDR STRUCTURED FIELD IN AN OBJECT ENVIRONMENT GROUP.

Explanation

A Fully Qualified Name (FQN) triplet with an FQNType of Begin Resource Object Reference (X'84') or Other Object Data Reference (X'CE') is not allowed on a Map Data Resource (MDR) structured field in an Object Environment Group (OEG).

In addition, an FQN triplet with an FQNType of Data Object External Resource Reference (X'DE') can only map a data object font or a color management resource (CMR) in a bar code object, a graphics object, or a presentation text object with OEG.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2025I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN ERROR WAS FOUND IN A FULLY QUALIFIED NAME TRIPLET SPECIFIED IN A REPEATING GROUP ON AN *structuredfield* STRUCTURED FIELD.

Explanation

One of these errors was found:

- More than one Fully Qualified Name (FQN) triplet with one of these FQNTypes was found in a repeating group on a Map Data Resource (MDR) structured field:
 - Begin Resource Object Reference (X'84')
 - Other Object Data Reference (X'CE')
 - Data Object External Resource Reference (X'DE')
 - Code Page Name Reference (X'85')
- More than one FQN triplet with one of these FQNTypes was found in a repeating group on a Preprocess Presentation Object (PPO) structured field:
 - Begin Resource Object Reference (X'84')
 - Other Object Data Reference (X'CE')
- An FQNTYPE that is not valid was specified on a FQN triplet on an MDR.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2026I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE OBJECT CLASS SPECIFIED IN AN OBJECT CLASSIFICATION TRIPLET ON AN MDR STRUCTURED FIELD IS NOT VALID.

Explanation

The ObjClass specified in an Object Classification triplet on a Map Data Resource (MDR) structured field must be X'40' or X'41' if the Fully Qualified Name (FQN) triplet type in the repeating group is a Data Object External Resource Reference (X'DE'). The ObjClass specified must be X'01' if the FQN triplet type in the repeating group is an Other Object Data Reference (X'CE').

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. If the structured field is correct, the error might be an ACIF logic error. If you used a

program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2027I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN MDR STRUCTURED FIELD SPECIFIES THE SAME RESOURCE REFERENCE MORE THAN ONCE IN AN ENVIRONMENT GROUP.

Explanation

The same resource reference cannot be made in a Map Data Resource (MDR) structured field in an environment group.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2029I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: OBJECT OID *objectoid1* DOES NOT MATCH THE OBJECT OID *objectoid2* SPECIFIED ON THE *structuredfield* STRUCTURED FIELD.

Explanation

The object OID specified on a structured field must match the object OID specified on the Map Data Resource (MDR) or Include Object (IOB) structured field that referenced it. A value of *** indicates an OID was not specified.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2030I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SECONDARY RESOURCE THAT IS NOT A CMR IS SPECIFIED ON AN IOB STRUCTURED FIELD THAT INCLUDES A BAR CODE, GRAPHICS, OR PRESENTATION TEXT WITH OEG OBJECT.

Explanation

A Fully Qualified Name (FQN) triplet of type Data Object External Resource Reference (X'DE') is specified in an Include Object (IOB) structured field that has a bar code, graphics, or presentation text with OEG object. Only color management resources (CMRs) are allowed as secondary resources for these objects.

System action

The secondary resource reference that is not a CMR is ignored and processing continues.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2033I

THE BAR CODE DATA OR BAR CODE DATA PLUS THE ADDITIONAL 2D BAR CODE PARAMETERS EXCEED THE OUTPUT COMMAND BUFFER.

Explanation

Either the bar code data itself or the bar code data plus the macro control block data specified for a 2D bar code exceeds the size of the output command buffer. The macro control block data is specified in your page definition as part of the BCXPARMS (additional bar code parameters).

System action

PSF issues this message and continues processing.

Operator response

None.

System programmer response

None.

User response

Change the amount of data specified for your bar code or reduce the amount of data in the macro control block.

APK2039I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A DUPLICATE FINISHING OPERATION WAS FOUND IN THE *mapname* MEDIUM MAP.

Explanation

The same finishing operation was specified more than once in a medium map. This nesting of the same finishing operation is not allowed. The Media Finishing Control (MFC) structured field is in a form definition or an internal medium map in the print data set.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

None.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

[Advanced Function Presentation: Programming Guide and Line Data Reference](#)

APK2040I

THE NUMBER OF MEDIA COLLECTION FINISHING NESTING LEVELS IS MORE THAN 4.

Explanation

A maximum of four levels of nesting is allowed for media collection finishing. The Medium Finishing Control (MFC) structured field can be contained in a form definition or internal medium map in a page.

System action

ACIF stops processing the data set.

System programmer response

None.

User response

If you created the form definition or internal medium map, you must remove one or more levels of media collection finishing operations. Resubmit the print request. If the total number of nesting levels is less than or equal to four, the error might be an ACIF logic error.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2041I

DATA IN AN INPUT RECORD OR PAGEDEF IS NOT VALID: INPUT DATA BEING USED FOR A VARIABLE RESOURCE NAME IN LND OR RCD STRUCTURED *number* IS DOUBLE BYTE DATA.

Explanation

A Resource Object Include triplet or an Extended Resource Local ID triplet on a Line Descriptor (LND) or Record Descriptor (RCD) structured field requests that the input data for the resource name is included. This input data cannot be double-byte data.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

[Advanced Function Presentation: Programming Guide and Line Data Reference](#)

APK2042I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: AN XML PAGE DEFINITION REQUESTED THAT THE INPUT DATA BE USED FOR A RESOURCE NAME ON XMD STRUCTURED FIELD NUMBER *number*.

Explanation

An Object Reference Qualifier (ORQ) triplet has been specified on an XML Descriptor (XMD) structured field. This function is not supported when using an XML page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource, correct the error and resubmit the print request. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

[Advanced Function Presentation: Programming Guide and Line Data Reference](#)

APK2044I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE FIELD XMD POINTER VALUE IN XMD STRUCTURED FIELD NUMBER *number* WILL CAUSE AN INFINITE LOOP.

Explanation

The Field XML Descriptor Pointer value in the XML Descriptor (XMD) structured field identified in this message caused an infinite loop condition. The XMD structured field is contained in the page definition.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

[Advanced Function Presentation: Programming Guide and Line Data Reference](#)

APK2045I

THE ENCODING SCHEME SPECIFIED IN A PAGE DEFINITION USED TO PROCESS XML DATA IS NOT SUPPORTED BY ACIF.

Explanation

The encoding scheme specified is not supported by ACIF.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

You must use an encoding scheme that is supported by ACIF for XML data processing. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

[Advanced Function Presentation: Programming Guide and Line Data Reference](#)

APK2046I

XML DATA FORMATTING WAS REQUESTED BY THE PAGE DEFINITION BUT THAT FUNCTION IS NOT SUPPORTED BY THIS RELEASE OF ACIF.

Explanation

The XML data formatting function is not supported by this release of ACIF.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

None.

User response

To use the XML data formatting function, submit this job to a version of ACIF that supports XML data formatting.

APK2047I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: DATA MAP *datamapname1* AND DATA MAP *datamapname2* HAVE DIFFERENT ENCODING SCHEMES SPECIFIED FOR THE USER DATA. ALL DATA MAPS IN THE PAGE DEFINITION MUST SPECIFY THE SAME ENCODING SCHEME.

Explanation

All the data maps in a page definition used to process XML data must use the same encoding scheme for the user data.

System action

ACIF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

[Advanced Function Presentation: Programming Guide and Line Data Reference](#)

APK2048I

DATA IN AN INPUT RECORD IS NOT VALID: A DTD DECLARATION AT CHARACTER COUNT NUMBER *number* IS SPECIFIED OUTSIDE OF A DTD.

Explanation

A document type definition (DTD) declaration is only allowed inside a DTD. The character count number specified in this message is relative to the start of the record.

System action

ACIF stops processing the current data set and issues a message identifying the position of the error in the data stream.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the XML data, correct the error and resubmit the print request. See the XML specification, Extensible Markup Language (XML) 1.0, on the World Wide Web Consortium website. If the XML data does not have an error, the error might be an ACIF logic error. If you used a program to create the XML data, contact your system programmer.

APK2049I

DATA IN AN INPUT RECORD IS NOT VALID: THE XML COMMENT SYNTAX AT CHARACTER COUNT NUMBER *number* IS NOT VALID.

Explanation

After an XML comment has been started, you can only use two dashes in a row when ending a comment. The character count number specified in the message is relative to the start of the record.

System action

ACIF stops processing the current data set and issues a message identifying the position of the error in the data stream.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the XML data, correct the error and resubmit the print request. See the XML specification, Extensible Markup Language (XML) 1.0, on the World Wide Web Consortium website. If the XML data does not have an error, the error might be an ACIF logic error. If you used a program to create the XML data, contact your system programmer.

APK2050I

DATA IN AN INPUT RECORD IS NOT VALID: THE XML END TAG AT CHARACTER COUNT NUMBER *number* DOES NOT MATCH THE LAST START TAG.

Explanation

An XML end tag must exactly match its start tag. The character count number specified in this message is relative to the start of the record.

System action

ACIF stops processing the current data set and issues a message identifying the position of the error in the data stream.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the XML data, correct the error and resubmit the print request. See the XML specification, Extensible Markup Language (XML) 1.0, on the World Wide Web Consortium website. If the XML data does not have an error, the error might be an ACIF logic error. If you used a program to create the XML data, contact your system programmer.

APK2051I

DATA IN AN INPUT RECORD IS NOT VALID: THE END OF A DOCUMENT TYPE DECLARATION AT CHARACTER COUNT NUMBER *number* IS NOT THE CORRECT SYNTAX.

Explanation

The end of a document type declaration (DTD) did not have the correct syntax. The character count number specified in this message is relative to the start of the record.

System action

ACIF stops processing the current data set and issues a message identifying the position of the error in the data stream.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the XML data, correct the error and resubmit the print request. See the XML specification, Extensible Markup Language (XML) 1.0, on the World Wide Web Consortium website. If the XML data does not have an error, the error might be an ACIF logic error. If you used a program to create the XML data, contact your system programmer.

APK2052I

DATA IN AN INPUT RECORD IS NOT VALID: THE CHARACTER CODE AT CHARACTER COUNT NUMBER *number* IS NOT A VALID VALUE FOR A CHARACTER REFERENCE.

Explanation

A character code inside a character reference is not one of the allowed values. The character count number specified in this message is relative to the start of the record.

System action

ACIF stops processing the current data set and issues a message identifying the position of the error in the data stream.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program is valid. If the input is valid, see your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the XML data, correct the error and resubmit the print request. See the XML specification, Extensible Markup Language (XML) 1.0, on the World Wide Web Consortium website. If the XML data does not have an error, the error might be an ACIF logic error. If you used a program to create the XML data, contact your system programmer.

APK2053I

DATA IN AN INPUT RECORD IS NOT VALID: THE ENTITY AT CHARACTER COUNT NUMBER *number* IS NOT DEFINED IN THE DOCUMENT TYPE DEFINITION.

Explanation

ACIF allows only internal general entity references, which must be defined in an internal document type definition (DTD). The character count number specified in this message is relative to the start of the record.

System action

ACIF stops processing the current data set and issues a message identifying the position of the error in the data stream.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the XML data, correct the error and resubmit the print request. See the XML specification, Extensible Markup Language (XML) 1.0, on the World Wide Web Consortium website. If the XML data does not have an error, the error might be an ACIF logic error. If you used a program to create the XML data, contact your system programmer.

APK2054I

DATA IN AN INPUT RECORD IS NOT VALID: THE CHARACTER IN A TAG NAME AT CHARACTER COUNT NUMBER *number* IS NOT VALID.

Explanation

A character in an XML tag name is not valid. The character count number specified in this message is relative to the start of the record.

System action

ACIF stops processing the current data set and issues a message identifying the position of the error in the data stream.

Operator response

If this message is displayed on the operator's console, it indicates that PSF cannot be initialized or cannot print error messages. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference for your system for assistance in determining the source of the problem.

User response

If you created the XML data, correct the error and resubmit the print request. See the XML specification, Extensible Markup Language (XML) 1.0, on the World Wide Web Consortium website. If the XML data does not have an error, the error might be an ACIF logic error. If you used a program to create the XML data, contact your system programmer.

APK2055I

DATA IN A PAGEDDEF RESOURCE IS NOT VALID: THE ENCODING SCHEME IDENTIFIER FOR THE USER DATA IS NOT SPECIFIED IN THE ENCODING SCHEME TRIPLET ON THE BDM STRUCTURED FIELD.

Explanation

The Encoding Scheme Identifier for User Data (ESidUD) is missing on the Encoding Scheme triplet (X'50') on a Begin Data Map (BDM) structured field. This information is required when processing an XML page definition.

System action

ACIF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

You must provide the encoding scheme for the user data. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

[Advanced Function Presentation: Programming Guide and Line Data Reference](#)

APK2056I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE SAME QUALIFIED TAG WAS SPECIFIED IN XMD STRUCTURED FIELD NUMBERS *number1* AND *number2*. ALL QUALIFIED TAGS MUST BE UNIQUE IN THE SAME DATA MAP.

Explanation

All XML Descriptor (XMD) structured fields in a data map must have a unique qualified tag specified; except for these types of XMD structured fields:

- Default Page Header
- Default Page Trailer
- Field
- Conditional Processing
- Attribute

System action

ACIF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

[Advanced Function Presentation: Programming Guide and Line Data Reference](#)

APK2057I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: RELATIVE INLINE POSITIONING ON AN XMD STRUCTURED FIELD CAN ONLY BE USED TO PLACE TEXT DATA.

Explanation

One of the following items is specified on an XML Descriptor (XMD) structured field that uses relative inline positioning:

- A Resource Object Include
- Extended Resource Local ID
- Bar Code Symbol Descriptor
- Graphics Descriptor triplet

You must use absolute inline positioning when including a page segment, overlay, or object with an XMD structured field. You must also use absolute inline positioning when generating a bar code or graphics object with an XMD structured field.

System action

ACIF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

You need to change your inline positioning to an absolute value. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

[Advanced Function Presentation: Programming Guide and Line Data Reference](#)

APK2072I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN INCORRECT COMBINATION OF TRIPLETS WAS SPECIFIED WHEN MAPPING A DATA OBJECT FONT IN AN MDR STRUCTURED FIELD.

Explanation

When mapping a data object font (DOF) in a Map Data Resource (MDR) structured field, you must also specify a Fully Qualified Name (FQN) type X'DE', FQN type X'BE', and DOF Descriptor X'8B' triplets. In addition, the FQN type X'BE' triplet must specify a one-byte local ID.

System action

ACIF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. If the structured field has no error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

[Advanced Function Presentation: Programming Guide and Line Data Reference](#)

APK2073I

DATA IN AN INPUT RECORD IS NOT VALID: THE FULLY QUALIFIED TRIPLET TYPE AND THE OBJECT TYPE SPECIFIED IN A REPEATING GROUP ON A PREPROCESS PRESENTATION OBJECT STRUCTURED FIELD DO NOT AGREE.

Explanation

When a repeating group in a Preprocess Presentation Object (PPO) structured field is mapping an object container, you must use a Fully Qualified Name (FQN) triplet of type X'CE'. When the repeating group is mapping an IOCA object or overlay, you must use an FQN triplet of type X'84'.

System action

ACIF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or resource with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference for your system for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. It is possible that the problem is the object type OID specified in the X'10' Object Classification triplet. It might specify that a TrueType or OpenType collection is being mapped when a font was mapped. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2074I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN MDR STRUCTURED FIELD IS MAPPING THE NAME OF A TRUETYPE OR OPENTYPE COLLECTION.

Explanation

When mapping a data object font (DOF), you can specify only the name of a TrueType or OpenType font. This font might be stored in a collection, but the Map Data Resource (MDR) structured field needs the font name in the collection.

System action

ACIF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. It is possible that the problem is the object type OID specified in the X'10' Object Classification triplet. It might specify that a TrueType or OpenType collection is being mapped when a font was mapped. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2075S

TRCS ARE NOT ALLOWED WITH A PAGE THAT HAS FONTS MAPPED IN BOTH AN MCF AND AN MDR. THE DATA MAP BEING PROCESSED IS *datamap*.

Explanation

You can use table reference characters (TRCs) with fonts mapped in a Map Coded Font (MCF) structured field (FOCA fonts) or a Map Data Resource (MDR) structured field (TrueType and OpenType fonts). However, you cannot have a mixture of both types of fonts in a data map and use TRCs.

System action

ACIF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

Change your page definition to use either all FOCA fonts (mapped in an MCF) or all TrueType or OpenType fonts (mapped in an MDR).

APK2076I

PAGE BASED SOSI PROCESSING HAS BEEN REQUESTED BUT A SINGLE BYTE FONT WITH A FONT ID OF 1 AND A DOUBLE BYTE FONT WITH A FONT ID OF 2 HAVE NOT BEEN MAPPED. THE DATA MAP BEING PROCESSED IS *datamap*.

Explanation

When doing page-based SOSI processing, there is switching back and forth between the same two fonts. As a result, there must be two fonts mapped by using font IDs 1 and 2.

System action

ACIF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

Change your page definition to map a single-byte font with font ID 1 and a double byte font with font ID 2. For information about how to map fonts to specific font IDs, see the documentation for the application that you use to generate page definitions.

APK2077I

DATA IN AN INPUT RECORD IS NOT VALID: AN INLINE TRUETYPE OR OPENTYPE COLLECTION DOES NOT HAVE ANY BASE FONTS SPECIFIED.

Explanation

The Begin Resource (BRS) structured field must have Fully Qualified Name triplet of type X'6E' for each base font contained in the collection.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference for your system for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2078I

DATA IN AN INPUT RECORD IS NOT VALID: AN INLINE RESOURCE HAS AN INCORRECT SPECIFICATION OF BASE FONTS, LINKED FONTS, OR MAPPED CMRS.

Explanation

A Begin Resource (BRS or BR) structured field has an error. Base fonts (Fully Qualified Name triplets of type X'6E') can only be specified for TrueType or OpenType collections. Linked fonts (Fully Qualified Name triplets of type X'7E') can only be specified for a TrueType or OpenType font or for a base font of a TrueType or OpenType collection. Mapped CMRs (Fully Qualified Name triplets of type X'41') can only be specified for color management resources (CMRs).

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set, correct the error and resubmit the print request. Refer to Mixed Object Document Content Architecture Reference for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APK2079I

THE INFORMATION NEEDED TO DESCRIBE A TRUETYPE OR OPENTYPE FONT OR COLLECTION *name* EXCEEDS THE BEGIN OBJECT CONTAINER STRUCTURED FIELD.

Explanation

The number of names and linked fonts for a TrueType or OpenType font or the number of base fonts and linked fonts for a TrueType or OpenType collection exceeds the Begin Object Container structured field.

System action

ACIF stops processing the object container.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

You cannot collect this TrueType or OpenType font or font collection.

APK2080I

INPUT DATA *inputdata* CANNOT BE CONVERTED TO AN ENCODING OF *ccsid*. RETURN CODE *returncode* AND REASON CODE *reasoncode* VALUES WERE RETURNED BY THE CONVERTER.

Explanation

ACIF must convert the input data to the specified encoding to continue processing. An error occurred during this conversion. If the input data is a resource name, the CCSID indicates that mixed single-byte or double-byte EBCDIC data is being converted to mixed single-byte or double-byte ASCII data for a QR Code Bar code. If the error occurs on data for a bar code, only the first 50 bytes of the data are shown in the message. The return codes and reason codes are returned by the system's conversion services (ICONV on z/OS and ICU on AIX and Windows). Refer to the system documentation for these conversion services for more information about the errors.

System action

ACIF stops processing the input file and issues a message identifying the position of the structured field in the file or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, refer to your system's diagnosis reference for assistance in determining the source of the problem.

User response

Correct the error as described by the system documentation for the conversion service.

APK2082I

DATA IN AN INPUT RECORD IS NOT VALID. RESOURCE *resourcename* IS SPECIFIED ON A PREPROCESS PRESENTATION OBJECT (PPO) STRUCTURED FIELD BUT IS NOT MAPPED IN THE RESOURCE ENVIRONMENT GROUP.

Explanation

All resources specified on a PPO structured field must be mapped in the Resource Environment Group (REG). Overlays must be mapped with a Map Page Overlay (MPO) structured field. IOCA image and object containers must be mapped with a Map Data Resource (MDR) structured field.

System action

ACIF stops processing the input file and issues a message identifying the position of the structured field in the file or resource.

System programmer response

If a licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2083I

DATA IN A PAGEDEF RESOURCE IS NOT VALID: DATA MAP *data map name* HAS RECORD FORMAT IDs THAT ARE NOT THE SAME LENGTH.

Explanation

All the record format IDs for a data map in a page definition must be the same length. Blanks can be used in the record format ID to make it the required length.

System action

ACIF stops processing the current data set and issues additional messages that identify the processing environment when the error was found.

System programmer response

If a licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference for your system for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. If the structured field is correct, the error might be an ACIF or printer logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Related information

[Advanced Function Presentation: Programming Guide and Line Data Reference](#)

APK2084I

DATA IN AN INPUT RECORD IS NOT VALID: THE LENGTH OF DATA IN RECORD NUMBER *record number* DOES NOT MATCH THE LENGTH REQUIRED FOR THE USER DATA TYPE SPECIFIED IN THE PAGE DEFINITION.

Explanation

The possible causes of this error depend on the type of user data specified in the page definition:

- If you specified UTF16 data, the record length must be a multiple of 2.
- If you specified UTF8 data, the length of each character can vary from 1 to 4 bytes.

System action

ACIF stops processing the current data set and issues a message identifying the position of the error in the input data stream. ACIF issues additional messages that identify the processing environment when the error was found.

System programmer response

If a licensed program was used to create the data with the error, verify that the input to that program is valid.

User response

If you created the data, correct the data in the record to match the specified data type, and resubmit the print request. If the data has no error, the error might be an ACIF logic error. If you used a program to create the data, contact your system programmer.

APK2088I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: STRUCTURED FIELD *structuredfield* HAS AN INCORRECT SCOPE VALUE ON A CMR DESCRIPTOR TRIPLET.

Explanation

The scope value is not correct on the Color Management Resource (CMR) Descriptor triplet, X'91', for the specified structured field.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the data stream or resource.

System programmer response

User response

If you created the structured fields, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2089I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE *structuredfield* STRUCTURED FIELD CONTAINS UNPAIRED FQN X'DE' AND CMR DESCRIPTOR TRIPLETS.

Explanation

When specifying a color management resource (CMR), the CMR Descriptor triplet (X'91') must immediately follow a Fully Qualified Name (FQN) triplet with an FQNType of Data Object External Resource Reference (X'DE').

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the file or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2090I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: STRUCTURED FIELD *structuredfield* HAS AN INCORRECT PROCESSING MODE VALUE ON A CMR DESCRIPTOR TRIPLET.

Explanation

The processing mode value is not correct on the Color Management Resource (CMR) Descriptor triplet, X'91', for the specified structured field. Only audit, instruction, or device link CMR modes are valid.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the file or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2093I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A REPEATING GROUP IN AN MDR STRUCTURED FIELD CONTAINS AN INCOMPLETE SPECIFICATION FOR A CMR.

Explanation

A repeating group in a Map Data Resource (MDR) structured field for a color management resource (CMR) is missing one or both of the following information:

- a Fully Qualified Name (FQN) triplet (X'02') with an FQNType of Data Object External Resource Reference (X'DE')
- a CMR Descriptor triplet (X'91')

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the file or resource.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2096I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A COLOR MANAGEMENT RESOURCE (CMR) NAME HAS AN ERROR.

Explanation

A problem exists with the name of a color management resource (CMR) that was specified in a Map Data Resource (MDR) or a Begin Resource (BRS or BR) structured field. The possible problems are:

- A link (LK) CMR cannot be specified in an MDR.
- A generic CMR must have a type of tone transfer curve (TTC) or halftone (HT).
- A pass-through CMR must have a type of color conversion (CC).

- The CMR name length must be 73 bytes in single-byte encoding or 146 bytes in double-byte encoding.
- A device link (DL) CMR is device-specific and cannot be generic.

System action

ACIF stops processing the print data set and issues a message identifying the position of the structured field in the file or resource.

System programmer response

If a licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2102I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: STRUCTURED FIELD *structuredfield* HAS AN INCORRECT OBJECT TYPE IN AN OBJECT OFFSET TRIPLET.

Explanation

The object type in an Object Offset triplet (X'5A') is not correct. The object type must be "document" if the selected object is a document type object and "page" if the selected object is a page or paginated object.

System action

ACIF stops processing the print job.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2103I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE *structuredfield* STRUCTURED FIELD IN A PAGE DEFINITION IS MISSING A CMR DESCRIPTOR TRIPLET.

Explanation

When specifying a color management resource (CMR), a CMR Descriptor triplet (X'91') must immediately follow a Fully Qualified Name (FQN) triplet with an FQNType of Data Object External Resource Reference (X'DE').

System action

ACIF stops processing the data set.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2104I

TOO MANY CMRs HAVE BEEN SPECIFIED.

Explanation

One of these conditions occurred:

- Too many color management resources (CMRs) were specified in the data object resource access table (RAT) to fit on the Include Object (IOB) command or the Preprocess Presentation Object (PPO) command.
- Too many CMRs were specified on a Begin Image (BIM) or Begin Object Container (BOC) structured field to write the OID from the data object RAT on the BIM or BOC.

System action

ACIF stops processing the data set.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

You must specify thousands of CMRs to create this condition. Contact the generator of your data stream to have the extraneous CMRs removed.

APK2105W

THE DATA STREAM IS MISSING STRUCTURED FIELD *structuredfield*.

Explanation

A Begin Named Group (BNG) structured field must have a matching End Named Group (ENG) structured field. However, an ENG structured field was not found for at least one BNG. Therefore, the indexing created for the data set might not be valid.

System action

ACIF builds the output document and index files as requested, but the output might not be what the user expects.

System programmer response

If an IBM licensed program was used to create the data stream with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

Check the input data stream to ensure that each BNG structured field has a matching ENG structured field. If it does not meet this requirement, add the missing ENG structured fields.

APK2108I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A RESOURCE OTHER THAN A CMR HAS BEEN SPECIFIED IN AN MDR STRUCTURED FIELD FOR A FORM DEFINITION.

Explanation

Only color management resources (CMRs) can be specified in a Map Data Resource (MDR) structured field for a form definition.

System action

ACIF stops processing the print job.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2116S

DATA IN A PAGEDEF RESOURCE IS NOT VALID. CONFLICTING SEQUENCE NUMBER TYPES HAVE BEEN SPECIFIED FOR A CONCATENATED BAR CODE ON A *structuredfield* STRUCTURED FIELD.

Explanation

All segments of a given concatenated bar code must specify the same type of sequence numbering. All segments must specify either sequence numbers or no sequence numbers. Concatenated bar code sequence numbers are part of the Concatenate Bar Code Data triplet (X'93'), which is specified as one of the following structured fields in the page definition:

- Line Descriptor (LND)
- Record Descriptor (RCD)
- XML Descriptor (XMD)

System action

ACIF stops processing the print job.

System programmer response

If a licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. If the structured field does not have an error, the error might be an ACIF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

Related information

[Mixed Object Document Content Architecture Reference](#)

APK2120I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE INITIAL TEXT CONDITIONS IN THE PTD STRUCTURED FIELD ARE INCORRECT.

Explanation

The Presentation Text Descriptor (PTD) structured field is in the Object Environment Group (OEG) of a PTOCA object. This object can be in a page, overlay, or a resource.

System action

ACIF stops processing the input file and issues another message identifying the position of the structured field in the data stream or resource.

System programmer response

If a licensed program was used to create the structured fields for the object with the error, verify that the input to that program is valid. If the input is valid, see the diagnosis reference of your system for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. For information about the correct format of the referenced structured field, see *Presentation Text Object Content Architecture Reference*. If the structured field is correct, the error might be an ACIF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APK3506I

DATA OBJECT RESOURCE TYPE *objectid* COULD NOT BE FOUND IN THE RESOURCE LIBRARY.

Explanation

The registration ID (object-type OID) for the specified data object resource cannot be read from the resource library. Only objects with valid data object resource names or resource locator names are supported by ACIF. The registration ID is specified in the object classification triplet on an IOB, BOC, BR, or MDR structured field. If the *objectid* specified in this message is ***, ACIF either does not support the registration ID or does not have enough information to identify the *objectid*.

System action

If this error is encountered when processing a Resource Environment Group (REG), PSF skips over this particular data object resource and tries to process any other resources specified in the REG. If this error is encountered while processing a page or overlay object, PSF terminates the page or overlay object. PSF attempts to locate the end of the current page and resume processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues additional messages that identify the processing environment when the error was found.

System programmer response

If an IBM licensed program was used to create the structured fields, verify that the input to that program was valid and the correct printer is being used. If the input was valid, refer to *Print Services Facility for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the data object resource, ensure that the registration ID is correct. If the registration ID is correct, submit the print job to a printer that supports this object type. For more information about what object types are supported by your printer, refer to your printer documentation.

APK3507I

RESIDENT COLOR PROFILE *type*, OBJECT ID *objectid*, WAS NOT FOUND IN THE RESOURCE LIBRARY.

Explanation

The resident color profile with object ID (object-type OID) was not found because no resource locator name was specified. ACIF cannot access objects by OID name only.

System action

ACIF ignores the request for the resident color profile and, because the profile is not necessary, continues processing.

System programmer response

None.

User response

Modify the structured field that refers to the object to include a resource locator triplet.

Chapter 5. Structured APIs messages

Structured APIs provide customer applications in CICS®, IMS™, TSO, and batch environments with the ability to invoke the following server functions.

Table 1: Server functions and their descriptions

Function	Description
LOGON	Establishes a connection to the Content Manager OnDemand library server. After a successful logon, the server returns a list of authorized folders that can be accessed by a specific user.
FOLDER OPEN	Identifies the folder name to be processed by subsequent search and retrieve requests.
HIT LIST	Requests that the Content Manager OnDemand server return a list of items that match the user-supplied search criteria.
RETRIEVE	Retrieves a document from a Content Manager OnDemand archive.
LOGOFF	Allows users to log off from a Content Manager OnDemand server.
RELEASE	Frees storage areas that are used in the running of the LOGON, FOLDER OPEN, HIT LIST, and RETRIEVE functions.

Structured APIs messages

The structured APIs return informational and error messages in field CS-Message of the common structure, which is defined in the sample copybook ARSZDCWS. Messages that indicate function-related conditions can be up to 160 bytes in length. Messages that indicate data-related conditions contain criteria field names, values, and the reason that they might be invalid.

9101

Undefined function

Explanation

The value in CS-Request is not recognized.

User response

Correct the specified request.

9102

Failed to get 32-bit Internet address

Explanation

The interface program was unable to convert the IP address to its internal format. Verify that the IP address was entered correctly. If the IP address is correct, this message might indicate an installation problem.

User response

Notify the Report Administrator.

9103

Get stream socket failed

Explanation

The interface program was unable to open a socket in TCP/IP. This message might indicate a TCP/IP setup problem.

User response

Notify the Report Administrator.

9104

Error connecting to server

Explanation

The interface program was unable to connect to the mid-tier server. This message can indicate that the mid-tier server is not active or that the port number which was specified for the mid-tier server is incorrect.

User response

Verify that the mid-tier server is active, and correct the IP address and port number. If the problem persists, notify the Report Administrator.

9105

Error sending Common Structure

Explanation

The interface program cannot send the Common Structure to the mid-tier server. This message indicates a probable logic problem.

User response

Contact your IBM service representative.

9106

Error sending Logon Structure

Explanation

The interface program cannot send the Logon Structure to the mid-tier server. This message indicates a probable logic problem.

User response

Contact your IBM service representative.

9107

Error sending Search Criteria Structure

Explanation

The interface program cannot send the Search Criteria Structure to the mid-tier server. This message indicates a probable logic problem.

User response

Contact your IBM service representative.

9108

Error sending Retrieve document

Explanation

The interface program was unable to send the Retrieve Document Structure to the mid-tier server. This message indicates a probable logic problem.

User response

Contact your IBM service representative.

9109

Error receiving Folder List

Explanation

The interface program cannot receive the Folder List Structure from the mid-tier server. This message indicates a probable logic problem.

User response

Contact your IBM service representative.

9110

Error receiving Folder Criteria

Explanation

The interface program cannot receive the Folder Criteria Structure from the mid-tier server. This message indicates a probable logic problem.

User response

Contact your IBM service representative.

9111

Error receiving Hit List

Explanation

The interface program cannot receive the Hit List Structure from the mid-tier server. This message indicates a probable logic problem.

User response

Contact your IBM service representative.

9112

Error receiving Document

Explanation

The interface program cannot receive the Document Structure from the mid-tier server. This message indicates a probable logic problem.

User response

Contact your IBM service representative.

9113

Error receiving the Common Structure

Explanation

The interface program cannot receive the Common Structure from the mid-tier server. This message indicates a probable logic problem.

User response

Contact your IBM service representative.

9114

Error freeing memory pointed to by pFolderList

Explanation

The RELEASE request to free the Folder List Structure failed. This error is usually due to an inadvertent overlay of the structure.

User response

Review the application program for possible storage overlay.

9115

Error freeing memory pointed to by pFolderCriteria

Explanation

The RELEASE request to free the Folder Criteria Structure failed. This error is usually due to an inadvertent overlay of the structure.

User response

Review the application program for possible storage overlay.

9116

Error freeing memory pointed to by pHitList

Explanation

The RELEASE request to free the Hit List Structure failed. This error is usually due to an inadvertent overlay of the structure.

User response

Review the application program for possible storage overlay.

9117

Error freeing memory pointed to by pDocument

Explanation

The RELEASE request to free the Document Structure failed. This error is usually due to an inadvertent overlay of the structure.

User response

Review the application program for possible storage overlay.

9118

No hits found for *connection_id*

Explanation

The HIT LIST request did not result in any hits that met the search criteria.

User response

Change the search criteria and retry the HIT LIST request.

9119

No match found for *connection_id*

Explanation

The FOLDER OPEN request did not find the requested folder name in the active folder list.

User response

Correct the folder name to match an entry in the folder list.

9120

Error freeing memory pointed to by pNote

Explanation

The RELEASE request to free the annotations list structure failed. This error is usually due to an inadvertent overlay of the structure.

User response

Review the application program for possible storage overlay.

9121

Error sending Retrieve Note Structure

Explanation

The interface program cannot send the annotations structure to the mid-tier server. Probable logic problem.

User response

Notify IBM Software Support.

9122

Error sending Retrieve Note Structure

Explanation

The interface program cannot receive the annotations list structure from the mid-tier server. Probable logic problem.

User response

Notify IBM Software Support.

9123

"ODFolder.recreateHit Failed for" connectID

Explanation

The mid-tier server must use the "ODHITobject" to access the ODWEK Java APIs in order to complete the RETRIEVE or ANNOTATIONS request. This message documents the failure of the "ODFolderRecreateHIT" request issued by the mid-tier to recreate the "ODHITobject".

User response

Notify IBM Software Support.

9124

"No notes found for" connectID

Explanation

The mid-tier server received a "no notes" response to a request to retrieve notes for a document.

User response

Review the application program to make sure that the HL-NotesIndicator for the document has a non-zero value.

9125

"Invalid segment requested"

Explanation

The mid-tier Server determined the segment requested is greater than the number of segments in the document.

User response

Change the application program to not request a segment greater than the segment count.

9126

Error while sending the Bulk Retrieve Structure

Explanation

This message indicates a communication problem, the expected data was not received by TCP/IP.

User response

Investigate the potential sources of the problem, correct any problems you find, and retry the transaction.

9127

Disk Write Mode must be 0 (write directly to disk) or 1 (receive document data in memory then write to disk)

Explanation

An invalid Disk Write Mode was specified. Valid values are:

0

write directly to disk

1

receive document data in memory then write to disk

User response

Enter a valid value of either 0 or 1.

9128

Bulk Retrieve debug trace level must be between 0 and 7

Explanation

An invalid Bulk Retrieve debug trace level was specified. Valid values are between 0 and 7.

User response

Enter a value between 0 and 7.

9129

The no. of threads for Bulk Retrieve must be between 0 and 10.

Explanation

An invalid number of threads for Bulk Retrieve was specified. Valid values are between 0 and 10.

User response

Enter a value between 0 and 10.

9130

The no. of SQLs for Bulk Retrieve must be between 0 and 10.

Explanation

An invalid number of SQLs for Bulk Retrieve was specified. Valid values are between 0 and 10.

User response

Enter a value between 0 and 10.

9131

"TCP/IP error while sending the Common Structure"

Explanation

A communication problem occurred due to an untimely response from TCP/IP. This could be the result of a TCP/IP failure or an overloaded network.

User response

Investigate the potential sources of the problem, correct them, and try the transaction again.

9132

"Time out error while sending the Common Structure"

Explanation

This message indicates a communication problem: the expected data was not received by TCP/IP.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9133

"TCP/IP error while sending the Logon Structure"

Explanation

This message indicates a communication problem due to an untimely response from TCP/IP. This could be the result of a TCP/IP failure or an overloaded network.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9134

"Time out error while sending the Logon Structure"

Explanation

This message indicates a communication problem: the expected data was not received by TCP/IP.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9135

"TCP/IP error while sending the Search Criteria Structure"

Explanation

This message indicates a communication problem due to an untimely response from TCP/IP. This could be the result of a TCP/IP failure or an overloaded network.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9136

"Time out error while sending the Search Criteria Structure"

Explanation

This message indicates a communication problem: the expected data was not received by TCP/IP.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9137

"Memory Allocation error while sending the Retrieve Request Structure"

Explanation

The interface program was unable to allocate memory to hold the Retrieve Request Structure before sending it to the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9138

"TCP/IP error while sending the Retrieve Request Structure"

Explanation

This message indicates a communication problem due to an untimely response from TCP/IP. This could be the result of a TCP/IP failure or an overloaded network.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9139

"Time out error while sending the Retrieve Request Structure"

Explanation

This message indicates a communication problem: the expected data was not received by TCP/IP.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9140

"Memory Allocation error while sending the Retrieve Note Structure"

Explanation

The interface program was unable to allocate memory to hold the Retrieve Note Structure before sending it to the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9141

"TCP/IP error while sending the Retrieve Note Structure"

Explanation

This message indicates a communication problem as a result of an untimely response from TCP/IP. This could be the result of a TCP/IP failure or an overloaded network.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9142

"Time out error while sending the Retrieve Note Structure"

Explanation

This message indicates a communication problem: the expected data was not received by TCP/IP.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9143

"TCP/IP error while receiving the Common Structure"

Explanation

This message indicates a communication problem due to an untimely response from TCP/IP. This could be the result of a TCP/IP failure or an overloaded network.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9144

"Time out error while receiving the Common Structure"

Explanation

This message indicates a communication problem: the expected data was not received from TCP/IP.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9145

"Memory Allocation error while receiving the Folder Name list"

Explanation

The interface program was unable to allocate memory to hold the Folder Name list returned by the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9146

"Memory Allocation error while receiving the Folder Description list"

Explanation

The interface program was unable to allocate memory to hold the Folder Description list returned by the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9147

"Memory Allocation error while receiving the Folder List Structure"

Explanation

The interface program was unable to allocate memory to hold the Folder List Structure returned by the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9148

"TCP/IP error while receiving the Folder List"

Explanation

This message indicates a communication problem due to an untimely response from TCP/IP. This could be the result of a TCP/IP failure or an overloaded network.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9149

"Time out error while receiving the Folder List"

Explanation

This message indicates a communication problem: the expected data was not received from TCP/IP.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9150

"Memory Allocation error while receiving the Folder Criteria Structure"

Explanation

The interface program was unable to allocate memory to hold the Folder Criteria Structure returned by the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9151

"TCP/IP error while receiving the Folder Criteria Structure"

Explanation

This message indicates a communication problem due to an untimely response from TCP/IP. This could be the result of a TCP/IP failure or an overloaded network.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9152

"Time out error while receiving the Folder Criteria Structure"

Explanation

This message indicates a communication problem: the expected data was not received from TCP/IP.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9153

"Memory Allocation error while receiving the Hit List Structure"

Explanation

The interface program was unable to allocate memory to hold the Hit List Structure returned by the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9154

"Memory Allocation error while receiving DocId in the Hit List"

Explanation

The interface program was unable to allocate memory to hold the DocId in the Hit List returned by the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9155

"TCP/IP error while receiving the Hit List Structure"

Explanation

This message indicates a communication problem due to an untimely response from TCP/IP. This could be the result of a TCP/IP failure or an overloaded network.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9156

"Time out error while receiving the Hit List Structure"

Explanation

This message indicates a communication problem: the expected data was not received from TCP/IP.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9157

"Memory Allocation error while receiving the document"

Explanation

The interface program was unable to allocate memory to hold the document returned by the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9158

"Memory Allocation error while receiving the Document Structure"

Explanation

The interface program was unable to allocate memory to hold the Document Structure returned by the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9159

"TCP/IP error while receiving the Document Structure"

Explanation

This message indicates a communication problem due to an untimely response from TCP/IP. This could be the result of a TCP/IP failure or an overloaded network.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9160

"Time out error while receiving the Document Structure"

Explanation

This message indicates a communication problem: the expected data was not received from TCP/IP.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9161

"Memory Allocation error while receiving the Notes Structure"

Explanation

The interface program was unable to allocate memory to hold the Notes Structure returned by the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9162

"Memory Allocation error while receiving the note"

Explanation

The interface program was unable to allocate memory to hold the note returned by the mid-tier server.

User response

Allocate more memory and retry the job. If the error still occurs, notify OnDemand for z/OS support.

9163

"TCP/IP error while receiving the Note Structure"

Explanation

This message indicates a communication problem due to an untimely response from TCP/IP. This could be the result of a TCP/IP failure or an overloaded network.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9164

"Time out error while receiving the Note Structure"

Explanation

This message indicates a communication problem: the expected data was not received from TCP/IP.

User response

Investigate the potential sources of the problem, correct it, and retry the transaction.

9165

"Invalid criteria"

Explanation

An invalid search criteria was detected in the Hit List request.

User response

Enter a valid search criteria.

Chapter 6. XML messages

Content Manager OnDemand includes an XML interface for importing data into, and exporting data from, a Content Manager OnDemand system. This interface gives user applications and Web interfaces the ability to create an XML file and import a single object or multiple objects into the system. Similarly, objects currently in a Content Manager OnDemand system can be exported to an XML file and then later imported back into the same system or into another Content Manager OnDemand system.

The XML messages in this section are associated with the `arsxml` program, which can be used to:

- Import data in a Content Manager OnDemand XML file into a Content Manager OnDemand system
- Update data in a Content Manager OnDemand system
- Delete data from a Content Manager OnDemand system
- Export data from a Content Manager OnDemand system

XML messages

XML messages can occur for a variety of reasons. These reasons include, but are not limited to, the following:

- To present information (such as `arsxml` command syntax, a progress indicator, and so on)
- To prompt the user for information
- To indicate that the input XML file does not conform to the Content Manager OnDemand XML schema
- To indicate that an error occurred during processing of the `arsxml` command

ARS7700I

Usage: `arsxml add | update | delete | export | validate [options]`
Version: *version*

Explanation

This message displays the syntax of the `arsxml` command.

User response

Informational; no action is required.

ARS7701I

Usage: `arsxml export [options]`
Version: *version*

Options:

-h *hostname* Host Name (required).

-u *username* OnDemand User Name for logging in

-p *password* Password stash file for the specified User Name

-e *err* Error Handling Value (default is 'a')

a Stop processing if an error is encountered.

c Continue processing if an error is encountered.

-r *ext* Export Extent Value (can be specified more than once).

a When exporting an application group, also export the applications contained within the group

d Export Dependent Objects

p Export Permissions

l Export Logical Views

i Export only objects from the input XML file. Cannot be combined with a, d, p, or l.

-d *directory* Directory for the input XML file

-i *file* Input XML file
-y *directory* Directory for the output XML file
-o *file* Output XML file
-s *directory* Directory for the schema file location
-w *encode* Output XML File encoding value (default is 'UTF-8').
-x Disable Prompting
-v Enable Verbose Mode
-1 <trace_file> Trace file
-2 <trace_level> Trace level

Explanation

This message displays the usage of the `arsxml` export command.

User response

Informational; no action is required.

ARS7702I

Usage: `arsxml add` [options]

Version: *version*

-h *hostname* IP or web address of the Content Manager OnDemand server. This option is required.
-u *username* ID or user name of a Content Manager OnDemand user.
-p *password* Stash file that contains the password for the specified *username*.
-d *directory* Path that identifies location of the XML input file.
-i *file* Name of the XML input file. This option is required.
-e *err* Error handling value, which can be any of the following values:
a Stop processing if an error is encountered. This is the default.
c Continue processing if an error is encountered.
u If an object already exists, then update the object instead of adding it.
-v Enable verbose mode.
-1 <trace_file> Trace file.
-2 <trace_level> Trace level.

Explanation

This message displays the usage of the `arsxml add` command.

User response

ARS7703I

Usage: `arsxml update` [options]

Version: *version*

-h *hostname* Host Name (required)
-u *username* OnDemand User Name for logging in
-p *password* Password stash file for the specified User Name
-d *directory* Directory for the input XML File
-i *file* Input XML File (required)
-e *err* Error Handling Value (default is 'a')
a Stop processing if an error is encountered.
c Continue processing if an error is encountered.
-x Disable prompting.
-v Enable Verbose Mode
-1 <trace_file> Trace file
-2 <trace_level> Trace level

Explanation

This message displays the usage of the `arsxml update` command.

User response

ARS7704I

Usage: arxml delete [options]
Version: *version*
-h *hostname* Host Name (required)
-u *username* OnDemand User Name for logging in
-p *password* Password stash file for the specified User Name
-d *directory* Directory for the input XML File
-i *file* Input XML File (required)
-e *err* Error Handling Value (default is 'a')
a Stop processing if an error is encountered.
c Continue processing if an error is encountered.
-x Disable Prompting
-v Enable Verbose Mode
-1 <trace_file> Trace file
-2 <trace_level> Trace level

Explanation

This message displays the usage of the `arxml delete` command.

User response

ARS7705I

No input file was specified. Do you want to export all of the objects on the system? (Y/N)

Explanation

Because no input file was specified, OnDemand assumes that you want to export all of the objects on the system. This message prompts you to confirm this assumption.

User response

Type Y to continue and export all of the objects on the system; type N to stop the export operation.

ARS7706I

Export process stopped at the user's request.

Explanation

The export operation was stopped in response to a negative (N) response to message 7705.

User response

Informational; no action is required.

ARS7707I

The *objectType* object named '*objectName*' is about to be deleted.
Do you want to delete this object? (Y/N)

Explanation

The command prompts for a confirmation before deleting an object.

User response

Specify Y to delete the object or N to keep the object.

ARS7708I

Delete stopped at the user's request

Explanation

This message is displayed if the user replies negatively to message 7707.

User response

No action is required.

ARS7709I

Adding *objectType, objectName*

Explanation

This message displays the progress during an import operation.

User response

Informational; no action is required.

ARS7710I

Updating *objectType, objectName*

Explanation

This message displays the progress during an update operation.

User response

Informational; no action is required.

ARS7711I

Deleting *objectType, objectName*

Explanation

This message displays the progress during a delete operation.

User response

Informational; no action is required.

ARS7712I

Exporting *objectType, objectName*

Explanation

This message displays the progress during an export operation.

User response

Informational; no action is required.

ARS7713I

Add of *objectType, objectName* was successful.

Explanation

This message is displayed after a successful import operation.

User response

Informational; no action is required.

ARS7714I

Update of *objectType*, *objectName* was successful.

Explanation

This message is displayed after a successful update operation.

User response

Informational; no action is required.

ARS7715I

Delete of *objectType*, *objectName* was successful.

Explanation

This message is displayed after a successful delete operation.

User response

Informational; no action is required.

ARS7716I

Export of *objectType*, *objectName* was successful.

Explanation

This message is displayed after a successful export operation.

User response

Informational; no action is required.

ARS7720E

Invalid option specified, *-option*

Explanation

An invalid option was passed to the `arsxml` command.

User response

Validate the input options to the `arsxml` command.

ARS7721E

Value missing or invalid for the *-option* option.

Explanation

The specified option requires a value.

User response

Update the option list to include a value for the specified option.

ARS7722E

Input and output file names cannot be the same.

Explanation

Output file cannot be the same as the input file.

User response

Specify a file name for output other than the input file name.

ARS7723E

Host name was not specified.

Explanation

A Content Manager OnDemand host name is required.

User response

Specify the Content Manager OnDemand host name using the -h option.

ARS7724E

Invalid error handling value specified, *value*. Valid values are 'a', 'c', and 'u'.

Explanation

An invalid error handling value was specified.

User response

Update the argument list to include an error handling value of 'a', 'c', or 'u'.

ARS7725E

Invalid action value specified, *value*. Valid values are 'add', 'update', 'delete', 'export', and 'validate'.

Explanation

An invalid action value was specified.

User response

Update the argument list to include an action value of 'add', 'update', 'delete', 'export', or 'validate'.

ARS7726E

The error handling option 'u' can only be used with an action of 'add'.

Explanation

The error handling option cannot be specified for this action.

User response

Correct the error handling option, -e, to specify a valid value for the action.

ARS7728E

Unable to set encoding value, *value*.

Explanation

The specified encoding value is not supported by the `arsxml` command.

User response

Correct the encoding option, -w, to specify a supported encoding value.

ARS7729E

The output file, *outputFile*, could not be written to.

Explanation

The output file could not be written to.

User response

Verify that the user has permission to write to the specified output file and directory.

ARS7730E

The input file, *inputFile*, was not found.

Explanation

The input file was not found.

User response

Validate the file name specified for the input file option, -i, and validate the directory name specified for the input directory option, -d.

ARS7732E

A parsing error occurred in file *inputFile*, Line *lineNumber*, Column *columnNumber*: *errorMsg*.

Explanation

An error occurred while parsing the input file.

User response

The input OnDemand XML file contains a syntax error and needs to be modified. The error message contains more information about the type of error. The most common errors include:

- Missing double quotes around attribute values, for example `timeOut=30` should be specified as `timeOut="30"`.
- Incorrect uppercase or lowercase specified for a keyword, for example `timeout="30"` should be `timeOut="30"`.
- A missing end of object tag, for example `<node . . . >` should be `<node . . . />`

ARS7733E

A parsing error occurred in file *inputFile*: *errorMsg*.

Explanation

An internal error occurred while parsing the input file.

User response

The error message contains more information.

ARS7734E

objectType attribute must be specified for the *objectName* object.

Explanation

A required attribute was not specified.

User response

Update the input XML file to specify the required attribute.

ARS7735E

objectType1 and *objectType2* attributes cannot both be specified for the *objectName* object.

Explanation

More than one mutually-exclusive attribute was specified.

User response

Update the input XML file to specify only one of the attributes.

ARS7736E

A value must be specified for either *objectType1* or *objectType2* for the *objectName* object.

Explanation

One of the listed attribute values must be specified.

User response

Update the input XML file to specify one of the attributes.

ARS7737W

The *attributeType* attribute of the *objectType* object cannot be updated.

Explanation

An attempt was made to update an attribute that cannot be updated by OnDemand.

User response

Remove the attribute from the input XML file.

ARS7738E

The *attributeValue* value of the *objectType* attribute is not valid for this operating system.

Explanation

An attempt was made to add or update an attribute value that is not supported on this operating system.

User response

Remove the attribute from the input XML file, or change the value of the attribute to a supported value.

ARS7739E

The *attributeName* attribute of the *objectType* object is not valid for this operating system.

Explanation

An attempt was made to add or update an attribute value that is not supported on this operating system.

User response

Remove the attribute from the input XML file.

ARS7740E

The *attribute1* attribute cannot have a value of *value1* when the *attribute2* attribute has a value of *value2*.

Explanation

An attempt was made to add or update an attribute value that is not valid for the current object.

User response

Remove the attribute from the input XML file, or change the value of the attribute to a supported value.

ARS7741E

The *attribute1* attribute of the *objectType* object is not valid when the *attribute2* attribute has a value of '*attributeValue*'.

Explanation

An attempt was made to add or update an attribute that is not valid for the current object.

User response

Remove the attribute from the input XML file, or change the value of the attribute to a supported value.

ARS7742E

The *objectType* object cannot be added because an object, *objectType*, is already associated with the parent object, *name*.

Explanation

An attempt was made to add an object to an object that already has the maximum number of children.

User response

Remove one of the existing child objects before attempting to add a new child object.

ARS7743E

An *objectType* object named *objectName* already exists.

Explanation

An attempt was made to add an object that already exists.

User response

Remove the specified object from the input XML file.

ARS7744E

An *objectType* object named *objectName* does not exist.

Explanation

An attempt was made to delete, update, or export an object that does not exist.

User response

Verify that the specified object exists, or remove the object from the input file.

ARS7745E

The *objectType* object named '*objectName*' could not be added because that object is already being processed. The *objectType* object named '*name*' cannot have more than *number objectType* objects.

Explanation

The number of child objects has exceeded allowable limit.

User response

Remove extra objects and try again.

ARS7747E

The *objectType* object cannot be processed on this operating system.

Explanation

An attempt was made to process an object that is not valid for the operating system.

User response

Remove the object from the input XML file.

ARS7748E

The name *objectName* for the *objectType* is not valid or is a reserved word.

Explanation

An attempt was made to add or update an object with a name attribute which is invalid or a reserved word.

User response

Provide a different name for the object.

ARS7749E

The *childObjectType* object cannot be added to the *parentObjectType* object named '*parentObjectName*' during update with the '*attributeName*' attribute set to *attributeValue*.

Explanation

An attempt was made to add an object that is not valid for the parent object during the update with the specified attribute set to true.

User response

Change the attribute value to false or remove the object from the input XML file.

ARS7750E

The *attributeName* attribute has a value of *value*, but must be greater than or equal to *minValue*.

Explanation

A value was entered which is lower than the minimum required value.

User response

Specify a value which is larger than or equal to the minimum required value.

ARS7751E

The *objectType* object cannot be deleted from the *parentObjectType* object named *parentObjectName*.

Explanation

An attempt was made to delete an object that cannot be deleted from Content Manager OnDemand.

User response

Remove the object from the input XML file.

ARS7754E

Permissions can not be added to the *objectType* object named '*objectName*' because the authority is set to '*authorityValue*'.

Explanation

An attempt was made to add permissions to an object which does not have access authority.

User response

Remove the object from the input XML file.

ARS7755E

The *childObjectName* object named '*childObjectType*' can not be updated unless the parent object is also being updated.

Explanation

An attempt was made to update a child object during an add.

User response

Remove the object from the input XML file or modify the XML file to update the parent object.

ARS7756E

The *childObjectName* object named '*childObjectType*' can not be deleted unless the parent object is being updated.

Explanation

An attempt was made to delete a child object during an add operation.

User response

Remove the object from the input XML file or modify the XML file to update the parent object.

ARS7757E

The *ObjectName* object named '*ObjectType*' can not be deleted.

Explanation

An attempt was made to delete a system defined object.

User response

Remove the object from the input XML file.

ARS7758E

The *attributeName* attribute has a value of '*value*', but cannot be longer than *maxLength* characters.

Explanation

The value you entered is longer than the allowable string length for the field.

User response

Specify a string value which is shorter than or equal to the maximum allowed length.

ARS7759E

The *attributeName* attribute has a value of *value*, but must be less than or equal to *maxValue*.

Explanation

The value you entered is greater than the maximum required value.

User response

Specify a value which is less than or equal to the maximum required value.

ARS7760E

The *attributeName* attribute has a value of *value*, but must be less than *maxValue*.

Explanation

The value you entered is greater than the maximum required value.

User response

Specify a value that is smaller than or equal to the maximum required value.

ARS7761I

Add of *objectType*, *objectName* failed.

Explanation

This message is displayed after a failed import operation.

User response

This is an informational message.

ARS7762I

Update of *objectType*, *objectName* failed.

Explanation

This message is displayed after a failed update operation.

User response

This is an informational message.

ARS7763I

Delete of *objectType*, *objectName* failed.

Explanation

This message is displayed after a failed delete operation.

User response

This is an informational message.

ARS7764I

Export of *objectType*, *objectName* failed.

Explanation

This message is displayed after a failed export operation.

User response

This is an informational message.

ARS7765E

The value, *attrValue*, is not valid for the *attrName* attribute of the *objectType* object.

Explanation

An invalid value was specified for the attribute.

User response

Update the XML file with a valid value for the attribute.

ARS7766E

The *objectType* named *objectName* is about to be deleted.

Warning: Data previously loaded in the application cannot be retrieved or viewed if the application is deleted.

Do you want to delete this object? (Y/N)

Explanation

The command prompts for a confirmation before deleting an application.

User response

Enter a Y or an N to confirm or reject the delete of the application.

ARS7767E

The folder field object requires zero or *numberOfMappings* mappings to *objectType*, *objectName* when the *mappingType* is set to '*mappingType*'.

Explanation

An incorrect number of mappings was specified for a folder field.

User response

Update the XML file to contain the correct number of mappings.

ARS7770E

The *fieldtype1* field cannot be mapped to the *fieldtype2* field. The *fieldtype2* field has a data type of *dataType2* and the *fieldtype1* field has a data type of *dataType1*.

Explanation

A mapping was attempted between two fields that are of different data types.

User response

Correct the mapping object to reference a field of the correct data type.

ARS7776E

The *appName* application can not contain index parameters when the value of the *indexer* attribute is *indexerType*.

Explanation

The application cannot contain index parameters.

User response

Update the XML file to remove the index parameters from the application.

ARS7779E

The *objectType* named *objectName* is about to be deleted. *numDocs* documents are loaded in the application group. Do you want to delete this object? (Y/N)

Explanation

The command prompts for a confirmation before deleting an application group.

User response

Enter a Y or an N to confirm or reject the delete of the application group.

ARS7781E

A *fieldType objectType* field has already been defined.

Explanation

A field of this type is already defined.

User response

Remove the field, or modify it to remove the duplication.

ARS7782E

The *fieldInfo* object cannot be added because the *objectName*, *userName*, does not have *userGroupFields* enabled for this folder.

Explanation

The field information cannot be created.

User response

Add a permission object for the user with the *userGroupFields* attribute enabled.

ARS7783E

The *attributeName* attribute has a value of *value*, but must be less than or equal to the *maxAttrName* attribute which has a value of *maxValue*.

Explanation

A value was entered which is greater than the maximum required value.

User response

Specify a value which is less than or equal to the maximum required value.

ARS7784E

The *attributeName* attribute has a value of *value*, but must be less than the *maxAttrName* attribute which has a value of *maxValue*.

Explanation

A value was entered which is greater than the maximum required value.

User response

Specify a value which is smaller than the maximum required value.

ARS7785E

The *attributeName* attribute has a value of *value*, but must be greater than or equal to the *minAttrName* attribute which has a value of *minAttrName*.

Explanation

A value was entered which is lower than the minimum required value.

User response

Specify a value which is larger than or equal to the minimum required value.

ARS7786E

The *attributeName* attribute has a value of *value*, but must be greater than the *minAttrName* attribute which has a value of *minAttrName*.

Explanation

The value you entered is lower than the minimum required value.

User response

Specify a value which is larger than or equal to the minimum required value.

ARS7787E

A value of *'attrValue'* for the *objectType* attribute is not valid for this server.

Explanation

An attempt was made to add or update an attribute value that is not supported on this server.

User response

Remove the attribute from the input XML file, or change the value of the attribute to a supported value.

ARS7793E

A *fieldType* field must be specified for this Application Group.

Explanation

An attempt was made to add an application Group without a required field type.

User response

Update the input XML file to add the appropriate field to the application group.

ARS7794E

The *attributeName1* value and the *attributeName2* value must be the same when the storage set contains cache only storage nodes.

Explanation

An attempt was made to add an application group with differing cache values.

User response

Update the input XML file to make the specified cache values the same.

ARS7795E

The input file contains XML objects that are specified in the wrong order.

Explanation

The order of objects in the input xml file is incorrect.

User response

The correct order for the XML objects is: 1-user, 2-group, 3-printer, 4-storageSet, 5-applicationGroup, 6-application, 7-folder, 8-cabinet, 9-hold. For more information, see the *Content Manager OnDemand Administration Guide*. Update the input XML file and verify that it reflects the correct object order.

ARS7796E

A value of *_ALL* for the name attribute is supported only during export.

Explanation

A name value of *_ALL* is supported only for export.

User response

Update the input XML file by excluding the *_All* attribute. For more information, see the *Content Manager OnDemand Administration Guide*.

ARS7797I

Usage: `arsxml validate [options]`

Version: *None*

`-d <directory>` Directory for the input XML File

-i <file> Input XML File (required)

Explanation

This message displays the usage of the `arsxml validate` command.

User response

No action is required.

ARS7798E

A *objectType* named *attributeValue* was not found and is needed to process *childObjectType* named *displayName*. An attempt to update or add this object will be made after input file processing.

Explanation

Object was not found, an attempt to process it will be made after all input file objects have been processed.

User response

No action is required.

ARS7799E

Unable to delete *objectName*. The object is in use by Report Distribution.

Explanation

The object could not be deleted because it is in use by Report Distribution.

User response

No action is required.

ARS7800I

Querying *objectType*, *objectName*

Explanation

This message displays the progress during an query operation.

User response

None

ARS7801I

Query of *objectType*, *objectName* was successful.

Explanation

This message displays after a successful query operation.

User response

None.

ARS7802E

The attribute '*attributeName*' cannot be specified because sibling object *objectName* already has that attribute set.

Explanation

The child attribute has already been specified in another sibling object.

User response

None

ARS7803E

The value '*attributeName*' cannot be specified for the '*objectName*' attribute because a sibling object already has that value set.

Explanation

The value has already been specified in another sibling object.

User response

None

ARS7804E

Position '*attributeName*' in the list of '*objectName*' is missing.

Explanation

The query, display and sort order attributes must not have any gaps.

User response

None

ARS7805E

The field, *fieldName*, cannot be mapped as its field type is *fieldType*.

Explanation

A mapping was attempted for a field whose field type does not permit mapping.

User response

No action is required.

ARS7806I

Searching *objectType* for *objectType objectName*.

Explanation

Searching folders, application groups or applications for containment.

User response

None

ARS7807E

No objects found.

Explanation

The search resulted in no objects being found on the server.

User response

None

ARS7808E

Unable to delete storageSet. The object is referenced by an application group object.

Explanation

The storage set could not be deleted because it is being referenced by an application group object.

User response

No action is required.

ARS7810E

The password specified cannot match the last *number* passwords used.

Explanation

An attempt was made to change the password to a previously used password.

User response

Try a different password.

ARS7811E

The password specified cannot match the userid.

Explanation

An attempt was made to use a password that matches the userid.

User response

Try a different password

ARS7812E

Not enough objects specified. The *objectType* object requires *number name* child objects.

Explanation

Not enough objects were specified.

User response

Specify the required number of objects.

ARS7813W

The *attribute* attribute for the *object* object is set to *count*. This value may be too small.

Explanation

Value for the specified attribute may be too small.

User response

Increase the number specified.

ARS7814E

The collection name *name* is not valid. The collection name must consist of (A-Z, a-z, 0-9, \$, #, @, and .)

Explanation

Value for the specified collection name is invalid.

User response

Correct the name and retry.

ARS7815E

The *applGroup* named '*applGroupName*' is about to be updated.
WARNING: OnDemand clients prior to V9 will not be able to access the application group.
Do you want to update this object? (Y/N)

Explanation

The command prompts for a confirmation before updating an application group

User response

Type a Y or an N to confirm or reject the update of the application group.

ARS7816E

The *objectType* object '*objectName*' cannot contain both new and old date type fields.

Explanation

Old and new date formats cannot be mixed.

User response

Correct the error and retry.

ARS7817E

The *objectType* object '*objectName*' cannot contain database mappings.

Explanation

The specified field cannot contain database mappings.

User response

Correct the type or attributes and try again.

ARS7818E

The *objectType* object '*objectName*' cannot contain NLS information.

Explanation

The specified field cannot contain NLS information.

User response

Correct the type and try again.

ARS7819E

A value of '*attrValue*' for the *objectType* attribute is not appropriate as the required feature is not enabled for this server.

Explanation

An attempt was made to add or update an attribute value that requires a feature that is not enabled on this server.

User response

Enable the required feature on the server.

ARS7820E

The *attributeName* attribute value is out of range. Enter new minimum/maximum values or change the *attributeName* attribute value.

Explanation

A default value is outside the range defined by minimum and maximum values.

User response

Specify a default value which is in the range defined by minimum and maximum values.

ARS7821E

At least one field must be specified for *objectType* '*objectName*'.

Explanation

An attempt was made to add an application Group or folder without any field specified.

User response

Update the input XML file to add at least one field to the application group or folder.

ARS7822E

Cannot delete mapping dbValue '*objectName*' as it is used by application '*objectName*' as the identifier.

Explanation

An attempt was made to delete an application group field mapping that is in use by an application.

User response

Correct the error and retry.

ARS7823W

The *attributeName* attribute value '*attributeValue*' will not be shifted to uppercase. *attributeName* value must match the value in the database.

Explanation

Due to the special character(s) in the attribute value, the attribute value cannot be converted to uppercase.

User response

None.

ARS7824E

The length of *attribute name* attribute value '*value*' exceeds the maximum length allowed when converted and stored on the server.

Explanation

Due to the special character(s) in the attribute value, the value string will exceed the maximum database field length when converted on the server to the target database encoding.

User response

None.

ARS7825E

The object, '*objectName*', is not valid when the data type is '*dataType*'.

Explanation

An invalid object was specified for the data type

User response

Remove the object from the XML file or update the XML file with a valid data type for the object.

ARS7826E

A logView object named '*objectName*' has already been defined as the default view for '*userName*'.

Explanation

A default view has already been defined for this user

User response

Remove the object from the XML file or update the XML file with a defaultView value for the object.

ARS7827E

A *objectType* object named '*name*' already exists for '*name*'.

Explanation

A duplicate object found for an identifier.

User response

Remove the object from the input file or change its name.

ARS7828E

A value of '*attrValue*' for the *attrName* attribute is not valid during add.

Explanation

An attempt was made to add an attribute value that is not supported

User response

Remove the attribute from the input XML file, or change the value of the attribute to a supported value.

ARS7829E

At least one operator must be set to true for the '*attrName*' attribute of the *name* object.

Explanation

All operators are set to false

User response

Set at least one supported operator to true.

ARS7830E

The attribute '*attrName*' cannot have a value of '*value*' when the fieldType is '*fieldType*'.

Explanation

An attempt was made to add an attribute value that is not supported

User response

Remove the attribute from the input XML file, or change the value of the attribute to a supported value.

ARS7831E

More than one operator is set to default for the '*attrName*' attribute of the *objectName* object.

Explanation

Only one operator can be set as default

User response

Change the value of the attribute to a supported value.

ARS7832E

The attribute '*attrName*' cannot have a value of '*value*' when the folder field is mapped to an application group field whose attribute '*fieldType*' is set to true.

Explanation

An attempt was made to add an operator value that is not supported

User response

Remove the attribute from the input XML file, or change the value of the attribute to a supported value.

ARS7833E

The *attrName* attribute must be set to true for one node on server *attrName* with *storageType* set to Local.

Explanation

The specified attribute must be set to true once for each server.

User response

Add the missing attribute or set the attribute value to true.

ARS7834E

The *attrName* attribute must be set to true for one node with *storageType* set to Fixed.

Explanation

The specified attribute must be set to true on one node.

User response

Add the missing attribute or set the attribute value to true.

ARS7835E

At least one '*objType*' object must be specified for the '*objName*' *objType* object.

Explanation

A required child object was not found for the specified parent object.

User response

Add the missing child object.

ARS7836E

The *attrName* attribute can be set to true for only one node on server *attrName* with storageType set to Local.

Explanation

The specified attribute can only be set to true once for each server.

User response

Change the value of the attribute to a supported value.

ARS7837E

The *attrName* attribute can be set to true for only one node with storageType set to Fixed.

Explanation

The specified attribute can only be set to true on one node.

User response

Change the value of the attribute to a supported value.

ARS7838E

The attribute '*attrName*' cannot have a value of '*value*' when the field mappingType attribute is set to '*mappingType*'.

Explanation

An attempt was made to add an attribute value that is not supported

User response

Remove the attribute from the input XML file, or change the value of the attribute to a supported value.

ARS7839W

No operator is set to default for the '*attrName*' attribute of the *objName* object. The '*attrName*' attribute has been set to '*value*'.

Explanation

No operator is set as default. ArsXML has set a default.

User response

Change the default to a different operator if the current default is not suitable.

ARS7840E

Value 'i' cannot be combined with value 'a', 'd', 'p' or 'l' for the -r option.

Explanation

The specified value can only be used alone.

User response

Update the value list to only contain 'i' or to remove other values for the specified option.

ARS7841W

'*attrName*' is an '*objName*' storage node. It cannot be added and will be ignored.

Explanation

The storage node is not longer supported. It will be ignored during add.

User response

Change the default to a different operator if the current default is not suitable.

ARS7842E

Either the *objectType* object name or a *attrName* attribute value specified for the *objectType* object is already used in an existing *objectType* object.

Explanation

An attempt was made to add an object with an NLS name that is already taken.

User response

Remove or rename the attribute value from the input file.

ARS7843E

A *attrName* attribute value specified for the *objectType* object is already used in an existing *objectType* object.

Explanation

An attempt was made to add an object with an NLS name that is already taken.

User response

Remove or rename the attribute value from the input file.

ARS7844E

attribute1 and *attribute2* attributes cannot both be false when the *attribute3* attribute has a value of 'value1'.

Explanation

An attempt was made to add or update attribute values that are not valid for the current object.

User response

Remove the attributes from the input XML file, or change the values of the attributes to a supported value.

ARS7845E

attribute1, *attribute2* and *attribute3* attributes cannot all be false when the *attribute4* attribute has a value of 'value1'.

Explanation

An attempt was made to add or update attribute values that are not valid for the current object.

User response

Remove the attributes from the input XML file, or change the values of the attributes to a supported value.

ARS7846E

The *attrName* attribute of the *objectType* object cannot have a value of '*attrValue*' when the *attrName* attribute has a value of '*attrValue*'.

Explanation

An attribute value is in conflict with another attribute value.

User response

Update the XML file with a valid value for one of the attributes to be compatible with another attribute value.

ARS7847E

The '*attrName*' attribute value of the *objectType* object must consist of (A-Z, 0-9 or @, #, \$) characters and must begin with (A-Z or @, #, \$).

Explanation

The attribute value is not valid for the given object type.

User response

Ensure the value only contains the valid characters and begin with one of required characters.

ARS7848E

The '*attrName*' attribute value of the *objectType* object must consist of (A-Z, 0-9 or @, #, \$) characters and must begin with (A-Z).

Explanation

The attribute value is not valid for the given object type.

User response

Ensure the value only contains the valid characters and begin with one of required characters.

ARS7849E

The string length of the sql attribute value of the *odfReportBundle* sequence *seq* object exceeds the maximum length of 32767 allowed when tokenized.

Explanation

The string length of the sql string was within the limit, but the tokenized version exceeded the limit.

User response

Reduce the string length so the tokenized version does not exceed the allowed limit.

ARS7850E

The string length of the sql attribute value of the *odfReportBundle* sequence *seq* object exceeds the maximum length of 32767 allowed.

Explanation

The string length of the sql string exceeded the limit.

User response

Reduce the string length so it does not exceed the allowed limit.

ARS7851E

The *childObjectType* object cannot have a data type of '*dataType*' as it is no longer supported. The *childObjectType* object cannot be added to the *parentObjectType* object named '*parentObjectName*'.

Explanation

An attempt was made to add an object which is not valid for the parent object because the data type of the child object is no longer supported.

User response

Remove the object from the input XML file, or change the child data type to a supported value.

ARS7852E

The *childObjectType* object cannot be added to the *parentObjectType* object named '*parentObjectName*' because the *parentAttributeName* attribute of the *parentObjectType* object is set to '*parentAttributeValue*'.

Explanation

An attempt was made to add an object which is not valid for the parent object because the data type of the object does not match the data type of the parent object.

User response

Remove the object from the input XML file, or change the parent data type to a supported value.

ARS7853E

A group cannot own itself. The value, '*attrValue*', is not valid for the *attrName* attribute.

Explanation

The *ownerGroup* attribute of a group cannot have a value of its own name.

User response

Update the XML file with a valid value for the attribute.

ARS7854E

A field must have the *attrName* attribute set to true when setting the *attrName* attribute to true for applicationGroup '*applGroupName*'.

Explanation

A field attribute is required before the related attribute can be set for an application group.

User response

Set the required field attribute to true and try again.

ARS7855W

The encryption setting of *applGroup* named '*applGroupName*' is about to be updated.

WARNING: Changing the encryption setting could result in some documents being encrypted while other documents in the application group are not encrypted.

Do you want to update this object? (Y/N)

Explanation

The command prompts for a confirmation before updating an application group.

User response

Type a Y or an N to confirm or reject the update of the application group.

ARS7856E

The logged on user, '*userName*', has a user type of 'System Admin (Read Only)' and is not permitted to add, update or delete objects.

Explanation

You are logged on as a read-only system administrator and are only allowed to export objects.

User response

Log on as another user type and try again.

ARS7857E

The logged on user, '*userName*', is not permitted to perform the requested action on systemParameters objects.

Explanation

If you are attempting to update systemParameters objects, you must be logged on as a 'System Admin' user type. If you are attempting to export systemParameters objects, you must be logged on as either a 'System Admin' or 'System Admin (Read-Only)' user type.

User response

Log on as 'System Admin' or 'System Admin (Read-Only)' and try again.

ARS7858E

The *attributeName1* value must be the same as the application group *attributeName2* value when the storage set contains cache only storage nodes.

Explanation

An attempt was made to add an application with differing cache values from the applicaton group.

User response

Update the input XML file to make the specified cache values the same.

ARS7859E

The *attributeName* attribute has a value of *value*, but must be greater than or equal to the application group *minAttrName* attribute which has a value of *minValue*.

Explanation

A value was entered which is lower than the minimum required value.

User response

Specify a value which is larger than or equal to the minimum required value.

ARS7860E

The *attributeName* attribute has a value of *value*, but must be greater than the application group *minAttrName* attribute which has a value of *minValue*.

Explanation

A value was entered which is lower than the minimum required value.

User response

Specify a value which is larger than the minimum required value.

ARS7861E

The *attributeName1* value must be the same as the *attributeName2* value of application '*applName*' when the storage set contains cache only storage nodes.

Explanation

An attempt was made to update an application group with differing cache values from the application.

User response

Update the input XML file to make the specified cache values the same.

ARS7862E

The *attributeName* attribute has a value of *value*, but must be less than or equal to the *maxAttrName* attribute of application '*applName*' which has a value of *maxValue*.

Explanation

A value was entered which is greater than the maximum required value.

User response

Specify a value which is less than or equal to the maximum required value.

ARS7863E

The *attributeName* attribute has a value of *value*, but must be less than the *maxAttrName* attribute of application '*applName*' which has a value of *maxValue*.

Explanation

A value was entered which is greater than the maximum required value.

User response

Specify a value which is less than the maximum required value.

ARS7864E

The *attributeName* attribute cannot have a value of '*value*' when the assigned storage set '*setName*' contains cache only storage nodes.

Explanation

An attempt was made to add or update an attribute to a value that is not valid when the assigned storage set is cache only.

User response

Remove the attribute from the input XML file, or change the value of the attribute to a supported value.

Chapter 7. ODF Server messages

You can use the information in this section to identify ODF server errors or problems and resolve them by using the appropriate recovery action.

ARS7900I

The config parm *parmname* = *parmvalue*

Explanation

Displays parameter and values found in the `ars.cfg` file

ARS7901E

The database operation failed, function is *function*, action is *action*, return code is *rc*.

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

No action is required.

ARS7902E

An invalid time *time* for `ars.cfg` parameter *parm* was detected. The default value *dflt_time* was used instead.

Explanation

The time value that was specified is invalid. ODF processing will not start without a valid time interval. A default time interval value was used instead.

User response

If you are not going to change the default value, no action is required. To change the default value, stop ODF processing, change the value in the `ars.cfg` file and restart ODF processing.

ARS7903E

The number *time* entered for the `ars.cfg` parameter *parm* contains too many digits. The default value of *dflt_time* was used instead.

Explanation

The time value that was specified is invalid. ODF processing will not start without a valid time interval. A default time interval value was used instead.

User response

If you are not going to change the default value, no action is required. To change the default value, stop ODF processing, change the value in the `ars.cfg` file and restart ODF processing.

ARS7904E

The number *time* entered for the `ars.cfg` parameter *parm* contains too many digits. The default value of *dflt_time* was used instead.

Explanation

The time value that was specified is invalid. ODF processing will not start without a valid time interval. A default time interval value was used instead.

User response

If you are not going to change the default value, no action is required. To change the default value, stop ODF processing, change the value in the `ars.cfg` file and restart ODF processing.

ARS7905E

The *userid %2\$s* value exceeds the maximum user ID length.

Explanation

The value specified exceeded the maximum length.

User response

Specify the correct value.

ARS7906E

An active DCT row was not found for Recipient = *recipient*, Distribution Name = *distname*.

Explanation

A distribution definition row could not be found in the DCT table for the distribution specified.

User response

Contact your ODF administrator to verify the distribution and report bundle definitions

ARS7907E

The UOT entry does not exist for Recipient = *recipient*, Distribution Name = *distname*.

Explanation

There was not a UOT entry in the table for the recipient specified.

User response

Verify the recipient specified is correct and add a UOT entry if necessary.

ARS7908E

The BDT entry could not be found for Recipient = *recipient*, Distribution Name = *distname*.

Explanation

A report bundle definition row could not be found in the BDT table for the distribution specified.

User response

Contact your ODF administrator to verify the distribution and report bundle definitions

ARS7909I

Distribution for Recipient = *recipient*, Distribution Name = *distname* is queued for print processing.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7910I

Distribution for Recipient = *recipient*, Distribution Name = *distname*, Jobname = *jobname* is queued for submitted job print processing.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7911I

Distribution print processing started for Recipient = *recipient*, Distribution Name = *distname*.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7912I

Distribution print processing completed successfully for Recipient = *recipient*, Distribution Name = *distname*.

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7913E

Distribution print processing completed with errors for Recipient = *recipient*, Distribution Name = *distname*.

Explanation

One or more report bundles in the distribution did not complete due to errors.

User response

Investigate and correct the problem by reviewing the ODF error JES spool file datasets. Use the ODF monitor to submit a reprint request.

ARS7914I

Distribution print processing completed with warnings for Recipient = *recipient*, Distribution Name = *distname*.

Explanation

The distribution completed with nonterminating errors.

User response

Investigate and correct the problem by reviewing the ODF error JES spool file datasets. Use the ODF monitor to submit a reprint request for the failing report bundles.

ARS7915E

A entry in the ARSDFDRT table was not found for Recipient = *recipient*, Distribution Name = *distname*.

Explanation

The Distribution request entry was not found for the report bundle being processed.

User response

Investigate and correct the problem.

ARS7916E

An error occurred in the ARSRPCJI *function* function. The return code = *retcode*, the reason code = *rsncode*.

Explanation

An error was detected in ARSRPCJI, the Change Job Id Service Processor.

User response

Return and reason codes for ARSRPCJI are documented in the ODF manual. Investigate and correct the problem. If the problem persists, contact IBM Software Support.

ARS7917E

ARSRPCJI detected an invalid jobname for Recipient = *recipient*, Distribution Name = *distname*, Report ID = *reportid*, Sequence Number = *seq*, Jobname = *jname*.

Explanation

Print processing for a submitted job detected an invalid jobname.

User response

Verify jobname specified in the distribution definition. Use the ODF Monitor to submit a reprint using the correct jobname.

ARS7918E

Dynamic allocation failed for the *filetype* file *ddname* for Recipient=*recipient*, Distribution Name=*distname*, Report ID=*reportid*, Sequence Number=*seq*.

Explanation

The dynamic allocation of the JES spool file dataset for the ODF message dataset failed.

User response

Check the value specified in the ARSODF_ODFMSG_Alloc_Parms parameter in the *ars.cfg* file. If these values are valid, check the console and ODF main task message dataset for ARSRALLO return codes.

ARS7919E

Error opening *filetype* file *ddname* for Recipient=*recipient*, Distribution Name=*distname*, Report ID=*reportid*, Sequence Number=*seq* (*errno=errno*, *errno2=errno2*).

Explanation

The open of the JES spool file dataset for the specified dd failed.

User response

Investigate and correct the problem by reviewing the syslog output. If the problem persists, contact your IBM Service Representative.

ARS7920E

An error occurred writing to the *filetype* file *ddname* for Recipient=*recipient*, Distribution Name=*distname*, Report ID=*reportid*, Sequence Number=*seq*.

Explanation

There was an error writing to the output file.

User response

Check the print options specified in the distribution and report bundle definitions. If these are valid check the console log and the odf main task syslog for ARSRALLO return codes.

ARS7922E

No PPT entries were found for Recipient = *recipient*, Distribution Name = *distname*.

Explanation

The distribution was submitted for processing but no report bundle entries were found.

User response

Contact the ODF administrator to verify the contents of the DB2 tables. If the problem persists, contact IBM Software Support.

ARS7923E

The report bundle completed with errors for Recipient = *recipient*, Distribution Name = *distname*, Report ID = *reportid*, Sequence Number = *seq*.

Explanation

The report bundle processing did not complete due to errors.

User response

Investigate and correct the problem by reviewing the ODF output. Use the ODF monitor to submit a reprint request.

ARS7924E

The recipient is not allowed access to the document report bundle. Recipient = *recipient*, Distribution Name = *distname*, Report ID = *reportid*, Sequence = *seq*, Text=*msg_text*.

Explanation

The recipient was denied access to the bundle by the ODF permission exit.

User response

Investigate and determine if access was correctly denied. Use the ODF monitor to submit a reprint request if necessary.

ARS7925E

Permission exit *exit* failed with return code *rc* Recipient = *recipient*, Distribution Name = *distname*, Report ID = *reportid*, Sequence = *seq*, Text=*msg_text*.

Explanation

The ODF permission exit returned an invalid return code.

User response

Investigate and correct the permission exit. Use the ODF monitor to submit a reprint request if necessary.

ARS7926E

The exit *exit* could not be loaded (errno=*errno*, errno2=*errno2*).

Explanation

An exit failed to load.

User response

Investigate and correct the issue associated with the specified errno and errno2 values. Use the ODF monitor to submit a reprint request if necessary.

ARS7927E

Error reading file=<*ddname*>, errno=*errno*, errno2=*errno2*.

Explanation

An error occurred reading the specified file.

User response

Investigate and correct the issue associated with the specified errno and errno2 values. Use the ODF monitor to submit a reprint request if necessary.

ARS7928E

DYNALLOC failed. DD=*ddname*, ERRCODE=*errno*, INFOCODE=*errno2*.

Explanation

An error occurred dynamically allocating the specified DD.

User response

Investigate and correct the issue associated with the specified errno and errno2 values. Use the ODF monitor to submit a reprint request if necessary.

ARS7929E

Error opening DD=*ddname*, errno=*errno*, errno2=*errno2*.

Explanation

An error occurred opening the specified DD.

User response

Investigate and correct the issue associated with the specified errno and errno2 values. Use the ODF monitor to submit a reprint request if necessary.

ARS7930E

Email processing failed for Recipient = *Recipient*, Distribution Name = *distname*, Report ID = *reportid*, Sequence = *seq*, Return code = *rc*.

Explanation

An error occurred sending an email.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7931E

An error occurred retrieving the report document for Recipient = *recipient*, Distribution Name = *distname*, Report ID = *reportid*, Sequence = *seq*. The return code = *rc*, and error number = *errnum*.

Explanation

An error occurred retrieving a document for a distribution.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7932E

DYNALLOC failed. Recipient = *recipient*, Distribution Name = *distname*, Report ID = *reportid*, Sequence = *seq* DSN=*dsname*, ERRCODE=*errno*, INFOCODE=*errno2*.

Explanation

An error occurred dynamically allocating the specified data set.

User response

Investigate and correct the issue associated with the specified errcode and infocode values. Use the ODF monitor to submit a reprint request if necessary.

ARS7933E

Open failed. Recipient = *recipients*, Distribution Name = *distname*, Report ID = *reportid*, Sequence = *seq* DSN=*dsname*, *errno=errno*, *errno2=errno2*.

Explanation

An error occurred opening the specified data set.

User response

Investigate and correct the issue associated with the specified *errno* and *errno2* values. Use the ODF monitor to submit a reprint request if necessary.

ARS7934W

The Content Manager OnDemand report document was not found for Recipient = *recipient*, Distribution Name = *distname*, Report ID = *reportid*, Sequence Number = *seq*.

Explanation

When retrieving a document for a bundle, no document met the criteria.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7935E

An error occurred retrieving the report document for Recipient = *recipient*, Distribution Name = *distname*, Report ID = *reportid*, Sequence = *seq*. The return code = *rc*, and error number = *rsn*.

Explanation

An error occurred dynamically allocating the specified data set.

User response

Investigate and correct the issue associated with the specified return code and error number values. Use the ODF monitor to submit a reprint request if necessary.

ARS7936E

The Content Manager OnDemand userid or password is invalid.

Explanation

The userid or password is invalid.

User response

Specify a correct userid and password. Use the ODF monitor to submit a reprint request if necessary.

ARS7937E

The Content Manager OnDemand server is unavailable.

Explanation

ODF could not connect to the server.

User response

Ensure the server is started. Use the ODF monitor to submit a reprint request if necessary.

ARS7938E

<ARSREDFM> uuencode produced *olen* bytes.

Explanation

An error occurred performing a uuencode.

User response

Restart ODF.

ARS7939I

ODF is terminating.

Explanation

The ODF processing is ending. This message is for informational purposes only.

User response

No action is required.

ARS7940E

The `<command>` command failed to open a pipe. Recipient = *recipient*, Distribution Name = *distname*, User = *user*, *errno=errno*, *errno2=errno2*.

Explanation

ODF was unable to open a pipe.

User response

Investigate and correct the issue associated with the specified *errno* and *errno2* values. Use the ODF monitor to submit a reprint request if necessary.

ARS7941E

The `<file>` file could not be opened. Recipient = *recipient*, Distribution Name = *distname*, User = *user*, *errno=errno*, *errno2=errno2*.

Explanation

ODF was unable to open a file.

User response

Investigate and correct the issue associated with the specified *errno* and *errno2* values. Use the ODF monitor to submit a reprint request if necessary.

ARS7942I

ARSODF for instance *instance* is ready

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7943I

The Content Manager OnDemand ODF feature has not been installed. Please ensure that the feature has been purchased and properly installed.

Explanation

This message is for your information only.

User response

No action is required.

ARS7944I

Usage: `arsodf` [*options*]
Version: *version*
`-d` *<dist_name>* Distribution name
`-e` External distribution

-f Only create needed definitions
-h <od_inst> OnDemand library server or instance name (same as -l)
-l <od_inst> OnDemand library server or instance name (same as -h)
-p <passwd> OnDemand User Login Password Stash File
-r <recipient> Recipient name
-S Start the OnDemand Distribution Facility for the given instance
-T Stop the OnDemand Distribution Facility for the given instance
-u <userid> OnDemand User Login Name
-v Verbose
-1 <trace_file> Trace file
-2 <trace_level> Trace level

Explanation

An incorrect parameter was specified for the command.

User response

Resubmit the command with the correct parameters. For more information about this command, please see the Content Manager OnDemand Distribution Facility guide.

ARS7945E

ARSRASCR failed. Function *function*, return code=*return*, reason code=*reason*.

Explanation

ODF received an error when invoking the ARSRASCR function.

User response

Investigate and correct the issue associated with the specified return and reason code values. Use the ODF monitor to submit a reprint request if necessary.

ARS7946I

ARSODF is running in direct mode. (ARSODF_USETCPIP=0).

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7947I

ODF Version <*version*> Operating System <*os*> <*os_ver*> OS Userid <*userid*> Install Location <*install_dir*>
misc

Explanation

This message is for your information only.

User response

No action is required.

ARS7948E

The distribution name *<dist_name>* and/or recipient *<user_name>* does not exist or user *<%3\$s>* does not have permission to access the distribution

Explanation

The specified distribution name and/or recipient is not correct or the specified user does not have permission to perform the action.

User response

Verify the name of the distribution. Verify the userid and verify that the userid has permission to perform the action. Then resubmit the command.

ARS7949E

The number *time* entered for the `ars.cfg` parameter *parm* is not valid. The expected range is between *dflt_time* and *%4\$s*

Explanation

The value that was specified is invalid. ODF processing will not start without a valid value.

User response

If you are not going to change the default value, no action is required. To change the default value, stop ODF processing, change the value in the `ars.cfg` file and restart ODF processing.

ARS7950E

Unexpected fatal error encountered, function is *function*, return code is *return_code*.

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

No action is required.

ARS7951E

Unable to process a DRT for distribution name *<dist_name>* and recipient *<recipient>*

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

No action is required.

ARS7952E

Unable to create directory <dir_name>

Explanation

Unable to create the directory. This is preventing the Content Manager OnDemand distribution facility program from running properly.

User response

Check the permissions for the stated directory and use the ODF monitor to submit a reprint request.

ARS7953I

Report Bundle processing started for Recipient = *recipient*, Distribution Name = *distname*, Sequence = *sequence*, Report ID = *reportid*

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7955E

Report Bundle processing failed for Recipient = *recipient*, Distribution Name = *distname*, Sequence = *sequence*, Report ID = *reportid*

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

No action is required.

ARS7956E

Report Bundle processing completed with warnings for Recipient = *recipient*, Distribution Name = *distname*, Sequence = *sequence*, Report ID = *reportid*

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7957E

The userexit `>userexit_name<` failed. The return code is `rc`

Explanation

The specified user exit program failed.

User response

Verify that the user exit program functions properly outside of the Content Manager OnDemand environment. Then resubmit the command.

ARS7958E

SMTP processing failed for Server = `smtp_server`, Return code = `rc`, File=`file`, Line=`line`

Explanation

An error occurred sending an email.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7959E

Encoding failed, Return code = `rc`, File = `file`, Line = `line`

Explanation

An error occurred sending an email.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7960E

Send failed, Return code = `rc`, File = `file`, Line = `line`

Explanation

An error occurred sending an email.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7961E

Send failed, Buffer = `buf`, Return code = `rc`, File = `file`, Line = `line`

Explanation

An error occurred sending an email.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7962E

Recv failed, Return code = *rc*, File = *file*, Line = *line*

Explanation

An error occurred sending an email.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7964E

Unable to process a storage set definition for Application Group Name = *applgrp_name*, Application Name = *appl_name*, Sid = *sid*

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7965E

Unable to process an application group definition for Application Group Name = *applgrp_name*, Agid = *agid*, Application Name = *appl_name*, Aid = *aid*

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7966E

Unable to process the recipients for *<recipient>*

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7967E

Unable to process the ppts for Recipient = *recipient*, Distribution Name = %2

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7968E

Unable to create thread. The return code is *rc*

Explanation

An error occurred while running this program.

User response

Ensure that the maximum number of threads per process is unlimited. If the problem persists, contact your IBM Service Representative.

ARS7969E

Unable to join the thread. The return code is *rc*

Explanation

An error occurred while running this program.

User response

Ensure that the maximum number of threads per process is unlimited. If the problem persists, contact your IBM Service Representative.

ARS7970E

Unable to load module *>function_name<*. The return code is *rc*

Explanation

The system failed when attempting to load the specified dynamic load library.

User response

Verify that the dynamic load library exists and verify the file permissions. Then resubmit the command.

ARS7971I

Email processing started for Recipient = *Recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*

Explanation

This message is for your information only.

User response

No action is required.

ARS7972I

Email processing completed for Recipient = *Recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*

Explanation

This message is for your information only.

User response

No action is required.

ARS7973E

Email processing failed for Recipient = *Recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*, Return code = *rc*.

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7974I

Email notification processing started for Recipient = *Recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*

Explanation

This message is for your information only.

User response

No action is required.

ARS7975I

Email notification processing completed for Recipient = *Recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*

Explanation

This message is for your information only.

User response

No action is required.

ARS7976E

Email notification processing failed for Recipient = *Recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*, Return code = *rc*.

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7977I

Transform processing started for Recipient = *Recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*

Explanation

This message is for your information only.

User response

No action is required.

ARS7978I

Transform processing completed for Recipient = *Recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*

Explanation

This message is for your information only.

User response

No action is required.

ARS7979E

Transform processing failed for Recipient = *Recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*, Return code = *rc*.

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

ARS7980I

Report break is not enabled, Recipient = *Recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid* is being grouped into Sequence = *seq*

Explanation

This message is for your information only.

User response

No action is required.

ARS7981I

Report Bundle staging completed for Recipient = *recipient*, Distribution Name = *distname*, Sequence = *sequence*, Report ID = *reportid*

Explanation

This message is for your information only.

User response

No action is required.

ARS7982E

Report Bundle staging failed for Recipient = *recipient*, Distribution Name = *distname*, Sequence = *sequence*, Report ID = *reportid*

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

No action is required.

ARS7983E

Report Bundle staging completed with warnings for Recipient = *recipient*, Distribution Name = *distname*, Sequence = *sequence*, Report ID = *reportid*

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7984I

File processing started for Recipient = *recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7985I

File processing completed for Recipient = *recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*, File = *file*

Explanation

This message is for informational purposes only.

User response

No action is required.

ARS7986E

File processing failed for Recipient = *recipient*, Distribution Name = *distname*, Sequence = *seq*, Report ID = *reportid*, Return code = *rc*.

Explanation

See the other messages that were generated by the ARSODF program and see messages in the Content Manager OnDemand System Log to correct the problem and then resubmit the command. If the problem persists, contact your IBM Service Representative.

User response

Investigate and correct the issue. Use the ODF monitor to submit a reprint request if necessary.

Chapter 8. ABEND Codes

ABEND Code U-0013 (X'000D') is issued when a failure or error condition occurs for which normal program execution cannot continue. An associated reason code (usually contained in general register 15 at the time of ABEND) further describes the condition.

The reason code is an 8-digit hexadecimal value of the form *mmmmrrrr* where:

- *mmmm* (the high order 4-digits) is the Binary Coded Decimal representation of an associated message number. If these digits are 0000 then no message has been issued.
- *rrrr* (the low order 4-digits) is a reason code which identifies the failure or error condition.

Unless indicated otherwise, the following items apply to all reason codes:

System Action

The system might create LOGREC records and might also create an SVC dump.

System Programmer Response

Search problem reporting databases for a fix for the problem. If no fix exists, have the following diagnostic and problem determination materials available and contact IBM Support.

- Binary machine readable dump data sets (for example, SVC dump and/or SYSMDUMP data sets). Note that print image formatted dumps written to data sets referenced by the SYSUDUMP and SYSABEND DD statements are inadequate when performing problem determination.
- Formatted LOGREC records related to the failure. Refer to the *Environmental Record Editing and Printing Program (EREP) User's Guide* and the *Environmental Record Editing and Printing Program (EREP) Reference* for information regarding the selection and formatting of LOGREC records.
- Relevant sections of the MVS system log.
- All related job logs and JCL listings.

0A01

Explanation

An unexpected return code was received from the z/OS Lock Manager when attempting to release a lock.

At the time of ABEND registers are loaded as follows:

- R0 Indicates which lock was being manipulated:
 1. Local
 2. CMS
- R14 Contains the Lock Manager Return code.

Module

ARSRPCJI

0A02

Explanation

An unexpected return code was received from the z/OS Lock Manager when attempting to obtain a lock.

At the time of ABEND registers are loaded as follows:

- R0 Indicates which lock was being manipulated:

1. Local
 2. CMS
- R14 Contains the Lock Manager Return code.

Module
ARSRPCJI

0A03

Explanation

An invalid Lock Type code was presented to the lock release procedure.

At the time of ABEND registers are loaded as follows:

- R0 Contains the invalid Lock Type code.

Module
ARSRPCJI

0A04

Explanation

An invalid Lock Type code was presented to the lock acquisition procedure.

At the time of ABEND registers are loaded as follows:

- R0 Contains the invalid Lock Type code.

Module
ARSRPCJI

0B0F

Explanation

The address space is being forcibly terminated via the CALLRTM TYPE=ABTERM interface. This generally occurs when an address space does not complete its termination within the permissible time limit in response to a shutdown request.

Module
ARSRASC2

0B01

Explanation

An unexpected return code was received from the z/OS Lock Manager when attempting to release a lock.

At the time of ABEND registers are loaded as follows:

- R0 Indicates which lock was being manipulated:
 1. Local

- 2. CMS
- R14 Contains the Lock Manager Return code.

Module
ARSRASC2

OB02

Explanation

An unexpected return code was received from the z/OS Lock Manager when attempting to obtain a lock.

At the time of ABEND registers are loaded as follows:

- R0 Indicates which lock was being manipulated:
 1. Local
 2. CMS
- R14 Contains the Lock Manager Return code.

Module
ARSRASC2

OB03

Explanation

An invalid Lock Type code was presented to the lock release procedure.

At the time of ABEND registers are loaded as follows:

- R0 Contains the invalid Lock Type code.

Module
ARSRASC2

OB04

Explanation

An invalid Lock Type code was presented to the lock acquisition procedure.

At the time of ABEND registers are loaded as follows:

- R0 Contains the invalid Lock Type code.

Module
ARSRASC2

OC01

Explanation

An unexpected return code was received from the z/OS Lock Manager when attempting to release a lock.

At the time of ABEND registers are loaded as follows:

- R0 Indicates which lock was being manipulated:
 1. Local
 2. CMS
- R14 Contains the Lock Manager Return code.

Module
ARSRASC1

0C02

Explanation

An unexpected return code was received from the z/OS Lock Manager when attempting to obtain a lock.

At the time of ABEND registers are loaded as follows:

- R0 Indicates which lock was being manipulated:
 1. Local
 2. CMS
- R14 Contains the Lock Manager Return code.

Module
ARSRASC1

0C03

Explanation

An invalid Lock Type code was presented to the lock release procedure.

At the time of ABEND registers are loaded as follows:

- R0 Contains the invalid Lock Type code.

Module
ARSRASC1

0C04

Explanation

An invalid Lock Type code was presented to the lock acquisition procedure.

At the time of ABEND registers are loaded as follows:

- R0 Contains the invalid Lock Type code.

Module
ARSRASC1

OC06

Explanation

The attempt to establish an ESTAEX recovery environment was unsuccessful.

At the time of ABEND registers are loaded as follows:

- R14 Contains the ESTAEX Return code.

Module

ARSRASC1

OC07

Explanation

The attempt to obtain the Linkage Stack Level was unsuccessful.

At the time of ABEND registers are loaded as follows:

- R14 Contains the IEALSQRY Return code.

Module

ARSRASC1

OD01

Explanation

An unexpected return code was received from the z/OS Lock Manager when attempting to release a lock.

At the time of ABEND registers are loaded as follows:

- R0 Indicates which lock was being manipulated:
 1. Local
 2. CMS
- R14 Contains the Lock Manager Return code.

Module

ARSRASCR

OD02

Explanation

An unexpected return code was received from the MVS Lock Manager when attempting to obtain a lock.

At the time of ABEND registers are loaded as follows:

- R0 Indicates which lock was being manipulated:
 1. Local
 2. CMS
- R14 Contains the Lock Manager Return code.

Module
ARSRASCR

OD03

Explanation

An invalid Lock Type code was presented to the lock release procedure.

At the time of ABEND registers are loaded as follows:

- R0 Contains the invalid Lock Type code.

Module
ARSRASCR

OD04

Explanation

An invalid Lock Type code was presented to the lock acquisition procedure.

At the time of ABEND registers are loaded as follows:

- R0 Contains the invalid Lock Type code.

Module
ARSRASCR

OD05

Explanation

While attempting to create an address space, no unallocated ARSRASCA array element could be found. Either the upper limit on the number of ARSRASCA array elements has been reached or the maximum number of additional array allocation attempts have been performed.

At the time of ABEND registers are loaded as follows:

- R14 Contains the ARSRASCT address.

Module
ARSRASCR

OD06

Explanation

The attempt to establish an ESTAEX recovery environment was unsuccessful.

At the time of ABEND registers are loaded as follows:

- R14 Contains the ESTAEX Return code.

Module
ARSRASCR

OD07

Explanation

The attempt to obtain the Linkage Stack Level was unsuccessful.

At the time of ABEND registers are loaded as follows:

- R14 Contains the IEALSQRY Return code.

Module

ARSRASCR

OD0F

Explanation

ASCRE for a target address space was only partially successful. The target space is being forcibly terminated through CALLRTM.

Module

ARSRASCR

OD10

Explanation

Both the Local and CMS locks were expected to be held, but at least one of these locks was not held.

At the time of ABEND registers are loaded as follows:

- R0 Contains the PSA CPU Locks Held String (PSACLHS).
- R14 Contains the ASCB Local Lock word (ASCBLOCK).

Module

ARSRASCR

OD11

Explanation

An invalid signal type code was presented to the signal broadcast procedure.

At the time of ABEND registers are loaded as follows:

- R0 Contains the invalid signal type code.

Module

ARSRASCR

OD12

Explanation

The attempt to establish an End of Task Resource Manager for a given address space was unsuccessful.

At the time of ABEND registers are loaded as follows:

- R14 Contains the RESMGR Return code.

Module

ARSRASCR

OD13

Explanation

A SWA Manager request to obtain access to a SWA block was unsuccessful.

At the time of ABEND registers are loaded as follows:

- R0 Contains the SWAREQ Return code.
- R14 Contains the SVA of the SWA block being accessed.

Module

ARSRASCR

OD14

Explanation

Dynamic allocation of an intermediate temporary data set was unsuccessful.

At the time of ABEND registers are loaded as follows:

- R0 Contains the dynamic allocation request block (S99RB) address.
- R14 Contains the address of the related ARSRASCS_DDSTATUS structure.

Module

ARSRASCR

OE01

Explanation

An obsolete version of ARSRASCX has been invoked.

Module

ARSRASCX

OF01

Explanation

An unexpected return code was received from the z/OS Lock Manager when attempting to release a lock.

At the time of ABEND registers are loaded as follows:

- R0 Indicates which lock was being manipulated:
 1. Local
 2. CMS
- R14 Contains the Lock Manager Return code.

Module

ARSRASC3

OF02

Explanation

An unexpected return code was received from the z/OS Lock Manager when attempting to obtain a lock.

At the time of ABEND registers are loaded as follows:

- R0 Indicates which lock was being manipulated:
 1. Local
 2. CMS
- R14 Contains the Lock Manager Return code.

Module

ARSRASC3

OF03

Explanation

An invalid Lock Type code was presented to the lock release procedure.

At the time of ABEND registers are loaded as follows:

- R0 Contains the invalid Lock Type code.

Module

ARSRASC3

OF04

Explanation

An invalid Lock Type code was presented to the lock acquisition procedure.

At the time of ABEND registers are loaded as follows:

- R0 Contains the invalid Lock Type code.

Module
ARSRASC3

OF05

Explanation

An unexpected return code was received from ASEX.

At the time of ABEND registers are loaded as follows:

- R0 Contains the ASEX Reason code.
- R14 Contains the ASEX Return code.

Module
ARSRASC3

OF06

Explanation

The ASPARM data for the address space being initialized is not valid.

At the time of ABEND registers are loaded as follows:

- R0 Contains the ASPARM data area pointer.

Module
ARSRASC3

OF07

Explanation

The attempt to establish an End of Memory Resource Manager for a given address space was unsuccessful.

At the time of ABEND registers are loaded as follows:

- R14 Contains the RESMGR Return code.

Module
ARSRASC3

OF08

Explanation

The attempt to obtain the STOKEN for the current Home address space was unsuccessful.

At the time of ABEND registers are loaded as follows:

- R0 Contains the ALESERV Reason code.
- R14 Contains the ALESERV Return code.

Module
ARSRASC3

0F09

Explanation

The attempt to establish an ESTAEX recovery environment was unsuccessful.

At the time of ABEND registers are loaded as follows:

- R14 Contains the ESTAEX Return code.

Module
ARSRASC3

0FOA

Explanation

The attempt to obtain the Linkage Stack Level was unsuccessful.

At the time of ABEND registers are loaded as follows:

- R14 Contains the IEALSQRY Return code.

Module
ARSRASC3

0FOB

Explanation

The task requesting the creation of a target address space did not complete the handshake with the target address space initialization procedure within the timeout interval. The requesting task is being forcibly terminated via CALLRTM.

Module
ARSRASC3

0901

An unexpected return code was received from the CSVQUERY service attempting to locate a support module.

Explanation

An unexpected return code was received from the CSVQUERY service attempting to locate a support module. At the time of ABEND registers are loaded as follows:

- R0 Contains the pointer to the name of the module being queried.
- R14 Contains the CSVQUERY return code.

Module
ARSRPRN1

Explanation

An unexpected return code was received from ARSRASCR when attempting to establish the special DD names processing environment. At the time of ABEND registers are loaded as follows:

- R0 Contains the pointer to the ARSRASCP structure.
- R14 Contains the ARSRASCR Reason and Return codes.

Module

ARSRPRN1

Note: If R14=00030002 then check the APF authorization of all datasets in the STEPLIB concatenation.

Chapter 9. Hints and tips

Troubleshooting scenarios

Incorrect code page conversion of AFP to line data

This topic does not apply to Content Manager OnDemand V10.1.

Symptoms

Causes

Resolving the problem

Cannot read AFP documents in Internet Explorer 6.0

Symptoms

Internet Explorer 6.0 fails to render AFP to HTML converted pages.

Causes

The enhanced security in Internet Explorer 6.0 no longer allows a browser page to run an applet or JavaScript to retrieve and display pages that do not come from the original page. In Content Manager OnDemand Web Enablement Kit, the applet comes from the mid-tier server and attempts to display a page from the local cache. Internet Explorer 6.0 considers this a security violation, even if the applet that issues the request is signed.

Resolving the problem

Add the site from where the applet is originated to the list of trusted sites or intranet sites (whichever is relevant) in Internet Explorer 6.0. To add to the list of trusted sites:

1. Start Internet Explorer 6.0.
2. From the **Tools** menu, select **Internet Options**.
3. Click **Security**.
4. Select **Trusted Sites** from the list of zones.
5. Click **Sites**.
6. Type the relevant site URL in the **Add this Web site to the zone** field. If the site is not `https://`, then clear the **Require server verification (https:) for all sites in this zone** check box.
7. Click **Add**.
8. Click **OK**.
9. Close Internet Explorer.

Unable to initialize PDF document from Content Manager OnDemand Windows client

Symptoms

Trying to view a PDF document from the Content Manager OnDemand Windows client results in an "Unable to Initialize Document" or "Failure to Initialize Document" message.

Causes

The client was unable to start the Adobe Acrobat reader. The most common cause of this problem is an incorrect key value in the Windows registry.

Resolving the problem

To correct the registry key's value, do the following steps:

1. Using Notepad, create a .reg file that contains these lines:

```
[HKEY_CLASSES_ROOT\AcroExch.Document\DefaultIcon]
@="C:\\Program Files\\Adobe\\adobe_version_dir\\Acrobat\\Acrobat.exe,1"
```

Note: If Adobe Acrobat Reader is installed in a different directory than C:\\Program Files\\Adobe\\Acrobat 6.0\\Acrobat\\, modify the second line to reflect the actual path.

2. Save the .reg file.
3. Double-click the .reg file to merge this key into the Windows registry.
4. Restart the Content Manager OnDemand Windows client.

ARSLOAD fails to start

Symptoms

The Content Manager OnDemand Load Data Service (ARSLOAD) fails to start.

Causes

Your server is affected by this problem if the Content Manager OnDemand Load Data service (ARSLOAD) was created by Content Manager OnDemand, Version 7.1.0.6 or earlier, Windows server, and you have configured the service to automatically load data into an instance that is not named ARCHIVE.

Resolving the problem

Make sure that your Content Manager OnDemand instance is named ARCHIVE.

Note: This section applies only to Content Manager OnDemand for Multiplatforms.

ARSLOAD: Unable to establish connection

Symptoms

Attempting to run the ARSLOAD command results in a "connection cannot be established" error even though the server is up and the correct host name was specified for the -h parameter.

Causes

If you specified only the -h parameter, the name of the default instance must be archive and you must be using the default port number (1445). This error can occur if the default instance is not archive or you are not using port 1445.

Resolving the problem

Use the -I parameter to specify the instance in the following cases:

- The name of the default instance is not archive.
- You are using a port number other than 1445.
- You are running more than one instance on the same workstation and you want to process an instance other than the default instance.
- You are running ARSLOAD from an object server that resides on a different system or node than the library server.

ARSLOAD error when loading report from spool

Symptoms

When attempting to load a report from spool with the following JCL:

```
//ARSLOAD EXEC PGM=ARSLOAD,REGION=0M,  
// PARM=('/-A JOBNAME -uadmin -ppassword -v -C F  
//      -g "ClaseU" -f -c/u/u1/ctemp ')  
//STEPLIB DD DISP=SHR,DSN=ARS.V710.SARSLOAD  
//      DD DISP=SHR,DSN=SYS1.DSN610M.SDSNEXIT  
//      DD DISP=SHR,DSN=DSN610M.SDSNLOAD  
//      DD DISP=SHR,DSN=APK.ACIF.ONDE.SAPKMOD1  
//SYSPRINT DD SYSOUT=*  
//SYSOUT DD SYSOUT=*
```

This ARSLOAD error occurs:

```
The application >< does not exist within the application group >ClaseU<
```

Causes

If you use the -g option to specify an application group, ARSLOAD is unable to determine the application or application group from the spool file. The -G and -A options are ignored. As a result, ARSLOAD tries to perform a load to application group ClaseU, with no application specified, and it fails.

Resolving the problem

Use "-G WRITER -W CLASEU -A JOBNAME, and have the jobs specify a writer name of CLASEU, for example:

```
PARM=('/-G WRITER -W CLASEU -A JOBNAME -v -f')
```

Important: This action requires that you define each job name as an application.

Note: This section applies to Content Manager OnDemand for z/OS only.

ARSLOAD not loading from HFS directory

Symptoms

ARSLOAD will not load from the HFS directory (/ars/upload) specified in the following JCL statement excerpt:

```
//ARSLOAD ...  
// PARM=('-h ARCHIVE -C A -d /ars/upload')
```

Causes

The -C and -d parameters are mutually exclusive. If the -C parameter is specified, ARSLOAD will attempt to load from spool and will not monitor the directory specified by the -d parameter.

Resolving the problem

Remove the -C parameter from the JCL statement excerpt so that it looks like this:

```
//ARSLOAD ...  
// PARM=('-h ARCHIVE -d /ars/upload')
```

Note: This section applies only to Content Manager OnDemand for z/OS.

ARSLOAD unable to store data to cache

Symptoms

In an environment with two object servers and a storage set that is defined with a load type of local, the following error occurred:

```
x087770@njros1ud202[/home/x087770] /usr/lpp/ars/bin/arsload -nfv
-hnjros1ud199 -u... -gAH115 -aAH115DCK /ODDownload/AH115DCK.RPT
OnDemand Load Id = 5013-8-0-8FAA-12041-12041
Loaded 616 rows into the database
Document compression type used - OD77. Bytes Stored = 42406<
arsload: 01/30/03 14:02:54 Loading completed
arsload: Processing successful for file /odarsacif/acif1/AH115DCK.RPT<
An unexpected error occurred. Contact your System Administrator and/or
consult the System Log. File=arsadmin.c, Line=121

arsload: Unable to log load information
arsload: Processing has stopped. The remaining files will NOT be processed.
```

Causes

It is incorrect to define a storage set with a load type of local for the System Log application.

Resolving the problem

If your system does not use Tivoli Storage Manager, you should assign the System Log application group to a cache-only storage set on the library server, or specify a load type of Fixed on the object server.

Note: This section applies only to Content Manager OnDemand for z/OS.

LOADEXIT error for DB2 subsystem occurs during otherwise successful ARSLOAD

Symptoms

When running ARSLOAD, the load portion appears to work, however, there are errors referencing DB2 subsystem DSN and it should be DSNA. The error message is similar to the following:

```
Allocation of connection handle failed
LOADEXIT entry print_error rtn
LOADEXIT SQLSTATE: 58004
LOADEXIT Native Error Code: -99999
LOADEXIT buffer: {DB2 for OS/390}{ODBC Driver}  SQLSTATE=58004  ERRLOC=2
CAF "CONNECT" failed using DB2 system:DSN
RC=0c and REASON=00f30006
```

>

```
LOADEXIT exit print_error rtn
Loaded 1 rows into the database
Document compression type used - OD77. Bytes Stored = >9999<
arsload: 01/01/04 12:00:00 Loading completed
arsload: Processing successful for file >/ars/tmp/HLQ.SYSTEM.LLQ
```

Causes

The ARSLOAD JCL is missing a DSNAOINI DD.

Resolving the problem

Review the ARSLOAD JCL that you submitted to be sure the DSNAOINI DD is properly specified. The LOADEXIT processing that is failing exists to insert rows in the proper ODF tables. These row insertions are to notify ODF when the report has successfully stored and is ready for distribution, should it be part of a distribution.

Check whether the DSNAOINI DD is defined. It should be the same as what you have in the ARSSOCKD job and point to the cli.ini for ODBC. If you have the DSNAOINI defined, be sure it is correctly directed to the proper ODBC parameter file.

If you do not use ODF, you should rename the ARSULOAD exit in /usr/lpp/ars/bin/exits so it is not executed during report loading with ARSLOAD. The arsuload exit is only necessary for ODF. Rename the exit to arsuload.bak if the exit exists and you do not have ODF installed.

Note: Depending on your installation, this problem can reference incorrect DB2 subsystems other than DSN.

ARSADMIN fails when attempting to run from USS

Symptoms

Attempting to run the Content Manager OnDemand ARSADMIN program from Unix System Services (USS) fails with the message: "arsadmin: FSUM7351 not found".

Causes

A link is required to run ARSADMIN from USS. It is possible that the link does not exist.

Resolving the problem

Make sure that the link exists: look for an external link to ARSADMIN from /usr/lpp/ars/bin. It will look like this:

```
OD39090:/usr/lpp/ars/bin: >ls -l arsadmin
erwxrwxrwx 1 root root 8 Oct 15 2001 arsadmin -> ARSADMIN
```

Your SARSLOAD PDS will need to be part of STEPLIB, for example:

```
OD39090:/usr/lpp/ars/bin: >echo $STEPLIB
ARSV710.ODMP710.SARSLOAD:DB2.V10R1M0.DSNA.SDSNEXIT:DB2.V10R1M0.SDSNLOAD
```

[other]: If you do not have an external link to ARSADMIN from /usr/lpp/ars/bin, the ARSISMKD job did not run. This job creates the links in /usr/lpp/ars/bin for ARSLOAD and other executables, and directories needed by SMP. The ARSISMKD sample job is in SARSINST. Refer to the section "Allocate SMP/E Target and Distribution Libraries and Paths" in *Program Directory for IBM Content Manager OnDemand for z/OS*.

[other]: PTFs that change ARSISMKD or the REXX EXEC that it invokes (ARSMKDIR) also have a ++HOLD ACTION, which indicates that the ARSISMKD job must be run again.

Note: This section applies only to Content Manager OnDemand for z/OS.

ARSADMIN fails with unload [options] syntax

Symptoms

When attempting to execute ARSADMIN with the following batch JCL:

```
//ARSLOAD EXEC PGM=ARSADMIN,REGION=0M,TIME=NOLIMIT,
// PARM=('unload -L 5039-2-0-1FAA-8778-8778 -g DLQCY2 ')
//STEPLIB DD DISP=SHR,DSN=SYS1.ONDEMAND.SARSLOAD
//SYSPRINT DD SYSOUT=X,HOLD=YES
//SYSOUT DD SYSOUT=X,HOLD=YES
```

This message occurs:

```
Usage: arsadmin unload [options]
Version: 7.1.0.5
unload Unload a LoadId from OnDemand
```

```

-g <name>           Application Group Name
-h <hostname>       OnDemand Hostname
-p <passwd>         OnDemand User Login Password
-u <userid>         OnDemand User Login Name
-L <load_id>        LoadId to delete from OnDemand
-Q                 Continue if unable to find LoadId in System Log

```

Causes

The -h parameter is missing from the PARM section of the JCL statement. (Unlike ARSLOAD, the -h parameter is required with ARSADMIN.)

Resolving the problem

Add the -h parameter to the JCL statement. Here is some sample JCL for invoking ARSADMIN from a batch job:

```

//OD39090M JOB (TSS40000), 'name',MSGCLASS=1,CLASS=A,
//          MSGLEVEL=(1,1),NOTIFY=OD39090
//PROCESS  OUTPUT  DEFAULT=YES,CLASS=*,JESDS=ALL,OUTDISP=HOLD
//*****
//STEP1    EXEC PGM=ARSADMIN,REGION=0M,
//          PARM='unload -g gname -h ARCHIVE -L 5324-56-0-53FAA-0-0
//          -u OD39090 -p password'
//STEPLIB DD DISP=SHR,DSN=ARSV710.ODMP710.SARLOAD
//SYSPRINT DD SYSOUT=*
//SYSOUT   DD SYSOUT=*

```

Note: This section applies only to Content Manager OnDemand for z/OS.

Informational messages appear in z/OS SYSLOG instead of OnDemand system log

Symptoms

The message ARS0082I, among others, is showing up on the z/OS SYSLOG instead of in the Content Manager OnDemand system log folder hitlist.

Resolving the problem

Check the following items:

- The `ars.cache` file identified by `SRVR_SM_CFG` in `ars.ini`. Is the directory (or directories) specified in `ars.cache` writable by ARSSOCKD?
- Any error messages showing up in the z/OS SYSLOG after restarting ARSSOCKD and generating a message that shows up in the z/OS SYSLOG, but not in the Content Manager OnDemand system log folder (for example, directory permission or database authorization errors).
- The `/etc/resolv.conf` file to ensure all parameters are specified correctly. This problem can occur if the DNS name in `/etc/resolv.conf` is incorrect.

The DB2 log is full

Symptoms

The archive log directory for DB2 is full. It has no more space to write the log data to the predefined log directory, and trying to use the `db2uexit.disk` (or `db2uext2.disk`) to copy online archived log files from the primary log file directory to the archive log file directory does not seem to work. In this case, you cannot connect to the database.

Resolving the problem

Try running `ARSDB -y` or `ARSDB -z` to backup the database. If the backup completes, with a return code of 0, the ARSDB removes to unneeded archive log files. If the archive file system is full, then the

db2uext2.disk cannot copy files from the primary log. Be sure that the database backups are running and ending with RC=0.

Here is the way that logging works:

1. If the backup returns a Return Code = 0, then the ARSDB program or the ars_db script removes log files from the archive log. If the archive log files are not removed after a backup, then the backup did not give an RC=0.
2. The function of db2uext2.disk or db2uext2.tsm is to copy files from the primary log to the archive log.
3. After the primary log files are copied to the archive log and no applications is attached to a primary log, the DB2 database manager removes the log file or clears the file and reuses it.

As shown, the db2uext2 does not remove any log files. The main function of this exit is to copy log files from the primary to the archive log.

If the problem is with the user exit, then check the /tmp or /arstmp directories for the exit log file. Look for /arstmp/db2uext2.err. If the user exit has a return code higher than 8, it shuts down and does not run again until DB2 is restarted.

SMP/E apply job results in GIM23911E message

Symptoms

Performing an SMP/E APPLY CHECK received return code 04, then return code 08. The SMP/E apply job resulted in the following message:

```
GIM239IIE **LINK-EDIT PROCESSING FOR SYSMOD UQXXXXX FAILED FOR MODULE ARSXXX
THE RETURN CODE (12) EXCEEDED THE ALLOWABLE VALUE.
DATE...
```

Later in the linkage edit section, the following message occurred:

```
IEW2606S 4B39 MODULE INCORPORATES PROGRAM MANAGEMENT 3 FEATURES
AND CANNOT BE SAVED IN LOAD MODULE FORMAT
```

Causes

This problem is caused by using a partitioned data set (PDS) other than PDSE for certain libraries, most likely, SMPLTS.

Resolving the problem

Change the allocation of the library. The *Program Directory for IBM Content Manager OnDemand for z/OS* states that the library type for certain libraries that are used by Content Manager OnDemand should be defined as PDSE. These libraries include:

- AARSOBJ1
- SARSDFS
- SARSLOAD
- SMPLTS

Member ARSBALLO in the SARSINST library AARSOBJ1 should be allocated as "DSNTYPE=LIBRARY".

Note: This section applies only to Content Manager OnDemand for z/OS.

Other SMP/E tips

Other SMP/E tips for Content Manager OnDemand include:

- Use FORFMID(XXX) for apply.
- Resolve all ++HOLD system actions after the apply process.

- Refresh LLA when necessary.
- Reapply customization to user exits if the supplied source code is changed.

Attempting to stop DB2 results in SQL1035 message

Symptoms

Attempting to stop DB2 by using the Content Manager OnDemand command `arsdb -h` results in an SQL1035 "Database in use" message.

Causes

This problem can occur if a Content Manager OnDemand database table is damaged.

Resolving the problem

Review the `db2diag.log` file for the following type of message:

```
2001-12-12-09.39.02.760439 Instance:archive Node: 000
PID:24832(db2agent (ARCHIVE)) Appid:*LOCAL.archive.011212143855
buffer_pool_services sqlbrdpg Probe:1141 Database:ARCHIVE
DIA3726C An invalid page checksum was found for page " ".
ZRC=FFFFE119
```

where ZRC refers to a damaged Content Manager OnDemand database table.

To recover, restore the Content Manager OnDemand database table from a good backup, and then roll forward.

Note: This section applies only to Content Manager OnDemand for z/OS.

IBM Content Manager OnDemand PDF Indexer trace facility

An enhanced tracing capability for the IBM Content Manager OnDemand PDF Indexer is available. The tracing capability provides assistance to users who are attempting to debug problems, such as when the system fails during the indexing and loading of PDF documents.

To trace or debug a problem with the IBM Content Manager OnDemand PDF Indexer, the following are required:

- The parameter file, which specifies the fields, triggers, indexes and other indexing information
- The PDF input file to process

The parameter file and PDF input file can be processed by running the IBM Content Manager OnDemand PDF Indexer from the command line. For example:

```
arspdoci parmdd=filen.parms inputdd=filen.pdf outputdd=filen.out
indexdd=filen.ind
tracedd=filen.trace
```

where

arspdoci

Name of the command-line version of the IBM Content Manager OnDemand PDF Indexer program

parmdd=

Specifies the name of the input file that contains the indexing parameters

inputdd=

Specifies the name of the PDF input file to process

outputdd=

Specifies the name of the output file that contains the indexed PDF documents created by the IBM Content Manager OnDemand PDF Indexer

indexdd=

Specifies the name of the output file that contains the index information that will be loaded into the database

tracedd=

Specifies the name of the output file that contains the trace information

See also: See your IBM Content Manager OnDemand *Indexing Reference* for more information about the parameters that may be specified when running the ARSPDOCI program.

After you run the IBM Content Manager OnDemand PDF Indexer with the trace, the output file that is specified by the tracedd=parameter contains detailed information about the processing that took place and where the PDF indexer is failing during the process. The trace information identifies whether a trigger was not found, a field was not found, the PDF data was corrupted, there was a problem extracting a PDF page from the document, or even if there was not enough memory or disk space to complete the required operations. The following is an example of the trace information that may be generated by the PDF Indexer.

```
COORDINATES=IN
ARSPDOCI completed code get_keyword <-----
ARSPDOCI completed code get_keyword 003 ----->
TRIGGER1=UL(7.00,0.25),LR(7.70,0.57),*, 'Page: '
ARSPDOCI completed code get_keyword <-----
ARSPDOCI completed code get_keyword 003 ----->
ARSPDOCI completed code parse_trigger <-----
ARSPDOCI completed code parse_quoted_parm <-----
ARSPDOCI completed code parse_quoted_parm 001 ----->
ARSPDOCI completed code parse_trigger 001 ----->
FIELD1=UL(7.00,0.48),LR(7.90,0.77),0,(TRIGGER=1,BASE=0)
ARSPDOCI completed code get_keyword <-----
ARSPDOCI completed code get_keyword 003 ----->
ARSPDOCI completed code parse_field <-----
ARSPDOCI completed code parse_subfields <-----
ARSPDOCI completed code get_keyword <-----
ARSPDOCI completed code get_keyword 003 ----->
ARSPDOCI completed code get_keyword <-----
ARSPDOCI completed code get_keyword 003 ----->
ARSPDOCI completed code parse_subfields 001 ----->
ARSPDOCI completed code parse_field 001 ----->
FIELD2=UL(6.11,1.39),LR(7.15,1.57),0,(TRIGGER=1,BASE=0)
ARSPDOCI completed code get_keyword <-----
ARSPDOCI completed code get_keyword 003 ----->
ARSPDOCI completed code parse_field <-----
ARSPDOCI completed code parse_subfields <-----
ARSPDOCI completed code get_keyword <-----
.
.
.
ARSPDOCI completed code get_keyword <-----
ARSPDOCI completed code get_keyword 003 ----->
ARSPDOCI completed code arsparm_final_sanity_check <-----
ARSPDOCI completed code arsparm_final_sanity_check 001 ----->
ARSPDOCI completed code ArspProcessOpt <-----
ARSPDOCI completed code ArspOpenIndex <-----
ARSPDOCI completed code ArspOpenIndex 001 ----->
Adobe PDF Library version -732512488.-1
Editing is :-1
Number of input pages =130
ARSPDOCI completed code ArspProcessOpt:Calling ArspSearchDocPages()
ARSPDOCI completed code ArspSearchDocPages <-----
ARSPDOCI completed code ArspSearchDocPages:ArspCreateWordFinder()
```

```

ARSPDOCI completed code ArspSearchDocPages:PDWordFinderAcquireWordList()
ARSPDOCI completed code ArspSearchDocPages:PDDocAcquirePage()
ARSPDOCI completed code ArspSearchDocPages:ArspSearchPage()
ARSPDOCI completed code ArspSearchDocPages:PDPageRelease()
ARSPDOCI completed code ArspSearchDocPages:PDWordFinderReleaseWordList()
Trigger(s)not found by page 1
ARSPDOCI completed code ArspSearchDocPages 004 ----->
ARSPDOCI completed code ArspProcessOpt:Calling ArspCloseIndex()
ARSPDOCI completed code ArspCloseIndex <-----
ARSPDOCI completed code ArspCloseIndex 001 ----->
ARSPDOCI completed code ArspProcessOpt:Calling PDDocClose()
ARSPDOCI completed code ArspProcessOpt 002 ----->
ARSPDOCI completed code 1
ARSPDOCI completed code ArspFreeParms ()

```

Table space file systems

Important: This section applies only to Content Manager OnDemand for z/OS.

When configuring DB2 table space file systems under Solaris, each file system that you define to contain SMS table spaces must be located on a different mount point.

<i>Table 2: SMS table space files systems under Solaris</i>	
Directory in ARS.DBFS	Mount Point
/arsdb/db1/SMS	/dev/HDISK6
/arsdb/db2/SMS	/dev/HDISK7

The Content Manager OnDemand server cannot initialize if you have defined more than one SMS table space file system on the same mount point.

Tivoli Storage Manager issues

Important: This section applies only to Content Manager OnDemand for Multiplatforms.

Deleting application groups

If the owner of the Content Manager OnDemand instance is not root, when a user deletes an application group, Content Manager OnDemand deletes the application group table(s) from the Content Manager OnDemand database, but does not delete the application group data from Tivoli Storage Manager. In this case, Content Manager OnDemand issues message number ARS0022, which states that the user must manually delete the application group data from Tivoli Storage Manager. To delete the data from Tivoli Storage Manager, log on to Tivoli Storage Manager and use Tivoli Storage Manager utilities to delete the filespace in Tivoli Storage Manager that is associated with the application group. The name of the filespace is specified in message number ARS0022. See your Tivoli Storage Manager information for details about logging on to Tivoli Storage Manager and using Tivoli Storage Manager utilities to delete data.

Detecting network communication errors involving Content Manager OnDemand

ARSSOCK is a debug option for arssockd that logs TCP/IP errors. After ARSSOCK is enabled, it saves the following information to a file:

- Timestamp
- Program in use

- `arssock.c` line where the problem occurred
- Activity
- Reason code (RC) that is provided by the called function

For example,

```
Wed May 21 13:09:52 2003: OnDemand(1596) -> bind rc = 67
```

where

Wed May 21 13:09:52 2003

Timestamp

OnDemand(1596)

The line in `arssock.c` where the problem occurred

bind

Attempted activity

67

Reason code that is returned by the called function

The usual source of the reason code is the operating system's `errno.h` file. In this example taken from an AIX system, the reason code indicates that the address is already in use. Refer to your operating system documentation for reason codes.

To enable this debug option, you must specify the file to save the debug information in. In the `ars.cfg` file, uncomment or add the following line:

```
ARSSOCK=/tmp/arssock.dbg
```

Important:

- You must have permission to write to the file that is specified by `ARSSOCK=`
- You must provide the full path to the file. You can change the file name and location according to your preferences. Once the debug file is identified, you need to restart the `arssockd` parent process.

Notices

This information was developed for products and services that are offered in the US. This material might be available from IBM in other languages. However, you may be required to own a copy of the product or product version in that language in order to access it.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing
IBM Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
US*

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
19-21, Nihonbashi-Hakozakicho, Chuo-ku
Tokyo 103-8510, Japan*

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you provide in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*IBM Director of Licensing
IBM Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
US*

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

The client examples cited are presented for illustrative purposes only. Actual performance results may vary depending on specific configurations and operating conditions.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

Statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Each copy or any portion of these sample programs or any derivative work must include a copyright notice as follows:

© (your company name) (year).

Portions of this code are derived from IBM Corp. Sample Programs.

© Copyright IBM Corp. _enter the year or years_.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other company, product, and service names may be trademarks or service marks of others.

Terms and conditions for product documentation

Permissions for the use of these publications are granted subject to the following terms and conditions.

Applicability

These terms and conditions are in addition to any terms of use for the IBM website.

Personal use

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of IBM.

Commercial use

You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

Rights

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

IBM Online Privacy Statement

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

This Software Offering does not use cookies or other technologies to collect personally identifiable information.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at www.ibm.com/privacy and IBM's Online Privacy Statement at www.ibm.com/privacy/details the section entitled "Cookies, Web Beacons and Other Technologies" and the "IBM

Software Products and Software-as-a-Service Privacy Statement” at www.ibm.com/software/info/product-privacy.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "[Copyright and trademark information](http://www.ibm.com/legal/copytrade.shtml)" www.ibm.com/legal/copytrade.shtml.

Adobe, Acrobat, Portable Document Format (PDF), and PostScript are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, other countries, or both.

Intel, Intel logo, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo, Celeron, Intel Xeon, Intel SpeedStep, Itanium, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, and Windows NT are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Portions of the OnDemand Windows client program contain licensed software from Pixel Translations Incorporated, © Pixel Translations Incorporated 1990, 2003. All rights reserved.



All rights reserved.

FairCom Corp. and other company, product or service names might be trademarks or service marks of others.

Privacy policy considerations

IBM Software products, including software as a service solutions, (“Software Offerings”) may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering’s use of cookies is set forth below.

This Software Offering does not use cookies or other technologies to collect personally identifiable information.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, See IBM’s Privacy Policy at <http://www.ibm.com/privacy> and IBM’s Online Privacy Statement at <http://www.ibm.com/privacy>

www.ibm.com/privacy/details the section entitled “Cookies, Web Beacons and Other Technologies” and the “IBM Software Products and Software-as-a-Service Privacy Statement” at <http://www.ibm.com/software/info/product-privacy>.



SC19-3356-02

